

					SHEET
	6	PRO	JECT NO.		NO.
	STATE TEXAS	STATE DIST.			
	CONT.	SECT.	JOB	HIGHWAY	NO.
	0915	12	562	WATSO	N RD
BEXAR COUNTY: FM 2790-SOMERSET & WATSON DESIGN SPEED = 40 MPH ADT 3,900 (2021) ADT 5,400 (2041) PROJECT CLASSIFICATION - CO AREA OF DISTURBED SOIL = 6.4 <u>FINAL PLANS</u>	N RD LLECT(40 ACF	DR RES			
LETTING DATE:					
DATE CONTRACTOR BEGAN WORK:					
DATE WORK WAS ACCEPTED:					
FINAL CONTRACT COST: \$					
CONTRACTOR:					
				_	
FINAL PLANS STATEMENT: THE CONSTRUCTION WORK WAS PERFO ACCORDANCE WITH THE PLANS.	RMED	IN			
AREA ENGINEER D	ATE				
TEXAS DEPARTMENT OF TRANSPO	ORTATI	ON		_	
	OMMENDED	FOR LETTI	NG		
DESIGN SUPPORT DIRECTOR TxL	DOT DISTR	ICT DESIG	N ENGIN	NEER	

RECOMMENDED	FOR	LETTING	

DIRECTOR OF TRANSPORTATION PLANNING & DEVELOPMENT

RECOMM	ENDED FO	R LETTING L	
TxDOT	DISTRICT	ENGINEER	

RECOMMENDED FOR LETTING

BEXAR COUNTY DIRECTOR OF PUBLIC WORKS

	SHEET NO.	GENERAL	SHEET NO.	ROADWAYPLANS		
	1	TITLE SHEET	96	HORIZONTAL ALIGNMENT DATA	SHEET NO.	SIGNING, PAVEMENT MARKING &
	2	INDEX OF SHEETS	97 - 105	ROADWAY PLAN & PROFILE	186 - 190	SIGNING. PAVEMENT MARKINGS
	3		106	VERANO PLAN & PROFILE	100 100	
	4 - 5		107 108		SHEET NO.	SIGNING, PAVEMENT MARKING &
	6 - 7		100 - 100		101 102	DOM (2 5 8)/(A) 15
	8		109		191 - 195	DOM (2, 3 & VIA)-13
	9		110		194 - 195	
	10 - 11	DRAINAGE GENERAL NOTES	111	MISCELLANEOUS RDWY DETAIL	196	SMD(GEN)-08
	10 11				197	SMD(FRP)-08
	12	SW3P SUMMARY	SHEET NO		198 - 200	SMD(SLIP 1, 2, &3)-08
	13	ROADWAY SUMMARY	SHEET NO.	ROADWAYSTANDARDS	201	SMD(TWT)-08
	14	DRAINAGE SUMMARY	112 - 115	PED-18	202	SPRFBA(3)-13
	15	SIGNING, PAVEMENT MARKING AND DELINEATION SUMMARY	116 - 119	MB15(1)	203	RS(5)-13
	10	EARTHWORK SUMMARY	120	JS-14		
	17	SMALL SIGN SUMMARY	121 - 122	CPCD-14	SHEET NO.	IELOMINATION FEAN
			123 - 124	CRCP(1)-17	204 - 206	ILLUMINATION PLAN LAYOUTS
	SHEET NO				SHEET NO	ILLUMINATION STANDARD
	19 10				SHEET NO.	
	10 - 19		301EET NO.		207 - 215	ED(1,3 THRU 7)-14, ED(10 THRU 12
	20 - 22	TRAFFIC CONTROL PLAN TYPICAL SECTIONS	125	OVERALL DRAINAGE AREA MAP	216	RID(1)-17
	23	SCHEDULE OF TRAFFIC CONTROL AND ADVANCED WARNING DEVICES	126 - 127	INTERIOR DRAINAGE AREA MAP	217	RID(2)-17
	24	TCP HORIZONTAL ALIGNMENT DATA	128 - 131	HYDRAULIC COMPUTATIONS	218 - 221	RIP(1THRU 4)-19
	25 - 27	TCP PHASE 1 STAGE 1	132 - 144	DRAINAGE PLAN AND PROFILE SHEETS		
	28	DETOUR #1	145 - 147	INLET CROSS-SECTIONS	SHEET NO.	EXISTING UTILITY LAYOUTS
	29 - 31	TCP PHASE 2 STAGE 1	148	BOX CULVERT SUPPLEMENT WINGS AND END TREATMENTS	222 - 226	EXISTING UTILITY SHEETS
	32	TCP PHASE 2 STAGE 2	149	CULVERT PLAN AND PROFILE		
	33	DETOUR #2	150 - 151	CULVERT DETAILS	SHEET NO.	CROSS-SECTIONS
	34 - 38	TCP PHASE 3 STAGE 1	152 - 158	DITCH PLAN AND PROFILE	227 - 255	CROSS-SECTION SHEETS
	39 - 40	TCP PHASE 3 STAGE 2	159	4WAY INLET AND SYSTEM B OUTFALL DETAIL		
	41 - 42	TCP PHASE 3 STAGE 3	160	PIPE BEDDING & MISCELLANEOUS DRAINAGE DETAILS	SHEET NO.	WATER PLANS
	43	TCP PHASE 3 STAGE 4			1 - 15	WATER PLANS
	44	TCP PHASE 3 STAGE 5				
-	45	DETOUR #3	SHEET NO.	DRAINAGE STANDARDS		
dgr	46		161	PR I		
<u>Q</u>	47 - 51		101			
z	52 - 57		102	FB		
S	58		103			
IAT	59	SW3P NARRATIVE	164			
Ž	55	EPIC	165	PC0-02		
ы Ш			166	CGI-PCO		
TS/			167 - 170	CCO-1THRU4		
но <mark>.</mark>	SHEET NO.	TRAFFIC CONTROL & SW3P STANDARDS	171	CURB INLET TY C WITH INLET EXTENSION TYPE C-E (MOD) SHT 1 OF 2 (DISTRICT STAN	DARD)	
Z	60 - 71	BC(1THRU 12)-14	172	CURB INLET TY C WITH INLET EXTENSION TYPE C-E SHT 2 OF 2 (DISTRICT STANDARD)		
ل ا	72	TREATMENT FOR VARIOUS EDGE CONDITIONS	173	PAZD		
<u>í</u>	73	TCP(1-2)-18	174	ARMOR CURB SLOT (DISTRICT STANDARD)		
CA	74	TCP(2-1)-18	175	PSL 01		
los	75	TCP(2-2)-18	176	PSL 02		
Vats	76	TCP(2-3)-18	177	SCP-3		
	77	TCP(2-6)-18	178	SCP-4		
U V	78	TCP(2-8)-18	179	SCP-MD		
â	79	TCP(3-1)-13	180	FW-0		
800	80	TCP(3-3)-14	181	PW		
543	81	TCP(7-1)-13	182	SW-0		
Ē	82	WZ(BRK)-13	183	TXDOT RIPRAP		
16	83 - 84	WZ(BTS-1THRU 2) - 13	184 - 185	PR11		
PM [85	WZ(RCD)-13				
Pro Pro	86	WZ(RS)-16				
PD 14 fra\	87	WZ(STPM)-13				
	88	WZ()_13				
ati BL	80	W7(TD)_17				
ez SO X 1 X 1 X 1 X 1	00 04					
'ald 1 AT: 25/2 IE	90 - 91					
ev VAT W 6/2 IAM	92					
SCA DN ER <	93	EC(2)-16				
	94	EC(3)-16				
	95 - 95B	EC(9)-16				
LO L						
ᅭᅭᅭᇿᄔᄔ						

G & DELINEATION PLANS

S AND DELINEATION LAYOUTS

3 & DELINEATION STANDARDS

J 12)-14





OTTED.



LEGEND

- PROP EDGE OF ROADWAY
- EXISTING FEATURES
- - EXISTING RIGHT OF WAY
 - - PROP RIGHT OF WAY
 - CONCRETE PAVEMENT - 1
 - CONCRETE APRON
 - \checkmark BLOCK SOD

DRIVEWAY

1

•

 \checkmark

 \mathbf{V}

PROP TRAFFIC ARROW

REMAINING PORTION OF 306.391 ACRES OF LAND

208+00









PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 12:51:46 PM

PLOTTED BY: evaldez PLOTTED SCALE: 1:10 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 12:51:46 PM PLOTTED ON: 6/25/2020 @ 12:51:46 PM



PLOTTED BY: evaldez PLOTTED SCALE: 1:10 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOT DRIVER: WATSON_@ 12:51:47 PM DESIGN FILENAME: X:\data\Infra\Proj_2016\

ROW

EXIST

AREA

NXIS

REVISION NO DATE GRAPHIC SCALE (IN FEET) 30 15 1" = 10' ~~~~···· THE SEAL APPEARING ON THIS DOCUMENT WAS AUTHORIZED BY JULIO RAMOS, P.E. 107672 JULIO RAMOS 107672 6/25/2020 11550 IH 10 WEST, SUITE 395 SAN ANTONIO, TEXAS 78230-1037 TEL: (210) 641-9499 JFAX: (210) 641-6440 TBPE REGISTRATION NO: F-2214 TBPLS REGISTRATION NO: 100410-00 CEC NG CONSULTANTS BEXAR COUNTY PUBLIC WORKS DEPARTMENT WATSON ROAD TYPICAL SECTIONS EXISTING AND PROPOSED SHEET 2 OF 2 Texas Department C 2019 of Transportation FED.RD DIV.NO PLAN SH NO. FEDERAL AID PROJECT NO. 6 STATE DIST. TEXAS SAT COUNTY BEXAR JOB HIGHWAY / STREET 562 WATSON RD SECT. CONT. 12 0915

 PHORT D CONSTRUCTION. THE CONTRACTOR SHALL OBTAIN ALL REQUERES STORM WATER PERMITS, FEES, AND APPROXALS, NO CONSTRUCTION OR PARTICATION SHALL BEINI, UNIT, THE CONTRACTOR SHALL OBTAIN ALL REQUERES STORM WATER PERMITS, FEES, AND APPROXALS, NO CONSTRUCTION OR PARTICATION SHALL BEINI, UNIT, HE CONTRACTOR HAS REGEDED AND TOHOROUGH. UNIVERSIDE ALL MEMBER STORM DAVAGE ACCULTY WITHIN A DRAINAGE EASEMENT OR STREET RIGHT OF WAY, NOT NIDICATED ON THE CONSTRUCTION PLANS. THE CONTRACTOR IS REPARNED BEOR PROTECTINE SYSTIMS ORFANDE FACILITIES FROM DAVAGE. AND HAMDE TO EXISTING DRAINAGE SYSTEM IS DRAINAGE TO EXISTING DRAINAGE SYSTEM IS DRAINAGE DEVICTION. THE CONTRACTOR IS RESPONDED TO BE PARLY DRAINAGE FACILITIES FROM DAVAGE. AND HAMDE TO EXISTING DRAINAGE SYSTEM IS DRAINAGE DURING CONSTRUCTION. ON STRUCTURE IS RESPONDED THE CONTRACTOR SYSTEM ORFANDALES SYSTEM IS DRAINAGE DURING CONSTRUCTION. NO STRUCTURE FENCES, WALLS, LANDGAPING, OR OTHER DESTRUCTIONS THAT IMPEDE DRAINAGE SYSTEM IS DRAINAGED DURING CONSTRUCTION. NO STRUCTURE, FENCES, WALLS, LANDGAPING, OR OTHER DESTRUCTIONS THAT IMPEDE DRAINAGE SYSTEM IS DRAINAGED DURING CONSTRUCTION. NO STRUCTURE, FENCES, WALLS, LANDGAPING, OR OTHER DESTRUCTIONS THAT IMPEDE DRAINAGE SHALL BE PLACED WITHIN THE LIMITS OF THE DRAINAGE EASEMENTS SHOWN ON THE CONTRUCTION DOCUMENTS. UNO STRUCTURE, FENCES, WALLS, LANDGAPING, OR OTHER DESTRUCTIONS THAT IMPEDE DRAINAGE SHALL BE PLACED WITHIN THE LIMITS OF THE DRAINAGE EASEMENTS SHOWN ON THE CONTRUCTION DOCUMENTS. UNO STRUCTURE, FENCES, WALLS, LANDGAPING, OR OTHER DESTRUCTIONS THAT IMPEDE DRAINAGE SHALL DE PLACED WITHIN THE LIMITS OF THE DRAINAGE EASEMENTS SHOWN ON THE CONTRUCTION BOOMENTS. UNO STRUCTURE, FENCES, WALLS, LANDGAPING, DRAINAGE MASS DAYS AND HAVEN THE SHALL DECONTRUCTIONS. UNO STRUCTURE, FENCES, WALLS, LANDGAPING, DRAINAGE MASS DAYS AND THE STAND STORMET TONS. UNO STRUCTURE, THE DRAI	<u>AC</u>	DDITIONAL NOTES
 THE CONTRACTOR SHALL NOTEY BEXAR COUNTY AT LEAST 24 HOURS PRIOR TO THE INSTALLATION OF ANY DRAINAGE FACILITY WITHIN A DRAINAGE EASEMENT OR STREET RIGHT OF WAY NOT NOTICATED ON THE CONSTRUCTION PLANS. THE CONTRACTOR IS RESPONDED FOR PORTECTING EXISTING DRAINAGE FACILITIES FROM DMAMAGE MAY DAMAGE TO EXISTING DRAINAGE SYSTEMS WITCHING TO NOT SHOWN ON THE CONTRACTOR SHALL NOTIFY BEXAR COUNTY AS SOON AS CONFLICTS WITH UTILITIES ARE ENCOUNTERED OR ANY DRAINAGE SYSTEM IS DAMAGED DURING CONSTRUCTION. CONSTRUCTURE FENCES, WALLS, LANDSCAPING, OR OTHER DESTRUCTIONS THAT IMPEDE DRAINAGE SHALL BE PLACED WITHIN THE LIMITS OF THE PROJECT MOD SHALL BE DROSED OFFSITE IN COMPLIANCE WITH OURSENT APPLICABLE REGULATIONS. NO STRUCTURE, FENCES, WALLS, LANDSCAPING, OR OTHER DESTRUCTIONS THAT IMPEDE DRAINAGE SHALL BE PLACED WITHIN THE LIMITS OF THE DRAINAGE EASEMENTS BRONNON THE CONFILMINGS THE AREA WILL BE BACKFILLED AND COMPACTED TO ITS ORGANL. CONDITION THEOLOGINAL MOTIVIDANCE AND PROVENT DOWNON THE CONFILMING THE AREA WILL BE BACKFILLED AND COMPACTED TO ITS ORGANL. CONDITION THEOLESSING PITS TO BE OPEN AND LIVATTENDED LONGERT THAN 34 LIVADIS SHALL BE PROFECTED OT WITHIN THAN DALL PHOPODOTATION. SHALL BE BACKFILLED WITHIN THE LIMITS OF THE DRAINAGE EASEMENTS AND DROVENT TO DE OCENE LONGER THAN 30 DAYS AFTERS TARTING EXCAVATION SHALL BE BACKFILLED WITH A SEMPERATION CONTRECTOR DROVENT AND AND THOROGOTATIC FORCES AND PREVENT DOWNSTREAM MARCET. TRENCHESSIONE PITS TO BE OPEN LONGER THAN 30 DAYS AFTERS TARTING EXCAVATION SHALL BE BACKFILLED WITH A SEMPERATION CONTRECTOR DROVENT AND AND THOROGOTATIC FORCES AND PREVENT DOWNSTREAM MARCET. TRENCHESSIONE PITS TO DE OFEN LONGER THAN 30 DAYS AFTERS TARTING EXCAVATION SHALL BE BACKFILLED WITH A SEMPERATION CONTRECTOR DROVENT AND AND THOROGOTATIC FORCES AND PREVENT DOWNSTREAM MARCET. TRENCHESSIONE PITS TO DE OFEN LONGER THAN 30 DAYS AFTERS TARTING EXCAVATION SHALL BE BACKFILLED WITH A SEMPERATION FOR THE DRAINAGE EXCAVATION WITH A LIVADE PROPERT	1.	PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL OBTAIN ALL REQUIRED STORM WATER PERMITS, FEES, AND APPROVALS. NO CONSTRUCTION OR FABRICATION SHALL BEGIN UNTIL THE CONTRACTOR HAS RECEIVED AND THOROUGHLY REVIEWED ALL PERMITS REQUIRED FOR CONSTRUCTION IN DRAINAGE EASEMENTS, RIGHT OF WAYS, AND FLOODPLAINS.
 THE CONTRACTOR IS RESPONSIBLE FOR PROTECTING EXSITING DRAMAGE FACULTIES FROM DMAGE. ANY DMAGE TO EXISTING DRAMAGE SYSTEMS. WHETHER OR NOT SHOWN ON THE PLANS, SHALL BIT HER PERSONSIBILITY OF THE CONTRACTOR TO REPARA THIS EXPENSE. THE CONTRACTOR MALL NOTEY BEXAR COUNTY AS SOON AS CONFLICTS WITH UTILITIES ARE EXECUTIVEED ON ANY DRAMAGE SYSTEMS IB DMAGED DURING CONSTRUCTION. CONSTRUCTION SPOLS WILL NOT THE ALXIVED TO DE DEPOSITED ANY MERRICATE TO THE ORDING CONSTRUCTION. CONSTRUCTION ENDLS WILL AND EALING THE ALXIVED TO DE DEPOSITED ANY MERRICATE REGULATIONS. NO STRUCTION FORLS SHALL BE LANDSCAPING. OR OTHER OBSTRUCTIONS THAT IMPEDE DRAMAGE SHALL BE PLACED WITHIN THE LIMITS OF THE DRAMAGE EXSEMENTS SHOWN ON THE CONSTRUCTION DOLIMENTS. UPON COMPLETION OF TRENCHING. THE AREA WILL BE BOACHLIED AND COMPACTED TO ITS ORIGINAL CONDITION THENELESSING PITS TO BE OPEN AND UNATTENDED LONGERT THAN JAN UNIS SHALL BE PROTECTED TO WITH THE ADD ALT MODED YMALL AND DRAVEN THE DWANS REAM BACIELING. THE RENCHANGE THIS TO BE OPEN LONGERT THAN 3D DAYS AFTER STARTING EXCANTION SHALL BE BACKFILLED AND REVENT DWANS REAM BACIELING RESIDENCINC OF LARTHEN CHANNES AND LARYS REAM DEL PRODEONYMAIC AND MORESTATIC PORCESS AND REVENT DWANS REAM BACIELING. MICHON DRAVEN DAYS SHALL BE PROTECTED TO WITH START DALL PRODEONYMAIC AND HORDESTATIC PORCESS AND REVENT DWANS REAM BACIELING. MICHON DRAVEN DAYS SHALL BE PROFECTED ON WITH REAM AND START THE DRAVING START THE DRAVEN DWANS REAM BACIELING. MICHON DRAVEN DAYS DWAS BALL BE PROFECTED ON WITH AND DAYS AFTER STARTING START DE OPEN AND UNATER AREA MUST HAVE ESTRUCTURES AND RECAST THE START AT TOP OF CURB AT NOMINAL FACE OF CURB. MICHONS DAYS DAYS DE THE DRAVEN DYNOWY WILL ACCEPT THE DRAVEN DYNOWS. CONTRACTOR SHALL NOT PLACE WEEP HOLDS IN PRECAST DOS CULVERTS. THE CONTRACTOR SHALL NOT DRAVEN DYNOWS AND AND PLACE TO STRUCTURES SHALL BE CAST-IN-PLACE TO ENSURE PROPE	2.	THE CONTRACTOR SHALL NOTIFY BEXAR COUNTY AT LEAST 24 HOURS PRIOR TO THE INSTALLATION OF ANY DRAINAGE FACILITY WITHIN A DRAINAGE EASEMENT OR STREET RIGHT OF WAY NOT INDICATED ON THE CONSTRUCTION PLANS.
 CONTROLTON SPOLS WILL NOT BE ALLOYED TO BE DEPOSITED ANYWHERE WITHIN THE RIGHT OF WAY OR FLOODPLAIN WITHIN THE LIMITS OF THE PROJECT AND SHALL BE DEPOSED OFFSEN COMPLANCE WITH CURRENT PAPILCABLE REGULATIONS. NO STRUCTURE, FENCES, WALLS, LANDSCAPING, OR OTHER OBSTRUCTIONS THAT IMPEDE DRAINAGE SHALL BE PLACED WITHIN THE LIMITS OF THE DRAINAGE EASEMENTS SHOWN ON THE CONSTRUCTION DOCUMENTS. UPON COMPLETION OF TERENCIEMUL BE BACKFILLED WITH DEB BACKFILLED WITH DEPOSITED TO ITS ORIGINAL CONDITION. TRENCHESBORE PITS TO BE OPEN AND UNATTENDED LONGER THAN 24 HOURS SHALL BE PROTECTED TO MITHISTAND ALL HYDRODYNAMIC AND HYDROSTATIC FORCES AND PREVENT DOWNSTREAM MIRACITS. TRENCHESBORE PITS TO BE OPEN LONGER THAN 30 ADM SPRITE STATEMINE SECUNATION DATALL DE BACKFILLED WITH A SEMI-PERMANENT REPAR BACKFILL. UINROVED SECTIONS OF EARTHEN CHANNES AND/OR WATERWAYS WILL BE VEGETATED BY SEEDING OR SODDING. EICHTY FIVE PERCENT OF THE CHANNEL SURFACE AREA MUST HAVE ESTABLISHED VEGETATION BEFORE THE BEXAR COUNTY WILL ACCEPT THE CHANNEL FOR MAINTENANCE. CONTROL POINT FOR ALL CURB INLETS AND TREAS ARE TO BE TAKEN AT TOP OF CURB AT NOMINAL FACE OF CURB. COSTING-OF SHALL NOT FLACE WEEP HOLES IN PRECAST BOX CULVERTS. THE CONTROL POINT FOR ALL CURB INLETS ARE PROPOSED WITHIN DESIGN. THE FOLLOWING INLETS SHALL BE CAST-IN-PLACE TO ENSURE PROPER TIE INS TO CONNECTING PIPEIGA JADIOR CULVERTISI: SYSTEM B: B30 B30 B30 B30 B30 B30 B30 B30 B30 B30	3.	THE CONTRACTOR IS RESPONSIBLE FOR PROTECTING EXISTING DRAINAGE FACILITIES FROM DAMAGE. ANY DAMAGE TO EXISTING DRAINAGE SYSTEMS, WHETHER OR NOT SHOWN ON THE PLANS, SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO REPAIR AT HIS EXPENSE. THE CONTRACTOR SHALL NOTIFY BEXAR COUNTY AS SOON AS CONFLICTS WITH UTILITIES ARE ENCOUNTERED OR ANY DRAINAGE SYSTEM IS DAMAGED DURING CONSTRUCTION.
 No STRUCTURE: FENCES: WALLS LANDSCAPING. OR OTHER OBSTRUCTIONS THAT IMPEDE DRAINAGE SHALL BE PLACED WITHIN THE LIMITS OF THE DRAINAGE EASEMENTS SHOWN ON THE CONSTRUCTION DOCUMENTS. UPON COMPLETION OF THENCHING, THE AREA WILL BE BACKFILLED AND COMPACTED TO ITS ORIGINAL CONDITION. TRENCHES/BORE PITS TO BE OPEN AND UNATTERNED LONGER THAN 20 HOURS SHALL BE PROTECTED TO WITHSTAND ALL HYDRODYNAMIC AND HYDROSTATIC: FORCES AND PREVENT DOWNSTREAM WAYCCTS. TRENCHES/BORE PITS TO BE OPEN LONGER THAN 30 UNAS AFTER STANTING EXCLAVITION SHALL BE BACKFILLED WITH STEMPERAMMENT REPAR BACKTL. IMPROVED SECTIONS OF EARTHEN CHANNELS AND/OR WATERWAYS WILL BE VEGETATED BY SEEDING OR SODDING. EIGHTY FIVE PERCENT OF THE CHANNEL SURFACE AREA MUST HAVE ESTABLISHED VEGETATION BEFORE THE BEXAR COUNTY WILL ACCEPT THE CHANNEL FOR MAINTENANCE. CONTRACTOR SHALL NOT PLACE WEEP HOLES IN PRECAST BOX CULVERTS. THE CONTROL POINT FOR ALL CURB INLETS ARE TO BE TAKEN AT TOP OF CURB AT NOMINAL FACE OF CURB. CASTI-NPLACE INLETS AND PRECAST INLETS ARE ROPORSED WITHIN DESIGN. THE FOLLOWING INLETS SHALL BE CAST-IN-PLACE TO ENSURE PROPER TIE INS TO COMMECTING PIPE(S) AND/OR CULVERT(S). CASTI-NPLACE INLETS AND PRECAST INLETS ARE PROPOSED WITHIN DESIGN. THE FOLLOWING INLETS SHALL BE CAST-IN-PLACE TO ENSURE PROPER TIE INS TO COMMECTING PIPE(S) AND/OR CULVERT(S). SYSTEM B: B30 B30 B30 B30 B30 B30 B30 B30 B30 B30	4.	CONSTRUCTION SPOILS WILL NOT BE ALLOWED TO BE DEPOSITED ANYWHERE WITHIN THE RIGHT OF WAY OR FLOODPLAIN WITHIN THE LIMITS OF THE PROJECT AND SHALL BE DISPOSED OFFSITE IN COMPLIANCE WITH CURRENT APPLICABLE REGULATIONS.
 G. UPON COMPLETION OF TRENCHING. THE AREA WILL BE BACKFILLED AND COMPACTED TO ITS ORIGINAL CONTITION. TRENCHESIGORE PITS TO BE OPEN AND UNATTENDED LONGER THAN 24 HOURS SHALL BE PROTECTED TO WITHSTADA ULH PYDRONAMIC AND HYDROSTATIC FORCES AND PREVENT DOWNSTREAM MACTS. TRENCHESIGORE PITS TO BE OPEN LONGER THAN 30 DAYS AFTER STARTING EXCAVATION SHALL BE BACKFILLED WITH A SEMI-PERVENT OWNER TREAM BACKFILL. 7. IMPROVED SECTIONS OF EARTHEN CHAINNELS AND OR WATERWAYS WILL BE VEGETATED BY SEEDING OR SODDING. EIGHTY FIVE PERCENT OF THE CHAINNEL SANDOR WATERWAYS WILL BE VEGETATED BY SEEDING OR SODDING. EIGHTY FIVE PERCENT OF THE CHAINNEL SURFACE AREA MUST HAVE ESTABLISHED VEGETATION BEFORE THE BEXAR COUNTY WILL ACCEPT THE CHAINNEL FOR MAINTENANCE. 8. CONTRACTOR SHALL NOT PLACE WEEP HOLES IN PRECAST BOX CULVERTS. 9. THE CONTROL POINT FOR ALL CURB INLETS ARE TO BE TAKEN AT TOP OF CURB AT NOMINAL FACE OF CURB. 10. CASTINUPLACE INLETS AND PRECAST INLETS ARE PROPOSED WITHIN DESIGN. THE FOLLOWING INLETS SHALL BE CAST-IN-PLACE TO ENSURE PROPER TIE INS TO SYSTEM A: A20 A30 A55 SYSTEM B: B30 B30 B30 B30 B30 B30 B30 B30 B30 B30	5.	NO STRUCTURE, FENCES, WALLS, LANDSCAPING, OR OTHER OBSTRUCTIONS THAT IMPEDE DRAINAGE SHALL BE PLACED WITHIN THE LIMITS OF THE DRAINAGE EASEMENTS SHOWN ON THE CONSTRUCTION DOCUMENTS.
 IMPROVED SECTIONS OF EARTHEN CHANNELS AND/OR WATERWAYS WILL BE VEGETATED BY SEEDING OR SODDING, EIGHTY FIVE PERCENT OF THE CHANNEL SURFACE AREA MUST HAVE ESTABLISHED VEGETATION BEFORE THE BEXAR COUNTY WILL ACCEPT THE CHANNEL FOR MAINTENANCE. CONTRACTOR SHALL NOT PLACE WEEP HOLES IN PRECAST BOX CULVERTS. THE CONTROL POINT FOR ALL CURB INLETS ARE TO BE TAKEN AT TOP OF CURB AT NOMINAL FACE OF CURB. CONSTINUE FLAGE INLETS AND DRECAST INLETS ARE PROPOSED WITHIN DESIGN. THE FOLLOWING INLETS SHALL BE CAST-IN-PLACE TO ENSURE PROPER TIE INS TO CONNECTIVE IN PLACE STREED AND ADD STREED AND DRECAST INLETS ARE PROPOSED WITHIN DESIGN. THE FOLLOWING INLETS SHALL BE CAST-IN-PLACE TO ENSURE PROPER TIE INS TO CONNECTIVE IN PLACE A30 A50 A53 A50 B55 B90 B01 E50 B55 B90 B01 E50 E55 B90 B01 E50 E55 B90 B01 E50 E55 B90 B01 E50 E55 B90 B01 E50 E55 B90 B10 E10 E10 E10 E10 E10 E10 E10 E10 E10 E	6.	UPON COMPLETION OF TRENCHING, THE AREA WILL BE BACKFILLED AND COMPACTED TO ITS ORIGINAL CONDITION. TRENCHES/BORE PITS TO BE OPEN AND UNATTENDED LONGER THAN 24 HOURS SHALL BE PROTECTED TO WITHSTAND ALL HYDRODYNAMIC AND HYDROSTATIC FORCES AND PREVENT DOWNSTREAM IMPACTS. TRENCHES/BORE PITS TO BE OPEN LONGER THAN 30 DAYS AFTER STARTING EXCAVATION SHALL BE BACKFILLED WITH A SEMI-PERMANENT REPAIR BACKFILL.
 8. CONTRACTOR SHALL NOT PLACE WEEP HOLES IN PRECAST BOX CULVERTS. 9. THE CONTROL POINT FOR ALL CURB INLETS ARE TO BE TAKEN AT TOP OF CURB AT NOMINAL FACE OF CURB. 10. CASTI-INFLACE INLETS AND PRECAST INLETS ARE POPOSED WITHIN DESIGN. THE FOLLOWING INLETS SHALL BE CAST-IN-PLACE TO ENSURE PROPER TIE INS TO CONNECTING PRPE(s) AND/OR CULVERT(s): SYSTEM A: A20 A30 A55 A60 A55 B00 B00 B00 B00 B00 B00 B00 B00 B00 B	7.	IMPROVED SECTIONS OF EARTHEN CHANNELS AND/OR WATERWAYS WILL BE VEGETATED BY SEEDING OR SODDING. EIGHTY FIVE PERCENT OF THE CHANNEL SURFACE AREA MUST HAVE ESTABLISHED VEGETATION BEFORE THE BEXAR COUNTY WILL ACCEPT THE CHANNEL FOR MAINTENANCE.
 9. THE CONTROL POINT FOR ALL CURB INLETS ARE TO BE TAKEN AT TOP OF CURB AT NOMINAL FACE OF CURB. 10. CAST-IN-PLACE INLETS AND PRECAST INLETS ARE PROPOSED WITHIN DESIGN. THE FOLLOWING INLETS SHALL BE CAST-IN-PLACE TO ENSURE PROPER TIE INS TO CONNECTING PIPE(S) AND/OR CULVERT(S): SYSTEM A: A20 A30 A55 A60 A65 SYSTEM B: B30 B33 B36 B30 B36 B30 B36 B30 B30 B30 B30 B31 B30 B32 B30 B31 B30 B32 B30 B31 B30 B32 B30 B31 B30 B32 B30 B31 B30 B32 B30 B31 B30 B31 B30 B32 B30 B31 B30 B31 B31 B31 B31 B31 B31 B31 B31 B31 B31	8.	CONTRACTOR SHALL NOT PLACE WEEP HOLES IN PRECAST BOX CULVERTS.
 10. CAST-IN-PLACE INLETS AND PRECAST INLETS ARE PROPOSED WITHIN DESIGN. THE FOLLOWING INLETS SHALL BE CAST-IN-PLACE TO ENSURE PROPER TIE INS TO CONNECTING PIPE(S) AND/OR CULVERT(S): SYSTEM A: A0 A0 A0 A0 A0 A0 A0 A0 A0 A0 A0 A0 A0	Э.	THE CONTROL POINT FOR ALL CURB INLETS ARE TO BE TAKEN AT TOP OF CURB AT NOMINAL FACE OF CURB.
SYSTEM B: B30 B33 B40 B55 B60 B70 B80 B85 B90 ALL OTHER INLETS AND STRUCTURES SHALL BE PRECAST. 11. NO SEPARATE TXDOT UNIT ITEM OR DESCRIPTION IS ASSOCIATED WITH CAST-IN-PLACE INLETS. CONTRACTOR'S UNIT PRICE FOR STRUCTURE SHALL INCLUDE AND ACCOUNT FOR CAST-IN-PLACE INSTALLATION FOR STRUCTURE LISTED ABOVE IN NOTE 10. 12. FOR LOCATION OF UNDERGROUND ELECTRIC AND GAS FACILITIES, TELEPHONE CABLES, AND TIME WARNER CABLE TV CALL TEXAS STATE WIDE ONE CALL LOCATOR NUMBER 1-300-545-6005 48 HOURS PRIOR BEFORE BEGINING ANY EXCAVATION. DUE TO FEDERAL REGULATION TITLE 49. PART 192:181, C.P.S. MUST MAINTAIN ACCESS TO GAS VALVES TALL TIMES. THE CONTRACTOR WIST PROTECT AND WORK AROUND ANY GAS VALVES THAT ARE IN THE PROJECT AREA. THE CONTRACTOR WILL BE RESPONSIBIL FOR PROTECTING C.P.S. OVERHEAD AND UNDERGROUND ELECTRIC FACLITIES IF ADJACENT TO WORK AREA. THE CONTRACTOR WILL BE RESPONSIBILTY TO PROTECTING C.P.S. OVERHEAD AND UNDERGROUND ELECTRIC FACLITIES IF ADJACENT TO WORK AREAS. THE CONTRACTOR WILL HAVE RESPONSIBILTY TO PROTECT AND SUPPORT CABLE TV AND TELEPHONE COMPANY PLANT DURING CONTRACTOR AND/OR CONTRACTOR AND/OR CONTRACTOR. THE PLANE TAKEN FROM AVAILABLE RECORDS AND ARE NOT GURAANTEED TO BE ACCURRE. PROPOSED UTILITIES ARE SHOWN FOR REFERENCE ONLY. SEE FINAL RELAKED UTILITY PLANS FOR DETAILS CONTRACTORS AND/OR RAND/OR CONTRACTORS PLANS SINDEPENDENTLY RETAINED EMPLOYEE ON STRUCTURAL DESIGNCITICAL/SAFETY EQUIPMENT CONSULTANT, IF AND TELEPTONS FOLMPRATICE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITE(S) IN ORDER TO DEVELOP THE CONTRACTOR'S PLANS TANDARDS FOR TRENCH EXCAVATIONS. CONTRACTOR'S NADA'S TANDARDS FOR TRENCH EXCAVATIONS. CONTRACTOR'S NIDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL DEVELOP AND HAND AND AND AND AND AND AND AND AND AND	10.	CONNECTING PIPE(S) AND/OR CULVERT(S): SYSTEM A: A20 A50 A55 A60 A65
 ALL OTHER INLETS AND STRUCTURES SHALL BE PRECAST. 11. NO SEPARATE TXDOT UNIT ITEM OR DESCRIPTION IS ASSOCIATED WITH CAST-IN-PLACE INLETS. CONTRACTOR'S UNIT PRICE FOR STRUCTURE SHALL INCLUDE AND ACCOUNT FOR CAST-IN-PLACE INSTALLATION FOR STRUCTURE LISTED ABOVE IN NOTE 10. 12. FOR LOCATION OF UNDERGROUND ELECTRIC AND GAS FACILITIES, TELEPHONE CABLES, AND TIME WARNER CABLE TV CALL TEXAS STATE WIDE ONE CALL LOCATOR NUMBER 1-800-545-6005 48 HOURS PRIOR BEFORE BEGINNING ANY EXCAVATION. DUE TO FEDERAL REGULATION TITLE 49, PART 192.181, C.P.S. MUUT MAINTAN ACCESS TO GAS VALVES AT ALL TIMES. THE CONTRACTOR MUST PROTECT AND WORK AROUND ANY GAS VALVES THAT ARE IN THE PROJECT AREA. THE CONTRACTOR WILL BE RESPONSIBLE FOR PROTECTING C.P.S. OVERHEAD AND UNDERGROUND ELECTRIC FACILITIES IF ADJACENT TO WORK AREAS. THE CONTRACTOR WILL HAVE RESPONSIBLE FOR PROTECTING C.P.S. OVERHEAD AND UNDERGROUND ELECTRIC FACILITIES IF ADJACENT TO WORK AREAS. THE CONTRACTOR WILL HAVE RESPONSIBLITY TO PROTECT AND SUPPORT CABLE TV AND TELEPHONE COMPANY PLANT DURING CONSTRUCTION. THE EXISTENCE AND LOCATION OF UTILITIES INDICATED ON THE PLAN ARE TAKEN FROM AVAILABLE RECORDS AND ARE NOT GUARANTEED TO BE ACCURATE. PROPOSED UTILITIES ARE SHOWN FOR REFERENCE ONLY. SEE FINAL RELEASED UTILITY PLANS FOR DETAILS CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION STE(S) IN ORDER TO DEVELOP THE CONTRACTOR'S PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATIONS SHALL PROVIDE FOR ADEQUATE TRENCH SAFETY SYSTEMS THAT COMPLY WITH, AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. CONTRACTOR'S NUDERENT STALL AREIDED INTHE CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OF AND IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND T		SYSTEM B: B30 B35 B40 B50 B55 B60 B70 B80 B80 B85 B80 B80 B85 B80 B85 B80 B85 B80
 NO SEPARATE TXDOT UNIT ITEM OR DESCRIPTION IS ASSOCIATED WITH CAST-IN-PLACE INLETS. CONTRACTOR'S UNIT PRICE FOR STRUCTURE SHALL INCLUDE AND ACCOUNT FOR CAST-IN-PLACE INSTALLATION FOR STRUCTURE LISTED ABOVE IN NOTE 10. FOR LOCATION OF UNDERGROUND ELECTRIC AND GAS FACILITIES, TELEPHONE CABLES, AND TIME WARNER CABLE TV CALL TEXAS STATE WIDE ONE CALL LOCATOR NUMBER 1-800-545-6005 48 HOURS PRIOR BEFORE BEGINNING ANY EXCAVATION. DUE TO FEDERAL REGULATION TITLE 49, PART 192.181, C.P.S. MUST MAINTAIN ACCESS TO GAS VALVES AT ALL TIMES. THE CONTRACTOR MUST PROTECT AND WORK AROUND ANY GAS VALVES THAT ARE IN THE PROJECT AREA. THE CONTRACTOR WILL BE RESPONSIBLE FOR PROTECTING C.P.S. OVERHEAD AND UNDERGOUND ELECTRIC FACILITIES IF ADJACENT TO WORK AREAS. THE CONTRACTOR WILL HAVE RESPONSIBILE TO PROTECT AND SUPPORT CABLE TV AND TELEPHONE COMPANY PLANT DURING CONSTRUCTION. THE EXISTENCE AND LOCATION OF UTILITIES INDICATED ON THE PLAN ARE TAKEN FROM AVAILABLE RECORDS AND ARE NOT GUARANTEED TO BE ACCURATE. PROPOSED UTILITIES ARE SHOWN FOR REFFERENCE ONLY. SEE FINAL RELEASED UTILITY PLANS FOR DETAILS CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITE(S) IN ORDER TO DEVELOP THE CONTRACTOR'S PLANS TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S PLANS TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S PLANS TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S PLANS TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S PLANS TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S PLANS TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S PLANS TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S PLANS TO DEVELOP THE CONTRACTOR'S NEDEPENDENTLY		ALL OTHER INLETS AND STRUCTURES SHALL BE PRECAST.
12. FOR LOCATION OF UNDERGROUND ELECTRIC AND GAS FACILITIES, TELEPHONE CABLES, AND TIME WARNER CABLE TV CALL TEXAS STATE WIDE ONE CALL LOCATOR NUMBER 1-800-545-6005 48 HOURS PRIOR BEFORE BEGINNING ANY EXCAVATION. DUE TO FEDERAL REGULATION TITLE 49, PART 192.181, C.P.S. MUST MAINTAIN ACCESS TO GAS VALVES AT ALL TIMES. THE CONTRACTOR MUST PROTECT AND WORK AROUND ANY GAS VALVES THAT ARE IN THE PROJECT AREA. THE CONTRACTOR WILL BE RESPONSIBLE FOR PROTECTING C.P.S. OVERHEAD AND UNDERGROUND ELECTRIC FACILITIES IF ADJACENT TO WORK AREAS. THE CONTRACTOR WILL HAVE RESPONSIBILITY TO PROTECT AND SUPPORT CABLE TV AND TELEPHONE COMPANY PLANT DURING CONSTRUCTION. THE EXISTENCE AND LOCATION OF UTILITIES INDICATED ON THE PLAN ARE TAKEN FROM AVAILABLE RECORDS AND ARE NOT GUARANTEED TO BE ACCURATE. PROPOSED UTILITIES ARE SHOWN FOR REFERENCE ONLY. SEE FINAL RELEASED UTILITY PLANS FOR DETAILS CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITE(S) IN ORDER TO DEVELOP THE CONTRACTOR'S PLANS TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S PLANS SHALL PROVIDE FOR ADEQUATE TERENCH SAFETY YSTEMS THAT COMPLY WITH, AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURE ACTIONS. CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL DEVELOP AND IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.	11.	NO SEPARATE TXDOT UNIT ITEM OR DESCRIPTION IS ASSOCIATED WITH CAST-IN-PLACE INLETS. CONTRACTOR'S UNIT PRICE FOR STRUCTURE SHALL INCLUDE AND ACCOUNT FOR CAST-IN-PLACE INSTALLATION FOR STRUCTURE LISTED ABOVE IN NOTE 10.
	12.	FOR LOCATION OF UNDERGROUND ELECTRIC AND GAS FACILITIES, TELEPHONE CABLES, AND TIME WARNER CABLE TV CALL TEXAS STATE WIDE ONE CALL LOCATOR NUMBER 1-800-545-6005 48 HOURS PRIOR BEFORE BEGINNING ANY EXCAVATION, DUE TO FEDERAL REGULATION TITLE 49, PART 192.181, C.P.S. MUST MAINTAIN ACCESS TO GAS VALVES AT ALL TIMES, THE CONTRACTOR MUST PROTECT AND WORK AROUND ANY GAS VALVES THAT ARE IN THE PROTECTING C.P.S. OVERHEAD AND UNDERGROUND ELECTRIC FACILITES IF ADJACENT TO WORK AREAS. THE CONTRACTOR WILL BE RESPONSIBILITY TO PROTECTING C.P.S. OVERHEAD AND UNDERGROUND ELECTRIC FACILITES IF ADJACENT TO WORK AREAS. THE CONTRACTOR WILL HAVE RESPONSIBILITY TO PROTECT AND SUPPORT CABLE TV AND TELEPHONE COMPANY PLANT DURING CONSTRUCTION. THE EXISTENCE AND LOCATION OF UTILITIES INDICATED ON THE PLAN ARE TAKEN FROM AVAILABLE RECORDS AND ARE NOT GUARANTEED TO BE ACCURATE. PROPOSED UTILITIES ARE SHOWN FOR REFERENCE ONLY. SEE FINAL RELEASED UTILITY PLANS FOR DETAILS CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITE(S) IN ORDER TO DEVELOP THE CONTRACTOR'S PLANS TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACTO DOCUMENTS. THE CONTRACTOR'S PLANS SHALL PROVIDE FOR ADEQUATE TRENCH SAFETY SYSTEMS THAT COMPLY WITH, AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY WITH, AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL DEVELOP AND IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.



					0400-6008	0502-6001	0508-6001	0512-6009	0512-6010	0512-6033	Γ
РН	STG	SH#	HWY/ROAD	STATION LIMITS	CUT & RESTORE ASPH PAVING	BARRICADES SIGNS AND TRAFFIC HANDLING	CONSTRUCTING DETOURS	PORT CTB (FUR & INST) (LOW PROF) (TY 1)	PORT CTB (FUR & INST) (LOW PROF) (TY 2)	PORT CTB (MOVE) (LOW PROF) (TY 1)	(
					SY	мо	SY	LF	LF	LF	F
		SHEET 1 OF 3	WATSON	BEGIN PROJECT TO STA 117+00	85		276				F
		SHEET 2 OF 3	SW VERANO	STA 200+00 TO STA 206+00	46						F
1	2	SHEET 3 OF 3	SW VERANO	STA 206+00 TO STA 211+00	36						F
			PF	HASE 1 SUBTOTAL	167		276				F
		SHEET 1 OF 3	WATSON	STA 134+00 TO STA 139+00			674				F
		SHEET 2 OF 3	WATSON	STA 139+00 TO END PROJECT							F
2		SHEET 3 OF 3	SW VERANO	STA 206+00 TO STA 211+00							F
			PHASE	2 STAGE 1 SUBTOTAL			674				F
		SHEET 1 OF 1	WATSON	STA 135+00 TO STA 139+00							
2	2		PHASE	2 STAGE 2 SUBTOTAL							Γ
			PH	IASE 2 SUBTOTAL			674				
		SHEET 1 OF 5	WATSON	BEGIN PROJEC TO STA 117+00				650	20		Γ
		SHEET 2 OF 5	WATSON	STA 117+00 TO STA 126+00				900			Γ
		SHEET 3 OF 5	WATSON	STA 126+00 TO STA 134+00				775			Γ
3		SHEET 4 OF 5	WATSON	STA 134+00 TO STA 139+00				295	40		Γ
		SHEET 5 OF 5	WATSON	STA 139+00 TO END PROJECT				100	20		Γ
			PHASE	3 STAGE 1 SUBTOTAL				2720	80		
		SHEET 1 OF 2	WATSON	STA 134+00 TO STA 139+00							Γ
3	2	SHEET 2 OF 2	WATSON	STA 139+00 TO END PROJECT							
			PHASE	3 STAGE 2 SUBTOTAL							
		SHEET 1 OF 2	WATSON	STA 134+00 TO STA 139+00							
3	3	SHEET 2 OF 2	WATSON	STA 139+00 TO END PROJECT							
			PHASE	3 STAGE 3 SUBTOTAL							
3		SHEET 1 OF 1	WATSON	STA 134+00 TO STA 139+00							
Ľ			PHASE	3 STAGE 4 SUBTOTAL							L
		SHEET 1 OF 1	WATSON	STA 135+00 TO STA 139+00						20	L
3	5		PHASE	3 STAGE 5 SUBTOTAL						20	L
			PH	IASE 3 SUBTOTAL				2720	80	20	L
		SHEET 1 OF 5	WATSON	BEGIN PROJEC TO STA 117+00						60	L
		SHEET 2 OF 5	WATSON	STA 117+00 TO STA 126+00						20	L
4		SHEET 3 OF 5	WATSON	STA 126+00 TO STA 134+00						20	L
	'	SHEET 4 OF 5	WATSON	STA 134+00 TO STA 139+00						20	L
		SHEET 5 OF 5	WATSON	STA 139+00 TO END PROJECT							L
			PHASE	4 STAGE 1 SUBTOTAL						120	L
				PROJECT TOTAL	167	12	950	2720	80	140	L

s\WATSON_TCP_SUM.dgn 2 42 04 PM PLOTTED ON DESIGN FILENAME:

0512-6034	0512-6057				
PORT CTB (MOVE) (LOW PROF) (TY 2)	PORT CTB (REMOVE) (LOW PROF) (TY 1)				
IF	IF				
	LF				
200		·	1		
200			-		
200		NO DATE	-	REVISION	APPROVED
380	20				
63	20				
97	20				
700	80 80				
300	00				
		SANC	HEZ-SAL	AZAR	
		& ASS	OCIATES	S, LLC	<u>کچ</u>
				NO. 15685 11550 IH	10 WEST, SUITE 395
				SAN ANTON TEL: (210) 641	NIO, TEXAS 78230-1037 9999 FAX: (210) 641-6440 STRATION NO: E 2214
		OT THE ENGINEER	DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: 100410-00
			WAIS	UN KUA	ט
			TRAFFI		ROL
			SU	VIVIARY	
			SHE	ET 1 OF 2	
			B PUBLIC V	EXAR CC WORKS F	OUNTY DEPARTMENT
		FED.RD.	FEDERA	L AID PROJEC	T NO. PLAN SHT
		6			10
		TX	DIST.		BEXAR
		CONT.	SECT.	JOB	
					WAISUNKU

PH STA INVIGAD STATION LIMITS PORT CTS (MEDICAPIUS) VMC2NPAVINS (NCARENOV (MC2PAVINS) VMC2NPAVINS (NCARENOV (MC2PAVINS) VMC2NPAVINS (NCARENOV (MC2PAVINS) POLCE OFFICES PORTABLE (MCARENOV (MC2PAVINS) POLCE OFFICES POLCE OFFICES <						0512-6058	0662-6012	0662-6016	0662-6033	0662-6034	5000	6001-6002
Image: Control of the second	РН	STG	SH#	HWY/ROAD	STATION LIMITS	PORT CTB (REMOVE) (LOW PROF) (TY 2)	WK ZN PAV MRK NON-REMOV (W) 8"(SLD)	WK ZN PAV MRK NON-REMOV (W) 24"(SLD)	WK ZN PAV MRK NON-REMOV (Y) 4"(DOT)	WK ZN PAV MRK NON-REMOV (Y) 4"(SLD)	POLICE OFFICER	PORTABLE CHANGEABLE MESSAGE SIGN
1 2 SHEET 10F3 WMTSON BEORM PROJECT 10 STA 117-00 Image: Control of Sta 200-00 TO STA 200-00 2 1 SHEET 20F3 SW VERANO STA 200-00 TO STA 201-00 Image: Control of Sta 200-00 Image: Control of				1	1	LF	LF	LF	LF	LF	HR	EA
1 2 SHEET 2073 SW VERANO STA 200-00 TO \$TA 200-00 Image: Standard Control State 200 Image: State 200 I			SHEET 1 OF 3	WATSON	BEGIN PROJECT TO STA 117+00							
1 2 SHEET SOP3 WW TRANO STA 200-00 TSR 211-00 Image: STA 200-00 Image: STA 200-00 TSR 212-00 Image: STA 200-00 Image: STA 200-00 TSR 212-00			SHEET 2 OF 3	SW VERANO	STA 200+00 TO STA 206+00							
Image: Constraint of the second sec		2	SHEET 3 OF 3	SW VERANO	STA 206+00 TO STA 211+00							
2 1 SHEET 10F 3 INSECT 20F 3 SHEET 10F 3 SHEET 10F 1 VMATSON STA 128-001 OSTA 139-00 STA 228-001 OSTA 128-00 STA 238-001 OSTA 128-001 OSTA 128-00 STA 238-001 OSTA 128-001 OSTA 128-00 STA 238-001 OSTA 128-001 OSTA 128-				PF	HASE 1 SUBTOTAL						288	
2 1 SHEET 20F 3 WATSON STA 139-00 TO END PROJECT Image: constraint of the state			SHEET 1 OF 3	WATSON	STA 134+00 TO STA 139+00							
2 1 SHEET 10 F3 SW VERANO STA 226-070 STA 211+00 Image: Constraint of the state			SHEET 2 OF 3	WATSON	STA 139+00 TO END PROJECT							
Image: Control of the second state of the s	2	1	SHEET 3 OF 3	SW VERANO	STA 206+00 TO STA 211+00							
2 2 3HEET 10F1 WATSON STA 139+00 TO STA 139+00 40 2 PHASE 2 SUBTOTAL 940 40 40 3 1 SHEET 10F5 WATSON BEGIN PROJECT OS TA 117+100 11 60 1340 3 1 SHEET 30F5 WATSON STA 117+00 TO STA 128+00 11 60 1340 111 3 1 SHEET 30F5 WATSON STA 117+00 TO STA 128+00 1382 1111 1382 1111 1382 11111 1382 1111 1382 1111 1382 11111 1382 11111 1382 11111 1382 11111 1382 11111 1382 11111 1382 11111 1382 11111 1382 11111 1382 11111 1383 11111 1383 11111 1383 11111 1383 11111 1383 11111 1383 11111 1383 11111 1383 11111 1383 11111 1383 1111111 1383				PHASE	2 STAGE 1 SUBTOTAL						40	
2 2 PHASE 2 STAGE 2 SUBTOTAL 40 PHASE 2 SUBTOTAL 11 60 1340 80 3 1 SHEET 10F5 WATSON BEGIN PROJEC TO STA 137+00 11 60 1840 3 1 SHEET 20F5 WATSON STA 129+00 TO STA 139+00 79 23 1141 3 SHEET 10F5 WATSON STA 129+00 TO STA 139+00 79 23 1141			SHEET 1 OF 1	WATSON	STA 135+00 TO STA 139+00							
Image: Prior	2	2		PHASE	2 STAGE 2 SUBTOTAL						40	
3 3 4 SHEET 10F 5 WATSON BEGIN PROJECTO STA 117-00 11 60 1340 3 1 SHEET 20F 5 WATSON STA 129-00 TO STA 128-00 1800 1352 1352 5 SHEET 30F 5 WATSON STA 129-00 TO STA 138-00 79 23 1141 1 6 SHEET 30F 5 WATSON STA 139-00 TO STA 139-00 79 23 1141 1 7 PHASE 3 STAGE 1SUBTOTAL 79 34 80 5753 40 7 SHEET 10F 2 WATSON STA 139-00 TO END PROJECT 1 40 1 1 40 7 SHEET 10F 2 WATSON STA 139-00 TO END PROJECT 1 40 1 40 1 1 40 1 1 40 1 1 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 <td></td> <td></td> <td></td> <td>PH</td> <td>IASE 2 SUBTOTAL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>80</td> <td></td>				PH	IASE 2 SUBTOTAL						80	
3 1 SHEET 20F5 WATSON STA 117+00 TO STA 128-00 0 1 1000 1000 1000 SHEET 30F5 WATSON STA 128-00 TO STA 138+00 79 23 1141 1 SHEET 40F5 WATSON STA 138+00 TO STA 138+00 79 23 1141 1 SHEET 40F5 WATSON STA 138+00 TO STA 138+00 79 34 60 5753 40 SHEET 40F5 WATSON STA 138+00 TO STA 139+00 79 34 60 5753 40 SHEET 10F2 WATSON STA 134+00 TO STA 139+00 1 4 40 1 SHEET 10F2 WATSON STA 134+00 TO STA 139+00 1 40 40 1 SHEET 10F2 WATSON STA 134+00 TO STA 139+00 1 40 40 1 SHEET 10F1 WATSON STA 134+00 TO STA 139+00 1 40 40 1 SHEET 10F1 WATSON STA 134+00 TO STA 139+00 2020 1 40 1			SHEET 1 OF 5	WATSON	BEGIN PROJEC TO STA 117+00			11	60	1340		
$ \begin{array}{ c c c c c c c } \hline 1 & \frac{SHEET 3 0 F 5}{SHEET 4 0 F 5} & WATSON & STA 126+00 TO STA 139+00 & 79 & 23 & 1141 &$			SHEET 2 OF 5	WATSON	STA 117+00 TO STA 126+00					1800		
3 1 SHEET 4 OF 5 WATSON STA 134-00 TO STA 139-00 79 23 1141 3 4 SHEET 5 OF 5 WATSON STA 139-00 TO END PROJECT 79 34 60 5753 40 3 2 SHEET 10F 2 WATSON STA 139-00 TO STA 139-00 79 34 60 5753 40 3 2 SHEET 10F 2 WATSON STA 139-00 TO STA 139-00 79 34 60 5753 40 3 2 SHEET 10F 2 WATSON STA 139-00 TO STA 139-00 70			SHEET 3 OF 5	WATSON	STA 126+00 TO STA 134+00					1352		
No. SHEET 5 OF 5 WATSON STA 139+00 TO END PROJECT 79 34 60 5753 40 3 2 SHEET 10F2 WATSON STA 139+00 TO STA 139+00 1 60 5753 40 3 2 SHEET 10F2 WATSON STA 139+00 TO END PROJECT 1	3		SHEET 4 OF 5	WATSON	STA 134+00 TO STA 139+00		79	23		1141		
Image: Phase 3 STAGE 1 SUBTOTAL 79 34 60 5753 40 3 2 SHEET 10F2 WATSON STA 134+00 TO STA 139+00			SHEET 5 OF 5	WATSON	STA 139+00 TO END PROJECT					120		
3 2 SHEET 10F 2 WATSON STA 134+00 TO STA 139+00 <th<< td=""><td></td><td></td><td></td><td>PHASE</td><td>3 STAGE 1 SUBTOTAL</td><td></td><td>79</td><td>34</td><td>60</td><td>5753</td><td>40</td><td></td></th<<>				PHASE	3 STAGE 1 SUBTOTAL		79	34	60	5753	40	
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $			SHEET 1 OF 2	WATSON	STA 134+00 TO STA 139+00							
$ \begin{array}{ c c c c c c c } \hline \begin{tabular}{ c c c c c c c } \hline & \ & \ & \ & \ & \ & \ & \ & \ & \ &$	3	2	SHEET 2 OF 2	WATSON	STA 139+00 TO END PROJECT							
$ \begin{array}{ c c c c c c c c } \hline \ \ \ \ \ \ \ \ \ \ \ \ \$				PHASE	3 STAGE 2 SUBTOTAL						40	
$ \frac{3}{3} \frac{3}{3} \frac{\text{SHEE 2 OF 2}}{3} \frac{\text{WATSON}}{3} \frac{\text{STA 139+00 TO END PROJECT}}{3} \frac{1}{3} \frac{3}{3} \frac{\text{SHEE 1 OF 2}}{3} \frac{\text{WATSON}}{3} \frac{\text{STA 139+00 TO END PROJECT}}{3} \frac{1}{3} \frac{3}{3} \frac{\text{SHEE 1 OF 1}}{3} \frac{\text{WATSON}}{3} \frac{\text{STA 134+00 TO STA 139+00}}{3} \frac{\text{STA 134+00 TO STA 139+00}}{3} \frac{1}{3} $			SHEET 1 OF 2	WATSON	STA 134+00 TO STA 139+00							
$ \frac{1}{3} + \frac{1}{4} + 1$	3	3	SHEET 2 OF 2	WATSON	STA 139+00 TO END PROJECT							
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$				PHASE	3 STAGE 3 SUBTOTAL						40	
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$			SHEET 1 OF 1	WATSON	STA 134+00 TO STA 139+00							
$ \frac{1}{3} \frac{1}{5} 1$	3	4		PHASE	3 STAGE 4 SUBTOTAL						40	
3 5 PHASE 3 STAGE 5 SUBTOTAL 2020 79 34 60 5753 200 4 1 SHEET 10F 5 WATSON BEGIN PROJECT O STA 117+00 380 11 63 1340 5 SHEET 2 OF 5 WATSON STA 117+00 TO STA 126+00 160 11 63 1340			SHEET 1 OF 1	WATSON	STA 135+00 TO STA 139+00	2020						
Image: Phase 3 substoral 2020 79 34 60 5753 200 4 SHEET 10F5 WATSON BEGIN PROJECT 0 STA 117400 380 11 63 1340 5 SHEET 2 OF 5 WATSON STA 117400 TO STA 126400 160 1800 1800	3	5		PHASE	3 STAGE 5 SUBTOTAL	2020					40	
A SHEET 10F5 WATSON BEGIN PROJEC TO STA 117+00 380 11 63 1340 4 SHEET 20F5 WATSON STA 117+00 TO STA 126+00 160 1 63 1800 1 63 1600 1 63 1				PH	IASE 3 SUBTOTAL	2020	79	34	60	5753	200	
A SHEET 2 OF 5 WATSON STA 117+00 TO STA 126+00 160 1800 1800 1800 SHEET 3 OF 5 WATSON STA 126+00 TO STA 134+00 63 63 1600			SHEET 1 OF 5	WATSON	BEGIN PROJEC TO STA 117+00	380		11	63	1340		
4 1 SHEET 3 OF 5 WATSON STA 126+00 TO STA 134+00 63 1600 1600 1600 SHEET 4 OF 5 WATSON STA 134+00 TO STA 139+00 97 1 384 1 1 SHEET 5 OF 5 WATSON STA 139+00 TO END PROJECT 1 800 1 1 FHASE 4 STAGE 1 SUBTOTAL 700 11 63 5924 100 1 FUNCTIONAL 2720 79 45 123 11677 668 4			SHEET 2 OF 5	WATSON	STA 117+00 TO STA 126+00	160				1800		
4 1 SHEET 4 OF 5 WATSON STA 134+00 TO STA 139+00 97 384 SHEET 5 OF 5 WATSON STA 139+00 TO END PROJECT 800 800 <t< td=""><td></td><td> _ [</td><td>SHEET 3 OF 5</td><td>WATSON</td><td>STA 126+00 TO STA 134+00</td><td>63</td><td></td><td></td><td></td><td>1600</td><td></td><td></td></t<>		_ [SHEET 3 OF 5	WATSON	STA 126+00 TO STA 134+00	63				1600		
SHEET 5 OF 5 WATSON STA 139+00 TO END PROJECT 800 800 PHASE 4 STAGE 1SUBTOTAL 700 11 63 5924 100 VEXTEX PROJECT TOTAL 2720 79 45 123 11677 668 4	4		SHEET 4 OF 5	WATSON	STA 134+00 TO STA 139+00	97				384		
PHASE 4 STAGE 1 SUBTOTAL 700 11 63 5924 100 PROJECT TOTAL 2720 79 45 123 11677 668 4			SHEET 5 OF 5	WATSON	STA 139+00 TO END PROJECT					800		
PROJECT TOTAL 2720 79 45 123 11677 668 4		PHASE 4 STAGE 1 SUBTOTAL						11	63	5924	100	
		· ·			PROJECT TOTAL	2720	79	45	123	11677	668	4

PLOTTED ON: 2:42:05 PM DESIGN FILENAME: \\Ssa-main\pmwork\Jobs\15024-Watson-Rd\Techprod\Summaries\WATSON_TCP_SUM.dgn



		0160 6003	0162 6002	0168 6001	0192 6013	0506 6004	0506 6011	0506 6020	0506 6024	0506 6038	0506 6039	0506 6041	0506 6043
PLAN SHEET NO.	STATION TO STATION	FURNISHING AND PLACING TOPSOIL (4")	BLOCK SODDING	VEGETATIVE WATERING	MULCH	ROCK FILTER DAMS (INSTALL) (TY 4)	ROCK FILTER DAMS (REMOVE)	CONSTRUCTION EXITS (INSTALL) (TY 1)	CONSTRUCTION EXITS (REMOVE)	TEMP SEDMT CONT FENCE (INSTALL)	TEMP SEDMT CONT FENCE (REMOVE)	BIODEG EROSN CONT LOGS (INSTL) (12")	BIODEG EROSN CONT LOGS (REMOVE)
SW3P Pł	IASE-1SHEETS	SY	SY	MG	SY	LF	LF	SY	SY	LF	LF	LF	EA
52	BEGIN TO 117+00	1962	299	42	1962	30	30	444	444	1247	1247	220	220
53	117+00 TO 126+00	2733		43	2733					1810	1810	260	260
54	126+00 TO 134+00	2085		33	2085					1634	1634	180	180
55	134+00 TO 139+00	6932		108	6932	60	60			1366	1366	340	340
56	139+00 TO END	1255		20	1255			444	444	458	458	40	40
57	204+00 TO END	4463		70	4463	15	15			658	658		
	PROJECT TOTALS	19430	299	314	19430	105	105	888	888	7173	7173	1040	1040

Z E0543800_Bx_Co_W PLOTTED BY: evaldez PLOTTED SCALE: 1:1 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOT DRIVER: WATSON_BW_PDF.2:51:48 PM PLOTTED ON: 6/25/2020 @ 12:51:48 PM PLOTTED ON: 6/25/2020 @ 12:51:48 PM

DATE

INITIALS

ORIGINATED BY: CHECKED BY: BACK CHECKED BY: CORRECTED BY: VERIFIED BY:



NOTE:

- SW3P BMPS TO BE INSTALLED CONCURRENT WITH TCP PHASING AS REQUIRED.
 COORDINATE WITH BEXAR COUNTY REPRESENTATIVE FOR CONSTRUCTION EXIT LOCATION.

		0100 6001	0100 6002	0106 6002	0110 6001	0132 6003	0216 6001	0275 6001	0275 6002	0316
PLAN SHEET NO.	STATIONTO STATION	* PREPARING ROW	PREPARING ROW	OBLITERATING ABANDONED ROAD	EXCAVATION (ROADWAY)	EMBANKMENT (FINAL)(ORD COMP)(TY B)	PROOF ROLLING	CEMENT	CEMENT TREAT (EXIST MATL) (6")	ASPH (MUI
ROADWAY	SHEETS	AC	STA	SY	CY	CY	HR	TON	SY	G
97	BEGIN TO 113+00	1					4	20	1803	
98	113+00 TO 117+00		4				6	30	2491	
99	117+00 TO 121+50		5				7	36	2945	
100	121+50 TO 126+00		5				7	36	2750	
101	126+00 TO 130+00		4				6	32	2444	
102	130+00 TO 134+00		4	146			5	33	2538	
103	134+00 TO 139+00		5	759				42	5291	
105	139+00 TO END		4	79			5	10	936	1.
PROJECT	TOTALS	1	30	984	16534	715	40	239	21198	1

		0316 6175	0340 6011	0340 6034	0340 6122	0360 60XX	0432 6001	0528 6001	0529 6002	0529 6004
PLAN SHEET NO.	STATION TO STATION	AGGR(TY-B GR-4 SAC-B)	D-GR HMA(SQ) TY-B PG64-22	D-GR HMA(SQ) TY-C PG64-22	D-GR HMA(SQ) TY-D PG70-22	CONC PAV (JOINT REINF) (11")	RIPRAP (CONC)(4 IN)	COLORED TEXTURED CONC (4")	CONC CURB (TY II)	CONC CURB (MONO (TY I)
ROADWA	AY SHEETS	СҮ	TON	TON	TON	SY	СҮ	SY	LF	LF
97	BEGIN TO 113+00		595	364	175				584	
98	113+00 TO 117+00		595	487	185		20		1424	
99	117+00 TO 121+50		972	571	219				892	
100	121+50 TO 126+00		908	528	176				900	
101	126+00 TO 130+00		807	469	156				800	
102	130+00 TO 134+00		838	490	167				800	
103	134+00 TO 139+00		1746	1208	491	1025		274	1415	270
105	139+00 TO END	8	309	197	94				403	
PROJEC		8	6770	4314	1663	1025	20	274	7218	270

		0530 6005	05316001	05316004	05316016	0536 6002	0560 6002	6056 6001
PLAN SHEET NO.	STATION TO STATION	DRIVEWAYS(ACP)	CONC SIDEWALKS (4")	CURB RAMPS (TY 1)	CURB RAMPS (TY 21)	CONC MEDIAN	MAILBOX INSTALL-D (TWG-POST) TY 1	PREFORMED IN-LANE(TRANS) RUMBLE STRIP
ROADWAY	SHEETS	SY	SY	EA	EA	SY	EA	LF
97	BEGIN TO 113+00	20	312			64		
98	113+00 TO 117+00	135	429				1	
99	117+00 TO 121+50		487			602		
100	121+50 TO 126+00	45	500			800		
101	126+00 TO 130+00		445			711		40
102	130+00 TO 134+00		445			705		40
103	134+00 TO 139+00		505	18	2	3365		160
105	139+00 TO END							40
PROJECT	TOTALS	200	3123	18	2	6247	1	280

5001
(IOPTION)
L
Ð
9

TE OF TE JULIO RAMOS THE SEAL APPEARING ON THIS DOCUMENT WAS AUTHORIZED BY JULIO RAMOS, P.E. 107672 107672 6/25/2020 NOVONAL ENGIN INIL ENGINEERING CONSULTANTS BON DURDEN, INC. THERE REGISTRATION NO.: 7243 THERE REGISTRATION NO.: 7244 TBPLS REGISTRATION NO.: 104410-00 BEXAR COUNTY PUBLIC WORKS DEPARTMENT WATSON ROAD ROADWAY SUMMARY SHEET 1 OF 1 Texas Department of Transportation 7 C 2019 PLAN SHI NO. 13 FED.RD. DIV.NO. FEDERAL AID PROJECT NO. 6 -----
 STATE
 DIST.
 COUNTY

 TEXAS
 SAT
 BEXAR

 CONT.
 SECT.
 JOB
 HIGHWAY / STREET

 0915
 12
 562
 WATSON RD

NOTES: * 1. PREP ROW (AC) WILL INCLUDE THE DEMOLITION OF THE 3 STRUCTURES.

	DRAINAGE SUMMARY																						
ITEM No.	104 6009	104 6015	104 6021	160 6003	162 6002	400 6008	401 6001	402 6001	420 6002	420 6057	432 6007	450 6103	462 6001	462 6004	464 6005	464 6007	464 6008	464 6030	464 6034	496 6002	497 6007	529 6001	531 6001
SHEET No.	REMOVING CONC (RIPRAP)	REMOVING CONC (SIDEWALKS)	REMOVING CONC (CURB)	FURNISHING AND PLACING TOPSOIL(4")	BLOCK SODDING	CUT & RESTORE ASPH PAVING	FLOWABLE FILL	TRENCH EXCAVATION PROTECTION	CL A CONC (MISC)	CL C CONC (WINGWALLS)	5" RIPRAP (CONC) (CL C)	RAIL (TY PR11)	CONC BC	(4 FT X 3 FT)	RE (24 IN)	C PIPE (CI (30 IN)	_ III) (36 IN)	RC PIPE (ARCH) (CL III) (DES 3)	RC PIPE (ARCH) (CL III) (DES 5)	REMOV STR (INLET)	REMOV STR (PIPE)	CONC CURB (TY1)	CONC SIDEWALKS (4")
	SY	SY	LF	SY	SY	SY	CY	LF	CY	CY	CY	LF	LF	LF	LF	LF	LF	LF	LF	EA	LF	LF	SY
132	0	0	0	0	0	0	4.7	0	4	0	0	0	136	0	0	0	0	0	121	0	0	0	0
133	0	0	0	0	0	0	9.3	0	6	0	28	0	0	0	0	0	0	392	57	0	0	0	0
134	0	0	0	0	0	0	6.3	0	3	0	0	0	0	0	0	0	0	309	0	0	0	0	0
135	0	0	0	0	0	0	3.4	0	4	0	26	0	0	0	0	0	0	144	0	0	0	0	0
136	0	0	0	0	0	0	6.8	0	6	0	11	0	0	0	293	0	0	94	0	0	0	0	0
137	0	0	0	0	0	0	0.0	262	3	0	6	0	0	0	132	209	53	0	0	0	0	0	0
138	0	0	0	0	0	0	0.0	443	4	0	0	0	0	0	65	0	378	0	0	0	0	0	0
139	0	0	0	0	0	0	0.0	488	6	0	6	0	0	0	283	0	205	0	0	0	0	0	0
140	0	0	0	0	0	0	0.0	311	3	0	0	0	0	97	35	0	179	0	0	0	0	0	0
141	0	0	0	323	323	0	0.0	394	2	0	0	0	0	394	0	0	0	0	0	0	0	0	0
142	16	23	40	350	350	35	0.0	393	5	0	6	0	0	393	0	0	0	0	0	1	135	40	23
143	0	0	0	0	0	0	0.0	140	2	0	0	0	0	0	140	0	0	0	0	0	0	0	0
144	0	0	0	0	0	0	0.0	0	0	0	10	0	0	0	0	0	0	0	0	0	0	0	0
149	0	0	0	0	0	0	0.0	198	1	18	43	86	198	0	0	0	0	0	0	0	225	0	0
TOTALS	16	23	40	673	673	35	30	2629	49	18	136	86	334	884	948	209	815	939	178	1	360	40	23

		JL	INCTION E	30X & INLE	T SUMMA	RY						
ITEM No.	465 6006	465 6009	465 6011	465 6013	465 6024	465 6054	465 6176	465 6338				
	JCTB	OX (COML)	(PJB)	INLET (COMPL)								
SHEET No.	(4FTX4FT)	(5FTX5FT)	(6FTX6FT)	(PCO)(3FT)	(PCO)(5FT)	(PSL)(SL) (3FTX3FT)	(CURB)(TY C1)	(TY ARMOR CURB SLOT)				
	EA	EA	EA	EA	EA	EA	EA	EA				
132	0	1	0	0	4	0	0	0				
133	0	1	0	0	4	0	0	0				
134	1	0	0	0	2	0	1	0				
135	2 0		0	0	0	1	0	0				
136	0 0		0	2	4	2	0	0				
137	0	0	0	0	4	1	0	0				
138	0	0	0	2	4	0	0	0				
139	0	1	0	8	2	1	0	0				
140	0	0	1	0	4	0	0	0				
141	0	0	1	0	0	0	0	0				
142	0	0	2	0	0	0	1	0				
143	0	0	0	2	2	0	0	0				
144	0	0	0	0	0	0	0	2				
TOTALS	3	3	4	14	30	5	2	2				

PLOTTED BY: ivette PLOTTED SCALE: 1:1 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:36:16 AM PLOTTED ON: 6/24/2020 @ 11:36:16 AM DESIGN FILENAME: Z:\Projects\Watson Road\Drainage\M058-DRN-SUM



		0636 6001	0644 6001	0644 6017	0666 6030	0666 6036	0666 6048	0666 6054	0666 6078	0666 6099	0666 6156
PLAN SHEET NO.	STATIONTO STATION	ALUMINUM SIGNS (TY A)	IN SM RD SN SUP&AM TY10BWG(1)SA(P)	IN SM RD SN SUP&AM TY10BWG(2)SA(P)	REFL PAVMRK TY I (W) 8" (DOT) (100MIL)	REFL PAVMRK TY I (W) 8" (SLD) (100MIL)	REFL PAVMRK TY I (W) 24" (SLD) (100MIL)	REFL PAVMRK TY I (W) (ARROW) (100MIL)	REFL PAVMRK TY I (W) (WORD) (100MIL)	REF PAV MRK TY I (W) 18" (YLD TRI) (100MIL)	REFL PAVMRK TY I (Y) (MED NOSE) (100MIL)
PAVEMENTMA	RKING SHEETS	SF	EA	EA	LF	LF	LF	EA	EA	EA	EA
186	BEGIN TO 117+00	41	5	1		375	40	4	4		1
187	117+00 TO 126+25	24	4			90		1	1		
188	126+25 TO 134+25	6	1			466		2	1		
189	134+25 TO 139+00	169	30		81	2414	340	4	2	24	
190	139+00 TO END	7	1			39				8	
	PROJECT TOTALS	247	41	1	81	3384	380	11	8	32	1

		0666 6300	0666 6303	0666 6315	0672 6009	0672 6010
PLAN SHEET NO.	STATION TO STATION	RE PM W/RET REQ TY I (W) 4" (BRK) (100MIL)	RE PM W/RET REQ TY I (W) 4" (SLD) (100MIL)	RE PM W/RET REQ TY I (Y) 4" (SLD) (100MIL)	REFL PAVMRKR TY II-A-A	REFL PAVMRKR TY II-C-R
PAVEMENT MA	RKING SHEETS	LF	LF	LF	EA	EA
186	BEGIN TO 117+00	578	1243	880	44	19
187	117+00 TO 126+25	1809	1800	1803	91	91
188	126+25 TO 134+25	1305	1600	1600	80	66
189	134+25 TO 139+00	190	1369	1563	78	10
190	139+00 TO END		801	967	49	
	PROJECT TOTALS	3882	6813	6813	342	186

E0543800 Bx Co PLOTTED BY: evaldez PLOTTED SCALE: 1:100 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 12:51:51 PM PLOTTED ON: 6/25/2020 @ 12:51:51 PM



		WATSON		
ST	A 125+50.	00 TO STA ²	141+50.00	
	CUT	FILL	АССИМ СИТ	ACCUM FILL
TATION NUMBER	(CY)	(CY)	(CY)	(CY)
25+50.00	231	1	4509	634
26+00.00	205	2	4714	636
26+50.00	209	2	4923	638
27+00.00	224	2	5147	640
27+50.00	240	1	5387	641
28+00.00	253	0	5640	641
28+50.00	266	0	5906	641
29+00.00	283	0	6189	641
29+50.00	302	0	6491	641
30+00.00	319	0	6810	641
30+50.00	333	0	7143	641
31+00.00	336	0	7479	641
31+50.00	312	0	7791	641
32+00.00	287	0	8078	641
32+50.00	301	0	8379	641
33+00.00	348	0	8727	641
33+50.00	397	1	9124	642
34+00.00	475	1	9599	643
34+50.00	524	0	10123	643
35+00.00	556	0	10679	643
35+50.00	583	0	11262	643
36+00.00	663	1	11925	644
36+50.00	744	1	12669	645
.37+00.00	698	0	13367	645
37+50.00	563	0	13930	645
38+00.00	373	1	14303	646
38+50.00	253	3	14556	649
39+00.00	182	4	14738	653
39+50.00	108	11	14846	664
40+00.00	71	17	14917	681
40+50.00	63	14	14980	695
41+00.00	60	8	15040	703
41+50.00	0	0	15040	703

5

	w	ATSON		
STA	110+50.0	0 TO STA	125+00.00	
	CUT	FILL .	ACCUM CUT	ACCUM FILI
STATION NUMBER	(CY)	(CY)	(CY)	(CY)
110+50.00	0	0	0	0
111+00.00	76	94	76	94
111+50.00	104	26	180	120
112+00.00	112	18	292	138
112+12.60	25	5	317	143
112+50.00	63	21	380	164
113+00.00	49	51	429	215
113+50.00	34	69	463	284
114+00.00	52	64	515	348
114+50.00	83	42	598	390
115+00.00	121	21	719	411
115+50.00	169	9	888	420
116+00.00	180	6	1068	426
116+50.00	181	3	1249	429
116+71.27	79	1	1328	430
117+00.00	96	2	1424	432
117+50.00	155	10	1579	442
118+00.00	156	18	1735	460
118+50.00	157	15	1892	475
119+00.00	148	16	2040	491
119+50.00	143	18	2183	509
120+00.00	135	24	2318	533
120+50.00	137	24	2455	557
121+00.00	140	22	2595	579
121+50.00	134	25	2729	604
122+00.00	150	17	2879	621
122+27.01	94	3	2973	624
122+50.00	84	2	3057	626
123+00.00	191	4	3248	630
123+50.00	228	3	3476	633
124+00.00	260	0	3736	633
124+50.00	274	0	4010	633
125+00.00	268	0	4278	633

ă 13800 PLOTTED BY: evaldez PLOTTED SCALE: 1:125 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pttcfg PLOTTED ON: 6/25/2020 @ 12:51:52 PM PLOTTED ON: 6/25/2020 @ 12:51:52 PM STATION N 201+50.00 202+00.00 202+50.00 203+00.00

	VERANO												
STA 201+50.00 TO STA 203+00.00													
	CUT	FILL	АССИМ СИТ	ACCUM FILL									
IUMBEF	(CY)	(CY)	(CY)	(CY)									
0	526	3	526	3									
0	450	0	976	3									
0	304	4	1280	7									
0	214	5	1494	12									



				SUM	MARY	OF SMA	LL SIGNS						
								SN	IRD SGN ASSM TY X	(XXX (X) XX (X-XXX	X)	BRIDGE	E MOUN
					PEA	PEG	Post Type	Posts	Anchor Type	Moun	ting Designation	CLEARAN (SEE N	NCE SI
PLAN SHEET NO.	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM TY	EXAL ALUMINUM TY	FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	10R 2	UA=Univer-Conc UB=Univer-Bolt SA=Slip-Conc SB=Slip-Bolt WS=Wedge Steel WP=Wedge Plastic	PREFABRICATED P = "Plain" T = Prefab. "T" U = Prefab. "U"	1EXT or 2EXT =# of Ext. BM = Extruded Wind Beam WC = 1.12 #/ft Wing Chan. EXAL= Extruded Aluminum	TYPEN	TVDE S
10	f 5												
	1	R2-1		30X36	X		10BWG	1	SA	P			_
	2	W1-2		36X36	X		10BWG	1	SA	P			
	3	W1-8		18X24	x		10BWG	1	SA SA	P			-
		W1-8		18X24	X		10BWG			· ·			
		W1-8		18X24	x		10BWG						
	4	W3-3		30X30	Х		10BWG	1	SA	Р			
	5	W1-6		48X24	x		10BWG	2	SA	Р			
2 of	f 5												-
	1	W3-5		36X36	+ ×		10BWG		SA SA	P P			+
	2	W1-2 W1-8		30730 18824	× v	$\left \right $	10BWG	1	5A SA	р Р Р		+	+
	~	W1-8		18X24	x x		10BWG	1	SA	<u>р</u>		1	+
3 0	f 5												
	1	R6-5P		30X30	X		10BWG	1	SA	P			
	2	R3-8LT_R		30X30	X		10BWG	1	SA	Р			-
					-								-
4 0	f 5												
	1	W11-2		36X36	x		10BWG	1	SA	Р			
		W11-2		36X36	x		10BWG	1	SA	Р			
		W11-2		36X36	х		10BWG	1	SA	Р			
		W11-2		36X36	Х		10BWG	1	SA	Р			
		W11-2		36X36	x		10BWG	1	SA	Р			
		W11-2		36X36	X		10BWG	1	SA	P		_	_
		W11-2 W11-2		36X36	×		10BWG	1	SA SA	P			+
		W11-2 W11-2		36X36	1 x		10BWG	1	SA	г Р			
		W11-2		36X36	X		10BWG	1	SA	P			
		W11-2		36X36	x		10BWG	1	SA	Р			
	1A	W16-7P		24X12	Х		10BWG	1	SA	Р			
		W16-7P		24X12	X		10BWG	1	SA	Р			
		W16-7P		24X12	X		10BWG	1	SA	P			
		W16-7P W16-7P		24X12			10BWG	1	SA SA	Р Р			
		W16-7P		24X12	1 x		10BWG	1	SA	P			
		W16-7P		24X12	X		10BWG	1	SA	P			
		W16-7P		24X12	X		10BWG	1	SA	Р			
		W16-7P		24X12	Х		10BWG	1	SA	P			
		W16-7P		24X12	X		10BWG	1	SA	P -			
		W16-7P		24X12	+ × ▼	$\left \right $	10BWG		SA SA	P		-	+
	4	R1-2		40740740	×		10BWG	1	SA SA	P P			+
		R1-2		48X48X48	X		10BWG	1	SA	P			
	3	R6-4		30X24	X		10BWG	1	SA	Р			
		R6-4		30X24	Х		10BWG	1	SA	Р			
		R6-4		30X24	X		10BWG	1	SA	Р			
	4	R6-5P		30X30	X		10BWG		SA	P			-
	5	R3-81 T P		30X30	× ×		10BWG	1	5A SA			+	+
	6	R3-8LT		307.30	+		100000		5A				
				1	1		L			1			
5 0	f 5												
	1	R1-2		48X48X48	X		10BWG	1	SA	P			1
					1	1		1		1	1	1	1

.OT DRIVER: WATSON_BW_PDF.pltcfg .OTTED ON: 6/25/2020 @ 12:51:54 PM :SIGN FILENAME: X:\data\Infra\Proj_2016\E0543800_Bx_Co_Watson\CADD\PLAN_SHTS\SUM\WATSON_SUM_SM_SGN.

NKS THICKNESS
Minimum Thickness
0.080''
0.100''
0.125''

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website.

http://www.txdot.gov/

NOTE:

- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
- For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS)Standard Sheet.
- For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).

-	-	-			-
-	-	-			-
NO	DATE	F	REVISION		APPROVED
111111111111	JULIO F	RAMOS 672 AL EN	THE SEAL AI DOCUMENT W JULIO RAP 6	PPEARING (/AS AUTHO MOS, P.E. 11 /25/2020	ON THIS RIZED BY 07672
CIVI			11550 H SAN ANTON TEL: (210) 641 - TBPE REGIS TBPLS REGIS	10 WEST, SU IO, TEXAS 78 9999 FAX: (2 STRATION NC TRATION NO.	TE 395 230-1037 10) 641-6440 F-2214 100410-00
		WATS	ON ROA	Ď	
	;	SMALL SIO	GN SUMN ET 1 OF 1	IARY	
		10	0		
	© 2019	7	Texas of Trai	Departr nsporta	nent tion
I	-ED.RD. DIV.NO	FEDERA	L AID PROJECT	NO.	PLAN SHT NO
	6				17
	STATE	DIST.		COUNTY	
Т	EXAS	SAT		BEXAR	
	CONT	SECT.	JOB	HIGHWAY	/ STREET
	0915	12	562	WATS	ON RD

GENERAL

A. HANDLE TRAFFIC APPROPRIATELY THROUGHOUT THE PROJECT DURING CONSTRUCTION. PROVIDE FOR THE SAFETY OF THE TRAVELING PUBLIC AT ALL TIMES. ROADWAY CLOSURES ARE NOT ALLOWED UNLESS OTHERWISE SPECIFIED IN THE PLANS AND/OR AS APPROVED BY THE COUNTY. PROVIDE ACCESS TO PROPERTIES AND BUSINESSES ADJACENT TO THE RIGHT-OF-WAY (ROW) AT ALL TIMES DURING THE DURATION OF THE PROJECT. THE ADEQUACY OF THE PROPERTY ACCESS WILL BE DETERMINED BY THE COUNTY. DO NOT LEAVE EQUIPMENT IN A POSITION THAT WILL ENDANGER THE TRAVELING PUBLIC. MAINTAIN ADEQUATE SAFETY PROVISIONS THROUGHOUT THE PROJECT BY INCLUSION OF SIGNING, MARKINGS, SIGNALS, BARRIERS AND BARRICADES. CONFORM TO THE LATEST EDITION OF THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TXMUTCD) WHEN USING THESE PROVISIONS.

B. THE USE OF THE ROW IS NOT EXCLUSIVE. COOPERATE WITH THE COUNTY, THE VARIOUS UTILITY COMPANIES AND THEIR CONTRACTORS, AS REQUIRED TO ALLOW ADJUSTMENTS TO BE MADE BY OTHERS. IF BY THE ADJUSTMENTS OF THESES UTILITIES, THE CONTRACTOR IS DELAYED, AN EXTENSION OF THE WORKING TIME MAY BE GRANTED; IF IN THE OPINION OF THE COUNTY IT IS WARRANTED.

C. ALL DETOURS, TRAFFIC MOVEMENTS, ETC., ARE DIRECTLY RELATED TO THE SEQUENCE OF WORK; THEREFORE, PROCEED WITH CONSTRUCTION OPERATIONS IN CONFORMITY WITH THE DETAILS SHOWN ON THE PLANS AND AS REQUIRED BY THIS NARRATIVE.

D. PROPOSE AND/OR RECOMMEND ANY MODIFICATIONS TO THE SEQUENCE OF WORK FOR CONSIDERATION TO THE COUNTY IN WRITING, INCLUDE ANY CHANGES TO THE VARIOUS PAY ITEMS, IMPACT TO TRAFFIC, THE EFFECT OF THE OVERALL PROJECT IN TIME, AND ETC., WITH ANY MAJOR RECOMMENDED MODIFICATIONS. WRITTEN APPROVAL FROM THE COUNTY IS REQUIRED PRIOR TO PROCEEDING WITH ANY CONSTRUCTION OPERATION BASED ON A REVISED PHASE/SEQUENCE OF WORK.

E. OFF-DUTY PEACE OFFICERS MAY BE HIRED TO SUPPLEMENT THE WORK FORCE TO CONTROL TRAFFIC AT INTERSECTIONS DURING THE DETOURING OF TRAFFIC, CLOSURE OF ROADWAYS AND/OR INTERSECTIONS, AND ANY OTHER CRITICAL PHASES OF TRAFFIC HANDLING AS DETERMINED BY THE COUNTY. APPROVAL BY THE ENGINEER TO USE OFF-DUTY POLICE OFFICERS WILL BE REQUIRED, WITH A 48-HOUR PRIOR NOTICE. ANY UNAPPROVED USE OF OFFICERS WILL BE AT THE EXPENSE OF THE CONTRACTOR.

F. THE COUNTY MAY DIRECT THE CONTRACTOR TO VARY THE NUMBER AND LOCATION OF SIGNS AND BARRICADES FROM THAT INDICATED ON THE PLANS.

G. COOPERATE FULLY WITH THE VARIOUS UTILITY COMPANIES.

H. "WEEKEND" HOURS ARE DEFINED AS THE HOURS BETWEEN 9:00 PM FRIDAY TO 5:00 AM MONDAY.

I. "OFF PEAK" HOURS ARE DEFINED AS A TIME FRAME BETWEEN 8:00 PM TO 5:00 AM MONDAY THROUGH FRIDAY.

J. MAINTAIN POSITIVE DRAINAGE DURING CONSTRUCTION, INCLUDING OFFSITE DRAINAGE FROM ADJACENT PROPERTIES AND AVOID IMPEDING FLOW FROM PRIVATE PROPERTY.

K. MAINTAIN ACCESS TO DRIVEWAYS AT ALL TIMES.

L. PLACE CONSTRUCTION EXITS AS NEEDED OR AS DIRECTED BY THE COUNTY.

M. CONSTRUCT ALL ROADWAYS UP TO THE 4" WMAC TY C MAT UNTIL SUCH A TIME AS THE ENTIRE PROJECT CAN RECEIVE THE FINAL SURFACE MAT OF OVERLAY EXCEPT FOR THE CONCRETE PAVEMENT AT THE ROUNDABOUT.

II. SEQUENCE OF WORK

THE SEQUENCE OF WORK WILL BE AS FOLLOWS UNLESS OTHERWISE DIRECTED/APPROVED BY THE COUNTY.

- 1. THIS PROJECT WILL BE CONSTRUCTED IN THREE (3) PHASES. BEFORE THE COMMENCEMENT OF EACH PHASE, INSTALL OR MAINTAIN ADVANCE WARNING SIGNS, TEMPORARY SIGNS, BARRICADES, AND SW3P ITEMS AS SHOWN ON THE PLANS AND/OR AS DIRECTED/APPROVED BY THE COUNTY. DAILY LANE CLOSURES WILL BE USED IN ACCORDANCE WITH STATE TCP STANDARDS. DROP OFF CONDITION OF GREATER THAN 2 INCHES MUST HAVE A 3:1 SLOPE AT THE END OF EACH DAY, AS WELL AS THROUGHOUT THE PROJECT WHERE ACCESS TO ADJACENT PROPERTIES IS ALLOWED TO DRIVEWAYS AND SIDE STREETS.
- 2. PREPARING ROW/REMOVAL OF EXISTING ITEMS TO BE DONE ONLY IN AREAS WHERE WORK IS OCCURRING, AS PER THE PHASES NOTED BELOW.
- 3. PERFORM PLANING, SURFACE TREATMENTS AND OVERLAYS IN THE DIRECTION OF TRAFFIC.
- 4. UNLESS NOTED OTHERWISE IN THE SEQUENCE OF WORK, CONSTRUCT JOINT BID UTILITIES AND DRAINAGE INFRASTRUCTURE WITHIN THE WORK ZONE OF EACH CORRESPONDING PHASE/STAGE PRIOR TO THE ROADWAY CONSTRUCTION.

A BRIEF DESCRIPTION OF EACH PHASE IS AS FOLLOWS:

PHASE 1 NARRATIVE - CULVERT CROSSING & TEMPORARY WIDENING

THE INTENT OF THIS PHASE IS TO CONSTRUCT THE PROPOSED WATERLINE ADJACENT TO THE NORTHERN ROW & CONSTRUCT THE WATERLINE ADJUSTMENT BETWEEN STA. 111+32 & 111+78. THESE ADJUSTMENTS WILL ALLOW FOR THE CONSTRUCTION OF THE CROSSING AT STA. 110+64.09 AS WELL AS THE SYSTEM "A" LATERAL. THIS PHASE WILL ALSO CONSTRUCT THE STA. 110+64.09 CROSSING WITHIN THE EXISTING ROADWAY LIMITS, THE OUTFALL FOR STORM SEWER SYSTEM "A" TO MAINTAIN DRAINAGE AND THE WIDENING OF THE EXISTING WATSON RD SOUTHBOUND LANE FOR APPROXIMATELY 900-FT FROM SOMERSET RD.

PHASE 1 STAGE 1- WATERLINE CONSTRUCTION

CONSTRUCT THE WATERLINE RUNNING PARALLEL TO THE NORTH ROW BETWEEN WATSON RD CENTERLINE STA. 110+55 AND VERANO PKWY CENTERLINE STA. 201+46.

DURING THIS PHASE CONSTRUCT WATERLINE ADJUSTMENT LOCATED BETWEEN STA. 111+32 & 111+78. PLACE TRAFFIC IN A ONE LANE TWO-WAY TRAFFIC CONTROL CONFIGURATION FOR A WEEKEND STARTING ON FRIDAY AT 9:00 PM AND COMPLETING THE WORK ON MONDAY NO LATER THAN 4:00 AM.

FLAGGERS AND OFF DUTY POLICE OFFICERS WILL BE REQUIRED DURING ONE LANE TWO-WAY TRAFFIC CONTROL OPERATIONS WITH DEVICES BEING PLACED IN ACCORDANCE TO TXDOT STD TCP (1-2B)-18. EQUIPMENT WILL BE REMOVED FROM THE WORK AREA AT THE END OF EACH AREA AND DROP OFFS WILL BE ADDRESSED APPROPRIATELY AT THE END OF EACH WORK DAY. NO CLOSURES WILL BE PERMITTED DURING PEAK HOURS.

PHASE 1STAGE 2 - CULVERT CROSSING & TEMPORARY WIDENING

TRAFFIC WILL BE CLOSED FOR A WEEKEND STARTING AT ON FRIDAY AT 9:00 PM AND OPENING ON MONDAY NO LATER THAN 4:00 AM. THIS WILL ALLOW FOR THE CONSTRUCTION OF THE CROSSING WITHIN THE EXISTING PAVEMENT LIMITS CUTTING AND RESTORING PAVEMENT TO EXISTING ELEVATION AS WELL AS THE CROSSING CONNECTING INLET A20 TO A30 ALL THE WAY TO THE OUTFALL. INLET A30 WILL BE PLACED IN A LATER PHASE. HEADWALL AND DISSIPATERS WILL BE DONE DURING THE CORRESPONDING PHASE. IN ADDITION WILL ALLOW FOR THE CONSTRUCTION OF CROSSING ALONG SW VERANO PKWY.

UNDER THE WEEKEND CLOSURE CONSTRUCT TEMPORARY PAVEMENT ALONG WATSON RD SOUTHBOUND LANE FROM STA. 110+59.00 TO STA. 114+73.60.

UNDER THIS WEEKEND CLOSURE WILL ALSO CONSTRUCT TRUNK LINE AND RESTORE PAVEMENT AT NORTHBOUND OF SW VERANO PKWY FROM INLET B3.1 TO MANHOLE B4 BETWEEN STA. 209+70.00 TO STA. 209+75.00.

ALSO CONSTRUCT LATERAL LINE AND RESTORE PAVMENT AT SOUTHBOUND OF SW VERANO PKWY FROM MANHOLE B7 TO INLET B140 BETWEEN STA. 201+50.00 TO STA. 202+00.00 WITHIN THE EXISTING PAVEMENT AND OVER PROPOSED DETOUR.

PHASE 2 NARRATIVE - DETOUR CONSTRUCTION AND SOUTHBOUND SW VERANO PKWY

THE INTENT OF THIS PHASE IS TO CONSTRUCT THE DETOURS AT THE INTERSECTION OF SW VERANO PKWY AND WATSON RD TO BE UTILIZED BY JUDITH A. RESNIK MIDDLE SCHOOL TRAFFIC DURING THE CONSTRUCTION OF THE PROPOSED ROUNDABOUT. A PORTION OF SB VERANO PKWY WILL CONSTRUCTED UP TO FINAL GRADES BETWEEN STA. 201+36 AND STA. 203+50 OF SOUTHBOUND SW VERANO PKWY.

PHASE 2 STAGE 1- DETOUR #2 CONSTRUCTION & SOUTHBOUND SW VERANO PKWY

MAINTAIN TRAFFIC ON EXISTING WATSON LANE CONFIGURATION. PLACE CHANNELIZING DEVICES AS SHOWN ON THE PLANS TO PROTECT THE WORK ZONE.

CONSTRUCT THE CONNECTION OF TEMPORARY DETOUR #2 BETWEEN EXISTING WATSON LANE AND VERANO PKWY FOLLOWING THE ALIGNMENTS AS SHOWN ON THE PLANS.

CLOSE LEFT LANES ON BOTH NB & SB VERANO PKWY. CONSTRUCT PROPOSED INSIDE LANE OF THE PROPOSED SOUTHBOUND SW VERANO PKWY BETWEEN STA. 201+00 AND 203+50. ALSO, CONSTRUCT CROSSOVER BETWEEN STA. 203+54 AND 205+00. INSIDE LANE OF SOUTHBOUND SW VERANO PKWY WILL BE CONSTRUCTED TO JUST BEFORE THE FINAL SURFACE COURSE. MINIMUM OF 11' LANES WILL BE MAINTAINED THROUGH THE CONSTRUCTION AREA.

CONSTRUCT SECTION OF TRUNK LINE CONNECTING INLET B160 AND B7 THAT WILL BE UNDER THE PROPOSED SECTION OF ROADWAY BEING CONSTRUCTED DURING THIS PHASE.

CONSTRUCT SECTION OF TRUNK LINE THAT WILL BE LOCATED IN THE MEDIAN OF SW VERANO PKWY EXISTING ROADWAY FROM STA. 203+50.00 TO STA. 209+78.00.

FLAGGERS AND LANE CLOSURES WILL BE PLACED IN ACCORDANCE TO TXDOT STD TCP (1-2B)-18. EQUIPMENT WILL BE REMOVED FROM THE WORK AREA AT THE END OF EACH AREA AND DROP OFFS WILL BE ADDRESSED APPROPRIATELY AT THE END OF EACH WORK DAY. NO CLOSURES WILL BE PERMITTED DURING PEAK HOURS.

PHASE 2 STAGE 2 - PROPOSED SOUTHBOUND SW VERANO PKWY

MAINTAIN TRAFFIC ON EXISTING LANE CONFIGURATION. PLACE CHANNELIZING DEVICES AS SHOWN ON THE PLANS TO PROTECT THE WORK ZONE.

SWITCH EXISTING TRAFFIC TO THE PREVIOUSLY CONSTRUCTED LEFT LANE OF SOUTHBOUND SW VERANO PKWY. CONSTRUCT PROPOSED OUTSIDE LANE OF SW VERANO PKWY BETWEEN STA. 201+22 AND 203+50. MINIMUM OF 11' LANES WILL BE MAINTAINED THROUGH THE CONSTRUCTION AREA. NOTE: DELAY CURB CONSTRUCTION BETWEEN STA. 202+00 AND 203+50 UNTIL FINAL PHASE.

FLAGGERS AND LANE CLOSURES WILL BE PLACED IN ACCORDANCE TO TXDOT STD TCP (1-2B)-18. EQUIPMENT WILL BE REMOVED FROM THE WORK AREA AT THE END OF EACH AREA AND DROP OFFS WILL BE ADDRESSED APPROPRIATELY AT THE END OF EACH WORK DAY. NO CLOSURES WILL BE PERMITTED DURING PEAK HOURS.

PHASE 3 NARRATIVE - NORTHBOUND LANES AND ROUNDABOUT CONSTRUCTION

THE INTENT OF THIS PHASE IS TO CONSTRUCT PROPOSED NB WATSON RD LANES, ROUNDABOUT, ROUNDABOUT CONNECTIONS, ILLUMINATION, DRAINAGE AND TEMPORARY DETOURS.



INSTALL LPCB, TEMPORARY PAVEMENT MARKINGS, TEMPORARY SIGNS, AND SW3P MEASURES AS PER PLAN.

PHASE 3 STAGE 1- CONSTRUCT NORTHBOUND LANES & ROUNDABOUT

SHIFT SB WATSON RD TRAFFIC TO THE TEMPORARY WIDENING AND NB WATSON RD TRAFFIC TO EXISTING SB LANE FOR APPROXIMATELY 900-FT FROM SOMERSET RD. PLACE LPCB AS SHOWN ON THE PLANS TO PROTECT THE WORK ZONE.

SHIFT MIDDLE SCHOOL TRAFFIC TO DETOUR #2. PLACE CHANNELIZING DEVICES AS SHOWN ON THE PLANS TO PROTECT THE WORK ZONE.

CONSTRUCT ALL ROADWAY ELEMENTS EXCEPT FOR THE FINAL SURFACE COURSE AS WELL AS THE FOLLOWING CURB FOR THE MEDIAN SECTION AT THE FOLLOWING STATIONS. 111+00 AND 116+39, MEDIAN SECTION BETWEEN 133+17 AND 135+00, AS WELL AS THE CURB SECTION ON THE OUTSIDE OF THE ROUNDABOUT 135+50 AND 136+75 ON THE OUTSIDE OF THE PROPOSED EASTBOUND PORTION OF THE ROUNDABOUT IN ORDER TO CONNECT DETOUR #3.

CONSTRUCT REMAINING ELEMENTS OF THE NORTH HALF OF DRAINAGE STRUCTURE AT INTERSECTION OF SOMERSET RD AND WATSON RD.

CONSTRUCT CURB INLETS, SHARE USED PATH ALONG THE PROPOSED NORTHBOUND LANES.

CONSTRUCT ILLUMINATION UNDERGROUND INFRASTRUCTURE (CONDUIT & GROUND BOXES).

CLOSE NB SOMERSET RD SHOULDER NORTH AND SOUTH OF WATSON RD USING TXDOT TCP (2-1B)-12.

PHASE 3 STAGE 2 - CONSTRUCT ROUNDABOUT CONNECTION TO EXISTING WATSON RD

PROVIDE ONE-WAY TRAFFIC CONTROL FOR SB WATSON RD BETWEEN SW VERANO PKWY AND END OF PROJECT AS SHOWN ON PLANS.

CONSTRUCT PERMANENT PAVEMENT BETWEEN STA. 138+50 AND STA. 143+00.

UTILIZE DETOUR #4 FOR ONE-WAY TRAFFIC CONTROL.

PHASE 3 STAGE 3 - CONSTRUCT ROUNDABOUT CONNECTION TO EXISTING WATSON RD

SHIFT SB WATSON RD TO NEWLY CONSTRUCTED PAVEMENT, MAINTAIN ONE-WAY TRAFFIC CONTROL BETWEEN SW VERANO PKWY AND END OF PROJECT, AND MAINTAIN MIDDLE SCHOOL TRAFFIC ON DETOUR #2 AS SHOWN ON THE PLANS.

CONSTRUCT PERMANENT PAVEMENT BETWEEN STA. 139+20 AND STA. 141+00 AS SHOWN ON THE PLANS.

UTILIZE DETOUR #4 FOR ONE-WAY TRAFFIC CONTROL.

PHASE 3 STAGE 4 - CONSTRUCT ROUNDABOUT TEMPORARY DETOUR CONNECTION

ELIMINATE THE EXISTING LEFT TURN LANE ONTO VERANO PKWY AND SHIFT NB WATSON RD TRAFFIC MAINTAINING ONE LANE OF TRAFFIC IN EACH DIRECTION. INTERSECTION WILL BE AN ALL STOP CONDITION.

CONSTRUCT THE CONNECTION OF TEMPORARY DETOUR #3 CONNECTING EXISTING WATSON LANE AND VERANO PRKWY ROUNDABOUT FOLLOWING THE ALIGNMENTS AS SHOWN ON THE PLANS.

PHASE 3 STAGE 5 - CONSTRUCT REMAINING CONNECTION OF THE ROUNDABOUT

MAINTAIN TWO-WAY TRAFFIC CONTROL THROUGHOUT THE PROJECT.

SHIFT MIDDLE SCHOOL TRAFFIC TO NEWLY CONSTRUCTED ROUNDABOUT AND DETOUR #3 AS SHOWN ON THE PLANS.

CONSTRUCT PERMANENT PAVEMENT FOR ROUNDABOUT AND SW VERANO PKWY AS SHOWN ON THE PLANS.

PHASE 4 NARRATIVE - SOUTHBOUND LANES CONSTRUCTION

THE INTENT OF THIS PHASE IS TO CONSTRUCT PROPOSED SOUTHBOUND LANES, MEDIAN, CURB INLET, ILLUMINATION AND SHARED USED PATH.

INSTALL LPCB, TEMPORARY PAVEMENT MARKINGS, TEMPORARY SIGNS AND SW3P MEASURES AS PER PLAN.

MAINTAIN TWO-WAY TRAFFIC AT ALL TIMES.

PHASE 4 STAGE 1- CONSTRUCT SOUTHBOUND LANES

SHIFT TRAFFIC TO NEWLY CONSTRUCTED NB WATSON RD LANES AND THE ROUNDABOUT. PLACE LPCB AS SHOWN ON THE PLANS TO PROTECT THE WORK ZONE.

CONSTRUCT THE SB LANES ALONG WITH THE REMAINING LATERALS AND INLETS.

COMPLETE DRAINAGE STRUCTURE AT INTERSECTION OF SOMERSET RD AND WATSON RD.

CONSTRUCT ILLUMINATION POLES AND ELECTRICAL SERVICE.

CLOSE NB SOMERSET RD SHOULDER NORTH AND SOUTH OF WATSON RD USING TXDOT TCP (2-1B)-12.

PHASE 4 STAGE 2 - CONSTRUCT MEDIANS AND FINAL SURFACE

SHIFT TRAFFIC TO NEWLY CONSTRUCTED NB/SB WATSON LANES AND ROUNDABOUT AND SET UP BASED ON TYPICAL SECTION.

CONSTRUCT REMAINING SECTIONS OF CURB LINES AND RAISED MEDIANS NOT COMPLETED IN PREVIOUS PHASES.

AFTER THE CONSTRUCTION OF THE SB WATSON RD LANES, CONSTRUCT THE FINAL PAVEMENT SURFACE, SEEDING & SODDING, FINAL PAVEMENT MARKINGS, SIGNING, MILL AND OVERLAY SECTIONS AT THE BEGINNING AND END OF THE PROJECT WHERE TEMPORARY PAVEMENT MARKINGS WERE APPLIED DURING CONSTRUCTION.

OPEN ALL LANES TO TRAFFIC.











7/6/2020 @ 2:43:12 PM IAME: G:\15024-Watson-Re PLOTTED ON: 7

DCATION	NAME ADDRESS CITY STATE CONTRACTOR	OBEY WARNING SIGNS STATE LAW	WORK ZONE	TRAFFIC FINES DOUBLE	REGI REGES ARE PRESENT	BEGIN ROAD WORK NEXT X MILES	STAY ALERT	ROAD WORK AHEAD	SPEED LIMIT XX	ROAD WORK NEXT MILES→	END ROAD WORK
L	G20-6T 48" x 30"	R20-3T 48" x 42"	G20-5aP 36" x 24"	R20-5T 36" x 36"	R20-5aTP 36" x 18"	G20-5T 48" x 24"	G20-10T 60" x 48"	CW20-1D 48" x 48"	R2-1 30" x 36"	G20-1bTL(R) 72" x 24"	G20-2 48" x 24"
1	х	х	х	х	х	х	x	х	х		
2								x		x	
3									х		x

WATSON RD

GENERAL NOTES:

- 1. LOCATION NO. 1 TO BE USED AT BEGINNING OF THE PROJECT.
- 2. LOCATION NO. 2 TO BE USED ENTERING SIDE STREETS.

 \bigcirc

3

ୖୖ

SOMERSFIED

- 3. LOCATION NO. 3 TO BE USED AT END OF THE PROJECT AND EXITING SIDE STREETS
- 4. REFER TO THE CURRENT TXDOT BC STANDARDS FOR ADDITIONAL INFORMATION.

5. BARRICADES AND CONSTRUCTION SIGNS ON THIS SHEET ARE CONSIDERED TO BE THE MINIMUM REQUIRED IN ACCORDANCE WITH THE CURRENT TXDOT BC STANDARDS AND THE TMUTCD. ADDITIONAL SIGNS MAY BE REQUIRED AS PER THE DIRECTION

OF THE ENGINEER.

PLOTTED ON: 7/6/2020 @ 2:43:19 PM DESIGN FILENAME: \\Ssa-main\pmwork\Jobs\15024-Watson-Rd\Techprod\TCP\WATSON-TC-BAR01.dan



3 1 0



DETOUR #2

DESCRIBE CHAIN DETOUR2

Chain DETOUR2 contains: DETOUR210 CUR DETOUR21 CUR DETOUR22 CUR DETOUR23

Beginning	chain	DE TOUR2	description	n		

Point DETOUR210 N 13,653,973.9127 E 2,097,055.9798 Sta 10+00.00 Course from DETOUR210 to PC DETOUR21 N 47° 58' 10.29" E Dist 146.1936

Curve Data						
**						
Curve DETOUR21						
P.I. Station	12+13.18	N	13,654,116.6454	E	2,097,214.3311	
Delta =	51° 08′ 34.97"	(RT)				
Degree =	40° 55′ 32.00"					
Tangent =	66.9912					
Length =	124.9660					
Rodius =	140.0000					
External =	15.2025					
Long Chord =	120.8585					
Mid. Ord. =	13,7134			-		
P.C. Station	11+46.19	N	13,654,071,7931	Ę	2,097,164.5707	
	12+11.16	N	13,654,106.0357	È.	2,097,280.4768	
L.L.	478 684 10 20" 6	N	13,653,967.8026	E	2,097,258.3044	
Abord - C	47 36 10.29 E					
Chord Boor - N	770 30' 07 70" E					
unora bear = N	13 32 21.18 E					

Course from PT DETOUR21 to PC DETOUR22 S 80° 53' 14.74" E Dist 136.3859

Curve Data **						
Curve DETOUR22 P.I. Station Delta = Degree = Tangent = Length = Radius = External = Long Chord =	14+44.00 25* 40' 19.83" 35* 48' 35.50" 36.4571 71.6902 160.0000 4.1009 71.0920	N (LT)	13,654,078.6617	E	2,097,451.1384	
Mid. Ord. = P.C. Station P.T. Station C.C. Back = S Ahead = N Chord Bear = N	3.9985 14+07.55 14+79.24 80° 53′ 14.74″ E 73° 26′ 25.44″ E 86° 16′ 35.35″ E	N N N	13,654,084.4356 13,654,089.0525 13,654,242.4163	E E E	2,097,415.1414 2,097,486.0834 2,097,440.4814	
Curve Data **						
Curve DETOUR23 P.I. Station Delta = Degree = Tangent = Length = Radius =	15+15,99 25° 52′ 24.83" 35° 48′ 35.50" 36.7530 72.2526 160.0000	N (RT)	13,654,099.5275	E	2,097,521.3120	
External = Long Chord = Mid. Ord. = P.C. Station C.C. Back = N Ahead = S Chord Bear = N	4, 1669 71, 6403 4, 0612 14+79, 24 15+51, 49 73* 26' 25, 44" E 80* 41' 09, 73" E 86* 22' 37, 85" E	N N N	13,654,089.0525 13,654,093.5793 13,653,935.6887	E E E	2,097,486.0834 2,097,557.5805 2,097,531.6854	

Ending chain DETOUR2 description

@ 2:43:22 PM 15024-Watson-Rd 7/6/2020 IAME G.\1 PLOTTED ON: DESIGN FILENA

DETOUR #3

	DESCRIBE CHAIN DETOUR3							
	Chain DETOUR3 contains: DETOUR310 DETOUR311							
	Beginning chain DETOUR3 description							
	Point DETOUR310	Ν	13,654,033.7542	E	2,097,002.1136 Sta			
	Course from DETOUR310	to	DETOUR411 N 46°	01′	37.39" E Dist 56.91			
	Point DETOUR311	Ν	13,654,073.2680	Е	2,097,043.0701 Sta			
Ending chain DETOUR3 description								

. 10+00.00 102 10+56.91





113+00.00 STA ш L MATCH



PUBLIC WORKS DEPARTMENT AN S NO. 25 JOB HIGHWAY / STREET 562 WATSON RD

BEXAR COUNTY

COUNTY

BEXAR

FEDERAL AID PROJECT NO

DIST.

SECT.

12

DIV.NC

6 STATE

TX

CONT.

0915



PLOTTED ON: 7/6/2020 @ 2:45:04 PM DESIGN FILENAME: \\Ssa-mainbmwork\Jobs\15024-Watson-Rd\Techprod\TCP\WATSON TCP PH2 STG1 01.



PLOTTED ON: 7/6/2020 @ 2:45:19 PM DESIGN FILENAME: \\Ssa-main\pmwork\Jobs\15024-Watson-Rd\Techprod\TCP\WATSON_TCP_PH1_STG1_01.dgn

TCP LEGEND WORK AREA PROP DETOUR CHANNELIZING DEVICES • Ø CHEVRONS PCTB (LOW PROFILE) TY III BARRICADE SIGN \Rightarrow EXIST TRAFFIC ARROW PROP TRAFFIC ARROW PHASE 2 PAVEMENT -NO DATE REVISION APPR GRAPHIC SCALE (IN FEET) 25 12.5 25 1" = 50' THE SEAL APPEARING ON THIS DOCUMENT WAS AUTHORIZED BY FERNANDO J. SALAZAR, P.E. #92678 TE OF TRU * Julion mudo 7/6/202 #92678 ONAL E SANCHEZ-SALAZAR & ASSOCIATES, LLC TBPE FIRM REGISTRATION NO. 15685 TISSO IH 10 WEST, SUITE 395 SAN ANTONIO, TEXAS 78230-1037 TEL: (210) 641-9399) [FAX: (210) 641-644 TBPE REGISTRATION NO.: F-2214 TBPLS REGISTRATION NO.: 100410-00 CEC WATSON ROAD TRAFFIC CONTROL PLAN SHEET PHASE 1 STAGE 2 SHEET 3 OF 3 BEXAR COUNTY PUBLIC WORKS DEPARTMENT PLAN SH NO. FEDERAL AID PROJECT NO. DIV.NO 6 27 STATE DIST. COUNTY ΤX BEXAR CONT. SECT. JOB HIGHWAY / STREET 12 562 WATSON RD 0915



PLOTTED ON: 2:45:25 PM DESIGN FILENAME: \\Ssa-main\pmwork\Jobs\15024-Watson-Rd\Techprod\TCP\WATSON_TCP_DETOUR_PLAN_



PLOTTED ON: 7/6/2020 @ 2:46:06 PM DESIGN FILENAME: \\Ssa-main\pmwork\Jobs\15024-Watson-Rd\Techprod\TCP\WATSON_TCP_PH2_STG1



@ 2:46:40 PM 7/6/2020 IAME: \\Ssi PLOTTED ON: DESIGN FII EN/



TCP LEGEND







PLOTTED ON: 7/6/2020 @ 2:47:54 PM DESIGN FILENAME: \\Ssa-main\pmwork\Jobs\15024-Watson-Rd\Techprod\TCP\WATSON_TCP_PH2 STG1 01



2.48.00 PM 0 7/6/2020 AME \\\\\\\\ TTED ON: 6 Ц

TCP LEGEND







РМ 18:41 5

0 2020 NO LED



13+00.00 -₹ 'ഗ LINE MATCH













TCP LEGEND







2 50 12 PM 0 7/6/2020 NO TED ᆋ



TCP LEGEND









PZ 50.24 N 0 S Ш

0915

12




TCP LEGEND







2.50.37 PM 0 7/6/2020 NO **JED** ۲

$\sim\sim$	WORK AREA
	PROP DETO
•	CHANNELIZI
Ø	CHEVRONS
	PCTB (LOW I
Ι	TY III BARRIO
	SIGN
⇒	EXIST TRAFF
•	PROP TRAFF
	PHASE 2 PA

ON DETAILS SEE DETOUR #2 PLAN & PROFILE.
--





FILES



7/6/2020

Ь

$\sim\sim$	WORK AREA
	PROP DETOUR
•	CHANNELIZING D
Ø	CHEVRONS
	PCTB (LOW PROF
[TY III BARRICADE
	SIGN
5	EXIST TRAFFIC AF
•	PROP TRAFFIC AF
	PHASE 2 PAVEME







$\sim\sim$	WORK AREA
	PROP DETOUR
•	CHANNELIZING
Ø	CHEVRONS
	PCTB (LOW PR
[TY III BARRICA
	SIGN
\$	EXIST TRAFFIC
•	PROP TRAFFIC
	PHASE 2 PAVE



$\sim\sim\sim$	WORK ARE
	PROP DETC
•	CHANNELIZ
Ø	CHEVRONS
	PCTB (LOW
[TY III BARR
	SIGN
\$	EXIST TRAF
•	PROP TRAF
	PHASE 2 PA



PLOTTED ON: 7/6/2020 @ 2:51:17 PM



2:52:16 PM 0 7/6/2020 TTED ON: 6

Ц



113+00.00 STA LINE LINE MATCH









2.53.09 PM 0 7/6/2020 NO **JED** ю ۲

TCP LEGEND













TCP LEGEND









2 53 23 PM 0 7/6/2020 NO **JED** ю ۲





TCP LEGEND







EROSION CONTROL LOG (12" DIA)

TEMPORARY SEDIMENT CONTROL FENCE

ROCK FILTER DAM (TY 4)

CONSTRUCTION EXIT

COMP MANUF TOPSOIL & MULCH

 \rightarrow ----DRAINAGE FLOW LINES

ITEM#	DESCRIPTION	UNIT	QTY
0160	FURNISHING AND PLACING TOPSOIL (4")	SY	1962
0162	BLOCK SODDING	SY	299
0168	VEGETATIVEWATERING	MG	42
0192	MULCH	SY	1962
0506	ROCK FILTER DAMS (INSTALL) (TY 4)	LF	30
0506	ROCK FILTER DAMS (REMOVE)	LF	30
0506	CONSTRUCTION EXITS (INSTALL) (TY 1)	SY	444
0506	CONSTRUCTION EXITS (REMOVE)	SY	444
0506	TEMP SEDMT CONT FENCE (INSTALL)	LF	1247
0506	TEMP SEDMT CONT FENCE (REMOVE)	LF	1247
0506	BIODEG EROSN CONT LOGS (INSTL) (12")	LF	220
0506	BIODEG EROSN CONT LOGS (REMOVE)	EA	220
0506 0506 0506 0506 0506 0506	CONSTRUCTION EXITS (INSTALL) (TY 1) CONSTRUCTION EXITS (REMOVE) TEMP SEDMT CONT FENCE (INSTALL) TEMP SEDMT CONT FENCE (REMOVE) BIODEG EROSN CONT LOGS (INSTL) (12") BIODEG EROSN CONT LOGS (REMOVE)	SY SY LF LF LF EA	444 444 1247 1247 220 220



NOTE:

- 1. SW3P BMPS TO BE INSTALLED CONCURRENT WITH TCP PHASING AS REQUIRED.
- 2. COORDINATE WITH BEXAR COUNTY REPRESENTATIVE FOR CONSTRUCTION EXIT LOCATION.



-ECD-

EROSION CONTROL LOG (12" DIA)

TEMPORARY SEDIMENT CONTROL FENCE

-RFD4-ROCK FILTER DAM (TY 4)

CONSTRUCTION EXIT

Ý \checkmark \vee \vee COMP MANUF TOPSOIL & MULCH

 \rightarrow ----DRAINAGE FLOW LINES

ITEM#	DESCRIPTION	UNIT	QTY
0160	FURNISHING AND PLACING TOPSOIL (4")	SY	2733
0168	VEGETATIVEWATERING	MG	43
0192	MULCH	SY	2733
0506	TEMP SEDMT CONT FENCE (INSTALL)	LF	1810
0506	TEMP SEDMT CONT FENCE (REMOVE)	LF	1810
0506	BIODEG EROSN CONT LOGS (INSTL) (12")	LF	260
0506	BIODEG EROSN CONT LOGS (REMOVE)	EA	260

NOTE:

- 1. SW3P BMPS TO BE INSTALLED CONCURRENT WITH TCP PHASING AS REQUIRED.
- 2. COORDINATE WITH BEXAR COUNTY REPRESENTATIVE FOR CONSTRUCTION EXIT LOCATION.





00+9 ∢ \vdash Ś ш

8

21+50.

-

₹

Ś ш

CHLINE

MAT



-ECD-

EROSION CONTROL LOG (12" DIA)

TEMPORARY SEDIMENT CONTROL FENCE

ROCK FILTER DAM (TY 4)

CONSTRUCTION EXIT

COMP MANUF TOPSOIL & MULCH

 \rightarrow ----DRAINAGE FLOW LINES

ITEM#	DESCRIPTION	UNIT	QTY
0160	FURNISHING AND PLACING TOPSOIL (4")	SY	2085
0168	VEGETATIVEWATERING	MG	33
0192	MULCH	SY	2085
0506	TEMP SEDMT CONT FENCE (INSTALL)	LF	1634
0506	TEMP SEDMT CONT FENCE (REMOVE)	LF	1634
0506	BIODEG EROSN CONT LOGS (INSTL) (12")	LF	180
0506	BIODEG EROSN CONT LOGS (REMOVE)	EA	180





562 WATSON RD

0915

12

NOTE:

- SW3P BMPS TO BE INSTALLED CONCURRENT WITH TCP PHASING AS REQUIRED.
- 2. COORDINATE WITH BEXAR COUNTY REPRESENTATIVE FOR CONSTRUCTION EXIT LOCATION.





-ECD-

EROSION CONTROL LOG (12" DIA)

TEMPORARY SEDIMENT CONTROL FENCE

-RFD4-ROCK FILTER DAM (TY 4)

CONSTRUCTION EXIT

Ý \checkmark \vee \vee

COMP MANUF TOPSOIL & MULCH

 \rightarrow ----DRAINAGE FLOW LINES



562 WATSON RD

0915

12

- 1. SW3P BMPS TO BE INSTALLED CONCURRENT WITH TCP PHASING
- COUNTY REPRESENTATIVE FOR CONSTRUCTION EXIT LOCATION.

RIPTION	UNIT	QTY
CING TOPSOIL (4")	SY	6932
NG	MG	108
	SY	6932
NSTALL) (TY 4)	EA	60
REMOVE)	LF	60
ENCE (INSTALL)	LF	1366
ENCE (REMOVE)	LF	1366
LOGS (INSTL) (12")	LF	340
LOGS (REMOVE)	EA	340



EROSION CONTROL LOG (12" DIA)

TEMPORARY SEDIMENT CONTROL FENCE

-RFD4-ROCK FILTER DAM (TY 4)

CONSTRUCTION EXIT

Ý ¢ $\vee \vee$ COMP MANUF TOPSOIL & MULCH

 \rightarrow ----DRAINAGE FLOW LINES

ITEM#	DESCRIPTION	UNIT	QTY
0160	FURNISHING AND PLACING TOPSOIL (4")	SY	1255
0168	VEGETATIVEWATERING	MG	20
0192	MULCH	SY	1255
0506	CONSTRUCTION EXITS (INSTALL) (TY 1)	SY	444
0506	CONSTRUCTION EXITS (REMOVE)	SY	444
0506	TEMP SEDMT CONT FENCE (INSTALL)	LF	458
0506	TEMP SEDMT CONT FENCE (REMOVE)	LF	458
0506	BIODEG EROSN CONT LOGS (INSTL) (12")	LF	40
0506	BIODEG EROSN CONT LOGS (REMOVE)	EA	40



NOTE:

- 1. SW3P BMPS TO BE INSTALLED CONCURRENT WITH TCP PHASING AS REQUIRED.
- 2. COORDINATE WITH BEXAR COUNTY REPRESENTATIVE FOR CONSTRUCTION EXIT LOCATION.



	B. BEST MANAGEMENT PRACTICES	C. OTHER REQUIREMENTS & PRACTICES
A. <u>GENERAL SITE DATA</u>	General timing or sequence for implementation of BMPs shall be as required	1. <u>MAINTENANCE:</u>
1. PROJECT LIMITS: FM 2790-SOMERSET ROAD TO 0.8 MI EAST OF WATSON ROAD	and/or as directed/approved by the Engineer to provide adequate controls. BMPs shown on plan sheets are to be considered "proposed" unless/until install date is shown.BMPs are to reduce sediments from road construction activities.	All erosion and sediment controls shall be maintained in good working order. If a repair is necessary, it shall be performed before the next anticipated storm event but no later than 7 calendar days after the surrounding exposed ground has dried sufficiently to prevent further damage from
2. <u>PROJECT SITE MAPS:</u>	1. <u>SOIL STABILIZATION PRACTICES:</u> (Select T = Temporary or P = Permanent, as applicable)	equipment. If maintenance prior to the next anticipated storm event is impracticable,
* Project Latitude <u>29,6838888889</u> Project Longitude <u>-98,065277778</u> * Project Location Map: Shown on Title Sheet		construction activities have ceased, temporarily or permanently, shall be stabilized within 14 calendar
* Drainage Patterns: Shown on Drainage Area Maps (Sheets 102-117)		days unless they are scheduled to and do resume within 2I calendar days. The areas adjacent to
* Approx.Slopes Anticipated After Major Gradings and Areas of Soil Disturbance: Shown on Typical Sections (Sheets 4-7)	BUFFER ZONES	creeks and arainageways shall have priority followed by profecting storm sewer thiefs.
* Major Controls and Locations of Stabilization Practices: Shown on SW3P Sheets (Sheets 165-172)	COMPOST/MULCH FILTER BERM P COMPOST MANUFACTURED TOPSOIL	2. INSPECTION:
 Project Specific Locations: Off-site waste,borrow,or storage areas are not part of this SW3P. Surface Waters and Discharge Locations: Shown on Drainage and Culvert Layout Speets (Speets 97-118) 	P SODDING P OTHER: (WINDROWS)	For areas of the construction site that have not been finally stabilized, areas used for storage of materials structural control measures and locations where vehicles enter or exit the site
	2. <u>STRUCTURAL PRACTICES:</u> (Select T = Temporary or P = Permanent, as applicable)	personnel provided by the permittee and familiar with the SW3P must inspect disturbed areas
3. PROJECT DESCRIPTION: REHAB EXISTING ROADWAY	SILT FENCES	at least once every seven (7) calendar days. An Inspection and Maintenance Report shall be prepared for each inspection and the controls shall be revised on the SW3P, within seven (7) calendar days
a late bid stilling and encoded to this OUTD (Choose 10/100)	HAT BALES ROCK FILTER DAMS	following the inspection.
* Joint-Did utilities are covered by this SW3P (Sneels 121-128) Non-Joint Bid Utilities are not part of this SW3P.	DIVERSION, INTERCEPTOR, OR PERIMETER DIKES	
	DIVERSION DIKE AND SWALE COMBINATIONS	
4. FOR MAJOR SOIL DISTURBING ACTIVITIES SEQUENCE OF EVENTS:	PPAVED FLUMES	
I. Install controls down-slope of work area and initiate inspection and maintenance activities.	ROCK BEDDING AT CONSTRUCTION EXIT	3. WASTE MATERIALS:
2. Begin phased construction with interim stabilization practices. Ad just erosion and sedimentation	TIMBER MAITING AT CONSTRUCTION EXIT	All non-hazardous municipal waste materials such as litter, rubbish, trash and garbage located on
controls during construction to meet requirements and changing conditions and as directed/	SEDIMENT_TRAPS	or originating from the project shall be collected and stored in a securely lidded metal dumpster,
approved by the Engineer.	STORM INLET SEDIMENT TRAP	provided by the Contractor.The dumpster shall be emptied as necessary or as required by local regulation and the trash shall be bauled to a permitted disposal facility. The burying of
3. Major soil disturbing activities may include but are not limited to: right-of-way preparation, cut	P CURBS AND GUTTERS	non-hazardous municipal waste on the project shall not be permitted. Construction material waste
and/or fill to improve roadway profile, final grading and placement of topsoil and the following (if marked).	STORM SEWERS	sites, stockpiles and haul roads shall be constructed to minimize and control the amount of sediment
	VELOCITY CONTROL DEVICES	wetland, water body or stream bed. Construction staging areas and vehicle maintenance areas
<u>X</u> Placement of road base <u>X</u> Exstensive ditch grading		shall be constructed in a manner to minimize the runoff of pollutants.
Upgrading or replacing culverts or bridges	3. STORM WATER MANAGEMENT:	
l'emporary defour road(s) Other:	The proposed facility was designed in consideration of hydraulic design standards to convey	4. OFFSTIE VEHICLE TRACKING:
	stormwater in a manner that is protective of public safety and property. The control of erosion from the facility is integrated to the decian Additional Factors of factors act construction	Utt-site vehicle tracking of sediments and the generation of dust must be minimized. Excess sediments on road shall be removed on a regular basis as directed/approved by the Engineer.
5. EXISTING AND PROPOSED CONDITIONS:	stormwater at the project location include: (mark all that apply)	
Description of existing vegetative over. North, Peadway Crasses along readway come weeded areas	<u>X</u> Existing or new vegetation provides natural filtration.	5. <u>OTHER:</u>
Percentage of existing vegetative cover: Approximately 40%	<u>X</u> The design includes provisions for permanent erosion controls	See the EPIC sheet for additional environmental information.
Existing vegetative cover:(mark one) <u>X</u> Thick or uniformly established	provided by strategically placed pervious and impervious surfaces.	
Thin and Patchy	<u>X</u> Velocities do not require dissipation devices.	
Description of soils: (Provide classification and description of soils)	Velocity-dissipation devices included in the design.	
Site Acreage: <u>38,73_AC</u> Acreage disturbed: <u>6,40_AC</u>	Other :	
Site runoff coefficient (pre-construction): <u>0.45</u> Site runoff coefficient (post-construction): <u>0.45</u>		
6 RECEIVING WATERS: (Mark all that apply)	4. NON-STORM WATER DISCHARGES:	
A classified stream does not pass through project output up to put to	Off-site discharges are prohibited except as follows:	
<u>X</u> A classified stream passes through project. Name <u>BELOW COMAL RIVER</u> Seament Number 1804	I.Discharges from fire fighting activities and/or fire hydrant flushings.	
Name of receiving waters that will receive discharges	2.Vehicle, external building, and pavement wash water where detergents and soaps are not used and where spills or leaks of toxic or hazardous materials have not occurred (unless	
from disturbed areas of the project: <u>GUADALUPE_RIVER_BELOW_COMAL_RIVER</u>	all spilled material has been removed).	11550 IH 10 WEST, SUITE 395 SAN ANTONO, TEXAS 78230-1037
Cite is a University Constants Storm Course Sustem (UCA)	3. Plain water used to control dust.	TEL: (210) 641-9999 [FAX: (210) 641-6440 CIVIL ENGINEERING CONSULTANTS TEDER ECISITAATION NO: F-2214 DOR DURGEN ING. TOPIS OF CONSULTANTS
MS4 Operator (name):	5.Uncontaminated aroundwater.spring water or accumulated stormwater.	
	6. Foundation or footing drains where flows are not contaminated with process	© 2012 Texas Department of Transportation
	materials such as solvents. 7.Other:	
	Concrete truck wash water discharges on the site should be prohibited or minimized. If allowed	FOR INTERIM REVIEW PURPOSES ONLY
	by the Engineer, they must be managed in a manner so as not to contaminate surface water. They must not be located in areas of concentrated flow Concrete truck washout locations.	UNDER THE AUTHORITY OF UNDER THE AUTHORITY OF UNDER THE AUTHORITY OF UNDER THE AUTHORITY OF UNDER THE AUTHORITY OF
	must be shown on the SW3P Layout and included in the inspections.	ON 6/25/2020
	Hazardous material spill/leak shall be prevented or minimized. At a minimum, this includes asphalt	
	products,tuels,oils,lubricants,solvents,paints,acids,concrete curing compounds and chemical additives for soil stabilization, BMPs shall be implemented to the storage areas of these products	DIV.NO. FEDERAL AID PROJECT NO. NO.
	All spills must be cleaned and disposed properly and reported to the Engineer. Report any	STATE DISTRICT COUNTY
	release at or above the reportable quantity during a 24 hour period to the National Response Center at 1-800-424-8802	, P.E. TEXAS SAT BEXAR SHEET
		CONTROL SECTION JOB NO.
		REVISION DATE: 0915 12 562 58

Note To Designer: 1. Do not after Sheet Design or Font style, size or weight - match text attributes. 2. If additional space is needed for a numbered section, fence and adjust sections up or down as needed for proportioning and readability but do not relocate from 17's relative position.

STORMWATER POLLUTION PR	REVENTION-CLEAN WATER A	CT SECTION 402	III. CULTURAL RESOURCES		VI. HAZARDOUS MATERIALS OR (CONTAMINATION ISSUES		
Texas Pollutant Discharge Elimina Discharge Permit or Construction or more acres distrubed soil. Pr erosion and sedimentation in acc	tion System (TPDES) TXR 150000 General Permit (CGP) required for ojects with any disturbed soil must cordance with Item 506.	Stormwater projects with 1 protect for	Refer to TxDOT Standard Specific archeological artifacts are found a archeological artifacts (bones, burn work in the immediate area and c	ations in the event historicalissues or luring construction. Upon discovery of It rock, flint, pottery, etc.) cease contact the Engineer immediately.	General (applies to all projects): Comply with the Hazard Communication hazardous materials by conducting safe making workers aware of potential hazar provided with personal protective equipm	Act (the Act) for personnel who will ty meetings prior to beginning cons ds in the workplace. Ensure that all lent appropriate for any hazardous r	be working with struction and workers are materials used	1
No Action Required Action No. 1. Prevent stormwater pollution	Required Action	entation in	🛛 No Action Required Action No.	Required Action	Obtain and keep on-site Material Safety used on the project, which may include, Paints, acids, solvents, asphalt products, compounds or additives. Provide protect	Data Sheets (MSDS) for all hazardo but are not limited to the following chemical additives, fuels and concre	us products g categories: te curing	
 accordance with TPDES Per Comply with the Storm Wanecessary to control pollution Post Construction Site Noticaccessible to the public an Environmental Protection Ag When Contractor project space 	rmit TXR 150000. Iter Pollution Prevention Plan (SW3F on or required by the Engineer. ce (CSN) with SW3P information or d Texas Commission on Environme ency (EPA) or other inspectors. pecific locations (PSL's) increase di	2) and revise when or near the site, htal Quality (TCEQ), sturbed soil area	1. 2. 3.		products which may be hazardous. Maint Maintain an adequate supply of on-site In the event of a spill, take actions to r in accordance with safe work practices, immediately. The Contractor shall be resp of all product spills.	tain product labelling as required by spill response materials, as indicated mitigate the spill as indicated in the , and contact the District Spill Coord ponsible for the proper containment	the Act. I in the MSDS. MSDS, Jinator t and cleanup	
to 5 acres or more, Contro the Engineer. 5. NOIrequired: Yes 🛛 No 🗌	actor shall submit Notice of Intent ()	NULL TO ICEQ and	4. IV. VEGETATION RESOURCES		Contact the Engineer if any of the follwi Dead or distressed vegetation (no Trash piles, drums, canister, barre	ing are detected: ot identified as normal) Is, etc.		
Note: If amount of soil disturbance	e changes, permit requirements ma	/ change.	Preserve native vegetation to the to Construction Specification Re 730, 751, 752 in order to compl beneficial landscaping, and tree/b	he extent practical. Contractor must adhere quirements Specs 162,164, 192, 193, 506, y with requirements for invasive species, rush removal commitments.	 Undesirable smells or odors Evidence of leaching or seepage Hazardous Materials or Contaminatio 	of substances n Issues Specific to this Project:		
. WORK IN OR NEAR STREAM ACT SECTIONS 401 AND	S, WATERBODIES AND WETL 404	ANDS CLEAN WATER	No Action Required	Required Action	Action No.			
US Army Corps of Engineers (excavating or other work in an such as, rivers, creeks, stream	USACE) Permit required for filling, c by potential USACE jurisdictional wate s, or wetlands.	redging, er,	Action No.		1. 2.			
The Contractor shall adhere to the following permit(s):	all of the terms and conditions as	sociated with	2.		3.			
No Permit Required Nationwide Permit (NWP) 14	- Pre-construction Notice (PCN) n	ot Required	3.		Does the project involve the demol	ition of a span bridge? Io further action required)		
Nationwide Permit 14 - PCN Individual 404 Permit Require Other Nationwide Permit Rec	l Required ed quired: NWP•		4. V. FEDERAL LISTED, PROPOSED	THREATENED, ENDANGERED SPECIES,	If "Yes", a pre- demolition notificati of State Health Services. The contr calendar days prior to the demolitic with the notification.	ion must be submitted to the Texa actor shall contact TxDOT's Project on of the bridges(s) on the project	s Department Engineer 25 to assist	
Required Actions: List waters of the US permit applies to, location in project and check Best Management Practices (BMPs) planned to control erosion,		CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS.		VII. OTHER ENVIRONMENTAL ISSUES				
			No Action Required	Required Action	(includes regional issues such as	Edwards Aquifer District, etc.)		
Ι.			Action No.		No Action Required	Required Action		
2.			1. MIGRATORY BIRD NESTS: Schedule	construction activities as needed to meet the	Action No.			
3. 4.			A. Do not remove or destroy any a containing eggs and/or flightless bird any active nests, they shall not be r	ctive migratory bird nests (nests ds) at any time of year. If there are emoved until the nests become inactive.	1.			
			B. On/in structures, if there are any removed until all nests become inacti and/or before nest activity begins, o the structures to prevent future nest	r active nests, they shall not be ve. After inactive nests are removed leterrent materials may be applied to st building.	2.			
			 See Item 5 in General Notes. Western and Eatern spotted skunk - 	Skunk BMP's: The Contractors will be advised of potential				
401 Best Management Pract	ices: (Not applicable if no LISA	CE permit)	to avoid unnecessary impacts to de	ns.				
Erosion	Sedimentation	Post-Construction TSS	If any of the listed species are observe do not disturb species or habitat and c work may not remove active pests fro	ed, cease work in the immediate area, ontact the Engineer immediately. The m. bridges and other structures during				
Temporary Vegetation	Silt Fence Rock Berm	Vegetative Filter Strips	nesting season of the birds associated are discovered, cease work in the imme Engineer immediately.	with the nests. If caves or sinkholes ediated area, and contact the		Texas D San Ar	epartment of ntonio District Stai	Transportation
Sodding	Sand Bag Berm	Constructed Wetlands						
Interceptor Swale	Straw Bale Dike	Wet Basin					ENTAL F	CRIVITS,
Diversion Dike	Brush Berms	Erosion Control Compost				ISSUES AN	ID COMM	11 FMENTS
Mulch Filter Berm and Socks	Lirosion Control Compost Mulch Filter Berm and Socks	Compost Filter Berm and Socks					EPIC	
Compost Filter Berm and Socks	Compost Filter Berm and Socks	Vegetation Lined Ditches				F⊪E: epic 2015-10-09 SAJ.dgn	DN: TxDOT CK:	· TxDOT DW: BW CK: GAG
	Storie Outlet Sealment Traps	🔲 Sana Fiiter Systems				© TxDOT OCTOBER 2015	CONT SECT	JOB HIGHWAY
	Sediment Basins	Sedimentation Chambers				REVISIONS		I

BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:

- 1. The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- The development and design of the Traffic Control Plan (TCP) is the 2. responsibility of the Engineer.
- The Contractor may propose changes to the TCP that are signed and sealed 3. by a licensed professional engineer for approval. The Engineer may develop. sign and seal Contractor proposed changes.
- 4. The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
- 5. Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
- 6. When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
- 7. The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
- 8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas." Latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
- The temporary traffic control devices shown in the illustrations of the 9. BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
- 10. As shown on BC(2), the OBEY WARNING SIGNS STATE LAW sign. STAY ALERT TALK OR TEXT LATER (see Sign Detail G20-10T) and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. However, the TRAFFIC FINES DOUBLE sign will not be required on projects consisting solely of mobile operation work, such as striping or milling edgeline rumble strips. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits.
- 11. Except for devices required by Note 10, traffic control devices should be in place only while work is actually in progress or a definite need exists.
- 12. The Engineer has the final decision on the location of all traffic control devices.
- 13. Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

WORKER SAFETY APPAREL NOTES:

Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.



Only Traff and t below

Texas Traff Phone

pre-qualified products shall be used. The "Compliant Work Zone ic Control Devices List" (CWZTCD) describes pre-qualified prod heir sources and may be found on-line at the web address given or by contacting:	ducts
Department of Transportation ic Operations Division - TE (512) 416-3118	
	SHEET 1 OF 12
THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT http://www.txdot.gov	Traffic Operations Texas Department of Transportation
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)	
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)	BARRICADE AND CONSTRUCTION
MATERIAL PRODUCER LIST (MPL)	GENERAL NOTES
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)"	AND REQUIREMENTS
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)	
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD) TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)	
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD) TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD) TRAFFIC ENGINEERING STANDARD SHEETS	BC (1) - 14 FILE: bc-14. dgn DN: TXDOT CK: TXDOT DW: TXDOT CK: TXDOT © TXDOT November 2002 cont SECT JOB HIGHWAY
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD) TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD) TRAFFIC ENGINEERING STANDARD SHEETS	BC (1) - 14 FILE: bc-14.dgn DN: TXDOT CK: TXDOT DW: TXDOT CK: TXDOT CK:



TYPICAL	CONSTRUCTION	WARNING	SIGN	SIZE	AND	SPACING 1.5.	Б

SIZE

Sign Number or Series	Conventional Road	Expressway/ Freeway
CW20 ⁴ CW21 CW22 CW23 CW25	48" × 48"	48" × 48"
CW1, CW2, CW7, CW8, CW9, CW11, CW14	36" × 36"	48" × 48"
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12	48" × 48"	48" × 48"

Posted Speed	Sign ^A Spacing "X"				
MPH	Feet (Apprx.)				
30	120				
35	160				
40	240				
45	320				
50	400				
55	500 ²				
60	600 ²				
65	700 ²				
70	800 ²				
75	900 ²				
80	1000 ²				
*	* 3				

SPACING

* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

△ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

GENERAL NOTES

- 1. Special or larger size signs may be used as necessary.
- 2. Distance between signs should be increased as required to have 1500 feet advance warning.
- 3. Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 4. 36" x 36" "ROAD WORK AHEAD" (CW20-1D)signs may be used on low volume crossroads at the discretion of the Engineer. See Note 2 under "Typical Location of Crossroad Signs".
- 5. Only diamond shaped warning sign sizes are indicated.
- 6. See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

ILE:

9-07

7-13 96

8-14



BC(2)-14 DN: TxDOT CK: TxDOT DW: TxDOT CK: TxDOT bc-14.dgn C)TxDOT November 2002 REVISIONS

CONT	SECT	JOB		HIGHWAY
915	12	562	WA	TSON RD
DIST		COUNTY		SHEET NO.
		BEXAR		61



BC(3)-14							L		
FILE:	bc-14,dgn		dn: Tx[DOT	ск: TxDOT	DW:	TxDOT	ск: TxDOT	θ
© ⊺xDOT	November 2002		CONT	SECT	JOB		н	GHWAY	Ľ.
REVISIONS			0915	12	562		WATSON RD		
9-07	9-07 8-14		DIST	T COUNTY SHEET N					\$
7-13					BEXAR			62	
97									



GENERAL NOTES FOR WORK ZONE SIGNS

- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- auide the travelina public safely through the work zone.
- verify the correct procedures are being followed.
- damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced. DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)
- regard to crashworthiness and duration of work requirements. Long-term stationary - work that occupies a location more than 3 days.
- more than one hour.
- Short-term stationary daytime work that occupies a location for more than 1 hour in a single daylight period.
- Short, duration work that occupies a location up to 1 hour.

SIGN MOUNTING HEIGHT

- as shown for supplemental plaques mounted below other signs.
- the around. Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- appropriate Long-term/Intermediate sign height.
- SIZE OF SIGNS

SIGN SUBSTRATES

- centers. The Engineer may approve other methods of splicing the sign face, REFLECTIVE SHEETING

- for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.

SIGN LETTERS

first class workmanship in accordance with Department Standards and Specifications.

REMOVING OR COVERING

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- intersections where the sign may be seen from approaching traffic. Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the
- Burlop shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face. Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

SIGN SUPPORT WEIGHTS

- 1. Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbaas will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact, Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbaas shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

FLAGS ON SIGNS

Flags may be used to draw attention to warning signs. When used the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

is governed by the "Texas Engineering Practice Act". No warranty of any purpose whatsoever. TxDDT assumes no responsibility for the conversion mats or for incorrect results or damages resulting from its use. ard any form DISCLAIMER: The use of this standa kind is made by TxDOT for of this standard to other

7/6/2020



Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.

All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and

The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes

The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD). The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can

The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or

Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used

The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in

Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting

Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except

The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above

Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to

Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

1. The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

1. The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports. "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave. All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide,

fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6"

All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 Orange sheeting, meeting the requirements of DMS-8300 Type BFL or Type CFL, shall be used for rigid signs with orange backgrounds.

1. All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of

Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any

entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.

98

SHEET 4 OF 12

Texas Department of Transportation

Traffic Operation Division Standard

BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES

	BC	: (4) -	14				
ILE:	bc-14.dgn	DN: T	xDOT	ск: TxDOT	Dw:	TxDOT	CK: TXDOT	÷
C TxDOT	November 2002	CONT	CONT SECT JOB		HIGHWAY			
	REVISIONS	0915	12	562		WAT	SON RD	E
9-07	8-14	DIST		COUNTY			SHEET NO.	ι.
7-13				BEXAR			63	1



PORTABLE CHANGEABLE MESSAGE SIGNS

- 1. The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to 2. eight characters per word), not including simple words such as "TO," "FOR, " "AT, " etc.
- 3. Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- 4. Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- 5. Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- 7. The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- 8. The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- 9. Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- 10. Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
 Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT"
- on a PCMS. Drivers do not understand the message. 13. Do not display messages that scroll horizontally or vertically across
- the face of the sign. 14. The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- 15. PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- 16. Each line of text should be centered on the message board rather than left or right justified.
- 17. If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

			-
WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Cannot	CANT	North	N
Center	CTR	Nor thbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	Y ING		
Detour Route	DETOUR RTE		
		Saturday	SAI
Fost	F	Service Rodd	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Edistocond	FMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S (resulta) C
Entrance Enter	ENT	Southbound	
Everess Lone	EXPIN	Speed	
Express Edite		Street	51
	YYYY FT		SUN
Fog Abead			PHONE
Freewoy		Temporary	TEMP
Freeway Blocked		Thursday	THURS
Friday		lo Downtown	TO DWNIN
Hazardous Driving			TRAF
Hazardous Material		Travelers	TRVLRS
		Tuesday	TUES
Vehicle		Time Minutes	TIME MIN
Hichway	HWY	Upper Level	UPR LEVEL
		Vehicles (s)	VEH, VEHS
		Warning	WARN
		Wednesday	WED
		Weight Limit	WT LIMIT
		West	W
		Westbound	(route) W
		Wet Pavement	WET PVMT
		Will Not	WONT
Lower Level			
Maintenance	MAINI	J	

RECOMMENDED	PHASES	AND	FORMATS	FOR	PCMS	MESSAGES	DUR
						• • • · · ·	

(The Engineer may approve other messages not specifically covered here.)

Phase 1: Condition Lists

Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE	FRONTAGE ROAD CLOSED	ROADWORK XXX FT	ROAD REPAIRS XXXX FT
ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT	FLAGGER XXXX FT	LANE NARROWS XXXX FT
ROAD CLSD AT FM XXXX	RIGHT LN CLOSED XXX FT	RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
RIGHT X LANES CLOSED	RIGHT X LANES OPEN	MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
CENTER LANE CLOSED	DAYTIME LANE CLOSURES	LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
N I GHT L ANE CLOSURE S	I-XX SOUTH EXIT CLOSED	DETOUR X MILE	ROUGH ROAD XXXX FT
VARIOUS LANES CLOSED	EXIT XXX CLOSED X MILE	ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
EXIT CLOSED	RIGHT LN TO BE CLOSED	BUMP XXXX FT	US XXX EXIT X MILES
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI	TRAFFIC SIGNAL XXXX FT	LANES SHIFT
XXXXXXXX BLVD CLOSED	* LANES SHIFT in F	Phose 1 must be used with	STAY IN LANE in Phase

Other Co	ndition List
ROADWORK XXX FT	ROAD REPAIRS XXXX FT
FLAGGER XXXX FT	LANE NARROWS XXXX FT
RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
DETOUR X MILE	ROUGH ROAD XXXX FT
ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
BUMP XXXX FT	US XXX EXIT X MILES
TRAFFIC SIGNAL XXXX FT	LANES SHIFT

NORTH STAY ON USE US XXX I-XX F SOUTH TO I-XX N TRUCKS WATCH USE FOR US XXX N TRUCKS WATCH EXPECT FOR DELAYS TRUCKS PREPARE EXPECT DELAYS ТΟ STOP REDUCE END SPEED SHOULDER XXX FT USE WATCH USE OTHER FOR ROUTES WORKERS STAY ΤN LANE

Action to Take/Effect on Travel

List

FORM

X LINES

RIGHT

USE

XXXXX

RD EXIT

USE EXIT

I-XX

MERGE

RIGHT

DETOUR

NEXT

X EXITS

USE

EXIT XXX

APPLICATION GUIDELINES

- 1. Only 1 or 2 phases are to be used on a PCMS. 2. The 1st phase (or both) should be selected from the
- "Road/Lane/Ramp Closure List" and the "Other Condition List".
- 3. A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- 4. A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- 5. If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- 6. For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

WORDING ALTERNATIVES

- 1. The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- appropriate.
- be interchanged as appropriate.
- 4. Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- 6. AHEAD may be used instead of distances if necessary. 7. FT and MI. MILE and MILES interchanged as appropriate.
- 8. AT. BEFORE and PAST interchanged as needed.
- 9. Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC. THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT FACH OF THE FOUR CORNERS OF THE UNIT.

FULL MATRIX PCMS SIGNS

- 1. When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 un CHANGEABLE MESSAGE SIGNS" above.
- 2. When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of t shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and 3. for, or replace that sign.
- 4. A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC some size arrow.

Roadway designation # IH-number, US-number, SH-number, FM-number

ING ROADWORK ACTIVITIES

Phase 2: Possible Component Lists



X X See Application Guidelines Note 6.

XX AM

2. Roadway designations IH, US, SH, FM and LP can be interchanged as EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can

	SHEET 6 OF 12								
	Tex	∽ [®] as Department c	of Tra	nsp	ortation		1 Ope D St	raffic erations ivision andard	
	BARR F	ICADE AN PORTABLE MESSAGE	ID Ci SI(CC HA GN	DNST NGEA (PC	RU BI	ICT LE S)	ION	
der "PORTABLE									I
he Engineer, it		BC	(6) -	- 1 4				
	FILE: DC	-14. dgn	dn: T>	DOT	ск: TxDOT	DW:	TxDOT	CK: TxDO	Т
I shall not substitute	C TxDOT No	vember 2002	CONT	SECT	JOB		ŀ	HIGHWAY	Т
	F	REVISIONS	0915	12	562		WAI	SON RD	1
(1), for the	9-07 8-	14	DIST		COUNTY			SHEET NO.	1
	7-13				BEXAR			65	
	100								-





GENERAL NOTES

- 1. For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- 2. For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- 3. For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in topers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

GENERAL DESIGN REQUIREMENTS

- Pre-qualified plastic drums shall meet the following requirements:
- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- 2. The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- 4. Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- 5. The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- 6. The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectorized space between any two adjacent stripes shall not exceed 2 inches in width.
- 7. Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- 9. Drum body shall have a maximum unballasted weight of 11 lbs.
- 10. Drum and base shall be marked with manufacturer's name and model number.

RETROREFLECTIVE SHEETING

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials," Type A reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be subplied difess offer wise spectrice in the plans.
 The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.

BALLAST

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- 2. Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- 3. Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- 4. The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- 5. When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- 6. Ballast shall not be placed on top of drums.
- 7. Adhesives may be used to secure base of drums to pavement.





DIRECTION INDICATOR BARRICADE

- The Direction Indicator Barricade may be used in tapers, transitions, and other areas where specific directional auidance to drivers is pecessary.
- guidance to drivers is necessary.If used, the Direction Indicator Barricade should be used in series to direct the driver through the transition and into the intended travel lane.
- 3. The Direction Indicator Barricade shall consist of One-Direction Large Arrow (CWI-6) sign in the size shown with a black arrow on a background of Type B_{FL} or Type C_{FL} Orange retroreflective sheeting above a rail with Type A retroreflective sheeting in alternating 4" white and orange stripes sloping downward at an angle of 45 degrees in the direction road users are to pass. Sheeting types shall be as per DMS 8300.
- 4. Double arrows on the Direction Indicator Barricade will not be allowed.
- 5. Approved manufacturers are shown on the CWZICD List. Ballast shall be as approved by the manufacturers instructions.



DETECTABLE PEDESTRIAN BARRICADES

- When existing pedestrian facilities are disrupted, cl relocated in a TIC zone, the temporary facilities sha detectable and include accessibility features consist the features present in the existing pedestrian facil
- 2. Where pedestrians with visual disabilities normally a closed sidewalk, a device that is detectable by a per with a visual disability traveling with the aid of a shall be placed across the full width of the closed s
- Detectable pedestrian barricades similar to the one p above, longitudinal channelizing devices, some concrebarriers, and wood or chain link fencing with a cont detectable edging can satisfactorily delineate a pede path.
- 4. Tape, rope, or plastic chain strung between devices of detectable, do not comply with the design standards "Americans with Disabilities Act Accessibility Guide for Buildings and Facilities (ADAAG)" and should not as a control for pedestrian movements.
- Warning lights shall not be attached to detectable p barricades.
- 6. Detectable pedestrian barricades may use 8" nominal barricade rails as shown on BC(10) provided that the rail provides a smooth continuous rail suitable for t trailing with no splinters, burrs, or sharp edges.

7/6/2020

	18" x 24" Sign (Maximum Sign Dimension) Chevron CWI-8, Opposing Traffic Lane Divider, Driveway sign D70a, Keep Right R4 series or other signs as approved by Engineer12" x 24" Vertical Panel mount with diagonals sloping down towards travel way
	Plywood, Aluminum or Metal sign substrates shall NOT be used on plastic drums
	SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS
tintended	 Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
See note 3 st for oved rian	 Chevrons and other work zone signs with an orange background shall be manufactured with Type B_{FL} or Type C_{FL}Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
ı Jiling	3. Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
	4. Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
	 Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
	 Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
	7. Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
losed, or	 R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.
stent with lity.	SHEET 8 OF 12
use The erson Long cane sidewalk. pictured ete	Traffic Operations Texas Department of Transportation Standard
inuous lestrian are not in the lines be used	BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES
pedestrian	BC (8) -14
top hand	FILE: bc-14.dgn DN: TxDOT CK: TXDOT DW: TxDOT CK: TXDOT CK: TXDOT CK: TXDOT CK: TXDOT CK: TXDOT
	REVISIONS 0915 12 562 WATSON RD 4-03 7-13 DIST COUNTY SHEET NO. 9-07 8-14 RFYAR C 7





and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway. 3. Chevrons, when used, shall be erected on the out side of a sharp curve or turn, or on the far side of an intersection. They shall be in line with

and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment

4. To be effective, the chevron should be visible

5. Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.

6. For Long Term Stationary use on tapers or transitions on freeways and divided highways self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.



- 1. LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- 3. LCDs shall be placed in accordance to application and installation requirements specific to the device, and
- 4. LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- 5. LCDs shall be supplemented with retroreflective delineation as required for temporary barriers
- 6. LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10) placed near the top of the
- 1. Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate NCHRP 350 crashworthiness requirements based on roadway speed and barrier application.
- 2. Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation
- or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings. 3. Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements
- specific to the device, and used only when shown on the CWZTCD list. 4. Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH)
- urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions. When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated
- as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

CW6-4

OPPOSING TRAFFIC LANE DIVIDERS (OTLD)

8" to 12"

Surface

,Mount

Base

8" to 12"

(Rigid or self-righting)

See

VP-1

Fixed Base

w/ Approved

Adhesive

GENERAL NOTES

- 1. Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- 2. Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- 3. Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- 4. The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- 5. Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- 7. The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed	Formula	D Tap	Minimur esirab er Lena X X	n le gths	Suggested Maximu Spacing of Channelizing Devices			
*		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{CO}$	150'	165′	180'	30'	60′		
35		205'	225'	245'	35′	70′		
40	60	265'	295′	320'	40′	80'		
45		450′	495′	540′	45′	90′		
50		500'	550'	600'	50 <i>'</i>	100′		
55	1 = W S	550'	605′	660'	55 <i>'</i>	110′		
60	L-#3	600 <i>ʻ</i>	660 <i>'</i>	720′	60 <i>'</i>	120′		
65		650′	715′	780'	65′	130'		
70		700′	770′	840′	70′	140'		
75		750'	8251	900,	75′	150′		
80		800'	880'	960'	80′	160'		

XX Taper lengths have been rounded off. L=Length of Taper (FT.) W=Width of Offset (FT.) S=Posted Speed (MPH)

SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS

SHEET 9 OF 12 Traffic Operations Division Standard Texas Department of Transportation

BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (9) - 14

FILE:	bc-14.dgn	DN: T:	KDOT	CK: TxDOT	DW:	TxDOT	cĸ:TxDOT	θ
© ⊺xDOT	November 2002	CONT	IT SECT JOB HIGH		GHWAY	Щ		
	REVISIONS	0915	12	562		WATS	ON RD	F
9-07	8-14	DIST		COUNTY			SHEET NO.	₩
7-13				BEXAR			68	
103								-



WORK ZONE PAVEMENT MARKINGS

GENERAL

- 1. The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- 2. Color, patterns and dimensions shall be in conformance with the Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- 3. Additional supplemental pavement marking details may be found in the plans or specifications.
- 4. Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- 5. When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- 6. When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- 7. All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

RAISED PAVEMENT MARKERS

- 1. Raised pavement markers are to be placed according to the patterns on BC(12).
- 2. All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

PREFABRICATED PAVEMENT MARKINGS

- 1. Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- 2. Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.

MAINTAINING WORK ZONE PAVEMENT MARKINGS

- 1. The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- 2. Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- 3. The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- 4. Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

REMOVAL OF PAVEMENT MARKINGS

- 1. Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- 2. The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- 3. Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Povement Markings and Markers".
- 4. The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- 5. Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- 6. Blast cleaning may be used but will not be required unless specifically shown in the plans.
- 7. Over-painting of the markings SHALL NOT BE permitted.
- 8. Removal of raised pavement markers shall be as directed by the Engineer.
- 9. Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS, " unless otherwise stated in the plans.
- 10.Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

Temporary Flexible-Reflective Roadway Marker Tabs



STAPLES OR NAILS SHALL NOT BE USED TO SECUR TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKE TABS TO THE PAVEMENT SURFACE

- 1. Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- 2. Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
 - A, Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
 - B. Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- 3. Small design variances may be noted between tab manufacturers.
- 4. See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- 1. Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200,
- 2. All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- 3. Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:

YELLOW - (two amber reflective surfaces with yellow body). WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICA	TIONS
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-824
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-824
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-824

pavement markings can be found at the Material Producer List

web address shown on BC(1).

RE	
ER	

Traffic Operations Traffic Operations Division Standard BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS BEC (111) - 14 FILE: bc-14. dgn DH: TXDOT CH: TXD	SHEET 11 OF 12									
BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS BC (111) - 14 FILE: bc-14. dgn DN: TXDOT CK: TXDOT DW: TXDOT CK: TXDOT CTXDOT FEDFUORY 1998 CONT SECT JOB HIGHMAY REVISIONS 2-98 9-07 1-02 7-13 DIST COUNTY SHEET NO. DIST COUNTY SHEET NO.	Texas Department of	of Tra	nsp	ortation		Ti Ope Di Sta	raffic ratio visior indar	ns n rd		
FILE: bc-14. dgn DN: TXDOT ck: TXDOT DW: TXDOT CK: TXDOT	BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS									
FILE: DC - 14, dgn DN: 1XUU1 CK: 1XUU1 1XUI1 1XUU1	BL			- 4		T 0.01	T	DOT		
Control Control <t< th=""><th>FILE: DC-14, dgn</th><th>DN: 13</th><th>SECT</th><th>CK: IXDUI</th><th>DW:</th><th>TXDOT</th><th></th><th>XDOT</th></t<>	FILE: DC-14, dgn	DN: 13	SECT	CK: IXDUI	DW:	TXDOT		XDOT		
2-98 9-07 1-02 7-13 DIST COUNTY SHEET NO. DIST COUNTY SHEET NO.	REVISIONS	0915	12	562		WAT	SON	RD		
1-02 $7-13$	2-98 9-07	DIST		COUNTY			SHEET	NO.		
	1-02 7-13			BEXAR			70)		









SCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". The use of this standard is governed by the "TxD01 assumes no responsibility and is made by TxD01 for any purpose whatsoever. TxD01 assumes no responsibility this standard to other formats or for incorrect results or damages resulting fro

LEGEND									
	z Тур	e 3 Bo	rrica	de	Cr		nanneliz		
) Hea	vy Wor	k Veh	icle			ruck Mour ttenuator		
Ē	Tra Fla	ailer Mounted ashing Arrow Board (M) Me		ortable essage S					
•	Sig	ר			$\langle \cdot \rangle$	Т	raffic F	low	
\bigtriangleup	FIO	g			LO	F	lagger]
Formula	р Тар	Minimur esirab er Len X X	n le gths	Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing	Stopping Sight Distance		
	10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		Distance	"B"	
	150'	1651	180'	30'	60′		120′	90,	200'
$L = \frac{WS}{60}$	205'	225'	245'	35′	70'		160′	120'	250 <i>ʻ</i>
00	265 <i>'</i>	295′	320'	40'	80'		240′	155'	305'
	450 <i>'</i>	495′	540'	45′	90'		320′	195'	360′
	500'	550'	600'	50ʻ	100'		400 <i>'</i>	240'	425′
I = W S	550'	605′	660'	55'	110'		500 <i>'</i>	295′	495 <i>'</i>
2	600ʻ	660′	720'	60 <i>'</i>	120'		600 <i>'</i>	350'	570′
	650'	715'	780'	651	130'		700'	410′	645′
	700′	770'	840'	70'	140'		8001	475′	730′
	750′	8251	900′	75′	150'		900'	540'	820′

X Conventional Roads Only

XX Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

MOBILE DURATION STATIONARY TERM STATIONARY STATI	TERM ONARY

1. Flags attached to signs where shown are REQUIRED.

2. All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.

3. The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4D "ONE LANE ROAD AHEAD" sign, but proper sign spacing shall be maintained.

4. Sign spacing may be increased or an additional CW20-1D "ROAD WORK AHEAD" sign may be used if advance warning ahead of the flagger or R1-2 "YIELD" sign is less than 1500 feet. 5. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.

6. Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.

7. R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work spaces should be no longer than one half city block. In rural areas on roadways with less than 2000 ADT, work spaces should be no longer than 400 feet.

8. R1-2 "YIELD" sign with R1-2aP "TO ONCOMING TRAFFIC" plaque shall be placed on a support at a 7 foot minimum mounting height.

9. Flaggers should use two-way radios or other methods of communication to control traffic. 10. Length of work space should be based on the ability of flaggers to communicate. 11. If the work space is located near a horizontal or vertical curve, the buffer distances

should be increased in order to maintain adequate stopping sight distance to the flagger and a queue of stopped vehicles (see table above).

12. Channelizing devices on the center-line may be omitted when a pilot car is leading traffic and approved by the Engineer.

3. Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.

Traffic Operations Division Standard									
TRAFFIC CONTROL PLAN ONE-LANE TWO-WAY TRAFFIC CONTROL TCP(1-2)-18									
FILE: tcp1-2-18, dgn	DN:		СК:	DW:	CK:				
© TxDOT December 1985	CONT	SECT	JOB		HIGHWAY				
A-90 A-98	0915	12	562		WATSON RD				
2-94 2-12	DIST		COUNTY		SHEET NO.				
1-97 2-18		BEXAR 73							


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDDI for any purpose whatsoever. TXDDI assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

LEGEND									
~~~~~	Type 3 Barricade	Channelizing Devices							
□¤	Heavy Work Vehicle	K	Truck Mounted Attenuator (TMA)						
Ē	Trailer Mounted Flashing Arrow Board	M	Portable Changeable Message Sign (PCMS)						
•	Sign	2	Traffic Flow						
$\langle \rangle$	Flag	٩	Flagger						

Posted Speed	Formula	D Tap	Minimur esirab er Leng X X	n le gths	Suggested Spacin Channe Dev	d Maximum ng of lizing ices	Minimum Sign Spacing "X"	Suggested Longitudinal Buffer Space
*		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	Distance	"В"
30		150'	1651	180'	30′	60 <i>`</i>	120′	90′
35	$L = \frac{WS}{60}$	205'	225'	245'	35′	70′	160′	120'
40	60	265′	295′	320'	40′	80′	240′	155'
45		450'	495′	540'	45′	90'	320′	195'
50		500'	550'	600'	50 <i>'</i>	100′	400′	240′
55	1 = W S	550'	605′	660 <i>'</i>	55 <i>'</i>	110'	500 <i>'</i>	295′
60	L-#5	600 <i>'</i>	660'	720'	60 <i>'</i>	120'	600 <i>'</i>	350′
65		650′	715′	780′	65 <i>'</i>	130'	700′	410′
70		700'	770'	840'	70'	140'	800′	475'
75		750'	825′	900'	75'	150'	900′	540'

X Conventional Roads Only

XX Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE									
MOBILE	MOBILE SHORT SHORT TERM INTERMEDIATE LONG TERM DURATION STATIONARY TERM STATIONARY STATIONARY								

### GENERAL NOTES

- 1. Flags attached to signs where shown, are REQUIRED.
- 2. All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated in the plans, or for routine maintenance work, when approved by the Engineer. 3. Stockpiled material should be placed a minimum of 30 feet from
- Shockprise indict of shock a process a minimum of the shock a minimum of the shock and the shock a minimum of the shock and the shock a minimum of the shock and the shock the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- 5. Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space. 6. See TCP(5-1) for shoulder work on divided highways, expressways and
- freeways. 7. Inactive work vehicles or other equipment should be parked near the
- right-of-way line and not parked on the paved shoulder. 8. CW21-5 "SHOULDER WORK" signs may be used in place of CW21-1D
- "ROAD WORK AHEAD" signs for shoulder work on conventional roadways.





No warranty of any for the conversion Practice Act". responsibility Texas Engineering TxDOT assumes no is governed by purpose whatso this standard TxDOT for any ٩ç DISCLAIMER: The use kind is mode

	LEGEND											
-		Гуре З	Be	arrico	ode		Channelizing Devices			1		
Ę	Þ	Heavy W	101	ork Vehicle								
)	1   F	Trailer Tashir	. I ng	Mounte Arrow	ed v Board		P N	Portable Message S	Changeable ign (PCMS)			
	5	Sign				2	Т	raffic F	low			
\	. 1	Flag				٩	F	lagger		]		
	т	Minim Desirc aper Le <del>X</del> <del>X</del>	iur ib l inç	n le gths	Suggeste Spaci Channe Dev	d Maximum ng of lizing vices		Minimum Sign Spacing "Y"	Suggested Longitudinal Buffer Space	Stopping Sight Distance		
	10 Offs	i 11' setOffse	e t	12' Offset	On a Taper	On a Tangen	t	Distance	"B"			
	150	0' 165	'	180'	30'	60′		120'	90′	200'		
	20	5′ 225	'	245'	35′	70'		160'	120'	250 <i>'</i>		
	265	5′ 295	1	320'	40'	80′		240'	155'	305′		
	450	0' 495	1	540'	45′	90'		320'	195'	360′		
	500	0' 550	1'	600′	50'	100'		400'	240'	425′		
	550	0' 605	1	660 <i>′</i>	55'	110'		500'	295'	495′		
	600	oʻ 660	1	720′	60'	1201		600'	350'	570′		
	650	0' 715	1	780′	65′	130'		700'	410'	645′		
	700	0' 770	'	840'	70'	140'		800'	475′	730'		
	750	0' 825	· T	900'	75'	150'		9001	540′	820′		

XX Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE										
 SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY							
<b>√</b>	1	4								

1. Flags attached to signs where shown, are REQUIRED. 2. All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved

3. The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4 "ONE LANE ROAD XXX FT" sign, but proper sign spacing shall be maintained. 4. Flaggers should use two-way radios or other methods of communication to control traffic. 5. Length of work space should be based on the ability of flaggers to communicate. 6. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow

7. Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown

8. The R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work space should be no longer than one half city block. In rural areas, roadways with less than 2000 ADT, work space should be no longer than 400 feet. 9. The R1-2aP "YIELD TO ONCOMING TRAFFIC" sign shall be placed on a support at a 7 foot minimum

10.Channelizing devices on the center line may be omitted when a pilot car is leading traffic and

11. If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain stopping sight distance to the flagger and a queue of stopped vehicles.

12.Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to

Texas Department of Transportation Standard											
TRAFFIC CONTROL PLAN ONE-LANE TWO-WAY TRAFFIC CONTROL											
	۲ <b>۲</b> –	27-10	9								
FILE: tcp2-2-18.dgn	DN:	СК: [	OW: CK:								
C TxDOT December 1985	CONT S	SECT JOB	HIGHWAY								
REVISIONS 8-95 3-03	0915	12 562	WATSON RD								
1-97 2-12	DIST	COUNTY	SHEET NO.								
4-98 2-18	SATX	BEXAR	75								
162											



	LEGEND									
	Type 3 Barricade  Channelizing Device									
B	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)							
	Trailer Mounted Flashing Arrow Board	••••	Raised Pavement Markers Ty II-AA							
ŀ	Sign	$\langle$	Traffic Flow							
$\bigtriangledown$	Flag	٩	Flagger							

Posted Formula Speed		Minimum Desirable Taper Lengths XX			Suggester Spacin Channe Dev	d Maximum ng of lizing ices	Minimum Sign Spacing "X"	Suggested Longitudinal Buffer Space
*		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	Distance	"B"
30		150'	165′	180'	30'	60 <i>'</i>	120'	90'
35	$L = \frac{WS}{60}$	205'	225'	245'	35′	70'	160'	120'
40	60	265'	295′	320'	40′	80'	240'	155'
45		450′	495′	540'	45′	90'	320′	195'
50		500'	550'	600′	50 <i>'</i>	100′	400′	240′
55	1 = WS	550'	605′	660'	55 <i>'</i>	110'	500 <i>'</i>	295′
60	L-#5	600'	660'	720'	60′	120'	600 <i>'</i>	350′
65		650′	715′	780'	65 <i>'</i>	130'	700'	410'
70		700'	770'	840'	70′	140'	800 <i>'</i>	475′
75		750'	825′	900 <i>'</i>	75′	150'	900'	540′

X Conventional Roads Only

XX Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE									
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY					
				TCP (2-3b) ONL Y					

### GENERAL NOTES

1. Flags attached to signs where shown, are REQUIRED.

2. All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer. When work space will be in place less than three days existing pavement markings may remain in place. Channelizing devices shall be used to separate traffic.

Flagger control should NOT be used unless roadway conditions or heavy traffic volume require additional emphasis to safely control traffic. Flagger should be positioned at end of traffic queue. The R4-1 "DO NOT PASS," R4-2 " PASS WITH CARE" and construction

regulatory speed zone signs may be installed within CW20-1D "ROAD WORK AHEAD" signs. Proper spacing of signs shall be maintained.

Conflicting pavement marking shall be removed for long term projects.

A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place. Type 3 Barricades or other channelizing devices may be substituted. Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space.

#### [CP (2-3a)

9. Conflicting pavement markings shall be removed for long-term projects. For shorter durations where traffic is directed over a yellow centerline, channelizing devices which separate two-way traffic should be spaced on tapers at 20' or 15' if posted speeds are 35 mph or slower, and for tangent sections, at 1/2(S) where S is the speed in mph. This tighter device spacing is intended for the area of the conflicting markings, not the entire work zone.

Texas Department of Transportation										
TRAFFIC CONTROL PLAN TRAFFIC SHIFTS ON TWO-LANE ROADS										
	<u>\Z</u>	<u>-                                    </u>	<u>) - i</u>	<u>o</u>						
FILE: tcp(2-3)-18.dgn	DN:		СК:	DW:	CK:					
© TxDOT December 1985	CONT	SECT	JOB		HIGHWAY					
REVISIONS	0915	12	562		WATSON RD					
1-97 2-12	DIST		COUNTY		SHEET NO.					
4-98 2-18	SATX		BEXAR	2	76					
163										



DATE:

LEGEND									
<u>e 7 7 7 7</u>	Type 3 Barricade	Channelizing Devices							
	Heavy Work Vehicle	K	Truck Mounted Attenuator (TMA)						
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)						
4	Sign	2	Traffic Flow						
$\Diamond$	Flag	LO	Flagger						

Posted Speed	Formula	D Tap	Minimur esirab er Lena X X	n le gths	Suggestee Spacin Channe Dev	d Maximum ng of lizing ices	Minimum Sign Spacing "x"	Suggested Longitudinal Buffer Space
*		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	Distance	"В"
30		150'	1651	180'	30′	60′	120'	90'
35	$L = \frac{WS}{60}$	205'	225'	245'	35′	70'	160'	120'
40	60	265′	295′	320'	40′	80'	240'	155'
45		450'	495′	540'	45′	90'	320′	195′
50		500'	550'	600'	50'	100'	400′	240'
55	1 = WS	550'	605 <i>'</i>	660'	55′	110'	500 <i>'</i>	295′
60	L - 11 J	600'	660'	720'	60 <i>'</i>	120′	600 <i>'</i>	350′
65		650 <i>'</i>	715′	780′	65′	130'	700′	410'
70		700'	770'	840'	70′	140'	8001	475'
75		750'	825′	900'	75'	150'	900'	540′

X Conventional Roads Only

** Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE						
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY		
			✓	✓		

### GENERAL NOTES

- Flags attached to signs where shown, are REQUIRED.
   All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer Channelizing devices used to close lanes may be supplemented with the Chevron Alignment Sign placed on every other channelizing device. Chevrons may be attached to plastic drums as per BC Standards.
- Channelizing devices used along the work space or along tangent sections may be supplemented with vertical panels (VP) placed on everyother channelizing device. If night time conditions make it difficult to see at least two VPs, the VPs may be placed on each channelizing device.
- The placement of pavement markings may be omitted on Intermediate-term stationary work zones with the approval of the Engineer.
- Shadow Vehicle with TMA and high intensity rotating, flashing, oscillating or strobe lights. Shadow Vehicle with TMA and high intensity rotating, flashing, oscillating or strobe lights. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned in each closed lane, on the shoulder or off the paved surface, next to those shown in order to protect a wider work space.

e							
ed ly	Texas Department	t of Transp	oortation	Traffic Operations Division Standard			
er	TRAFFIC	CONT	ROL P	LAN			
	LANE CI	LANE CLOSURES ON					
	DIVIDE	DHI	GHWAY	S			
3D 8"	ТСР	(2-6	) - 18				
0	FILE: tcp2-6-18.dgn	DN:	CK: DW:	CK:			
_	© TxDOT December 1985	CONT SECT	JOB	HIGHWAY			
S	REVISIONS	0915 12	562	WATSON RD			
-	8-95 2-12	DIST	COUNTY	SHEET NO.			
	1-97 2-18	SATX	BEXAR	77			
	166						



No warranty of any for the conversion w its use Texas Engineering Practice Act". TxDOT assumes no responsibility is governed by the purpose whatsoever mats or for incorre SCLAIMER: The use of this standard nd is made by TxDOT for any this standard to other for

DATE:

LEGEND						
<u>~~~~</u>	Type 3 Barricade		Channelizing Devices			
4	Sign	Ŷ	Traffic Flow			
$\langle$	Flag	۵O	Flagger			
••••	Raised Pavement Markers Ty II-AA	₽₽	Temporary or Portable Traffic Signal			

ated eed	Formula	Minimum Desirable Taper Lengths <del>X</del> <del>X</del>		Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing	Suggested Longitudinal Buffer Space	Stopping Sight	
*		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	Distance	"B"	
ō		150'	165′	180'	30'	60´	120'	90'	200'
5	$L = \frac{WS}{GO}$	205'	225′	245'	35′	70′	160'	120′	250'
0	60	265′	295′	320'	40′	80′	240′	155′	305′
5		450 <i>'</i>	495 <i>'</i>	540'	45′	90 <i>'</i>	320′	195′	360′
õ		500'	550'	600'	50 <i>'</i>	100′	400′	240′	425′
5	1 = W S	550'	605 <i>'</i>	660 <i>'</i>	55 <i>'</i>	110′	500 <i>'</i>	295′	495 <i>'</i>
Ō	L - # J	600 <i>'</i>	660 <i>'</i>	720′	60′	120'	600 <i>'</i>	350′	570′
5		650′	715′	780′	65 <i>'</i>	130'	700'	410′	645′
0		700′	770'	840′	70'	140'	800 <i>'</i>	475′	730'
5		750′	825′	900'	75'	150'	900′	540′	820'

* Conventional Roads Only

XX Taper lengths have been rounded off.

L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE					
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY	
			<ul> <li>✓</li> </ul>	1	

### GENERAL NOTES

1. Flags attached to signs where shown are REQUIRED. 2. When this TCP is used at a location which does not involve a bridge, a 48" x 48" CW20-4D "ONE LANE ROAD AHEAD" signs should be used in lieu of the CW5-3 "ONE LANE BRIDGE" signs. The CW13-1P Advisory Speed Plaque

is required with either warning sign. Raised pavement markers shall be placed 40 feet c-c on centerline between DO NOT PASS signs and stop or yield lines.

. For intermediate term situations, when it is not feasible to remove and restore pavement markings, the channelization must be made dominant by using a very close spacing. This is especially important in locations of conflicting information, such as where traffic is directed over a double yellow centerline. In such locations a maximum channelizing device spacing of 20 feet is recommended. The 20 foot channelizing device spacing recommendation is intended for the area of conflicting information and not the entire work zone.

### TCP (2-8a)

5. Traffic control by CW3-2 "YIELD AHEAD" symbol signs for one lane two-way traffic control operations should be limited to work spaces less than 400 feet long and roadways with less than 2000 ADT. Otherwise, portable traffic signals should be used.

6. If power is available, a flashing beacon should be attached to the CW3-2 "YIELD AHEAD" symbol sign for emphasis.

7. The R1-2 "YIELD" and R1-2aP "TO ONCOMING TRAFFIC" signs and other regulatory signs shall be installed at 7 foot minimum mounting height.

#### TCP (2-8b)

8. A list of approved Portable Traffic Signals can be found in the "Compliant Work Zone Traffic Control Devices" list.

9. Portable traffic signals should be located to provide adequate stopping sight distance for approaching motorist (See table above).

TRAFFIC CONTROL PLAN LONG TERM ONE - LANE TWO - WAY CONTROL           TUE:         tcp://similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/similar.org/sim	Texas Department	Traffic Operations Division Standard						
FILE:         tcp2-8-18, dgn         DN:         CK:         DW:         CK:           ① TxDDT         December         1985         CONT         SECT         JOB         HIGHWAY           8-95         3-03         FEVISIONS         0915         12         562         WATSON RD           1-97         2-12         DIST         COUNTY         SHEET NO.	TRAFFIC CONTROL PLAN LONG TERM ONE-LANE TWO-WAY CONTROL TCP(2-8)-18							
C T xDDT         December         1985         CONT         SECT         JOB         HIGHWAY           8-95         3-03         REVISIONS         0915         12         562         WATSON RD           1-97         2-12         DIST         COUNTY         SHEET NO.	FILE: tcp2-8-18.dgn	DN:	CK: DW:	CK:				
REVISIONS         0915         12         562         WATSON RD           1-97         2-12         DIST         COUNTY         SHEET NO.	© TxDOT December 1985	CONT SEC	JOB	HIGHWAY				
DIST COUNTY SHEET NO.	REVISIONS	0915 12	562	WATSON RD				
	1-97 2-12	DIST	COUNTY	SHEET NO.				
4-98 2-18  SATX  BEXAR 78	4-98 2-18	SATX	BEXAR	78				



No warranty for the conv Texas Engineering Practice Act". TxDOT assumes no responsibility the ned by t whatsoe for s n d SCLAIMER: The use of this standard nd is made by TxDOT for any this standard to other for

LEGEND						
Trail Vehicle						
Shadow Vehicle				ARROW BOARD DI	SPLAT	
Work Vehicle			<b>↑</b>	RIGHT Directional		
Heavy Work Vehicle 🗲			∎	LEFT Directional		
Truck Mounted Attenuator (TMA)			₽	Double Arrow		
Traffic Flow			•	CAUTION (Alter Diamond or 4 (	rnating Corner Flash)	
TYPICAL USAGE						
ILE	SHORT DURATION	SHOR	T TERM	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY	

EAD vehicles shall be equipped with arrow boards as
LEAD vehicle is not used the WORK vehicle must be
ow board. The Engineer will determine if the LEAD VEHICLE
are required based on prevailing roadway conditions.

ing roadway conditions, traffic volume, and sight distance restrictions. 2. The use of amber high intensity rotating, flashing, oscillating, or strobe lights

on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.

3. The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE and TRAIL VEHICLE

Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.

Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.

Each vehicle shall have two-way radio communication capability.

When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to

Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.

"X VEHICLE CONVOY" (CW21-10cT) or "WORK CONVOY" (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" X 48" diamond shaped "WORK CONVOY"(CW21-10T) or "X VEHICLE CONVOY" (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The "X VEHICLE CONVOY" sign shall not be used on the SHADOW VEHICLE

10. On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a "DO NOT PASS" (R4-1) sign should be placed on the back of the

Red Reflective White Reflective	Texas Department	Traffic Operations Division Standard						
± 6" (HEIGHT OF TMA)	TRAFFIC CONTROL PLAN MOBILE OPERATIONS UNDIVIDED HIGHWAYS							
	T(	CP (3)	-1)-1	3				
MA)	FILE: tcp3-1.dgn	dn: TxDOT	ск: TxDOT dw:	TxDOT CK: TxDOT				
	CTxDOT December 1985	CONT SECT	JOB	HIGHWAY				
	REVISIONS	0915 12	562	WATSON RD				
	8-95 7-13	DIST	COUNTY	SHEET NO.				
	1-97		BEXAR	79				
	175							



LEGEND						
*	Trail Vehicle					
* *	Shadow Vehicle	ARROW BOARD DISPLAT				
* * *	Work Vehicle	₽	RIGHT Directional			
þ	Heavy Work Vehicle	<b>€</b>	LEFT Directional			
	Truck Mounted Attenuator (TMA)	<b>₽</b>	Double Arrow			
$\Diamond$	Traffic Flow	0	CAUTION (Alternating Diamond or 4 Corner Flash)			

TYPICAL USAGE							
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY			
1							

1. TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as

illustrated. When a LEAD vehicle is not used on two way roads the WORK vehicle must have an arrow board. For divided roadways, the arrow board on the WORK vehicle is optional based on the type of work being performed. The Engineer will determine if the LEAD vehicle and/or TRAIL vehicle are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions. The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating, or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights. The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE, ADVANCE WARNING

and TRAIL VEHICLE are required. Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity

and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION

Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the

Each vehicle shall have two-way radio communication capability. When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles. Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary

depending on sight distance restrictions. Motorists approaching the convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors. X VEHICLE CONVOY (CW21-10cT) or WORK CONVOY (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" x 48" diamond shaped WORK CONVOY (CW21-10T) or X VEHICLE CONVOY (CW21-10DT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The X VEHICLE CONVOY sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used. LEFT LANE CLOSED (CW20-5bTL), RIGHT LANE CLOSED (CW20-5bTR), or CENTER LANE CLOSED (CW20-5dT) sign should be used on the Advance Warning Vehicle. As an

option, a portable changeable message sign (PCMS) or truck mounted changeable message sign (TMCMS) with a minimum character height of 12", and displaying the same legend may be substituted for these signs. An appropriate directional arrow display, simulating the size and legibility of the flashing arrow board may be used in the second phase of the PCMS/TMCMS message. When this is done, the arrow board will not be required on the Advance Warning Vehicle.

11.A double arrow shall not be displayed on the arrow board on the Advance Warning

12.For divided highways with three or four lanes in each direction, use TCP(3-2). 13.Standard diamond shape versions of the CW20-5 series signs may be used as an option if the rectangular signs shown are not available. 14. The Advance Warning Vehicle may straddle the edgeline when Shoulder width makes

15.0n two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a DO NOT PASS (R4-1) sign should be placed on the back of the rearmost protection vehicle.

Texas D	Department of Tra	nsportation	Tr Ope Div Sta	affic rations /ision ndard
TR/ M	AFFIC COM OBILE OP RAISED P RKER INST REMO TCP(3-	NTROL P ERATION AVEMENT IALLATI VAL 3) - 14	LAN NS [ ON/	
FILE: tcp3-3	dan DN: T)	OOT CK: TXDOT DW	* TxDOT	ск: TxDOT
© TxDOT Septem	iber 1987 CONT	SECT JOB	н	GHWAY
2.04 4.00 REVISI	ons 0915	12 562	WAT	SON RD
2-94 4-98 8-95 7-13	DIST	COUNTY		SHEET NO.
1-97 7-14		BEXAR		80
177				





- Prior to the beginning of construction, all currently striped no-passing zones shall be signed with the Α. DO NOT PASS (R4-1) signs and PASS WITH CARE (R4-2) signs placed at the beginning and end of each zone for each direction of travel except as otherwise provided herein. Signs marking these individual no-passing zones need not be covered prior to construction if the signs supplement the existing pavement markinas.
- At the discretion of the Engineer, in areas of numerous no-passing zones, several zones may be combined в. as a single zone. If passing is to be prohibited over one or more lengthy sections, a DO NOT PASS sign and a NEXT XX MILES (R20-1TP) plaque may be used at the beginning of such zones. The DO NOT PASS sign and the NEXT XX MILES plaque should be repeated every mile to the end of the no-passing zone. In areas where there is considerable distance between no-passing zones, the end of the no-passing zone may be signed with a PASS WITH CARE sign and a NEXT XX MILES plaque.
- с. Depending on traffic volumes and length of sections, it may be desirable to prohibit passing throughout the project to prevent damage to windshield and lights. The DO NOT PASS sign and NEXT XX MILES plaque should be used and repeated as often as necessary for this purpose. Where several existing zones are to be combined into one individual no-passing zone, the sign at the beginning of the zone should be covered until the surfacing operation has passed this location so as not to have the DO NOT PASS sign conflict with the existing pavement markings. Also, unless one days operation completes the entire length of such combined zones, appropriate DO NOT PASS and PASS WITH CARE signs should be placed at the beginning and end of the no-passing zones where the surfacing operation has stopped for the day.
- D. R4-1 and R4-2 are to remain in place until standard pavement markings are installed.

### "NO CENTER LINE" SIGN (CW8-12)

- Center line markings are yellow pavement markings that delineate the separation of travel lanes that Α. have opposite directions of travel on a roadway. Divided highways do not typically have center line markinas.
- At the time construction activity obliterates the existing center line markings(low volume roads may в. not have an existing centerline), a NO CENTER LINE (CW8-12) sign should be erected at the beginning of the work area, at approximately 2 mile intervals within the work area, beyond major intersections and other locations deemed necessary by the Engineer.
- C. The NO CENTER LINE signs are to remain in place until standard pavement markings are installed.

### "LOOSE GRAVEL" SIGN (CW8-7)

- When construction begins, a LOOSE GRAVEL (CW8-7) sign should be erected at each end of the work area Α. and repeated at intervals of approximately 2 miles in rural areas and closer in urban areas.
- B. The LOOSE GRAVEL signs are to remain in place until the condition no longer exists.

#### PAVEMENT MARKINGS

- Temporary markings for surfacing projects shall be Temporary Flexible-reflective Roadway Marker Tabs Α. unless otherwise approved by the Engineer. Tabs are to be installed to provide true alignment for striping crews or as directed by the Engineer. Tabs will be placed at the spacing indicated. Tabs should be applied to the pavement
- no more than two (2) days before the surfacing is applied. After the surfacing is rolled and swept, the cover over the reflective strip shall be removed.
- Tabs shall not be used to simulate edge lines.
- C. Tab placement for overlay/inlay operations shall be as shown on the WZ(STPM) standard sheet.

### COORDINATION OF SIGN LOCATIONS

- A. The location of warning signs at the beginning and end of a work area are to be coordinated with other signing typically shown on the Barricade and Construction Standards for project limits to ensure adequate sign spacing.
- Where possible the ROAD WORK AHEAD (CW20-1D), LOOSE GRAVEL (CW8-7), and NO CENTER LINE (CW8-12) signs should be placed in the sequence shown following the OBEY WARNING SIGNS STATE LAW (R20-3T) and the TRAFFIC FINES DOUBLE (R20-5T) sign, and one "X" sign spacing prior to the CONTRACTOR (G20-6T)sign typically located at or near the limits of surfacing. LOOSE GRAVEL and NO CENTER LINE signs will then be repeated as described above.

<u>ו</u>	Ξ	Ξ	Ξ	
	<u>ו</u>	<u>]</u>	<u>)</u> = = =	<u>]</u> = = = =

Posted Speed <del>X</del>	Minimum Sign Spacing "X" Distance
30	120'
35	160'
40	240'
45	320'
50	400'
55	500'
60	600
65	700'
70	800'
75	900'

* Conventional Roads Only

		TYPICAL	USAGE	
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
			1	4

# GENERAL NOTES

- The traffic control devices detailed on this sheet will be furnished and erected as directed by the Engineer on sections of roadway where tabs must be placed prior to the surfacing operation which will cover or obliterate the existing pavement markings.
- 2. The devices shown on this sheet are to be used to supplement those required by the BC Standards or others required elsewhere in the plans.
- Signs shall be erected as detailed on the BC 3. Standards or the Compliant Work Zone Traffic Control Devices List (CWZTCD) on supports approved for Long-Term / Intermediate-Term Work Zone Sign Supports.
- When surfacing operations take place on divided 4. highways, freeways or expressways, the size of diamond shaped construction warning signs shall be 48" x 48".
- 5. Signs on divided highways, freeways and expressways will be placed on both right and left sides of the roadway based on roadway conditions as directed by the Engineer.

Texas Department of Transportation

Traffic Operation Division Standard

# TRAFFIC CONTROL DETAILS FOR SURFACING OPERATIONS

	1		: 7 -	·1)-	· 1	3	
E:	tcp7-1.dgn	DN:	TxDOT	ск: TxDOT	DW:	TxDOT	CK: TXDOT
TxDOT	March 1991	CONT	SECT	JOB			HIGHWAY
	REVISIONS	091	512	562		WAT	SON RD
92 4-98		DIST		COUNTY			SHEET NO.
91 1-13				BEXA	٦_		81



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDDI for any purpose whatsoever. TXDDI assumes no responsibility for the conversion **don** this standard to other formars or for incortect results or damages resulting from its use.

J	MMARY OF	LARGE SIGN	S				
	SIGN	REFLECTIVE	SQ FT	GALVA STRUC S1	NIZE TURA EEL	ГO	DRILLED SHAFT
	DIMENSIONS	SHELTING		Size	и П	F)	24" DIA. (LF)
	96" X 48"	Type B _{FL} or C _{FL}	32				
	192" X 96"	Type B _{FL} or C _{FL}	128	W8×18	16	17	12

▲ See Note 6 Below

DEPARTMENTAL	MATERIAL	SPEC	IFICATIONS
PLYWOOD SIGN BLANKS			DMS-7100
ALUMINUM SIGN BLANKS			DMS-7110
SIGN FACE MATERIALS			DMS-8300

COLOR	USAGE	SHEETING MATERIAL
ORANGE	BACKGROUND	TYPE B _{FL} OR TYPE C _{FL}
BLACK	LEGEND & BORDERS	NON-REFLECTIVE ACRYLIC FILM

3. For projects more than two miles in length, Give Us a BRAKE signs should be repeated halfway through the project. The Give Us a Brake (CW21-1T) may be

4. Work zone speed limits are sometimes used in conjunction with GIVE US A BRAKE signing. See BC(3) for location and spacing of construction

5. Give Us a Brake (CW21-1T) signs and supports shall be considered subsidiary to Item 502, "Barricades, Signs and Traffic Handling."

6. The 96" X 48" Working For You Give Us A BRAKE (G20-7T) may use a 1/2" or 5/8" plywood substrate or 0.125" aluminum sheeting substrate and may be supported by two 4" x 6" wood posts with drilled holes for breakaway as per BC(5) and will be

7. The Working For You Give Us A BRAKE (G20-7T) 192" X 96" sign shall be paid for Item 647 - Large Roadside Sign Supports and Assemblies.

8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor

Texas Department	of Tra	nsp	ortation	Op D St	Traffic erations Division Candard	
WOR "GIVE U S WZ	K IS IG (B	Z( A N: Ri	DNE BRAK S () - 1 3	KE '		
FILE: wzbrk-13.dgn	DN: T)	<dot< th=""><th>CK: TXDOT DW:</th><th>TxDO</th><th>T CK:TxDOT</th><th>φ</th></dot<>	CK: TXDOT DW:	TxDO	T CK:TxDOT	φ
©TxDOT August 1995	CONT	SECT	JOB		H]GHWAY	Ц С
REVISIONS	0915	12	562	WA	TSON RD	F
6-96 5-98 7-13	DIST		COUNTY		SHEET NO.	₩
8-96 3-03			BEXAR		82	
116						-



	LEGEND						
<u>e 7 7 7 8</u>	Type 3 Barricade		Channelizing Devices				
₿	Heavy Work Vehicle	K	Truck Mounted Attenuator (TMA)				
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)				
-	Sign	$\langle$	Traffic Flow				
$\Diamond$	Flag	٩	Flagger				

Posted Speed	Formula	D Top	Minimur esirab er Lena X X	n Ie gths	Suggester Spacin Channe Dev	d Maximum ng of lizing ices	Minimum Sign Spacing "x"	Suggested Longitudinal Buffer Space
*		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	Distance	"В"
30		150′	1651	180'	30'	60′	120'	90'
35	$L = \frac{WS}{60}$	205′	225'	245'	35′	70′	160'	120'
40	60	265′	295′	320′	40′	80′	240'	1551
45		450′	495′	540'	45′	90′	320′	1951
50		500'	550'	600′	50 <i>'</i>	100'	400′	240'
55	1 = WS	550'	605′	660′	55 <i>'</i>	110'	500 <i>1</i>	295 <i>'</i>
60	2-113	600'	660′	720'	60′	120'	600′	350'
65		650'	715′	780′	65 <i>'</i>	130'	700′	410'
70		700'	770'	840'	70′	140′	800′	475′
75		750'	825′	900'	75′	150'	900 <i>'</i>	540'

* Conventional Roads Only

XX Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

WORKERS IN BUCKET TRUCKS SHALL NOT WORK ABOVE OPEN LANES OF TRAFFIC.

o-piece when			
ked			
cording			
) lights.			
s of	Sł	HEET 1 OF 2	
ignals er. R1-3P)	Texas Departme	nt of Transportation	Traffic Operations Division Standard
above ration		SIGNAL	WORK
ation an in the taper.	w w	7 (BTS-1)	-13
ed for	FILE: wzbts-13.dgn	DN: TXDOT CK: TXDOT D	w: TxDOT CK:TxDOT
ice from	(C) TxDOT April 1992	CONT SECT JOB	HIGHWAY
		091512 562	WAISON RD
	2-98 10-99 7-13 4-98 3-03	SATX BEXAR	SHEET NO.







DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TKDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion **130** this standard to other formats or for incortect results or damages resulting from its use. 7/6/2020

LEGEND				
<u>~~~~</u>	Type 3 Barricade			
4	Sign			

Posted Speed <del>X</del>	Minimum Sign Spacing "X" Distance
30	120′
35	160'
40	240′
45	320'
50	400′
55	500′
60	600′
65	700′
70	800′
75	900′

* Conventional Roads Only

### GENERAL NOTES

- 1. This sheet is intended to provide details for temporary work zone road closures. For permanent road closure details see the D&OM standards.
- 2. Barricades used shall meet the requirements shown on Barricade and Construction Standard BC(10) and listed on the Compliant Work Zone Traffic Control Devices list (CWZTCD).
- 3. Stockpiled materials shall not be placed on the traffic side of barricades.
- 4. Barricades at the road closure should extend from pavement edge to pavement edge.
- 5. Detour signing shown is intended to illustrate the type of signing that is appropriate for numbered routes or un-numbered routes as labeled. It does not indicate the full extent of detour signing required. Detour routes should be signed as shown elsewhere in the plans.
- If the road is open for a significant distance beyond the intersection or there are significant origin/destination points beyond the intersection, the signs and barricades at this location should be located at the edge of the traveled way.
- 7. The Street Name (M4-12T) sign is to be placed above the DETOUR (M4-9S) sign.
- 8. For urban areas where there is a shorter distance between the intersection and the actual closure location, the ROAD CLOSED XX MILES AHEAD (R11-3a) sign may be replaced with a ROAD CLOSED TO THRU TRAFFIC (R11-4) sign. If adequate space does not exist between the intersection and the closure a single ROAD CLOSED AHEAD (CW20-3D) sign spaced as per the table above may replace the ROAD CLOSED 1000 FT (CW20-3B) and ROAD CLOSED 500 FT (CW20-3C) signs.
- 9. Signs and barricades shown shall be subsidiary to Item 502. Locations where these details will be required shall be as shown elsewhere in the plans.

Texas Department	of Tra	nsp	ortation		Tra Oper Div Stai	affic rations rision ndard			
WORK ZONE ROAD CLOSURE DETAILS									
				DW:	TYDOT				
	CONT	SECT	.108		11001	SHWAY	Ÿ.		
REVISIONS	0915	12	562		WATS	SON RD			
1-97 4-98 7-13	DIST		COUNTY			SHEET NO.	ц		
2-98 3-03		BEXAR 85				85			



	LEGEND							
	Type 3 Barricade		Channelizing Devices					
□‡¤	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)					
	Trailer Mounted Flashing Arrow Panel	(M)	Portable Changeable Message Sign (PCMS)					
<b>_</b>	Sign	$\langle \cdot \rangle$	Traffic Flow					
$\bigcirc$	Flag	LO	Flagger					

Posted Speed	Minimum Desirable Formula Taper Lengths * *			Suggested Spacing Channeliz Devic	Maximum g of zing ces	Minimum Sign Spacing	Suggested Longitudinal Buffer Space	
*		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	Distance	"B"
30		150'	165'	180'	30'	60'	120'	90'
35	$L = \frac{WS}{60}$	205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45		450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55	= W S	550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	4 10 '
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only

* * Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE									
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY					
	✓	1							



	Texas Departme	ent of Tra	nsp	ortation	Op L S	Traffic erations Division tandard
listance ps in ay	TEMPORAR ¹ W	Y RL 7(RS	JM ) - `	BLE S	str	IPS
	FILE: wzrs16.dgn	dn: Tx	DOT	CK: TxDOT DW	· TxDO	í ск: TxDO
	C TxDOT November 2012	CONT	SECT	JOB		HIGHWAY
	REVISIONS	0915	12	562	WA	TSON RD
	2-14	DIST		COUNTY		SHEET NO.
	4-16	SAT		BE X AR		86





- greater than 14 calendar days unless weather conditions prohibit placement. Permanent pavement markings shall
- passing is permitted. Signs shall be in accordance with the "Texas Manual on Uniform Traffic Control Devices"



is governed by the "Texas Engineering Practice Act". purpose whatsoever. TxDOT assumes no responsibility mats or for incorrect results or damages resulting fro this standard i y TxDOT for any rd to other form °¢ ISCLAIMER: The use ind is mode ā

### DEPARTMENTAL MATERIAL SPECIFICATIONS

DMS-8240

DMS-8300

PERMANENT PREFABRICATED PAVEMENT MARKINGS TEMPORARY (REMOVABLE) PREFABRICATED PAVEMENT MARKINGS DMS-8241

SIGN FACE MATERIALS

USAGE	SHEETING MATERIAL
BACKGROUND	TYPE B _{FL} OR TYPE C _{FL} SHEETING
LEGEND & BORDERS	ACRYLIC NON-REFLECTIVE SHEETING

1. If spalling or holes occur, ROUGH ROAD (CW8-8) signs should be placed in advance of the condition and be repeated every two miles where the

 UNEVEN LANES (CW8-11) signs shall be installed in advance of the condition and repeated every mile. Signs installed along the uneven lane condition may be supplemented with the NEXT XX MILES (CW7-3aP) plaque or Advisory Speed (CW13-1P) plaque.

3. NO CENTER LINE (CW8-12) signs and temporary pavement markings as per the WZ(STPM) standard shall be installed if yellow centerlines separating two way traffic are obscured or obliterated. Repeat NO CENTER LINE signs every two miles where the center line markings are not in place. The signs and markings shall remain in place until permanent pavement markings are

4. Signs shall be spaced at the distances recommended as per BC standards.

5. Additional signs may be required as directed by the Engineer. Signs shall remain in place until final surface is applied. Signs shall be considered subsidiary to Item 502 "BARRICADES, SIGNS AND TRAFFIC HANDLING."

6. Signs shall be fabricated and mounted on supports as shown on the BC standards and/or listed on the "Compliant Work Zone Traffic Control Devices"

7. Short term markings shall not be used to simulate edge lines.

All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition.

		TABLE 1							
on	Edge Heig	ht (D)	* Warning Devices						
	Less than 1¼" (max 1½" (typ	or equal to: imum-planing) ical-overlay)	Sign: CW8-11						
,	Distance operation lanes wit after wor	Distance "D" may be a maximum of 1 1/4 " for planing operations and 2" for overlay operations if uneven lanes with edge condition 1 are open to traffic after work operations cease.							
D 77	Less than	or equal to 3" Sign: CW8-11							
	, Distance "D" may be a maximum of 3" if uneven lanes with edge condition 2 or 3 are open to traffic after work operations cease. Uneven lanes should not be open to traffic when "D" is greater than 3".								
RING NG OI E IN	PLANING, PERATIONS THE PLAN		Traffic Operations Division Standard       SIGNING FOR						
G SI	GN SIZE		UNEVEN LANES						
3	6" × 36"								
4	8" × 48"		WZ(UL)-13						
		a	zul-13.dgn DN: TxDOT CK:TxDOT DW: TxDOT CK:TxDOT						



No warranty of any for the conversion governed by the "Texas Engineering Practice Act". Topse whatsoever, IxDD dssumes no responsibility - Top for incorrect results or domone results on for ° d t of this standard by TxDOT for any LAIMER: The use is mode

	LEGEND				
<u></u>	Type 3 Barricade				
• • •	Channelizing Devices				
(L)	Trailer Mounted Flashing Arrow Board				
<b>_</b>	Sign				
~~~~	Safety glare screen				
DEPAR	TMENTAL MATERIAL SPECIFIC	ATIONS			
SIGN FACE	MATERIALS	DMS-8300			
DELINEATORS AND OBJECT MARKERS DMS-8600					
MODULAR GL	ARE SCREENS FOR HEADLIGHT BARRIER	DMS-8610			
Only pre-qualified products shall be used. A copy of the Compliant Work Zone Traffic Control Devices List" CWZTCD) describes pre-qualified products and their sources and may be found at the following web address: http://www.txdot.gov/business/resources/producer-list.html					



soever use. what its TxDOT for any purpose domages resulting from ይዖ is mode results kind 'rect incori anty of or for warr 1ats for Tor Engineering Practice Act". of this standard to other "Texas ersion the con Şţ for + this standard is gove es no responsibility DISCLAIMER: The use of T×DOT assum

7/6/2020



soever use. TxDOT for any purpose what damages resulting from its ይዖ is made resul†s any kind incorrect No warranty of formats or for Engineering Practice Act". of this standard to other "Texas | /ersion o the cor this standard is governed by es no responsibility for the DISCLAIMER: The use of T×DOT assum

7/6/2020





No warranty of any nsibility for the conver from its use this standard is governed by the "Texas Engineering Practice Act". s by TxDOT for any purpose whatsoever. TxDOT assumes no respon And to other formats or for incorrect results or domages resulting

Texas Department		De Di St	esign vision andard						
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE & VERTICAL TRACKING									
EC	(1)-	· 16	5						
FILE: ec116	dn: TxD	OT	ск: КМ	DM: ,	/P	DN/CK: LS			
C TxDOT: JULY 2016	CONT	SECT	JOB		1	HIGHWAY			
REVISIONS	0915	12 562			WATSON R				
	DIST	DIST COUNTY				SHEET NO.			
	SAT		BEXAR	2		92			









what its purpos from any Iting for resul anty of any kind is made by TxDOT or for incorrect results or damages warr ats Engineering Proctice Act". No of this standord to other forn "Texas rersion (the the by for gover ibility responsit stan no this mes DISCLAIMER: The use of t TxDOT assur

1. EROSION CONTROL LOGS SHALL BE INSTALLED IN ACCORDANCE WITH MANFACTURER'S

10. FOR HEAVY RUNOFF EVENTS, ADDITIONAL UPSTREAM STAKES MAY BE NECESSARY TO KEEP LOG FROM FOLDING IN ON ITSELF.

	MINIMUM COMPACTED DIAMETER	-			UM ACTEI TER	D -
S	DIAMETER MEASURE Control Logs SP	MENT PECIF	S IEC	OF ER) IN PL	OSI AN:	ION S
.5" over	Texas Department	t of Trar	nsp	ortation	D D Si	esign ivision tandard
	TEMPORA SEDIMEN POLLUTION CO	ARY FAN DNTF	E ID RO	ROSIOI WATE L MEA	N, IR NSL	JRES
	EROSION EC	CON -(9)	ITF - 16	ROL LO S)G	
	FILE: ec916	DN: TxDO	T	CK: KM DW:	LS/PT	CK: LS
	REVISIONS	0915	12	562	WA	TSON RD
		DIST				SHEET NO.
		SAL		BEXAR		95





201

2

6/25/2020 X:\data\Inf

DATE: FILE:



EROSION CONTROL LOG AT CURB INLET

ĆL-CI

SHEET 3 OF 3								
Texas Department	of Tra	nsp	ortation		Di Di Si	esign ivision andard		
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES								
EROSION	00	NTI	ROL	LC	C			
EC(9)-16								
FILE: ec916	dn: TxD	OT	ск: КМ	DW:	LS/PT	ск: LS		
C TxDOT: JULY 2016	CONT	SECT JOB				HIGHWAY		
REVISIONS	0915	12 562			WA	TSON RD		
	DIST COUNTY					SHEET NO.		
	SAT		BEXAR	2		95B		

Beginning chain WATSON description Point WAT01 N 13.655.632 7926 E 2.093.957.0278 Sta 100+00.00 Course from WAT01 to PC WATSON-1 S 45° 25' 12.73" E Dist 1,424 1041 Curve Data Curve WATSON-1 116+80.29 N 13,654,453.3911 E 2,095,153.8568 P.I. Station Delta 35° 06' 09.46" (LT) 7° 04' 24.79" Degree 256.1898 = Tangent 496.2517 Length = Radius = 810.0000 Externa _ 39.5488 Long Chord 488.5269 -Mid Ord = 37 7077 114+24 10 N 13.654.633.2112 E 2.094.971.3795 P C Station 119+20.36 N 13,654,411.2082 E 2,095,406.5499 P.T. Station СС N 13,655,210.1528 E 2,095,539.9201 Back = S 45° 25' 12.73" E Ahead = S 80° 31' 22.19" E Chord Bear = S 62° 58' 17.46" E Course from PT WATSON-1 to PC WATSON-2 S 80° 31' 22.19" E Dist 1,596.5779 Curve Data Curve WATSON-2 P.I. Station 136+50.94 N 13,654,126.2590 E 2,097,113.5177 Delta 67° 38' 53 55" (RT) 28° 38' 52 40" Degree = 134 0102 Tangent 236,1368 Lenath = 200.0000 Radius 40.7462 External 222.6581 Long Chord = Mid Ord -33 8499 135+16.93 N 13,654,148.3244 E 2,096,981.3366 P.C. Station 137+53.07 N 13,653,995.6178 E 2,097,143.3777 P.T. Station C.C. N 13,653,951.0541 E 2,096,948.4057 S 80° 31' 22.19" E Back Ahead = S 12° 52' 28.64" E Chord Bear = S 46° 41' 55.42" E Course from PT WATSON-2 to PC WATSON-3 S 12° 52' 28.64" E Dist 341.6340 Curve Data Curve WATSON-3 142+11.84 N 13,653,548.3830 E 2,097,245.5996 P.I. Station 12° 51' 07.85" (RT) Delta 5° 30' 33.15" Degree = Tangent = 117.1342 233.2854 Length = Radius 1,040.0000 External 6 5756 232.7966 Long Chord = Mid. Ord. 6.5343 = 140+94.70 N 13,653,662.5725 E 2,097,219.5000 143+27.99 N 13,653,431.2488 E 2,097,245.6455 P.C. Station P.T. Station N 13,653,430.8414 E 2,096,205.6456 C.C. = S 12° 52' 28.64" E Back Ahead = S 0° 01' 20.80" E Chord Bear = S 6° 26' 54.72" E Course from PT WATSON-3 to WAT02 S 0° 01' 20.80" E Dist 782.6403 Point WAT02 N 13,652,648.6085 E 2,097,245.9521 Sta 151+10.63 Ending chain WATSON description

Point VWB500 N 13,654,193.6957 E 2,096,870.5006 Sta 534+00.00 Course from VWB500 to VWB501 S 81° 40' 06.93" E Dist 24.8849 Point VWB501 N 13,654,190.0899 E 2,096,895.1229 Sta 534+24.88 Course from VWB501 to PC RPBVWB-1 S 80° 31' 22 19" E Dist 27 3405 Curve Data Curve RPBVWB-1 535+21.23 N 13,654,174.2264 E 2,096,990.1519 P.I. Station Delta = 21° 52' 45.35" (LT) Degree = 16° 02' 57.26" Tangent = 69 0035 Lenath = 136.3259 357.0000 Radius = External = 6.6076 Long Chord : 135,499 Mid. Ord. = 6.4875 P.C. Station P.T. Station 534+52.23 N 13,654,185.5881 E 2,096,922.0903 535+88.55 N 13,654,189.0464 E 2,097,057.5452 N 13,654,537.7156 E 2,096,980.8719 СС Back = S 80° 31' 22.19" E Ahead = N 77° 35' 52.46" E Chord Bear = N 88° 32' 15.14" E Curve Data Curve RPBVWB-2 536+10.44 N 13,654,193.7468 E 2,097,078.9203 P.I. Station Delta = 28° 33' 20.99" (RT) 66° 37' 22.80" = Degree Tangent = 21.8858 Length 42.8618 = Radius 86 0000 External = 2 7411 42 4196 Long Chord = Mid. Ord. = 2.6565 535+88.55 N 13,654,189.0464 E 2,097,057.5452 P.C. Station P.T. Station 536+31.41 N 13,654,187.6578 E 2,097,099.9421 N 13,654,105.0532 E 2,097,076.0155 C.C Back = N 77° 35' 52.46" E Ahead = S 73° 50' 46.55" E Chord Bear = S 88° 07' 27.05" E Curve Data Curve RPBVWB-3 P.I. Station 536+38.63 N 13,654,185.6512 E 2,097,106.8697 Delta = 6° 59' 43.43" (LT) 48° 33' 20.68" Degree = Tangent = 7.2124 14.4069 Lenath = Radius 118.0000 External 0.2202 Long Chord = 14.3980 Mid. Ord. = 0 2198 P.C. Station 536+31 41 N 13.654.187 6578 E 2.097.099 9421 P.T. Station 536+45.82 N 13.654.184.5032 E 2.097.113.9902 N 13,654,300.9990 E 2,097,132.7715 C.C. = S 73° 50' 46.55" E Back Ahead = S 80° 50' 29.99" E Chord Bear = S 77° 20' 38.27" E Course from PT RPBVWB-3 to VWB502 S 80° 50' 29.99" E Dist 143.0586

Point VWB502 N 13,654,161.7336 E 2,097,255.2252 Sta 537+88.88

Ending chain RPBVWB description

Beginning chain RPBVWB description

Beginning chain RPBWSB description ----N 13.654.155.9325 E 2.096.762.6711 Sta 433+00.00 Point WSB400 Course from WSB400 to WSB401 S 80° 31' 22 19" E Dist 75.0528 Point WSB401 N 13,654,143.5747 E 2,096,836.6994 Sta 433+75.05 Course from WSB401 to PC RPBWSB-1 S 72° 06' 46.88" E Dist 41.2823 Curve Data Curve RPBWSB-1 (Chord Definition) 434+94.45 N 13,654,106.9036 E 2,096,950.3238 P.I. Station = 44° 48' 12.67" (RT) Delta Degree = 30° 35' 51.10" Tangent = 78.1131 Length Radius Length 146.4286 Radius 189.5000 = External = 15 4681 Long Chord = 144 4364 14.3007 Mid Ord = 434+16.34 N 13,654,130.8952 E 2,096,875.9863 P.C. Station C.C. 435+62.76 N 13,654,037.4969 E 2,096,986.1618 P.T. Station N 13,653,950.5549 E 2,096,817.7832 СС Back = S 72° 06' 46.88" E Ahead = S 27° 18' 34.21" E Chord Bear = S 49° 42' 40.54" E Curve Data Curve RPBWSB-2 (Chord Definition) 436+15.34 N 13,653,990.7801 E 2,097,010.2839 P.I. Station Degree = 36° 16' 32.70" (LT) Delta Degree = 36° 18' 08.98" Tangent = 52 5769 99 9263 Length Radius = 160.5000 = External 8.3922 Long Chord = 99.9288 Mid. Ord. = 7.9752 435+62.76 N 13,654,037.4969 E 2,096,986.1618 436+62.69 N 13,653,967.3904 E 2,097,057.3717 P.C. Station C.C. P.T. Station CC N 13.654.111.1338 E 2.097.128.7727 Back = S 27° 18' 34.21" E Ahead = S 63° 35' 06.91" E Chord Bear = S 45° 26' 50.56" E Curve Data Curve RPBWSB-3 (Chord Definition) PI Station 437+23.93 N 13,653,940.1462 E 2,097,112.2193 = 38° 53' 01.12" (RT) Delta Degree = 33° 29' 54.90" Tangent = 61.2414 Length 116 0755 = Radius = 173,5000 External = 10.4912 115.4988 Long Chord = Mid. Ord. = 9.8930 P.C. Station 436+62.69 N 13,653,967.3904 E 2,097,057.3717 P.T. Station 437+78.77 N 13,653,884.5087 E 2,097,137.8116 C.C. N 13,653,812.0043 E 2,096,980.1875 Back = S 63° 35' 06.91" E Ahead = S 24° 42' 05.79" E Chord Bear = S 44° 08' 36 35" E

Course from PT RPBWSB-3 to WSB402 S 22° 40' 08.34" E Dist 55.9803 Point WSB402 N 13,653,832.8530 E 2,097,159.3868 Sta 438+34.75 Course from WSB402 to WSB403 S 16° 56' 15.17" E Dist 179.3132 Point WSB403 N 13,653,661.3179 E 2,097,211.6260 Sta 440+14.06 Ending chain RPBWSB description

N 13,653,954.9929 E 2,097,176.2562 Sta 638+00.00 Curve Data 639+19.31 N 13,654,070.2792 E 2,097,145.7082 71° 23' 59 79" 73 5258 = 119.0408 80.2463 28.5908 108.4221 21 0802 638+45.78 N 13,653,999.6247 E 2,097,166.0549 639+64.82 N 13,654,096.7124 E 2,097,214.3181 N 13,654,021.8313 E 2,097,243.1674 Curve Data 639+96.87 N 13,654,107.7978 E 2,097,244.3889 45° 48' 03.11" = 32 0490 62 7484 125 0976 4.0401 62.0926 3.9137 639+64.82 N 13,654,096.7124 E 2,097,214.3181 640+27.57 N 13,654,103.0588 E 2,097,276.0856 N 13.653.979.3364 E 2.097.257.5880 DATE REVISIO Jun 11 \bigstar DOCUMENT WAS AUTHORIZED BY JULIO RAMOS 107672 6/25/2020 ______ NOVONAL ENG Curve Data 200+74.18 N 13,654,151.9909 E 2,097,133.4537 34° 43' 28.97" 11550 IH 10 WEST, SUITE 395 SAN ANTONIO, TEXAS 78230-1037 TEL: (210) 641-9999 | FAX: (210) 641-644 TBPE REGISTRATION NO.: F-2214 CEC 74,1774 = 139.4211 165.0000 TBPLS REGISTRATION NO.: 100410-15.9069 135 3103 BEXAR COUNTY × 14 5082 PUBLIC WORKS DEPARTMENT 200+00.00 N 13.654.105.0532 E 2.097.076.0155 201+39.42 N 13,654,140.1846 E 2,097,206.6855 N 13,653,977.2880 E 2,097,180.4236 = N 50° 44' 41 15" F HORIZONTAL ALIGNMENT DATA SHEE<u>T 1 OF 1</u> Texas Department C 2019 of Transportation FFD PI AN EEDERAL AID PROJECT NO DIV.NO NO 96 6 STATE DIST COUNTY TEXAS SAT BEXAR CONT. SECT. JOB HIGHWAY / STREE 0915 12 562 WATSON RD

Beginning chain RPBWEB description Point WEB600 Course from WEB600 to PC RPBWEB-1 N 12° 52' 28.64" W Dist 45.7828 Curve RPBWEB-1 P.I. Station Delta = 84° 59' 42.29" (RT) Degree = Tangent = External = Long Chord = Mid Ord = P.C. Station P.T. Station Back = N 16° 03' 54.46" W Ahead = N 68° 55' 47.83" E Chord Bear = N 26° 25' 56.68" E Curve RPBWEB-2 P.I. Station Delta = 28° 44' 21.49" (RT) Tangent = Length = Radius = External = Long Chord = Mid. Ord. = P.C. Station P.T. Station Back = N 69° 45' 50.21" E Ahead = S 81° 29' 48 29" F Chord Bear = N 84° 08' 00.96" E _____ Ending chain RPBWEB description CUR VERANO1 VERANO2 Beginning chain VERANO description Curve VERANO1 P.I. Station Delta = 48° 24' 48.87" (RT) Degree = Tangent = Length Radius External = Long Chord = Mid Ord = P.C. Station P.T. Station C.C. Back Ahead = S 80° 50' 29.99" E Chord Bear = N 74° 57' 05.58" E Course from PT VERANO1 to VERANO2 S 80° 50' 29.99" E Dist 1,758.0419 Point VERANO2 N 13,653,860.3688 E 2,098,942.3163 Sta 218+97.46 Ending chain VERANO description

D BY: D SCALE: BLE: RIVER: WATSON_BW_PDF.pltcfg D ON: 12:52:14 PM LOTTED E LOTTED S EN TABLE LOT DRIV LOTTED (





ITEM#	DESCRIPTION	UNIT	QTY
0100	PREPARING ROW	AC	1
0216	PROOF ROLLING	HR	4
0275	CEMENT	TON	20
0275	CEMENT TREAT (EXIST MATL) (6")	SY	1803
0340	D-GR HMA(SQ) TY-B PG64-22	TON	595
0340	D-GR HMA(SQ) TY-C PG64-22	TON	364
0340	D-GR HMA(SQ) TY-D PG70-22	TON	175
0529	CONC CURB (TY II)	LF	584
0530	DRIVEWAYS(ACP)	SY	20
0531	CONC SIDEWALKS (4")	SY	312
0536	CONC MEDIAN	SY	64



		ITEN			DESCRIPT				ΟΤΥ
			·//						<u>س</u> انه ۸
		010							4
R	-	021			110				20
	*	027							30
	स्	027				(1L)(0")		51	2491
	Ņ	034		SK HMA(SQ	UTV 0 PC64	-22			595
		034		R HMA(SQ	UTY D D D D D D D D D D D D D D D D D D D	~~~		TON	487
		034		R HMA(SQ	1) 1 Y-D PG70-	22			185
		043		KAP (CON	u)(4 IN)			CY ·-	20
		052	9 <u>CO</u>	NC CURB (1 Y II)			LF	1424
		053		IVEWAYS(/	ACP)			SY	135
		053		NC SIDEWA	ALKS (4")			SY	429
		056	υ ΜΑ	ILBOX INS.	IALL-D (TWG	i-PUST) TY 1		EA	1
					PLA	AN VIEW L	EGEND)	
									-
				-		- PROP E	DGE OF F	ROADWAY	<i>,</i>
				-		- EXISTIN	G FEATU	RES	
						EVIATO			
		05-0		-		— EXISTIN	G RIGHT	OF WAY	
	STA	OFFSET	LT/RT	-		ם מעם		MΔV	
	113+90.65	2.00		•		- PROPR	IGHT UF	v v /~ T	
	113+86.23	14.00	RT		\rightarrow	PROP T	RAFFIC A	RROW	
	115+74.90	7.76		_					
	115+88.65	7.04		L		CONCR	ETE PAVE	MENT	
	116+33.12	0.01							
	116+33.29	7.09		l L			ETE APRO	JN	
	113+86.23	26.00	LT		1	DRIVEW	/AY		
	114+66.86	29.17	RT						
	116+31.33	31.21	RT		(#)	STA & C	FFSET		
)	116+43.27	30.94	RT			RADIUS			
	113+81.23	0.77			к=#				
	113+44.00	9.88	RT		()	PROPOS	SED MAILE	XOX	
	116+57.43	61.21	RT						
	116+80.41	64.66	RT						
;	116+86.88	48.21	RT			-			
i	113+29.59	12.00	RT			-			<u> </u>
						-	REVISION		APPROVED
					NO DATE	GRAF	HIC SCALE		1
	+			-	-	(II	N FEET)		
		1			25 12.5	0	25	50	75
				- ' I		4	" = 50'		
	<u> </u>	!		-		1 Vor	- 50 1" = 10'		
	I	ļ		l .		<u>, , , , , , , , , , , , , , , , , , , </u>			
	+			-	ATEO	FTEL			
	$\vdash \downarrow$			_	5. Sim J		THE SEAL	APPEARIN	G ON THIS
				_ I	<u>;*/</u>	1	JULIO R	WAS AUTH AMOS, P.F	IORIZED BY
						KAMUS		, • • •	
	г — — т	1		-		NGE		0/0-1-	
	·			-	SS/ON	AL ENGI		6/25/2020	
	. т І	-1							
		'		- '	·				
		,			1				
				1					
	$\vdash +$			-			11550	H 10 WEST	SUITE 395
					C	\mathbf{EC}	SAN ANT	ONIO TEXAS	78230-1037
					CIVIL ENGINEER	ING CONSULTANTS	TBPE RE	GISTRATION	NO. F 2214
						JOH JURDEN, INC.	IBPLS REG	ISTRATION N	10.:100410-00
	+			-		BE	XAR C	OUNTY	7
			_	_ _		PUBLIC W	VORKS	DEPAR	TMENT
				- ' <u>-</u>					
				-		WATS	<u>ON RC</u>	AD	
						RO/			
	$\vdash +$			-	1	PLAN AN	ND PRC	FILE	
				_		112:00:00	TO 074	117.00	00
					51/	× 113+00.00	TUSIA	117+00	.00
	г — — т	₁				SHE	<u>ET 2 OF 9</u>		
				-	[0		
-	· · ···				@ 2010		Texas	s Depar	tment
							of Tr	ansport	ation
					FED RD DIV NO	FEDERA	L AID PROJE	CT NO.	PLAN SHT NO
]			6				98
	$\vdash +$			S 2 – -	STATE	DIST.		COUNTY	
			i	<u>a</u> i	IEXAS	SAT		BEXAF	(
					CONT.	SECT.	JOB	HIGHW	AY / STREET
					I U915	12	1 562	I WAT	SON RD



PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOT TED ON: 6/25/2020 @ 12:52:28 PM



ITEM#	DESCRIPTION	UNIT	QTY
0100	PREPARING ROW	STA	5
0216	PROOF ROLLING	HR	7
0275	CEMENT	TON	36
0275	CEMENT TREAT (EXIST MATL) (6")	SY	2945
0340	D-GR HMA(SQ) TY-B PG64-22	TON	972
0340	D-GR HMA(SQ) TY-C PG64-22	TON	571
0340	D-GR HMA(SQ) TY-D PG70-22	TON	219
0529	CONC CURB (TY II)	LF	892
0531	CONC SIDEWALKS (4")	SY	487
0536	CONC MEDIAN	SY	602



PLAN AND PROFILE	

STA 117+00.00 TO STA 121+50.00

- i	SHEET 3 OF 9								
- 	© 2019	7*	D Texas of Tra	Departn nsporta	nent tion				
	FED.RD. DIV.NO.	FEDERAL AID PROJECT NO. PLAN SHT							
	6				99				
2 9 – –	STATE	DIST.	COUNTY						
Щ К	TEXAS	SAT		BEXAR					
	CONT.	SECT.	JOB	HIGHWAY	/ STREET				
	0915	12	562	WATS	ON RD				

#	STA	OFFSET	LT/RT
1	117+02.66	2.29	RT
2	117+91.11	2 <u>.</u> 17	RT
3	118+08.17	0.94	RT
4	119+39.25	8.00	LT
5	117+02.69	6.29	RT
6	119+39.26	8.00	RT
7	119+39.26	32.00	LT
8	117+06.83	30,26	RT
9	119+39.26	32.00	RT
10	121+41.89	8.00	LT



		ITEM#		DESCRIPT	ON		UNIT	QTY
1		0100	PREPARIN		STA	5		
٢		0216 PROOF ROLLING						7
K.		0275	TON	36				
R		0275	CEMENT T	REAT (EXIST MA	\TL)(6")		SY	2750
Ş		0340	D-GR HMA	(SQ) TY-B PG64-	-22		TON	908
		0340	D-GR HMA	(SQ) TY-C PG64	22		TON	528
a line of		0340	D-GR HMA	(SQ) TY-D PG70	22		TON	176
		0529	CONC CUR	RB (TY II)			LF	900
		0530	DRIVEWAY	(S(ACP)			SY	45
		0531	CONC SIDE	EWALKS (4")			SY	500
	0536 CONC MEDIAI						SY	800
					AN VIEW L PROP E EXISTIN PROP R PROP R PROP T CONCR	EGEND DGE OF RI IG FEATUR IG RIGHT OF W RAFFIC AR ETE PAVER ETE APRO	OADWA RES DF WAY VAY RROW MENT N	Y
#	STA	OFFSET	LT/RT	1	DRIVEW	/AY		
1	121+58.00	6.69			074.9.0	FFOFT		
2	122+00.00	1.00	RT	(#)	STA&C	FFSEI		
3	122+00.00	8.00		R = #	RADIUS			
<u>4</u> 5	122+48.81	8.00		\cap	PROPOS		אר	
6	122+40.01	4.00	RT		FROFUS		7	
7	123+63 22	1.88	RT					
8	123+89.04	5.88						
9	124+03 44	8.00		- -	-			-
•	121-00111	0.000			-			-
				NO DATE	F	REVISION		APPROVED
					GRAF			
 + -	- +	-	 	25 12.5	GRAF (1	PHIC SCALE N FEET) 25	50	75
 + − ⊥ _	- + 	 - _	 		GRAF (1	PHIC SCALE N FEET) 25	50	75
 + − ⊥ _ 		- _ 	 	25 12.5 	GRAF (1	PHIC SCALE N FEET) 25 	50	75
		 	 	25 12.5 	GRAF (II 0 1 Ver	HIC SCALE N FEET) 25 =	50	75
				25 12.5 	GRAF (II 0 1 Ver	HIC SCALE N FEET) 25 == 50' t: 1" = 10'	50	75
				25 12.5 	GRAF (II 0 1 Ver	HIC SCALE N FEET) 25 	50	75
				25 12.5 	GRAF (II 0 F TEL S	PHIC SCALE N FEET) 25 = = = 50' t: 1" = 10' THE SEAL A		75
				25 12.5 	GRAF (II 0 FF 75 F75 F75 F75 F75 F75 F75 F75 F75 F75 F	THE SEAL A THE SEAL A JULIO RA	50 APPEARIN WAS AUT	75 IG ON THIS HORIZED BY 107672
				25 12.5 	GRAF (II 0 1 Ver FF 75+4% RAMOS 672	HIC SCALE N FEET) 25 = = 50' t: 1" = 10' THE SEAL A DOCUMENT ' JULIO RA	50 APPEARIN WAS AUT AMOS, P.E	75 IG ON THIS HORIZED BY 107672
				25 12.5 	GRAF (II 0 1 Ver FF 754 490 RAMOS 672	HIC SCALE N FEET) 25 = = 50' t: 1" = 10' THE SEAL A DOCUMENT JULIO RA	50 APPEARIN WAS AUT MOS, P.E 6/25/2020	IG ON THIS HORIZED BY :. 107672
				25 12.5 25 12.5 26 12.5 27	GRAF (II 0 1 Ver FF 75+4% RAMOS 672	HIC SCALE N FEET) 25 = 50' t: 1" = 10' THE SEAL A DOCUMENT JULIO RA	50 APPEARIN WAS AUT AMOS, P.E	75 IG ON THIS HORIZED BY 107672
				25 12.5 25 12.5 26 12.5 27	GRAF (1) 0 1 Ver FF 75+4%	HIC SCALE N FEET) 25 = = = = = = = = = = = = = = = = = =	50 APPEARIN WAS AUT MOS, P.E 6/25/2020	75 IG ON THIS HORIZED BY 107672
				25 12.5 25 12.5 26 12.5 27 12.5 27 12.5 20 10.5 20 12.5 20	GRAF (1) 0 1 Ver FF 754 400 RAMOS 672	HIC SCALE N FEET) 25 = = = = = = = = = = = = = = = = = =	50 APPEARIN WAS AUT MOS, P.E 6/25/2020	75 IG ON THIS HORIZED BY 107672
				25 12.5 25 12.5 26 12.5 27 12.5 27 12.5 20 10.5 20	GRAF (III 0 1 Ver FF 75+4% RAMOS 672	HIC SCALE N FEET) 25 = = = = = = = = = = = = = = = = = =	50 APPEARIN WAS AUT AMOS, P.E 6/25/2020	75 IG ON THIS HORIZED BY 107672
				25 12.5 25 12.5 26 12.5 27	GRAF (III 0 1 Ver FF 75+4%	HIC SCALE N FEET) 25 = = = = = = = = = = = = = = = = = =	50 APPEARIN WAS AUT MOS, P.E	75 IG ON THIS HORIZED BY 107672
				25 12.5 25 12.5 25 12.5 26 12.5 27	GRAF (III 0 1 Ver RAMOS 672 80 41	HIC SCALE N FEET) 25 =	50 APPEARIN WAS AUT MOS, P.E 6/25/2020	75 IG ON THIS HORIZED BY 107672
						HIC SCALE N FEET) 25 =	50 APPEARIN WAS AUT MOS, P.E 6/25/2020	75 IG ON THIS HORIZED BY . 107672
				25 12.5 25 12.5 26 12.5 27	GRAF (III 0 1 Ver FF 75-1-0 RAMOS 672 872 872 872 872 872 872 872 872 872 8	HIC SCALE N FEET) 25 = 50' t: 1" = 10' THE SEAL A DOCUMENT A JULIO RA SAN ANTO TEL: (210) 641 TBPLS REG TBPLS REG	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 110 WEST, 100 TEX, 100 TEX, 101 JEX, 101 JEX,	75 IG ON THIS HORIZED BY 107672 \$78230-1037 (210) 641-6440 NO.F-2214 NO.: 100410-00
				25 12.5 25 12.5 26 12.5 27	GRAF (III 0 1 Ver F. TELSO RAMOS 672 672 672 672 672 672 672 672 672	HIC SCALE N FEET) 25 =	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 110 WEST, 410 WES	75 IG ON THIS HORIZED BY 107672 \$78230-1037 12(210) 641-5440 NO.: F-2214 NO.: F-2214 NO.: Tou410-00
				25 12.5 25 12.5 25 12.5 26 12.5 27	GRAF (III 0 1 Ver RAMOS 672 672 672 672 672 672 672 672 672 672	HIC SCALE N FEET) 25 = 50' t: 1" = 10' THE SEAL A DOCUMENT ' JULIO RA SAN ANTO TEL: (210) 641 TBPE REG TBPLS REG	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0/2000 0/200000000	75 IG ON THIS HORIZED BY 107672 \$78230-1037 12(210) 641-6440 NO.: F-2214 NO.: 100410-00
				25 12.5 25 12.5 25 12.5 26 12.5 27	GRAF (III 0 1 Ver RAMOS 672 672 672 672 672 672 672 672 672 672	HIC SCALE NFEET) 25 = 50' t: 1" = 10' THE SEAL # DOCUMENT ' JULIO R# SANANTO TEL: (210) 641 TBPE REG TBPLS REGI EXAR CO VORKS 1	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 110 WEST, 9999 [FAX ISTRATION STRATION D U N T ` D E P A I	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 578230-1037 578200-1037 578200-1037 578200-1037 578200-1037 578200-1037 578200-1037 578200-1037 578200-1037 578200-1037 578200-1037 5782000-1000-1000-1000-1000-1000-1000-1000
				25 12.5 25 12.5 25 12.5 26 12.5 27	GRAF (III 0 1 Ver RAMOS 672 672 672 672 672 672 672 8 672 8 672 8 672 8 672 8 672 8 672 8 672 8 672 8 672 8 672 8 7 8 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	110C SCALE N FEET) 25 1 25 1 25 1 25 1 26 1 25 1 25 1 25 1 26 1 27 11550 II SAN ANTO 1500 II SAN ANTO 1500 II 1500 II 1000000000000000000000000000000000000	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 110 WEST, 9999 [FAX 15TRATION DUNT DUNT DUNT	75 IG ON THIS HORIZED BY . 107672 SUITE 395 7 78230-1037 C 2101 644 NO.: F-2214 NO.: F-2214 NO.: 100410-00 Y R T M E N T
				25 12.5 25 12.5 25 12.5 26 12.5 27	GRAF (III 0 1 Ver F TE Vo RAMOS 672 8 672 8 8 8 8 8 8 8 8 8 9 8 9 8 9 8 9 8 9 8	11550 II SAN ANTO 11550 II SAN ANTO 11570 II SAN ANTO 11570 II SAN ANTO 11570 REG 11570 II SAN ANTO 11570 REG 11570 II SAN ANTO 11570 REG 11570 II SAN ANTO 11570 REG 11570 II SAN ANTO 11570 II 11570 II 11	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 10 WEST, NIO, 92 10 WEST, NIO, 92 10 WEST, 10 WEST, NIO, 92 10 WEST, 10 WEST, NIO, 92 10 WEST, 10 W	75 IG ON THIS HORIZED BY . 107672 SUITE 395 578230-1037 (210) 641-6440 NO.: F-2214 NO.: 100410-00 Y R T M E N T
				25 12.5 25 12.5 25 12.5 26 12.5 27	GRAF (III 0 1 Ver F TE Vo RAMOS 672 8 672 8 8 8 8 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9	11550 II SAN ANTO 11550 II 11550 II 11550 II 11550 II 11570 II 11 11 11 11 11 11 11 11 11	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 10 WEST, NIO, 10 WEST, NIO, 10 WEST, 10 WEST,	75 IG ON THIS HORIZED BY . 107672 SUITE 395 5 78230-1037 (210) 641-6440 NO.: F-2214 NO.: F
				25 12.5 25 12.5 20	GRAF (III 0 1 Ver F TE Vo F TE	111550 II SAN ANTO 111550 II 111550 II 111550 111550 II 111550 II 1115	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0/25/20 0/25/2020 0/25/200 0/25/200 0/25/200 0/25/	75 IG ON THIS HORIZED BY . 107672 SUITE 395 5 78230-1037 (2210) 6414 NO.: F-2214 NO.: F-22
				25 12.5 25 12.5 20 10.5 20	GRAF (III 0 1 Ver F TEL F TEL	11650 II SAN ANTO THE SEAL A DOCUMENT JULIO RA JULIO RA TIPE REG TBPLS REG TAR C CO VOR K S 10 ON ROA ADWAY ND PRO	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0.15TRATION STRATION D E P A I D E P A I D E P A I D E P A I	75 IG ON THIS HORIZED BY : 107672 SUITE 395 578230-1037 : (210) 641-5440 NO.: F-2214 NO.: 100410-00 Y R T M E N T
				25 12.5 25 12.5 20 10 20 10	GRAF (III 0 1 Ver F TE+ F TE+	11550 II: SAN ANTO SAN ANTO THE SEAL A DOCUMENT SAN ANTO TEL: (210) 641 TBPE REG TBPLS REG TDPLS REG	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0 U N T D E P A I D E P A I D E P A I AD FILE 126+00	75 IG ON THIS HORIZED BY : 107672 SUITE 395 5 78230-1037 : (210) 641-5440 NO.: F-2214 NO.: 100410-00 Y R T M E N T
				25 12.5 25 12.5 20 10 20	GRAF (III 0 1 Ver F TE + 10 F TE + 1	11550 II: SAN ANTO THE SEAL A DOCUMENT - 100	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0.0000 10000 10000 0.00000 0.0000 0.0000 0.00000 0.00000 0.00000 0.00000 0.0000 0.00000 0.000	75 IG ON THIS HORIZED BY : 107672 SUITE 395 3 78230-1037 : (210) 641-6440 NO.: F-2214 NO.: 100410-00 Y R T M E N T
				25 12.5 25 12.5 20 10 20 10 20 20 10 20 10	GRAF (III 0 1 Ver F TE + 75 RAMOS 672 F TE + 75 RAMOS F TE + 75 RA	11550 II: 25 11550 II: 26 11550 II: 27 28 29 29 29 20 20 20 20 20 20 20 20 20 20	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0.0000 10000 517ATION D E P A I D E P A I AD FILE 126+00	75 HORIZED BY : 107672 SUITE 395 3 78230-1037 : (210) 641-6440 NO.: F-2214 NO.: 100410-00 Y & T M E N T
				25 12.5 25 12.5 3 10 107 107 107 107 107 107 107 1	GRAF (III 0 1 Ver FF 72 FF 72	11550 II: 11550 II:	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0 0 0 T D E P A I AD FILE 126+00	75 HORIZED BY : 107672 SUITE 395 578230-1037 : (210) 641-6440 NO: F-2214 NO: 100410-00 Y R T M E N T
				25 12.5 25 12.5 3 10 107 107 107 107 107 107 107 1	GRAF (III 0 1 Ver F 72 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 873 RAMOS 873 RAM	THE SCALE NFEET) 25 THE SEAL A DOCUMENT 1550 IF SANANTO TEL: (210) 641 TBPL REG TBPLS REG TBPLS REG CALE SANATO TEL: (210) 641 TBPLS REG TBPLS REG TBPLS REG TBPLS REG TBPLS REG TO STA ADWAY ND PRO D TO STA ET 4 OF 9 Texas of Texas	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 100 VEXA 9999 [FAX 100 VEST, 100 VEST, DE P A I AD FILE 126+00 Depar	75 IG ON THIS HORIZED BY : 107672 SUITE 395 578230-1037 : (210) 641-6440 NO.: F-224 NO.: 100410-00 Y R T M E N T D.00
				25 12.5 3 10 107 107 107 107 107 107 107 1	GRAF (III 0 1 Ver RAMOS 672 RAMOS 873 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 672 RAMOS 873 RAMOS 874 RAMOS 875 RAMOS 87	11550 II THE SCALE N FEET) 25 15 15 15 15 15 15 15 15 15 1	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 FILE 10 WEST, NIO, TEXA 9999 [FAX 9999 [FAX 10 WEST, NIO, TEXA 0 DE P A I AD FILE 126+00 Depar	75 IG ON THIS HORIZED BY 107672 SUITE 395 5.78230-1037 (210) 641-6440 NO.: F0244 NO.: 100410-00 Y R T M E N T (210) 641-640 NO.: F024 NO.: F
				25 12.5 3 10 107 107 107 107 107 107 107 1	GRAF (III 0 1 Ver F. T.E. T.E. RAMOS 672 BE PUBLIC V WATS PUBLIC V WATS RO PLAN A A 121+50.00 SHE FEDERA	11550 II 25 17 = 50' 17 = 10' THE SEAL A DOCUMENT - 10' THE SEAL A DOCUMENT - 10' 1902 RCG 1902 RCG 1902 RCG 1902 RCG 1902 RCG 2X A R C C VOR K S I ON ROA ADWAY ND PRO 0 TO STA ET 4 OF 9 7 Texas of Tra L AID PROJEC	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 FILE 0 E P A I AD FILE 126+00 Depar Inspor T NO.	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 578230-1037 .: (210) 641-6440 NO.: F-2214 NO.: 100410-00 Y R T M E N T .: 100 0.00 .: 100
				25 12.5 3 10 107 107 107 107 107 107 107 1	GRAF (III 0 1 Ver F TE TO RAMOS 672 BE PUBLIC V WATS PUBLIC V WATS RO PLAN A A 121+50.00 SHE FEDERA	11550 II 25 17 FILE SEAL A DOCUMENT 1 18 FILE SEAL A DOCUMENT 1 19 FILE SEAL A DOCUMENT 1 19 FILE SEAL 19	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 FILE 0 E P A I AD FILE 126+00 Depar nspor T NO. COUNTY	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 578230-1037 .: (210) 641-6440 NO.: F-224 NO.: 100410-00 Y R T M E N T
				25 12.5 3 10 107 107 107 107 107 107 107 1	GRAF (III 0 1 Ver F. T.E. F. T	11550 II 25 1 = 50' t: 1" = 10' THE SEAL A DOCUMENT - JULIO RA 1902 REG 1902 R	50 APPEARIN WAS AUT MOS, P.E 6/25/2020 6/25/2020 6/25/2020 FILE 0 E P A I AD FILE 126+00 Depai nspor T NO. COUNTY BEXAF	75 IG ON THIS HORIZED BY 107672 SUITE 395 5.78230-1037 (210) 641-6440 NO.: F0244 NO.: 100410-00 Y R T M E N T 100410-00 Y R T M E N T 1000 1000
			EXISI II	25 12.5 25 12.5 3 10 107 3 107 3 107 107 107 107 107 107 107 107	GRAF (III 0 1 Ver F. TEL RAMOS 672 BE PUBLIC V WATS PUBLIC V WATS PLAN A A 121+50.00 SHE FEDERA DIST. SAT SECT.	11550 II 25 17 = 50' 17 = 10' THE SEAL A DOCUMENT - 10' THE SEAL A DOCUMENT - 10' 19 E REG 19 E REG 19 E REG 25 A R C C VOR K S I 19 E REG 27 A R C C VOR K S I ON ROA ADWAY ND PRO 0 TO STA ADWAY ND PRO 0 TO STA ET 4 OF 9 7 Texas of Tra L AID PROJEC 	50 муревані муревані муревані муревані муревані муревані б/25/2020 б/25/20 б/25/2020 б/25/20 б/25/20 б/25/20	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 778230-1037 .: 2(210) 643-6440 NO.: F-2214 NO.: 100410-000 Y R T M E N T D.000 rtment tation PLAN SHT D.000 R AV / STREET



ITEM#	DESCRIPTION	UNIT	QTY
0100	PREPARING ROW	STA	4
0216	PROOF ROLLING	HR	6
0275	CEMENT	TON	32
0275	CEMENT TREAT (EXIST MATL) (6")	SY	2444
0340	D-GR HMA(SQ) TY-B PG64-22	TON	807
0340	D-GR HMA(SQ) TY-C PG64-22	TON	469
0340	D-GR HMA(SQ) TY-D PG70-22	TON	156
0529	CONC CURB (TY II)	LF	800
0531	CONC SIDEWALKS (4")	SY	445
0536	CONC MEDIAN	SY	711
6056	PREFORMED IN-LANE(TRANS) RUMBLE STRIP	LF	40



	_											
				ITE	M#			DESCRIPT	ON		UNIT	QTY
				01	00	PRE	PARING	ROW			STA	4
				01	06	OBL	ITERAT	NG ABANDON	ED ROAD		SY	146
0216 PROOF ROLLI							OF ROL	LING			HR	5
0275 CEMENT										TON	33	
0275 CEMENT TREAT (EXIST MATL) (6")									SY	2538		
0340 D-GR HMA(SQ) TY-B PG64-22								22		TON	838	
					40	D-G			22		TON	490
				03	29	0-0		<u>יען די טייט אין אין אין אין אין אין א</u> די (דע ווי)	-22			107
				05	31	000		VALKS (4")			SY	445
				05	36	000					SY	705
				60	56	PRF	FORME	 DIN-LANE(TRA	NS) RUMBL F		LF	40
							_	PLA		EGEND		_
									- PROP E	DGE OF R	OADWA`	Y
									— EXISTIN	IG FEATUF	RES	
									— EXISTIN	ig right (OF WAY	
								<u> </u>	PROP R	RIGHT OF V	VAY	
								→	PROP T	RAFFIC AF	ROW	
										ETE PAVE	MENT	
								<u></u>	CONCR	ETE APRO	N	
									DRIVEW	/AY		
								(#)	STA & C	OFFSET		
								к=#	DDODO		2V	
		#	ST/	4	OFF	SET	LT/RT	ļШ	PROPOS	SED MAILB(JX	
		1	133+24	4.95	8.	00	LT					
	Ē	2	131+79	9.08	32	.00	RT		I-			
	Ē	3	132+7	9.08	36.	.00	RT		-			
	Ľ	4	133+8	8.18	36.	.00	RT		-	REVISION		
								DATE	GRAF	PHIC SCALE		INTROVED
-	+ -		+ -		- 1							
					1		- $-$	-	(1)	NFEEI)		
-	L _		⊥ _				 	25 12.5	0	25	50	75
-	⊥ _ 							25 12.5	0 	25 " = 50'	50	75
-	$\frac{1}{\frac{1}{1}}$ -				. .			25 12.5 	0 1 Ver	N FEET) 25 " = 50' t: 1" = 10'	50	75
-									0 1 Ver	25 = 50' t: 1" = 10'	50	75
-									0 1 Ver	" = 50' t: 1" = 10'	50	
-								= 25 12.5 = 25 12.5 = 25 12.5 = 25 12.5 = 25 12.5 = 25 12.5	0 1 Ver	THE SEAL /	50 APPEARIN WAS AUTI	IG ON THIS HORIZED BY
-		 		 					0 1 Ver	N FEET) 25 = 50' t: 1" = 10' THE SEAL / DOCUMENT JULIO R/	50 APPEARIN WAS AUTI	75 IG ON THIS HORIZED BY :. 107672
-				 		 		- 25 12.5 	0 1 Ver F 75-400 RAMOS 672 86	N FEET) 25 	50 APPEARIN WAS AUTI AMOS, P.E	75 IG ON THIS HORIZED BY 107672
-			$\begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} $					- 25 12.5 	0 1 Ver RAMOS 672	N FEET) 25 	50 APPEARIN WAS AUTI AMOS, P.E	75 IG ON THIS HORIZED BY .: 107672
-			·					- 25 12.5 	0 1 Ver	N FEET) 25 = 50' t: 1" = 10' THE SEAL / DOCUMENT JULIO R/	50 APPEARIN WAS AUTI AMOS, P.E	75 IG ON THIS HORIZED BY 107672
-								- 25 12.5 		N FEEI) 25 * = 50' t: 1" = 10' THE SEAL / JULIO R/	50 APPEARIN WAS AUTI MOS, P.E	75 IG ON THIS HORIZED BY . 107672
-								- 25 12.5 	1 Ver	N FEEI) 25 	50 APPEARIN WAS AUTI AMOS, P.E 6/25/2020	75 IG ON THIS HORIZED BY . 107672
-								25 12.5 	0 1 Ver	N FEE I) 25 	50 APPEARIN WAS AUTI AMOS, P.E 6/25/2020	IG ON THIS HORIZED BY : 107672
-		 	·						0 1 Ver F TE Vo RAMOS 672 RAMOS	N FEEI) 25 	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020	75 IG ON THIS HORIZED BY . 107672 SUITE 395 578/30-1037
-		 	·							11550 II SAN ANTC 11550 II SAN ANTC	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020	75 IG ON THIS HORIZED BY : 107672 SUITE 395 5 78230-1037 : (210) 641-6440 NO : E-2214
-			·					25 12.5 - 25 12.5 - 30 100 - 30 100 - 100 100 - 100 -		NTEEL) 25 	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 51/200 51/200	75 IG ON THIS HORIZED BY . 107672 SUITE 395 578230-1037 . (210) 641-6440 NO.: F-2214 NO.: 100410-00
-			· - - - + + - - + + - - + + - - + + - - +							NTEEL) 25 = = = = = = = = = = = = = = = = = = =	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 53937ATION STRATION STRATION	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 5 78230-1037 : (210) 641-6440 NO.: F-2214 NO.: 100410-00 Y
-		 	+ - + + - + + + + + + + + + +					- 25 12.5 - JULIO - JULIO - JULIO - JULIO - JULIO - CIVIL ENGINEER - CIVIL ENGINEER - CIVIL ENGINEER		NTEEL) 25 ==================================	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 5/25/2020 6/25/2020 0/25/200 0/25/200 0/25/200 0/25/200 0/25/2000 0/25/2000 0/25/2000 0/2	T5 IG ON THIS HORIZED BY . 107672 SUITE 395 5 78230-1037 . (210) 641-6440 . (210) 641-640 . (
			·					- 25 12.5 - JULIO - JULIO - JULIO - JULIO - JULIO - CIVIL ENGINEER - CIVIL ENGINEER - CIVIL ENGINEER		11550 II SANAMIC THE SEAL J DOCUMENT JULIO R/ 11550 II SANAMIC TEL: (210) TEL: (210) TEL	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0 U N T N D U N T N D U N T N	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 5 78230-1037 : (210) 641-6440 NO.: F-2214 NO.: 100410-00 Y X T M E N T
			· + + + + +					25 12.5 		11550 II SAN ANTC THE SEAL J DOCUMENT JULIO RJ TEL: (210)E TBPE REC TBPLS REGI EXAR CO VOR KS	50 APPEARIN WAS AUTI AMOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0/25/20 0/25/2020 0/25/2020 0/25/200 0/25/200 0/25/200 0/2	75 IG ON THIS HORIZED BY 107672 SUITE 395 78230-1037 .: (210) 641-6440 NO.: F-2214 NO.: 100410-00 Y X T M E N T
			$\begin{array}{cccccccccccccccccccccccccccccccccccc$					25 12.5 - 25 12.5 - 30 - 107 - 30 - 107 - 107	ING CONSULTANTS PUBLIC V WATS RO	11550 II SANANIC THE SEAL / DOCUMENT JULIO R/ SANANIC TEL: (20) 64' TBPL REG EXAR CC VORKS ON RO ADWAY	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0 UN T D UN T D UN T D UN T D UN T D UN T	75 IG ON THIS HORIZED BY : 107672 SUITE 395 5 78230-1037 : (210) 641-6440 NO: F-2214 NO: 100410-00 Y & T M E N T
			- - <td></td> <td></td> <td></td> <td></td> <td>- 25 12.5 - JULIO - JULIO - JULIO - JULIO - CIVIL ENGINEER - CIVIL ENGINEER </td> <td></td> <td>11550 II SAN ANTC THE SEAL / DOCUMENT JULIO R/ SAN ANTC TEL: (20) 64 TBPE REC TBPLS REG EX A R C C VOR K S ON RO ADWAY ND PRO</td> <td>50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0.00000000000000000000000000000000</td> <td>75 IG ON THIS HORIZED BY .: 107672 SUITE 395 5 78230-1037 : (210) 641-6440 NO.: F-2214 NO.: 100410-00 X T M E N T</td>					- 25 12.5 - JULIO - JULIO - JULIO - JULIO - CIVIL ENGINEER - CIVIL ENGINEER 		11550 II SAN ANTC THE SEAL / DOCUMENT JULIO R/ SAN ANTC TEL: (20) 64 TBPE REC TBPLS REG EX A R C C VOR K S ON RO ADWAY ND PRO	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0.00000000000000000000000000000000	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 5 78230-1037 : (210) 641-6440 NO.: F-2214 NO.: 100410-00 X T M E N T
			+ + + + + + + +							NTEE1) 25 "= 50' t: 1"= 10' DOCUMENT JULIO R/ SAN ANTC THE SEAL / DOCUMENT JULIO R/ SAN ANTC TEL: (20) 64 TBPLS REGI SX A R C (20) ON RO ADWAY ND PRO D TO STA	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0/25/20 0/25/200 0/25/200 0/25/200 0/25	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 5 78230-1031 .(210).6214 NO.: F-2214 NO.: F
			- - <td></td> <td></td> <td></td> <td></td> <td></td> <td>ING CONSULTANTS RAMOS 672 BE PUBLIC V WATS RO PLAN A A 130+00.00 SHF</td> <td>11550 II SAN ANTC 11550 II SAN ANTC 11550 II SAN ANTC 11550 II SAN ANTC 11550 II SAN ANTC 1505 REGI CON RO CON RO ADWAY ND PRO D TO STA EET 6 OF 9</td> <td>50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0/25/20 0/25/200 0/25/200 0/25/200 0/25</td> <td>75 IG ON THIS HORIZED BY .: 107672 SUITE 395 578230-1037 : (210) 641-6440 NO.: F-2214 NO.: 100410-00 Y R T M E N T</td>						ING CONSULTANTS RAMOS 672 BE PUBLIC V WATS RO PLAN A A 130+00.00 SHF	11550 II SAN ANTC 11550 II SAN ANTC 11550 II SAN ANTC 11550 II SAN ANTC 11550 II SAN ANTC 1505 REGI CON RO CON RO ADWAY ND PRO D TO STA EET 6 OF 9	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 0/25/20 0/25/200 0/25/200 0/25/200 0/25	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 578230-1037 : (210) 641-6440 NO.: F-2214 NO.: 100410-00 Y R T M E N T
			- - <td></td> <td></td> <td></td> <td></td> <td></td> <td>0 1 Ver F T RAMOS 672 S 675 S 675 S 675 S 675 S 675 S 675 S 675 S 675 S 675 S 675 S 675 6</td> <td>11550 II 25 11550 II 26000000000000000000000000000000000000</td> <td>50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 FILE DUNTS DUNTS AD FILE 134+00</td> <td>75 IG ON THIS HORIZED BY .: 107672 SUITE 395 578230-1037 : (210) 641-6440 NO.: F-2244 NO.: 100410-00 Y R T M E N T </td>						0 1 Ver F T RAMOS 672 S 675 S 675 S 675 S 675 S 675 S 675 S 675 S 675 S 675 S 675 S 675 6	11550 II 25 11550 II 26000000000000000000000000000000000000	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 FILE DUNTS DUNTS AD FILE 134+00	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 578230-1037 : (210) 641-6440 NO.: F-2244 NO.: 100410-00 Y R T M E N T
			- - <td></td> <td></td> <td></td> <td></td> <td>25 12.5 - 25 12.5 - 3 12.5 - 3 12.5 - 4 12.5 - 5 12</td> <td>ING CONSULTANTS RAMOS 672 F T T T T RAMOS 672 F T T T RAMOS PLAN A A 130+00.00 SHE</td> <td>NTEE1) 25 </td> <td>50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/200 6/25/200 6/25/200 6/25/200 6/2</td> <td>75 IG ON THIS HORIZED BY .: 107672 SUITE 395 5 78230-1037 (20).16374 NO: 100410-00 Y R T M E N T </td>					25 12.5 - 25 12.5 - 3 12.5 - 3 12.5 - 4 12.5 - 5 12	ING CONSULTANTS RAMOS 672 F T T T T RAMOS 672 F T T T RAMOS PLAN A A 130+00.00 SHE	NTEE1) 25	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/200 6/25/200 6/25/200 6/25/200 6/2	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 5 78230-1037 (20).16374 NO: 100410-00 Y R T M E N T
								25 12.5 - 25 12.5 - 3 12.5 - 3 12.5 - 3 12.5 - 4 12.5 - 5 12	ING CONSULTANTS RAMOS 672 NS CONSULTANTS CON DURDEN INC. BE PUBLIC V WATS RO PLAN A A 130+00.00 SHE FEDERA	NTEE1) 25	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 FILE 10 WEST, NIO, TEXAS 93978 (TON STRATION D E P A F AD FILE 134+00 D e pal mspor T NO.	75 IG ON THIS HORIZED BY 107672 SUITE 395 578230-1037 107672
								25 12.5 - 25 12.5 - 3 12.5 - 3 12.5 - 3 12.5 - 4 12.5 - 4 12.5 - 4 12.5 - 5 12	ING CONSULTANTS RAMOS 672 NS CONSULTANTS F T T SON DUMBER NAC BE PUBLIC V WATS RO PLAN A A 130+00.00 SHE FEDERA	1150 II SAN ANTC 11550 II SAN ANTC JULIO R/ 11550 II SAN ANTC TEL: (210) 64' TBPLS REGI GON RO, ADWAY ND PRO D TO STA ET 6 OF 9 Texas of Traxas of Traxas IL AID PROJEC	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/200 6/25/200 6/25/200 6/25/200 6/25/2000 6/25/2000 6/25/2000 6/2	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 578230-1037 .: 107672 (210) 641 6440 NO.: F-2214 NO.: 100416-00 Y X T M E N T D.00
			+ +					25 12.5 - 25 12.5 - 3 12.5 - 3 12.5 - 3 12.5 - 4 12.5 - 4 12.5 - 4 12.5 - 5 12.5 - 5 12.5 - 6 12.5 - 7 12	ING CONSULTANTS RAMOS 672 ING CONSULTANTS BE PUBLIC V WATS RO PLAN A A 130+00.00 SHE FEDERA	NTEE1) 25 "= 50' t: 1" = 10' DOCUMENT JULIO R/ SAN ANT TEL: (20) 6 REG TBPLS REG CN R CO ADWAY ND PRO D TO STA ET 6 OF 9 Texas of Trz L AID PROJEC	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 FILE 10 WEST, NNIO, TEXAS 1939RATIONI D U N T N D E P A F AD FILE 134+00 D e pai anspor T NO.	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 5 78230-1037 .: 107672 SUITE 395 7 78230-1037 .: 107672 SUITE 395 .: 107672 .: 107672
						FxidT		25 12.5 - 25 12.5 - 3 12.5 - 3 12.5 - 4 12.5 - 4 12.5 - 4 12.5 - 5 12	ING CONSULTANTS RAMOS 672 ING CONSULTANTS FT TO FT TO RAMOS 672 BE PUBLIC V WATS RO PLAN A A 130+00.00 SHE FEDERA DIST. SAT	NTEE1) 25 "= 50' t: 1" = 10' DOCUMENT JULIO R/ SAN ANT TEL: (20) 6K TBPLS REG CN R CO ADWAY ND PRO D TO STA ET 6 OF 9 Texas of Tra L AID PROJEC	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 FILE 0 U N T N D E P A F AD FILE 134+00 Depai nspor T NO.	75 IG ON THIS HORIZED BY .: 107672 SUITE 395 5 78230-1037 : 2101 641 6440 NO.: F-2214 NO.: F-2214 NO.: 100416-00 Y X T M E N T D.00 PLAN SHT D.00
						Line (1997)		25 12.5 - 25 12.5 - 3 12.5 - 3 12.5 - 3 12.5 - 4 12.5 - 4 12.5 - 4 12.5 - 5 12.5 - 5 12.5 - 5 12.5 - 6 12.5 - 7 12	ING CONSULTANTS RAMOS 672 FF TT RAMOS 672 FF TT RAMOS 672 FF PUBLIC V WATS RO PLAN A A 130+00.00 SHE FEDERA DIST. SAT SAT SCT. 12	11550 II 50' 11150 II SAN ANTC JULIO R/ 11550 II SAN ANTC THE SEAL J DOCUMENT JULIO R/ SAN ANTC TEL: (210) MR TEL: (210) MR SAN ANTC TEL: (210) MR GON RO ADWAY ND PRO D TO STA TEXAS of Tractas of Tractas JOB	50 APPEARIN WAS AUTI MOS, P.E 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 6/25/2020 FILE 0 U N T NO. COUNTY BEXAF HIGHW	75 IG ON THIS HORIZED BY 107672 SUITE 395 5 78230-1037 107672 SUITE 395 5 78230-1037 107672 S 78230-1037 107672



PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 12:52:38 PM

13,654,126.2590	Е	2,097,113.5177

13,653,995.6178 E 2,097,143.3777

PROP EDGE OF ROADWAY EXISTING FEATURES - - EXISTING RIGHT OF WAY PROP RIGHT OF WAY PROP TRAFFIC ARROW CONCRETE PAVEMENT • CONCRETE APRON 1 DRIVEWAY (#) STA & OFFSET RADIUS R = # PROPOSED MAILBOX NO DATE **REVISION** GRAPHIC SCALE (IN FEET) 25 12.5 0 25 1" = 50' OF TO \mathbf{x} THE SEAL APPEARING ON THIS DOCUMENT WAS AUTHORIZED B JULIO RAMOS, P.E. 107672 JULIO RAMOS 107672 CENSE 6/25/2020 SIONAL ENGL 11550 IH 10 WEST, SUITE 395 SAN ANTONIO, TEXAS 78230-1037 TEL: (210) 641-9999 | FAX: (210) 641-6440 TBPE REGISTRATION NO.: F-2214 CEC TBPLS REGISTRATION NO.: 100410-0 BEXAR COUNTY

SCRIPTION	UNIT	QTY	PUBLIC WORKS DEPARTMENT					
	STA	5						
ANDONED ROAD	SY	759		WAIS	WATSON ROAD			
	TON	42						
(IST MATL) (6")	SY	5291						
3 PG64-22	TON	1746	1					
CPG64-22	TON	1208	S1	ГА 134+00.0	0 TO STA	139+00.0	00	
) PG70-22	TON	491						
EINF) (11")	SY	1025		SHEE	<u>-170F9</u>			
ED CONC (4")	SY	274	1		U Tovas	Donartr	nont	
	LF	1415	© 2019		of Trai	nsporta	tion	
)) (TY I)	LF	270	FED.RD.	FEDERA	L AID PROJECT	Г NO.	PLAN SHT	
(4")	SY	505	6				103	
	EA	18	STATE	DIST.		COUNTY		
1)	EA	2	TEXAS	SAT		BEXAR		
	SY	3365	CONT.	SECT.	JOB	HIGHWAY	/ STREET	
NE(TRANS) RUMBLE STRIP	LF	160	0915	12	562	WATS	ON RD	

PLAN VIEW LEGEND



SEE PREVIOUS SHEET FOR PLAN VIEW

		-			-
		-			-
		-			
	NO DATE	GRAF			AFFROVED
_ +		(I)	N FEET)		
	25 12.5	0 ·	25	50	75
- L -					
		1	" = 50'		
		Ver	t: 1" = 10'		
	ATE O	FTEXAS			
	5*/ D		DOCUMENT W	AS AUTHC	RIZED BY
	JULIO I	RAMOS	JULIO RAI	MOS, P.E. 1	07672
	A 107	672 🔊			
	CE CE	NSED	6	/25/2020	
- +	S/ON/	IL EN			
628					
624					
- +			11550 H	10 WEST, SU	TE 395
	- CH		SAN ANTON	IO, TEXAS 78	3230-1037
620	CIVIL ENGINEER	NG CONSULTANTS	TBPE REG	STRATION NO) F-2214
		DON DURDEN, INC.	TBPLS REGIS	TRATION NO.	:100410-00
_ +		BE	XAR CO	UNTY	
616			VOPKS D	EDADT	MENT
- +		I UBLIC V	VORK5 D	LIARI	IVIEIN I
)	WATS		D	
- +		RO	ADWAY		
_ +		PLAN A	ND PROF	ILE	
	ST.	A 134+00.00) TO STA '	139+00.0	00
		0.115			
		SHE	<u>= 180F9</u>		
- +			Teras	Denarti	nent
	C 2019		of Trai	isporta	tion
	FED.RD.	EEDER4		.	PLAN SHT
+	DIV.NO. 6	, LULINA			NO.
	STATE	DIST.		COUNTY	1 104
7233 733	TEXAS	SAT		REXAR	
	CONT.	SECT.	ЈОВ	HIGHWAY	/STREET
108700	0015	12	562	W/ATS	



		ITE	M#	DESCRIPTION					ΟΤΥ
		01	00 PF	REPARING	ROW			STA	4
		01	06 01	BLITERATI	NGABANDON	ED ROAD		SY	79
FD_		02	16 PF	ROOF ROL	LING			HR	5
		02	75 CE	MENT					10
		02	75 CE	CEMENT TREAT (EXIST MATL) (6")				SY	936
		03	16 AS	SPH (MULT	IOPTION)			GAL	149
		03	16 AC	GR(TY-B	GR-4 SAC-B)			CY	8
		03	40 D-	GR HMA(S	Q) TY-B PG64-	22		TON	309
		034	40 D-	GR HMA(S		22		TON	197
						() TY-D PG70-22			94 403
) IN_I ANE(TRA	Y II) LF 403 N-LANE(TRANS) RUMBLE STRIP LE 40			405
PLAN VIEW LEGEND									
									v
								JADIIA	
EXISTING FEATURE								ES	
— — EXISTING RIGHT ()F WAY	
PROP RIGHT OF V								/AY	
PROP TRAFFIC AF								ROW	
COJECT CONCRETE PAVI								MENT	
C.S.T. 3+00.00						CONCR	ETE APROI	N	
					1	DRIVEW	/AY		
					(#)	STA & C	FFSET		
	# 6			I T/PT	R=#	RADIUS			
	# <u>5</u> 1 139+	94 70	12 46			PROPOS		ХC	
	2 140+	94.70	12.35						
	3 141+	00.00	12.35	LT					
	4 139+	16.22	28.11	RT		-			-
	5 140+	94.70	15.44	RT		-			
	6 141+	00.15	15.38	RT	NO DATE	- F	REVISION		APPROVED
						GRAF	HIC SCALE		
- + -						(1)	N FEET)	50	75
				_		0	25	50	/5
				_ I		1	" = 50'		
Ī				- <u> </u>		Ver	<u>t: 1" = 10'</u>		
- + -				-	TEO	FTEL			
_ ↓ _				_		- 70	THE SEAL A	PPEARIN	IG ON THIS
			I	_ I	5*		JOCUMENT \ JULIO RA	WAS AUTI AMOS, P.E	HORIZED BY 107672
					3 107	672			
-			— — ·	-	- 10 KICE	NSED	-	6/25/2020	
- + -				_ I		IL EN			
	∟62	8	I	_ I					
UJECT									
	⊢ — ┨				-				
- + -		4	I — — -				14550 "		
			I	_ I			SAN ANTO	1 TU WEST,	SUILE 395 S 78230-1037
	62	0			CIVIL ENGINEER	ING CONSULTANTS	TEL: (210) 641 TBPE REG	-9999 FAX	(210) 641-6440 NO: F-2214
	$\frac{1}{1} - \frac{1}{1} - \frac{1}$								
- + -									
									TMENT
· + -									
] _								
- + -									
					© 2019 T lexas Department of Transportation				
- -			·		FED.RD. DIV.NO.	FEDERA	L AID PROJEC	T NO.	PLAN SHT. NO.
			1	н. -	6		_ <u></u>		105
- +				Roi -		DIST.		COUNTY	
				шI Ф		JA I	100		<u>`</u>
					CONT.	SECI.	JOB	HIGHW	AY/STREET
					0915	<u>12</u>	<u>56</u> 2		SON RD






PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_B PLOTTED ON: 6/25/2020 @



WATSON_E PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TI PLOT DRIVER: WATSON PLOTTED ON: 6/25/2020

PLAN VIEW LEGEND



BEXAR COUNTY PUBLIC WORKS DEPARTMENT

WATSON ROAD

VERANO INTERSECTION MEDIAN DATA

	SHE	ET 1 OF 1							
© 2019 Texas Department of Transportation									
FED RD. DIV.NO.	RD. FEDERAL AID PROJECT NO.								
6				109					
STATE	DIST.		COUNTY						
TEXAS	SAT		BEXAR						
CONT.	SECT.	JOB	HIGHWAY	/ STREET					
0915	12	562	WATS	ON RD					

I/RT	ELEV
RT	622.28
RT	622.40
RT	622.51
RT	623.07
RT	622.92
RT	622.76
RT	621.98
RT	622.35
RT	622.45
RT	622.64
RT	622.90
RT	622.99
RT	622.74
RT	622.64
RT	622.06
RT	622.08
RT	622.77
RT	622.72
RT	622.60
RT	622.60
LT	622.84
LT	623.36
RT	623.36
RT	622.92
RT	622.71
RT	622.61
RT	622.22
RT	622.43
LT	622.02
RT	622.54



ERANO INTE	RSECTION	
136+57.67	52.92	RT
136+35.22	60.03	RT
136+10.05	60.14	RT
135+87.44	53.24	RT
135+71.23	40.74	RT
135+62.46	24.75	RT
135+60.30	7.26	RT
135+63.33	10.07	LT
135+70.19	26.00	LT
135+79.78	39.61	LT
135+91.25	50.21	LT
136+22.24	0.00	RT





- PROP EDGE OF ROADWAY
- EXISTING FEATURES
- - EXISTING RIGHT OF WAY
- - PROP RIGHT OF WAY
- CONCRETE PAVEMENT
 - CONCRETE APRON
- . ৺ ↓ ৺ BLOCK SOD

DRIVEWAY

1

(#)

 \checkmark

- PROP TRAFFIC ARROW
- STA & OFFSET

NOTES:

- 1. CONCRETE JOINT TYPICAL 15' SPACING UNLESS OTHERWISE NOTED.
- 2. ROUNDABOUT JOINTS ARE SET AT 14.4° AT EQUAL SPACING.





PLOTTED BY: evaldez PLOTTED SCALE: 1:11.2847 PEN TABLE: WATSON TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 12:53:23 PM PLOTTED ON: 6/25/2020 @ 12:53:23 PM



whats use. purpose v from its any Iting for esu T×DOT mages δď warranty of any kind is made nats or for incorrect results or Engineering Practice Act". No of this standard to other form "Texas the con h d for ndard is gover stan no this DISCLAIMER: The use of t T×DOT assum

6/22 DATE:

GENERAL NOTES

CURB RAMPS

1. Install a curb ramp or blended transition at each pedestrian street crossing.

- All slopes shown are maximum allowable. Cross slopes of 1.5% and lesser running should be used. Adjust curb ramp length or grade of approach sidewalks as directed.
- 3. Maximum allowable cross slope on sidewalk and curb ramp surfaces is 2%.
- 4. The minimum sidewalk width is 5'. Where the sidewalk is adjacent to the back of curb, a 6' sidewalk width is desirable. Where a 5' sidewalk cannot be provided due to site constraints, sidewalk width may be reduced to 4' for short distances. 5'x 5' passing areas at intervals not to exceed 200' are required.
- 5. Turning Spaces shall be 5'x 5' minimum. Cross slope shall be maximum 2%.
- 6. Clear space at the bottom of curb ramps shall be a minimum of 4'x 4' wholly contained within the crosswalk and wholly outside the parallel vehicular travel path.
- 7. Provide flared sides where the pedestrian circulation path crosses the curb ramp. Flared sides shall be sloped at 10% maximum, measured parallel to the curb. Returned curbs may be used only where pedestrians would not normally walk across the ramp, either because the adjacent surface is planted, substantially obstructed, or otherwise protected.
- 8. Additional information on curb ramp location, design, light reflective value and texture may be found in the latest draft of the Proposed Guidelines for Pedestrian Facilities in the Public Right of Way (PROWAG) as published by the U.S. Architectural and Transportation Barriers Compliance Board (Access Board).
- 9. To serve as a pedestrian refuge area, the median should be a minimum of 6' wide, measured from back of curbs. Medians should be designed to provide accessible passage over or through them.
- 10. Small channelization islands, which do not provide a minimum 5'x 5' landing at the top of curb ramps, shall be cut through level with the surface of the street.
- 11. Crosswalk dimensions, crosswalk markings and stop bar locations shall be as shown elsewhere in the plans. At intersections where crosswalk markings are not required, curb ramps shall align with theoretical crosswalks unless otherwise directed.
- 12. Provide curb ramps to connect the pedestrian access route at each pedestrian street crossing. Handrails are not required on curb ramps.
- 13. Curb ramps and landings shall be constructed and paid for in accordance with Item 531 "Sidewalks".
- 14. Place concrete at a minimum depth of 5" for ramps, flares and landings, unless otherwise directed.
- 15. Furnish and install No. 3 reinforcing steel bars at 18" o.c. both ways, unless otherwise directed.
- 16. Provide a smooth transition where the curb ramps connect to the street.
- 17. Curbs shown on sheet 1 within the limits of payment are considered part of the curb ramp for payment, whether it is concrete curb, gutter, or combined curb and gutter.
- 18. Existing features that comply with applicable standards may remain in place unless otherwise shown on the plans.

DETECTABLE WARNING MATERIAL

- 19. Curb ramps must contain a detectable warning surface that consists of raised truncated domes complying with PROWAG. The surface must contrast visually with adjoining surfaces, including side flares. Furnish and install an approved cast-in-place dark brown or dark red detectable warning surface material adjacent to uncolored concrete, unless specified elsewhere in the plans.
- 20. Detectable Warning Materials must meet TxDOT Departmental Materials Specification DMS 4350 and be listed on the Material Producer List. Install products in accordance with manufacturer's specifications.
- 21. Detectable warning surfaces must be firm, stable and slip resistant.
- 22. Detectable warning surfaces shall be a minimum of 24 inches in depth in the direction of pedestrian travel, and extend the full width of the curb ramp or landing where the pedestrian access route enters the street.
- 23. Detectable warning surfaces shall be located so that the edge nearest the curb line is at the back of curb and neither end of that edge is greater than 5 feet from the back of curb. Detectable warning surfaces may be curved along the corner radius.
- 24. Shaded areas on Sheet 1 of 4 indicate the approximate location for the detectable warning surface for each curb ramp type.

DETECTABLE WARNING PAVERS (IF USED)

- 25. Furnish detectable warning paver units meeting all requirements of ASTM C-936, C-33. Lay in a two by two unit basket weave pattern or as directed.
- 26. Lay full-size units first followed by closure units consisting of at least 25 percent (25%) of a full unit. Cut detectable warning paver units using a power saw.

SIDEWALKS

- Provide clear ground space at operable parts, including pedestrian push buttons. Operable parts shall be placed within unobstructed reach range specified in PROWAG section R406.
- 28. Place traffic signal or illumination poles, ground boxes, controller boxes, signs, drainage facilities and other items so as not to obstruct the pedestrian access route or clear ground space.
- 29. Street grades and cross slopes shall be as shown elsewhere in the plans.
- 30. Changes in level greater than 1/4 inch are not permitted.
- 31. The least possible grade should be used to maximize accessibility. The running slope of sidewalks and crosswalks within the public right of way may follow the grade of the parallel roadway. Where a continuous grade greater than five percent (5%) must be provided, handrails may be desirable to improve accessibility. Handrails may also be needed to protect pedestrians from potentially hazardous conditions. If provided, handrails shall comply with PROWAG R409.
- 32. Handrail extensions shall not protrude into the usable landing area or into intersecting pedestrian routes.
- 33. Driveways and turnouts shall be constructed and paid for in accordance with Item "Intersections, Driveways and Turnouts". Sidewalks shall be constructed and paid for in accordance with Item, "Sidewalks".
- 34. Sidewalk details are shown elsewhere in the plans.



SECTION VIEW DETAIL CURB RAMP AT DETECTIBLE WARNINGS

6/25/





whats use.

purpose v from its

any Iting

for esu

"Texas Engineering Practice Act". No ersion of this standard to other form

the conv

DISCL AIMER: The use of this standard is governed by TxDOT assumes no responsibility for the







NOTE: ITEMS NOT INTENDED FOR PUBLIC USE. MINIMUM 4'X 4'CLEAR GROUND SPACE REQUIRED AT PUBLIC USE FIXTURES.





whatsoe use. purpose v from its any Iting for esu the "Texos Engineering Practice Act". No warranty of any kind is made by TxDDT conversion of this standard to other formats or for incorrect results or damages DISCL AIMER: The use of this standard is governed by TXDOT assumes no responsibility for the





Act". No Practice no resp exas Engineering TxDOT assumes the hđt of this standard is governed by TxDOT for any purpose w R: use ade The t DISCL

SHE	ET 2	2 0	F 4				
Texas Department	t of Tra	nsp	ortation	,	Mai Divi Sta	intena ision ndaro	nce
MAILB CONNEC ME	ох стіло 8-1!	BR/ G [5 (аскет Эетан I)	LS			
FILE:MB14(1).DGN	DN:JEO		ск:	DW:J	EO	СК:	
© TxDOT APRIL 2015	CONT	SECT	JOB			HIGHWAY	
REVISIONS ADDED DHT 163730	0915	12	562		WA	TSON	RD
	DIST		COUNTY			SHEE	NO.
	SAT		BEXAR	ł		11	7





46625	WEDGE FOR V-WING SOCKET FOR TYPE 1 FOUNDATION		
40025	WEDGE FOR V-WING SUCKET FOR TIPE IFOUNDATION		
149540	WEDGE FOR TYPE 2 FOUNDATION		
14 7 4 7 4			
166103	ANCHOR FOR TYPE 2 FOUNDATION		
160801			
160892			
166104	WEDGE FOR TYPE 7 FOUNDATION		
100104			
4280			
4209			
164116			
166114			
16615.3	MULTIPLE MAILBOX POST (GALVANIZED OCTAGONAL)		
161442			
14 34 26	THIN-WALL GALVANIZED STEEL TUBE 2.375" OUTER DIAMETER		
162911	THINWALL WHITE STEEL TUBE 2.375" OUTER DIAMETER		
	SINGLE OR DOUBLE THIN-WALL MAILBOX POST GALVANIZED		
166152	2" OCTAGONAL		
	SINGLE OR DOUBLE THIN-WALL MAILBOX POST WHITECOATED		
166112	2" OCTAGONAL		
	REFLECTIVE SHEETING		
161812	REFLECTIVE SHEETING FOR EMERGENCY LOCATION NUMBER PANEL		
	CONNECTING HARDWARE		
2917	ANGLE BRACKET USED FOR TEMPORARY MAILBOX SUPPORT		
166105	BRACKET FOR SINGLE MOUNTING OF MAILBOXES (MOUNTING KIT)		
3789	PLATE FOR DOUBLE MOUNTING OF MAILBOXES		
166108	BRACKET FOR DOUBLE MOUNTING OF MAILBOXES (MOUNTING KIT)		
166111	BRACKET FOR MULTIPLE MOUNTING OF MAILBOXES (MOUNTING KIT)		
148939	BRACKET FOR ATTACHING SMALL OR MEDIUM SIZE MAIL BOX		
148938	EXTENDER TO BRACKET FOR ATTACHING LARGE MAILBOX		
159489	ANGLE BRACKET PART A		
159490	ANGLE BRACKET PART B		
	BRACKET FOR DOUBLE MOUNTING OF MAILBOXES ON THINWALL		
162323	STEEL POST, GALVANIZED OR POWDERCOATED. BRACKET FOR ATTACHING MAILBOX TO RECYCLED RUBBER POST		
161443	AND TO MULTIPLE WHITE MAILBOX POST		
158358	CASTING (NEWSPAPER RECEPTACLE BRACKET)		
163731	U-BOLT (NEWSPAPER RECEPTACLE BRACKET)		
160698	BOLT:HEX HEAD, GALV:3/8"DIA X 3/4"L HD, W/2-FLAT WASHERS		
163750	BOLT;HEX HEAD, GALV;3/8" X 1-1/2, 16 NC, W/WASHERS		
160701	BOLT;HEX HEAD, GALV;3/8"DIA X 2-1/2"L, HD, W/2-FLAT WASHERS		
163730	BOLT:HEX HEAD, GALV:3/8" X 3-1/2", NC, W/NUT, 2 FLAT WASHERS		
160699	BOLT:HEX HEAD, GALV:3/8"DIA X 3-3/4"L HD, W/2-FLAT WASHERS		
160700	BOLT:HEX HEAD, GALV;3/8"DIA X 4"L HD, W/2-FLAT WASHERS		
		SHEET 4 OF 4	
		••••••••••••••••••••••••••••••••••••••	Maintenance
		Texas Department of Transportation	Division Standard

DHT NUMBERS TABLE

MB-15(1)

FILE:MB14(1).DGN	DN:		ск:	DW:		Ск:	
© TxDOT APRIL 2015	CONT	SECT	JOB	HWAY			
REVISIONS	0915	12	562		WATSON RD		
	DIST		COUNTY		5	SHEET NO.	
	SAT		BEXAR	2		119	



J:	5-1	4					
E: js14.dgn	dn: TxD	OT	dn: HC	DW:	HC	СК	AN
)TxDOT: DECEMBER 2014	CONT SECT		JOB		HIGHWAY		
REVISIONS	0915	12	562		WAT	SON	I RD
	DIST		COUNTY			SHEE	T NO.
	CVL			<u> </u>			20







12

12

12

1'' X 18''

1 [|]/₄'' X 18''

1 <mark>/</mark>2" X 18"

6 to 7.5 8 to 10

>= 10.5

- .3.
- 4
- 5
- 6.
- SLABTHICKNESS (T/3).
- 9 REQUIREMENTS IN ITEM 361.
- 11.
- 12

TABLE NO.2 TIE	BARS (DEF	FORMED BARS
SLAB THICKNESS T (IN.)	BAR SIZE	AVERAGE SPACING (IN.)
6 to 7.5	#5	24
>= 8	#6	24

GENERAL NOTES

DETAILS FOR PAVEMENT WIDTH, PAVEMENT THICKNESS AND THE CROWN CROSS-SLOPE SHALL BE SHOWN ELSEWHERE IN THE PLANS. PAVEMENTS WIDER THAN 100 FT. WITHOUT A FREE LONGITUDINAL JOINT ARE NOT COVERED BY THIS STANDARD.

2. FOR FURTHER INFORMATION REGARDING THE PLACEMENT OF CONCRETE AND LOAD TRANSFER DEVICES REFER TO THE GOVERNING SPECIFICATION FOR "CONCRETE PAVEMENT".

THE SPACING BETWEEN TRANSVERSE CONTRACTION JOINTS SHALL BE 15 FT. UNLESS OTHERWISE SHOWN IN THE PLANS.

TRANSVERSE CONSTRUCTION JOINTS MAY BE FORMED BY USE OF METAL OR WOOD FORMS EQUAL IN DEPTH TO THE DEPTH OF PAVEMENT, OR BY METHODS APPROVED BY THE ENGINEER.

USE HAND-OPERATED IMMERSION VIBRATORS TO CONSOLIDATE THE CONCRETE ADJACENT TO ALL THE FORMED JOINTS.

PAVEMENT WIDTHS OF MORE THAN 15 FT. SHALL HAVE A LONGITUDINAL JOINT (SECTION Z-Z OR SECTION Y-Y). THESE JOINTS SHALL BE LOCATED WITHIN 6 IN. OF THE LANE LINE UNLESS THE JOINT LOCATION IS SHOWN ELSEWHERE ON THE PLANS.

7. THE JOINT BETWEEN OUTSIDE LANE AND SHOULDER SHALL BE A LONGITUDINAL CONTRACTION JOINT (SECTION Z-Z) UNLESS OTHERWISE SHOWN IN THE PLANS. THE SAW CUT DEPTH FOR THE LONGITUDIANL CONTRACTION JOINT (SECTION Z-Z) SHALL BE ONE THIRD OF THE

8. WHEN TYING CONCRETE GUTTER AT A LONGITUDINAL JOINT, THE TIE BAR LENGTH OR POSITION MAY BE ADJUSTED. PROVIDE 3 IN. OF CONCRETE COVER FROM THE BACK OF GUTTER TO THE END OF TIE BAR.

REPLACE MISSING OR DAMAGED TIE BARS WITHOUT ADDITIONAL COMPENSATION BY DRILLING MIN. 10 IN. DEEP AND GROUTING TIE BARS WITH TYPE III, CLASS C EPOXY. MEET THE PULL-OUT TEST

10. WHEN AN MONOLITHIC CURB IS SPECIFIED, THE JOINT IN THE CURB SHALL COINCIDE WITH PAVEMENT JOINTS AND MAY BE FORMED BY ANY MEANS APPROVED BY THE ENGINEER.

DOWEL BAR PLACEMENT TOLERANCE SHALL BE +/- 1/4 IN. HORIZONTALLY AND VERTICALLY UNLESS OTHERWISE SPECIFIED.WHERE DOWEL BAR BASKETS ARE USED, REMOVE THE SHIPPING WIRES.

THE DETAIL FOR JOINT SEALANT AND RESERVOIR IS SHOWN ON STANDARD SHEET "CONCRETE PAVING DETAILS, JOINT SEALS."

S)	SHEET 1 OF 2											
	Texas Department of Transportation	Design Division Standard										
	CONCRETE PAVEMENT DE	TAILS										
	CONTRACTION DESIGN											
	T-6 to 12 INCHES											
	CPCD-14											
	FILE: cpcd14.dgn DN: TxDOT DN: HC DW: H	HC CK: AN										
	C TXDOT: DECEMBER 2014 CONT SECT JOB	HIGHWAY										
	REVISIONS 0915 12 562	WATSON RD										
	DIST COUNTY	SHEET NO.										
	SAT BEXAR	121										



whats use. purpose from its any Ilting for esul "Texas Engineering Practice Act". No warranty of any kind is made by TxDDT version of this standard to other formats or for incorrect results or damages the con the by DISCLAIMER: The use of this standard is governed TxDOT assumes no responsibility for i SHTS/ST. M IO 6/25/2020 12:53:29 X:\data\Infra\Proj_2

DATE:



vhats use. se its purpos from any ting for T×DOT mages 28 is made results or kind ect r any anty of or for i ats وم آوت Act". other Practice dard to (Engineering of this stand "Texas rersion the by the for standard is goverr no responsibility f this mes DISCLAIMER: The use of t T×DOT assur

GENERAL NOTES



SHEET 1 OF 2

Texas Department	of Tra	nsp	ortation		De Dit Sta	sign vision andard
CONTINUOUSL CONCRET ONE LAYER STE T - 7 to	E E EL 13	R P A ba in	EINF VEM r pl4 ches	0 IE AC	RC NT eme	E D nt
CRC	Р(1) –	17			
FILE: crcp117.dgn	dn: Tx[DOT	ск: AN	DW:	нс	ск: VP/КМ
C TxDOT: May 2017	CONT	SECT	JOB		H	IGHWAY
REVISIONS 10/10/2011 ADD GN •12	0915	12	562		WAT	SON RD
04/09/2013 REMOVE 6" AND 6.5" ADD CTE REQUIREMENTS	DIST		COUNTY			SHEET NO.
05/05/2017 CoTE AS RATED 4.3	SAT		BEXAR	2		123

B T B A	HICKNESS R SIZE	REGULAR STEEL BARS	FIRST SPACING AT EDGE OR JOINT	ADDITIONA BARS AT CONSTRUC (SECTIO	AL STEEL TRANSVERSE TION JOINT)N X-X)	11/2" EXPANSION JOINT JOINTS 11/2" EXPANSION JOINT T/3 SAW CUT DEPTH
т	BAR	SPACING	SPACING	SPACING	LENGTH	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
N.)	SIZE	с (IN.)	(IN.)	2 x c (IN.)	(IN.)	$ \begin{bmatrix} \Delta & \cdot & \\ & & & \\ & & \\ & & & \\ & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ &$
7.0	#5	7.5	3 TO 4	15	50	
'.5	#5	7.0	3 TO 4	14	50	
3.0	#6	10.0	3 TO 4	20	50	SLAB
3.5	*6	9.5	3 TO 4	19	50	A . TWO LAYERS / · · · HMAC(UNDERLAYMENT) →
9.0	#6	9.0	3 TO 4	18	50	SULB RUUFING FELT
а 5	#6	8.5	3 TO 4	17	50	I TRANSVERSE EXPANSION JOINT DETAIL
0.0	#6	0 0		17	50	AT BRIDGE APPROACH
10.5	"O	0.0		16	50	
0.5	#6	7.5	5 10 4	15	50	
1.0	#6	7.0	3 TO 4	14	50	EXISTING CRCP NEW CRCP
1.5	*6	6.75	3 TO 4	13.5	50	MIN.30" EDGE OF CRCP PA
2.0	*6	6.50	3 TO 4	13	50	MIN.10''
2.5	*6	6.25	3 TO 4	12.5	50	
3.0	*6	6.0	3 TO 4	12	50	Δ ^Δ · Δ · TRANSVERSE CONSTRUCTION JOINT
1		-REINFORCING S SPLICES		GE OF CRCP LONGITUDIN	PAVEMENT AL JOINT	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
			AL TEEL EDC OR 	GE OF CRCP	PAVEMENT AL JOINT	A A A · B B · B B · B B · B B · B B · B B · B B · B B
			AL TEEL EDC OR COR COR COR COR COR COR COR	GE OF CRCP	PAVEMENT AL JOINT	A A A A A A A A A A A A A A
			AL TEEL EDC OR OR 	GE OF CRCP	PAVEMENT AL_JOINT	A A A · A · A · A · A A · A · DRILL AND GROUT WITH TYPE III, CLASS C E DEMONSTRATE THAT THE BOND STRENCH EPOXY-GROUTED LONGITUDINAL BARS MEETS REQUIREMENTS OF PULL-OUT TEST SPECIFIC ITEM 361. OPTION A: DRILL AND EPOXY PLAN VIEW (NOT TO SCALE) EXISTING CRCP NEW CRCP PARTIAL DEPTH SAWCUT · · MIN.36" NEW LONGITUDINAL STEEL BARS
>			AL TEEL EDC OR AL OR AL OR AL OR AL OR AL OR OR OR OR OR OR OR OR OR OR	GE OF CRCP	PAVEMENT AL JOINT	A A A A A A A A A A A A A A
	12-FT WIDT GER THE L	REINFORCING S SPLICES		GE OF CRCP LONGITUDIN	BY 2-FT LENG	A A A A A A A A A A A A A A A A A A A A A A A A A A A A A A A A A DRILL AND GROUT WITH TYPE III, CLASS C F DEMONSTRATE THAT THE BOND STRENGTH EPOXY-GROUTED LONGITUDINAL BARS MEETS FEOUREMENTS OF PULL-OUT TEST SPECIFIE THEM 361. OPTION A: DRILL AND EPOXY PLAN VIEW (NOT TO SCALE) PLAN VIEW (NOT TO SCALE) A A A A A A A A A A A A A A A A A A A A A A A A A A A A A A A <
	12-FT WIDT GER THE L/ 17UDINAL ST 2-FT. LENGT	H BY 2-FT LENG	AL TEEL EDC OR AL TH TH TH TH THAT NO MC N ANY GIVEN ENT. ANY OT	GE OF CRCP LONGITUDIN	BY 2-FT LENG	T A A A A A A A A A A A A A
	12-FT WIDT GER THE LA ITUDINAL ST 2-FT. LENGT IGURATION M	H BY 2-FT LENG AP LOCATIONS SO EEL IS SPLICED IN H OF THE PAVEM MEETING THIS REQ	AL TEEL ED(OR I OR I I I I I I I I I I I I I	GE OF CRCP LONGITUDIN	BY 2-FT LENG	T A A A A A A A A A A A A A



PLOTTED BY: ivette PLOTTED SCALE: 1:400 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:36:28 AM PLOTTED ON: 6/24/2020 @ 11:36:28 AM DESIGN FILENAME: Z:\Projects\Watson Road\Drainage\M058-DAM-01.d

Γ		Total			т	Overland	Flow		Tc -	Shallow Cor	ncentrated	I Flow		То	Tc	1-	0-	L.	0	Luc	0
	Area ID	Area	C _W	CA		Ic - Overland Flow			Reach 1			Reach 2		10	used	15	Q5	10	Q ₁₀	100	Q ₁₀₀
		Acres			L	slope	Т	Length	slope (ft/ft)	Tsc1 (min)	Length	slope (ft/ft)	Tsc2 (min)	min	utes	in/hr	cfs	in/hr	cfs	in/hr	cfs
Γ	C10	57.24	0.43	24.61	100	0.30%	20.00	1703	0.31%	31.41	1209	0.16%	10.02	61.43	61.43	2.39	58.72	2.86	70.39	4.57	112.41











Discharge Calculations w/ TxDOT Rainfall(Rational Method) Proposed Tc - Overland Flow Tc - Shallow Concentrated Flow Tc CA Tc - Overland Flow Tc

	Total			Т		Flow		10 -	Shallow Co	ncentiateu	FIOW		To	IC	1-		1	0	L	0
Area ID	Area	C _W	CA			11000		Reach 1			Reach 2		10	used	15	025	10	Q ₁₀	100	Q100
	Acres			L	slope	Т	Length	slope (ft/ft)	Tsc1 (min)	Length	slope (ft/ft)	Tsc2 (min)	min	utes	in/hr	cfs	in/hr	cfs	in/hr	cfs
A20	0.16	0.90	0.14	22	1.37%	5.00	144	0.76%	1.36				6.36	10.00	6.73	0.97	7.83	1.13	12.13	1.76
A30	0.24	0.90	0.22	25	2.91%	5.00	118	0.67%	1.19				6.19	10.00	6.73	1.45	7.83	1.69	12.13	2.62
A50	0.45	0.90	0.41	21	3.08%	5.00	221	0.63%	2.28				7.28	10.00	6.73	2.74	7.83	3.19	12.13	4.93
A55	0.23	0.90	0.21	142	0.12%	5.00	135	0.39%	1.78				6.78	10.00	6.73	1.41	7.83	1.64	12.13	2.54
A60	0.50	0.90	0.45	32	1.84%	5.00	414	0.45%	5.07				10.07	10.07	6.71	3.04	7.81	3.54	12.10	5.49
A65	0.29	0.90	0.26	46	3.30%	5.00	385	0.23%	6.59				11.59	11.59	6.32	1.63	7.38	1.91	11.45	2.96
A80	1.13	0.43	0.49	100	0.42%	20.00	502	0.39%	8.31	85		0.24	28.54	28.54	3.94	1.91	4.67	2.27	7.36	3.57
B80	0.33	0.90	0.30	35	1.12%	5.00	151	0.36%	2.06				7.06	10.00	6.73	1.99	7.83	2.31	12.13	3.58
B85	0.33	0.90	0.30	31	1.50%	5.00	303	0.36%	4.14				9.14	10.00	6.73	2.00	7.83	2.33	12.13	3.61
B86	1.55	0.43	0.67	100	0.36%	20.00	280	0.39%	4.66	90		0.25	24.91	24.91	4.27	2.85	5.05	3.38	7.94	5.31
B90	0.17	0.90	0.15	31	0.11%	5.00	145	0.36%	1.99				6.99	10.00	6.73	1.00	7.83	1.16	12.13	1.80
B95	1.85	0.43	0.79	100	0.56%	20.00	298	0.18%	7.30	144		0.40	27.70	27.70	4.01	3.18	4.76	3.78	7.49	5.95

PLOTTED BY: ivette PLOTTED SCALE: 1:200 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:36:30 AM PLOTTED ON: 6/24/2020 @ 11:36:30 AM DESIGN FILENAME: Z:NProjects/Watson Road/Drainage/M058-IDAM





	Total			т	c - Overland	Flow		Tc -	Shallow Co	ncentrated	Flow		Тс	Tc	l.	0-	lun.	0	lun	0
Area ID	D Area	C _W	CA	'	c - Overland	1 1000		Reach 1			Reach 2		10	used	15	X 5	10	Q 10	100	∞100
	Acres			L	slope	Т	Length	slope (ft/ft)	Tsc1 (min)	Length	slope (ft/ft)	Tsc2 (min)	min	utes	in/hr	cfs	in/hr	cfs	in/hr	cfs
B3.1	1.78	0.67	1.20	100	0.70%	20.00	324	0.40%	4.20	609	0.21%	1.69	25.90	25.90	4.17	4.99	4.95	5.92	7.78	9.31
B10	1.59	0.83	1.32	100	0.66%	20.00	659	0.29%	12.67	32		0.09	32.76	32.76	3.62	4.77	4.30	5.67	6.80	8.96
B100	0.38	0.90	0.34	30	2.00%	5.00	232	0.21%	4.13				9.13	10.00	6.73	2.31	7.83	2.69	12.13	4.17
B110	0.29	0.90	0.26	22	2.18%	5.00	258	0.69%	2.55				7.55	10.00	6.73	1.74	7.83	2.03	12.13	3.14
B120i	0.07	0.90	0.06	23	2.44%	5.00	107	0.42%	1.36				6.36	10.00	6.73	0.44	7.83	0.51	12.13	0.79
B130i	0.03	0.90	0.02	16	1.63%	5.00	73	0.11%	1.81				6.81	10.00	6.73	0.16	7.83	0.18	12.13	0.28
B140	0.39	0.90	0.35	20	1.87%	5.00	314	0.73%	3.01				8.01	10.00	6.73	2.36	7.83	2.75	12.13	4.26
B145	0.18	0.90	0.16	25	2.00%	5.00	65	0.25%	1.06				6.06	10.00	6.73	1.08	7.83	1.26	12.13	1.95
B20	0.22	0.90	0.20	18	1.50%	5.00	59	0.22%	1.03	52		0.14	6.18	10.00	6.73	1.34	7.83	1.56	12.13	2.42
B30	0.32	0.90	0.28	27	0.35%	5.00	191	0.53%	2.15				7.15	10.00	6.73	1.91	7.83	2.23	12.13	3.45
B33	4.95	0.43	2.13	100	0.46%	20.00	458	0.51%	6.62	196		0.54	27.17	27.17	4.05	8.63	4.81	10.24	7.57	16.12
B35	0.31	0.90	0.28	31	2.01%	5.00	230	0.38%	3.06				8.06	10.00	6.73	1.86	7.83	2.16	12.13	3.35
B40	0.15	0.90	0.14	30	1.72%	5.00	134	0.36%	1.84				6.84	10.00	6.73	0.93	7.83	1.08	12.13	1.67
B50	0.26	0.90	0.23	37	1.84%	5.00	107	0.36%	1.46				6.46	10.00	6.73	1.57	7.83	1.83	12.13	2.83
B55	0.43	0.90	0.39	30	2.55%	5.00	463	0.36%	6.33				11.33	11.33	6.38	2.48	7.45	2.90	11.55	4.49
B60	0.24	0.90	0.22	36	2.70%	5.00	209	0.35%	2.90				7.90	10.00	6.73	1.47	7.83	1.71	12.13	2.64
B65	3.93	0.43	1.69	100	0.10%	20.00	294	0.34%	5.21	330		0.92	26.13	26.13	4.15	7.00	4.92	8.31	7.74	13.07
B70	0.15	0.90	0.13	30	1.55%	5.00	127	0.39%	1.67				6.67	10.00	6.73	0.88	7.83	1.03	12.13	1.59

PLOTTED BY: ivette PLOTTED SCALE: 1:200 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pitcfg PLOT DRIVER: WATSON_BW_PDF_CEC.pitcfg PLOTTED ON: 6/24/2020 @ 11:36:34 AM DESIGN FILENAME: Z:Projects\Watson Road\Drai

U.S.	D.S.	Actual	Hyd.	N Value	Siono	No.	Snon	Bico	Fo	Soffit	Soffit	Invert	Invert	Unif. Donth	Unif.	Act. Vel.	Act. Depth	Act. Depth	HGL	HGL	EGL	EGL	Sum	•	Sum	Avg C	Rainfall
Noue	Noue	Lengui	Lengin	IN Value	Siope	Darreis	Span	Rise	15	0.3.	D.3.	0.3.	D.3.	Depu	vei.	D.3.	0.3.	D.3.	0.3.	D.3.	0.3.	0.3.	10	Q ₁₀	Alea	value	mensity
A10	Aout	8.26	10.76	0.013	0.17	1	3.00	2.00	0.002	620.91	620.90	618.91	618.90	0.99	3.28	1.62	2.00	2	620.93	620.90	620.97	620.94	33.09	9.73	3.01	0.75	n/a
A20	A10	69.49	77.49	0.013	0.20	1	3.00	2.00	0.002	621.05	620.91	619.05	618.91	0.93	3.50	1.62	1.92	2.00	620.98	620.93	621.02	620.97	33.03	9.73	3.01	0.75	4.31
A30	A20	57.72	65.53	0.013	0.21	1	3.00	2.00	0.002	621.17	621.05	619.17	619.05	0.87	3.51	1.58	1.84	1.92	621.02	620.98	621.06	621.02	32.66	9.12	3.01	0.75	4.31
A40	A30	178.50	186.50	0.013	0.20	1	3.61	2.22	0.002	621.75	621.39	619.53	619.17	1.25	3.26	2.04	1.62	1.84	621.15	621.02	621.24	621.06	32.35	8.34	2.84	0.74	4.34
A50	A40	167.59	175.59	0.013	0.20	1	2.41	1.49	0.002	621.36	621.02	619.87	619.53	1.07	3.15	2.35	1.49	1.49	621.40	621.15	621.48	621.24	31.40	6.30	2.60	0.72	4.42
A60	A50	141.42	152.42	0.013	0.30	1	2.41	1.49	0.003	621.79	621.36	620.30	619.87	0.69	3.31	1.53	1.19	1.49	621.48	621.40	621.54	621.48	30.47	4.09	2.08	0.67	4.50
A90	A60	87.95	95.45	0.013	0.30	1	2.41	1.49	0.003	622.05	621.79	620.56	620.30	0.41	2.78	1.03	0.94	1.19	621.50	621.48	621.53	621.54	29.70	2.27	1.63	0.59	4.57
A70	A90	91.27	95.27	0.013	0.31	1	2.41	1.49	0.003	622.33	622.05	620.84	620.56	0.41	2.78	1.29	0.73	0.94	621.57	621.50	621.62	621.53	29.13	2.27	1.13	0.43	4.68
A80	A70	7.00	10.50	0.012	0.36	1	2.50	1.58	0.004	622.45	622.42	620.87	620.84	0.45	3.17	1.63	0.75	0.73	621.61	621.57	621.66	621.62	28.56	2.27	1.13	0.43	4.68
A45	A40	40.74	45.24	0.013	0.34	1	2.41	1.49	0.003	621.16	621.02	619.67	619.53	0.50	3.34	1.30	1.49	1.49	621.19	621.15	621.22	621.24	31.40	3.48	2.60	0.72	4.42
A55	A45	147.45	154.95	0.013	0.31	1	2.41	1.49	0.003	621.61	621.16	620.12	619.67	0.51	3.25	1.30	1.13	1.49	621.25	621.19	621.30	621.22	13.46	3.48	0.52	0.95	7.10
A65	A55	161.42	172.22	0.013	0.30	1	2.41	1.49	0.003	622.10	621.61	620.61	620.12	0.37	2.69	0.94	0.72	1.13	621.33	621.25	621.37	621.30	12.67	1.98	0.52	0.95	7.10

					NL	ET H	HYDR	AULI	CS				
						By	By Pass		Inlet	Inlet	Computed	Computed	
Inlet			Profile			Pass	Flow	By Pass	Curb	Length	Ponded	Ponded	Street
ID	Station	Туре	Туре	Q ₁₀	Cap	Flow	Into	Node ID	Length	Req'd	Width	Depth	Slope
A20	111+50.00	Curb	Sag	1.2	7.39	0.00	0.00	0.00	10	13.29	6.91	0.12	n/a
A30	111+73.50	Curb	Sag	1.69	7.39	0.00	0.00	0.00	10	13.29	7.86	0.15	n/a
A50	115+40.50	Curb	Sag	3.7	7.39	0.00	0.34	0.00	10	79.91	12.62	0.25	n/a
A60	117+00.00	Curb	On Grade	3.76	3.42	0.34	0.03	A50	10	13.59	13.18	0.26	0.44
A80	119+00.00	Curb	Sag	2.27	8.03	0.00	0.00	0.00	12	10.46	8.62	0.17	n/a
A55	115+40.50	Curb	Sag	1.73	7.39	0.00	0.00	0.00	10	9.21	7.93	0.15	n/a
A65	117+11.50	Curb	On Grade	2.01	1.98	0.03	0.00	A60	10	11.08	10.42	0.21	0.44

						INLE	ET C	ONF	IGUF	RAT	ION							
					Inlet	Inlet		Inlet	Inlet	Curb	Max	Max						Grate
				Inlet	Profile	Spread	Inlet	Curb	Curb	Dep.	Ponded	Ponded	Grate	Grate	Grate	Grate	Grate	Clog
nlet ID	Station	Offset	T/C Elev.	Туре	Туре	Slope	Length	Dep.	Height	Width	Width	Depth	Туре	Length	Width	Area	Perimeter	Area
A20	111+50.00	28	623.21	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
A30	111+73.50	-26	623.34	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
A50	115+40.50	-31	622.74	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
A60	117+00.00	-33.7	623.28	Curb	On Grade	0.02	10	0.25	0.5	1.5	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
A80	119+00.00	-53.25	624.33	Curb	Sag	0.02	12	0.02	0.5	1	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
A55	115+40.50	9.1	623.48	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
A65	117+11.50	6.18	623.55	Curb	On Grade	0.02	10	0.21	0.44	3.46	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a

NOTES:

1. STORM SEWER TRUNKLINE AND INLETS ARE DESIGNED FOR 10-YEAR STORM EVENT.

2. HYDRAULIC COMPUTATIONS PERFORMED IN GEOPAK DRAINAGE.



PLOTTED BY: ivette PLOTTED SCALE: 1:100 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:36:41 AM PLOTTED ON: 6/24/2020 @ 11:36:41 AM DESIGN FILENAME: Z:\Projects\Watson Road\Drainage



									G	EOP	AK H	IYDR	AUL		ON	VEY	ΆΝ	CE									
																Act.	Act.	Act.									
U.S.	D.S.	Actual	Hyd.			No.			_	Soffit	Soffit	Invert	Invert	Unif.	Unif.	Vel.	Depth	Depth	HGL	HGL	EGL	EGL	Sum		Sum	Avg C	Rainfall
Node	Node	Length	Length	N Value	Slope	Barrels	Span	Rise	Fs	U.S.	D.S.	U.S.	D.S.	Depth	Vel.	D.S.	U.S.	D.S.	U.S.	D.S.	U.S.	D.S.	Tc	Q ₁₀	Area	Value	Intensity
B90	B80	147.00	158.00	0.013	0.31	1	n/a	2.00	0.003	622.90	622.45	620.90	620.45	0.84	3.63	1.58	1.37	1.71	622.27	622.16	622.34	622.46	28.51	4.52	4.23	0.53	4.68
B80	B70	262.00	273.00	0.013	0.31	1	n/a	2.00	0.003	622.45	621.65	620.45	619.65	1.41	4.44	4.07	1.71	1.53	622.16	621.18	622.46	621.38	29.54	10.50	4.37	0.55	4.58
B70	B60	209.00	220.00	0.013	0.31	1	n/a	2.50	0.003	622.15	621.50	619.65	619.00	1.21	4.64	2.55	1.53	2.04	621.18	621.04	621.38	621.33	30.33	10.92	8.54	0.50	4.51
B60	B50	107.00	118.00	0.013	0.33	1	n/a	3.00	0.003	622.00	621.65	619.00	618.65	1.52	5.41	3.67	2.04	2.10	621.04	620.75	621.33	621.07	30.69	19.40	9.23	0.54	4.48
B50	B40	247.50	258.50	0.013	0.30	1	n/a	3.00	0.003	621.65	620.90	618.65	617.90	1.67	5.48	3.51	2.10	2.51	620.75	620.41	621.07	620.62	31.48	22.21	9.39	0.54	4.41
B40	B30	85.46	96.46	0.013	0.35	1	n/a	3.00	0.004	620.90	620.60	617.90	617.60	1.63	5.75	3.33	2.51	2.74	620.41	620.34	620.62	620.85	31.76	22.51	14.96	0.52	4.39
B30	B25	194.79	202.79	0.013	0.31	1	n/a	3.00	0.003	620.60	620.00	617.60	617.00	2.29	5.93	5.48	2.74	2.49	620.34	619.49	620.85	620.09	32.33	34.33	15.85	0.55	4.34
B95	B90	14.39	19.80	0.012	0.35	1	2 50	1.58	0.004	622 53	622.48	620.95	620.90	0.58	3 71	1.32	1.35	1.37	622.30	622 27	622.33	622 34	27 79	3.78	2 0 1	0.47	4 75
B85	B80	65.00	72.26	0.012	0.54	1	2.50	1.58	0.005	622.38	622.40	620.80	620.45	0.00	3 75	0.79	1.00	1.57	622.00	622.27	622.00	622.04	28.51	2 46	4 23	0.53	4.68
B86	B80	14.56	19.97	0.012	0.48	1	2.50	1.58	0.005	622.00	622.03	620.52	620.45	0.50	4 00	1.09	1.58	1.58	622.18	622.16	622.20	622.10	28.51	3.38	4 23	0.53	4.68
B65	B60	14.56	19.07	0.012	0.40	1	n/a	2.00	0.000	621.05	621.00	619.05	619.00	1 14	4.00	2.64	2.00	2.00	621 17	621.04	621.28	621 33	30 33	8 31	8.54	0.50	4.50
B55	B50	65.00	72.26	0.013	0.38	1	n/a	2.00	0.004	620.90	620.65	618 90	618 65	0.63	3.61	0.97	1.88	2.00	620.78	620.75	620.80	621.00	30.69	3.06	9.23	0.54	4.48
B33	B30	14.92	20.33	0.013	0.67	1	n/a	2.00	0.007	619 70	619 60	617 70	617 60	1.06	6.03	3.26	2.00	2.00	620.55	620.34	620.71	620.85	31 76	10.24	14 96	0.52	4 39
B35	B30	76.76	84.02	0.013	0.52	1	n/a	2.00	0.005	620.00	619.00	618.00	617.60	0.51	3.65	0.20	2.00	2.00	620.36	620.34	620.36	620.85	31 76	2.28	14.96	0.52	4 39

					NL	ET F	IYDR	AULI	CS				
						By	By Pass		Inlet	Inlet	Computed	Computed	
Inlet			Profile			Pass	Flow	By Pass	Curb	Length	Ponded	Ponded	Street
ID	Station	Туре	Туре	Q ₁₀	Cap	Flow	Into	Node ID	Length	Req'd	Width	Depth	Slope
B90	122+91.00	Curb	On Grade	1.23	1.23	0.00	0.00	B80	10	6.87	9.04	0.18	0.35
B80	124+49.00	Curb	Sag	2.44	3.43	0.00	0.00	0.00	10	10.46	9.55	0.19	n/a
B70	127+22.00	Curb	On Grade	1.08	1.08	0.00	0.00	B60	10	6.39	8.62	0.17	0.35
B60	129+42.00	Curb	On Grade	1.8	1.8	0.00	0.00	B50	10	8.52	10.42	0.21	0.35
B50	130+60.00	Curb	Sag	1.93	3.43	0.00	0.00	0.00	10	8.77	8.26	0.16	n/a
B40	133+18.50	Curb	On Grade	1.14	1.14	0.00	0.00	B30	10	6.57	8.78	0.18	0.35
B30	134+15.00	Curb	Sag	2.35	3.43	0.00	0.00	0.00	10	8.77	9.32	0.19	n/a
B95	122+90.00	Curb	Sag	3.78	8.03	0.00	0.00	0.00	12	10.46	12.1	0.24	n/a
B85	124+49.00	Curb	Sag	2.46	3.43	0.00	0.00	0.00	10	10.46	9.6	0.19	n/a
B86	124+49.00	Curb	Sag	3.38	8.03	0.00	0.00	0.00	12	10.46	11.23	0.22	n/a
B65	129+42.00	Curb	Sag	8.31	8.03	0.00	0.00	0.00	12	10.46	20.46	0.41	n/a
B55	130+60.00	Curb	Sag	3.06	3.43	0.00	0.00	0.00	10	8.77	11.12	0.22	n/a
B33	134+15.00	Curb	Sag	10.2	8.03	0.00	0.00	0.00	12	10.46	23.52	0.47	n/a
B35	134+17.00	Curb	Sag	2.28	7.39	0.00	0.00	0.00	10	10.46	9.14	0.18	n/a

						INLE	ET C	ONF	IGUF	RAT	ON							
					Inlet	Inlet		Inlet	Inlet	Curb	Max	Max						Grate
				Inlet	Profile	Spread	Inlet	Curb	Curb	Dep.	Ponded	Ponded	Grate	Grate	Grate	Grate	Grate	Clog
nlet ID	Station	Offset	T/C Elev.	Туре	Туре	Slope	Length	Dep.	Height	Width	Width	Depth	Туре	Length	Width	Area	Perimeter	Area
B90	122+91.00	-32	624.68	Curb	On Grade	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B80	124+49.00	-32	624.12	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B70	127+22.00	-32	624.12	Curb	On Grade	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B60	129+42.00	-32	624.08	Curb	On Grade	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B50	130+60.00	-32	623.06	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B40	133+18.50	-32	622.84	Curb	On Grade	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B30	134+15.00	-33.8	622.46	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B95	122+90.00	-53.25	625.00	Curb	Sag	0.02	12	0.02	0.5	1	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
B85	124+49.00	32	624.12	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B86	124+49.00	-53.25	624.77	Curb	Sag	0.02	12	0.02	0.5	1	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
B65	129+42.00	-53.25	623.67	Curb	Sag	0.02	12	0.02	0.5	1	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
B55	130+60.00	32	622.94	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B33	134+15.00	-55.5	622.48	Curb	Sag	0.02	12	0.02	0.5	1	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
B35	134+17.00	42.3	622.30	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a

NOTES:

1. STORM SEWER TRUNKLINE AND INLETS ARE DESIGNED FOR 10-YEAR STORM EVENT.



PLOTTED BY: ivette PLOTTED SCALE: 1:100 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pttcfg PLOTTED ON: 6/24/2020 @ 11:36:49 AM PLOTTED ON: 6/24/2020 @ 11:36:49 AM DESIGN FILENAME: Z:\Projects\Watson Road\Drai



									GI	EOP	АК Н	YDR	AUL	IC C	ON	VEY	'ANC	CE									
U.S. Node	D.S. Node	Actual Length	Hyd. Lenath	N Value	Slope	No. Barrels	Span	Rise	Fs	Soffit U.S.	Soffit D.S.	Invert U.S.	Invert D.S.	Unif. Depth	Unif. Vel.	Act. Vel. D.S.	Act. Depth U.S.	Act. Depth D.S.	HGL U.S.	HGL D.S.	EGL U.S.	EGL D.S.	Sum Tc	0	Sum Area	Avg C Value	Rainfall Intensity
B10	B7	34.33	46.67	0.013	0.29	1	n/a	2.00	0.003	618.45	618.35	616.45	616.35	0.97	3.78	1.85	1.87	1.89	618.32	618.24	618.38	618.81	32.97	5.69	18.01	0.58	4.29
B25	B7	178.71	184.21	0.013	0.31	1	n/a	3.00	0.003	619.90	619.35	616.90	616.35	2.46	6.06	7.53	2.59	2.00	619.49	618.35	620.09	618.81	32.97	37.64	18.01	0.58	4.29
B7	B6	294.00	300.00	0.013	0.31	1	4.00	3.00	0.003	619.35	618.45	616.35	615.45	1.86	6.09	5.11	1.89	2.21	618.24	617.66	618.81	618.07	33.79	45.18	18.01	0.58	4.29
B6	B5	294.00	300.00	0.013	0.31	1	4.00	3.00	0.003	618.45	617.55	615.45	614.55	1.86	6.09	3.94	2.21	2.87	617.66	617.42	618.07	617.66	34.61	45.18	18.01	0.58	4.29
B5	B4	167.00	173.00	0.013	0.33	1	4.00	3.00	0.003	617.55	617.00	614.55	614.00	1.79	6.32	3.77	2.87	3.00	617.42	617.23	617.66	617.46	35.07	45.18	18.58	0.59	4.13
B4	B3.1	28.14	32.98	0.013	0.36	1	4.00	3.00	0.004	617.00	616.90	614.00	613.90	1.76	6.47	3.80	3.00	3.00	617.23	617.03	617.46	617.31	35.15	45.61	20.36	0.60	4.12
B3.1	B2	22.24	24.07	0.013	0.45	1	4.00	3.00	0.005	616.90	616.80	613.90	613.80	1.72	7.35	4.21	3.00	3.00	617.03	616.97	617.31	617.25	35.21	50.46	20.36	0.60	4.12
B2	Bout	78.68	78.68	0.013	0.32	1	4.00	3.00	0.003	616.80	616.55	613.80	613.55	1.95	6.47	4.21	3.00	3.00	616.97	616.72	617.25	616.99	35.41	50.46	20.36	0.60	n/a
D440	D 400	70.00	77.00	0.040	0.40		,	0.00	0.004	040 70	040.40	047 70	047.40	0.54	2.20	0.00	4.00		040.50	040.50	040.00		40.00	0.44	0.07	0.05	7 70
B110	B100	70.93	11.63	0.013	0.42	1	n/a	2.00	0.004	619.70	619.40	617.70	617.40	0.51	3.30	0.68	1.89	2.00	619.59	619.58	619.60	619.61	10.38	2.14	0.67	0.95	1.12
B100	B20	114.34	121.04	0.013	0.31	1	n/a	2.00	0.003	619.40	619.05	617.40	617.05	0.87	3.77	1.56	2.00	2.00	619.58	619.51	619.61	619.57	10.92	4.91	0.89	0.95	7.56
B20	B25	5.45	11.30	0.013	0.92	1	n/a	2.00	0.009	619.05	619.00	617.05	617.00	0.74	6.02	2.04	2.00	2.00	619.51	619.49	619.57	620.09	32.33	6.41	15.85	0.55	4.34
B145	B140	85.16	94.01	0.013	0.31	1	n/a	2.00	0.003	618.81	618.55	616.81	616.55	0.44	2.61	0.46	1.48	1.73	618.29	618.28	618.29	618.31	10.60	1.34	0.57	0.95	7.65
B140	B7	54.53	63.03	0.013	0.37	1	n/a	2.00	0.004	618.55	618.35	616.55	616.35	0.76	3.81	1.35	1.73	1.89	618.28	618.24	618.31	618.81	32.97	4.14	18.01	0.58	4.29

					NL	ET I	HYDR	AULI	CS				
1.1.1			Design			Ву	By Pass		Inlet	Inlet	Computed	Computed	0
Iniet	Ctation	T	Profile		0.00	Pass	FIOW	By Pass	Curb	Length	Ponded	Ponded	Street
U	Station	туре	туре	Q ₁₀	Cap	FIOW	into	Node ID	Lengin	Requ	vviatn	Depin	Siope
B20	135+98.33	Curb	Sag	1.65	3.43	0.00	0.00	0.00	10	6.8	7.79	0.15	n/a
B10	201+83.50	Curb	Sag	5.69	6.14	0.00	0.00	0.00	20	11.22	12.38	0.23	n/a
B3.2	209+73.63	Curb	Sag	3.72	8.8	0.00	0.00	0.00	5	10.46	16.4	0.33	n/a
B100	136+10.00	Curb	San	2.84	3 4 3	0.00	0.00	0.00	10	6.8	10.58	0.21	n/a
B110	136+89.50	Curb	Sag	2.04	3 43	0.00	0.00	0.00	10	6.8	8 77	0.18	n/a
DITO	100109.00		Joay	2.17	0.40	0.00	0.00	0.00	10	0.0	0.77	0.10	l Iva
B145	200+33.50	Curb	Sag	1.34	3.43	0.00	0.00	0.00	10	6.8	7.19	0.13	n/a
B140	137+05.00	Curb	Sag	2.9	3.43	0.00	0.00	0.00	10	6.8	10.73	0.21	n/a
B120i	140+88.00	Curb	On Grade	0 54	0 54	0.00	0.00	0.00	10	8 59	6.62	0.13	0 35
B130i	140+43.00	Curb	On Grade	0.19	0.19	0.00	0.00	0.00	10	5.05	4 51	0.09	0.35
2.001	110 10.00	Carb	Si Siddo	0.10	0.10	0.00	0.00	0.00		0.20		0.00	0.00

						INLE	ET C	ONF	IGUF	RAT	ION							
					Inlet	Inlet		Inlet	Inlet	Curb	Max	Max						Grate
				Inlet	Profile	Spread	Inlet	Curb	Curb	Dep.	Ponded	Ponded	Grate	Grate	Grate	Grate	Grate	Clog
Inlet ID	Station	Offset	T/C Elev.	Туре	Туре	Slope	Length	Dep.	Height	Width	Width	Depth	Туре	Length	Width	Area	Perimeter	Area
B20	135+98.33	-54.72	623.28	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B10	201+83.50	-36	621.98	Curb	Sag	0.02	20	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B3.2	209+73.63	34.04	619.38	Curb	Sag	0.02	5	0.21	0.52	2	13	0.58	n/a	n/a	n/a	n/a	n/a	n/a
B100	136+10.00	60.1	623 58	Curb	Sad	0.02	10	0.25	0.5	15	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B110	136+89.50	125.03	622.00	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
DIIO	150103.50	120.00	022.10	Cuib	Jay	0.02	10	0.25	0.5	1.5	12	0.24	IVa	IVa	11/a	IVa	11/a	11/a
B145	200+33.50	54.7	623.34	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B140	137+05.00	-107	621.79	Curb	Sag	0.02	10	0.25	0.5	1.5	12	0.24	n/a	n/a	n/a	n/a	n/a	n/a
B120i	140+88.00	15.75	623.14	Curb	On Grade	0.02	10	0.04	0.58	2	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a
B130i	140+43.00	-12	624.00	Curb	On Grade	0.02	10	0.04	0.58	2	12	0.4	n/a	n/a	n/a	n/a	n/a	n/a



PLOTTED BY: ivette PLOTTED SCALE: 1:100 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:36:59 AM PLOTTED ON: 6/24/2020 @ 11:36:59 AM DESIGN FILENAME: Z:NProjects/Watson Road/Drai

¢



HY - 8 Culvert Analysis Report

Table 1.1 - Summary of Culvert Flows at Crossing: Existing

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	Existing Discharge (cfs)	Roadway Discharge (cfs)	Iterations
622.7	5 year	65	62.82	0	100
622.71	10 year	76	62.96	12.73	7
622.71	100 year	121	63.11	56.71	3
622.7	Overtopping	62.87	62.87	0	Overtopping

Table 1.2 - Summary of Culvert Flows at Crossing: Proposed

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	Proposed Culvert Discharge (cfs)	Roadway Discharge (cfs)	Iterations
622.12	5 year	58.72	58.72	0	1
622.5	10 year	70.39	70.39	0	1
623.1	100 year	112.41	86.63	25.51	7
622.77	Overtopping	77.9	77.9	0	Overtopping

Table 2.1 - Culvert Summary Table: Existing

					-							
Disobargo	Total	Culvert	Headwater	Inlet	Outlet		Normal Critical		Outlot	Tailwator	Outlet	Tailwater
Namos	Discharge	Discharge	Elevation	Control	Control	Flow Type	Dopth (ft)	Dopth (ft)	Dopth (ff)	Dopth (ft)	Velocity	Velocity
Names	(cfs)	(cfs)	(ft)	Depth (ft)	Depth (ft)			Deptil (it)	Deptil (it)	Deptit (it)	(ft/s)	(ft/s)
5 year	65	62.82	622.7	3.089	3.32	4-FFf	2	1.638	2	1.605	6.666	2.718
10 year	76	62.96	622.71	3.096	3.439	4-FFf	2	1.64	2	1.716	6.68	2.832
100 year	121	63.11	622.71	3.104	3.825	4-FFf	2	1.641	2	2.095	6.696	3.195

Table 2.2 - Culvert Summary Table: Proposed Culvert

Disebargo	Total	Culvert	Headwater	Inlet	Outlet		Normal	Critical	Outlot	Tailwator	Outlet	Tailwater
Namos	Discharge	Discharge	Elevation	Control	Control	Flow Type	Dopth (ft)	Dopth (ft) Dopth (ft)		Dopth (ft)	Velocity	Velocity
Names	(cfs)	(cfs)	(ft)	Depth (ft)	Depth (ft)		Depth (it)	Deptil (it)	Deptil (it)	Depth (it)	(ft/s)	(ft/s)
5 year	58.72	58.72	622.12	2.318	1.34	5-S2n	1.15	1.438	1.19	0.659	8.223	5.355
10 year	70.39	70.39	622.5	2.704	2.064	5-S2n	1.314	1.623	1.361	0.733	8.618	5.703
100 year	112.41	86.63	623.1	3.3	2.777	5-S2n	1.534	1.864	1.589	0.96	9.086	6.686

Straight Culvert Inlet Elevation (invert): 619.40 ft, Outlet Elevation (invert): 618.90 ft Culvert Length: 80.00 ft, Culvert Slope: 0.0063

Site Data - Existing

Site Data Option: Culvert Invert Data Inlet Station: 0.00 ft Inlet Elevation: 619.40 ft Outlet Station: 80.00 ft Outlet Elevation: 618.90 ft Number of Barrels: 3

Culvert Data Summary - Existing

Barrel Shape: Circular Barrel Diameter: 2.00 ft Barrel Material: Concrete Embedment: 0.00 in Barrel Manning's n: 0.0120 Culvert Type: Straight Inlet Configuration: Square Edge with Headwall Inlet Depression: None Straight Culvert let Elevation (invert): 619.80 ft, Outlet Elevation (invert): 618.90 ft Culvert Length: 98.83 ft, Culvert Slope: 0.0091

Site Data - Proposed Culvert Site Data Option: Culvert Invert Data Inlet Station: 0.00 ft Inlet Elevation: 619.80 ft Outlet Station: 98.83 ft Outlet Elevation: 618.90 ft Number of Barrels: 2

Culvert Data Summary - Proposed Barrel Shape: Concrete Box Barrel Span: 3.00 ft Barrel Rise: 2.00 ft Barrel Material: Concrete Embedment: 0.00 in Barrel Manning's n: 0.0130 Culvert Type: Straight Inlet Configuration: 1:1 Bevel (45° flare) Wingwall

Inlet Depression: None

HY - 8 Culvert Analysis Report

Table 3 - Downstream Channel Rating Curve (Crossing)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)	Velocity (ft/s)	Shear (psf)	1
58.72	619.56	0.66	5.36	0.19	
70.39	619.63	0.73	5.7	0.21	
112.41	619.86	0.96	6.69	0.27	

Tailwater Channel Data - Proposed

Tailwater Channel Option:Irregular ChannelChannel Slope:0.0045

User Defined Channel Cross-Section:						
Coord No.	Station (ft)	Elevation (ft)	Manning's n			
1	0	621.98	0.013			
2	11.55	618.9	0.013			
3	26.26	618.9	0.013			
4	31.87	621.6	0.013			

Roadway Data for Crossing: Proposed

Roadway Profile Shape: Irregular Roadway Shape (coordinates) Irregular Roadway Cross-Section:

-	•		
	Coord No.	Station (ft)	Elevation (ft)
	0	11000	623.68
	1	11040	623.61
	2	11110	622.77
	3	11180	623.01
Roadway Surface:	Paved		

Roadway Top Width: 54.00 ft





NOTES:

- 1. CROSS CULVERTS ARE DESIGNED FOR 10-YEAR STORM EVENT.
- 2. CULVERT HYDRAULIC ANALYSIS PERFOMED IN HY-8 SOFTWARE.



		PROP 2 - 3'X2' SBC SEE SHEET 149 PLAN & PROFILE 110+00 PJB-A10, 5'X5' STA 110+72.67 O/S 35.75' RT	CI-A STA O/S 10°C 11°C 111+00 57.71 LI CURB OPENING	HESIQUIO MARTINEZ, S VOLUME 7125, PG. 202, O 30, 2-CCO 5'X5' 26.00' LT OPENING	R. PROP WATER MAIN PROP GRASSY DITCH. SEE DITCH P&P SHT 152 PROP 121.00 LF 30" CAP EXISTIN 112.400 WATSON RD	E STA 113+00.00	CAP = CONC ARCH PIPE RCP = REINF PROPOSED STRUCT PROPOSED CUBB PROPOSED CUBB PROPOSED RIGHT OF PROPOSED
	NOTES: 1. FOR CURB INLETS STATION LOCATIONS AND OFFSETS ARE AT THE FACE OF CURB AND THE MIDPOINT OF THE INLET(S). THE CONTPOL POINTS ARE TO BE TAKEN AT	SEE SHEET 145 FOR CROSS SECTION 8.26 LF 3'X2' SBC Aout STA 110+72.67 O/S 46.51' RT	69.50 LF 3 69.50 LF 3 69.50 LF 3 69.50 LF 3 69.50 LF 3 69.50 LF 3	X2' SBC	UG-FELE 5'X5' Construction UG-FELE EXISTIN SEE SHEEI 145 FOR COSS SECTION HERRERA JOE EDDIE & ESTHER JOYCE VOL. 5322, PG. 1806		EXISTING GROUND @ CL OF PIPE PROPOSED GRADE @ CL OF PIPE PROPOSED GRADE @ CL OF PIPE CONCRETE COLLA DETAIL ON SHEET 1TEM DESCRIPTION 420 6002 CL A CONC (MISC) CY 462 6001 CONC BOX CULV (3 FT X 2 FT) LF 464 6034 RC PIPE (ARCH) (CL III)(DES 5) LF 465 6024 NLET (COMPL)(PCO)(5FT) EA .
	CONTROL POINTS ARE TO BE TAKEN AT						$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
	4. CONTRACTOR SHALL GROUT BOTTOM OF INLETS OR STRUCTURES TO ENSURE POSITIVE DRAINAGE. GROUTING AND INVERT SHAPING IS SUBSIDIARY TO RESPECTIVE STRUCTURE.		$\begin{array}{c} - \begin{array}{c} - \end{array} \\ - \bigg $				
	coadt/Drainage/M058LT	+ - 620 		2 (-) 0.20%			THE CONSULTANTS TO BE CONSULTA
Property 100 mining Property 100 mining<				+ - \			DRAINAGE PLAN AND PROFILI STORM SYSTEM "A
							BEGINNING OF PROJECT TO ST

PLAN	N VIEW LEGEND				
CI = CURB INLET CS = CURB SLOT CAP = CONC ARCH	DI = DROP INLET P.B = JUNCTION BOX PIPE RCP = REINF CONC PIPE PROPOSED STRUCTURE PROPOSED CURB EXISTING RIGHT OF WAY PROPOSED RIGHT OF WAY EXISTING EASEMENT EXIST FEATURES BARB WIRE FENCE UNDERGROUND TELE GAS LINE WATER LINE OVERHEAD ELECTRIC				
w W	UTILITY POLE WATER VALVE				
Ç,	FIRE HYDRANT TELEPHONE PEDESTAL				
EJB	ELECTRIC JUNCTION BOX				
PROFI	PULL BOX				
	10 YR EGL 10 YR HGL EXISTING GROUND @ CL OF PIPE PROPOSED GRADE @ CL OF PIPE CONCRETE COLLAR SEE DETAIL ON SHEET 160				
ESTIMATED QUANTITIES					
	PLAN CI = CURB INLET CS = CURB SLOT CAP = CONC ARCH UG TELE GAS W-X" ELEC PROFI				

ESTIMATED QUANTITIES							
ITEM	DESCRIPTION	UNIT	QTY				
420 6002	CL A CONC (MISC)	CY	4				
462 6001	CONC BOX CULV (3 FT X 2 FT)	LF	136				
464 6034	RC PIPE (ARCH) (CL III)(DES 5)	LF	121				
465 6009	JCTBOX (COML) (PJB) (5FTX5FT)	EA	1				
465 6024	NLET (COMPL)(PCO)(5FT)	EA	4				



pltcfg

				PLAN	VIEW LE	GEND		
11.50	8		CI = CURI CS = CUR CAP = COI UG TE GAS UG TE ELE ELB ELB ELB ELB ELB ELB ELB ELB EL		I VIEW LEI DI = PJB PIPE RCF PROPOSED PROPOSED EXISTING RI PROPOSED EXISTING RI PROPOSED EXISTING FI EXIST FEATI BARB WIRE UNDERGRO GAS LINE WATER LINE OVERHEAD UTILITY POL WATER VAL' FIRE HYDRA TELEPHONE ELECTRIC JI PULL BOX LE VIEW L 10 YR EGL EXISTING GI @ CL OF PIF PROPOSED @ CL OF PIF PROPOSED	GENU DROP INL DROP INL DROP INL DROP INL DROP INL DROP INL DROP INL STRUCTU STRUCTU CURB GHT OF W RIGHT OF SEMENT JRES FENCE UND TELE E ELECTRIC E VE NT PEDESTA JNCTION E COUND PE GRADE COLLAR S	ET ON BOX ONC PIP RE AY WAY	
RT					DETAIL ON S	SHEET 160		
		ESTIM	TED QU	ANTIT	IES			
	ITEM	DE	SCRIPTIC	ON		UNIT	QTY	
	420 6002 CL A	CONC (MIS	C)			CY	6	
	432 6007 RIPR	RAP (CONC)	CLC)			CY	28	
	464 6030 RC F	PIPE (ARCH)	(CL III)(DE	ES 3)		LF	392	
	464 6034 RC F	PIPE (ARCH)	(CL III)(DI	ES 5)		LF	57	
	465 6009 JCTE	BOX (COML)	(PJB) (5F	TX5F	Τ)	EA	1	
	465 6024 INLE	T (COMPL)(F	PCO)(5FT)		EA	4	
				-			-	_
		ŀ		-			+ -	—
I		-	NO DATE		REVISION	_	APPRO	VED
640	$ \vdash+$				GRAPHIC SCAL (IN FEET)	E		
I			25 12.5	0	25	50		75
I					41 - 50			
_	$ \perp$				Vert: 1" = 10			
 630			CARLOS R 125 SS/ON	S LUNA I	THE SEA DOCUMEN CARLO	AL APPEARIN NT WAS AUTI S LUNA III , P 6/24/2020	IG ON TH HORIZED .E. 12504:	IS BY 2
 			MA	ES	STAS	8122 DATA SAN ANTON (210) 366-1 TBPE No.: F TBPLS No.:	POINT DR., STI IIO, TX 78229 988 -333 10194506	E. 840

620

11550 IH 10 WEST, SUITE 395 SAN ANTONIO, TEXAS 78230-1037 TEL: (210) 641-9399 [FAX: (210) 641-644 TBPE REGISTRATION NO.: F2214 TBPLS REGISTRATION NO.: 100410-00 CEC WATSON ROAD DRAINAGE

PLAN AND PROFILE 610 STORM SYSTEM "A" STA 113+00.00 TO STA 117+00.00 SHEET 2 OF 4 Texas Department C 2017 of Transportation PLAN SH NO. EEDERAL AID PROJECT NO DIV.NO PROP INVERT 133 6 STATE DIST COUNTY ΤX SAT BEXAR CONT. SECT. JOB HIGHWAY / STREET 562 WATSON RD 0915 12



PLOTTED BY: ivette PLOTTED SCALE: 1:50 PEN TABLE: M058_pentbl:tbl PLOT DRIVER: WATSON_BW_PDF_CI PLOTTED ON: 6/24/2020 @ 11:37:29

PLA	N VIEW LEGEND
CI = CURB INLET	DI = DROP INLET
CS = CURB SLOT	PJB = JUNCTION BOX
	PROPOSED STRUCTURE
	PROPOSED CURB
	EXISTING RIGHT OF WAY
	PROPOSED RIGHT OF WAY
	EXISTING EASEMENT
	EXIST FEATURES
——————————————————————————————————————	BARB WIRE FENCE
	UNDERGROUND TELE
— GAS —	GAS LINE
— W - X" —	WATER LINE
— ELEC —	OVERHEAD ELECTRIC
J J	UTILITY POLE
wv M	WATER VALVE
Ç.	FIRE HYDRANT
Ī	TELEPHONE PEDESTAL
EJB 🖾	ELECTRIC JUNCTION BOX
PBX	PULL BOX
PROF	LE VIEW LEGEND
	10 YR EGL
	10 YR HGL
	EXISTING GROUND
	@ CL OF PIPF
	CONCRETE COLLAR SEE
	DETAIL ON SHEET 160

CI-A65, TY C1 STA 117+11.50 O/S 6.25' RT 10' OPENING

ROV

. B

K

	ESTIMATED QUANTITIES		
ITEM	DESCRIPTION	UNIT	QTY
420 6002	CL A CONC (MISC)	CY	3
464 6029	RC PIPE (ARCH)(CL III)(DES 3)	LF	309
465 6006	JCTBOX (COML) (PJB) (4FTX4FT)	EA	1
465 6176	INLET (COMPL)(CURB)(TY C1)	EA	1
465 6024	INLET (COMPL)(PCO)(5FT)	EA	2

		-	-			-
		-	-			
	- NO	DATE	г <u>-</u> F	REVISION		APPROVED
			GRAF	PHIC SCALE		
			(1)	N FEET)		
	25	12.5	0	25	50	75
			. 1	" = 50'		
			Ver	t: 1" = 10'		
30^{-} $-\frac{1}{1}$ $ -\frac{1}{1}$ $ -\frac{1}{1}$ $ -\frac{1}{1}$ $ -$	"Thinking"	CARLOS 0 125	SLUNA III	THE SEAL A DOCUMENT V CARLOS LU	PPEARING VAS AUTH JNA III, P.E	S ON THIS ORIZED BY . 125042
20		MA	ES	TAS	8122 DATAPO SAN ANTONIC (210) 366-198 TBPE No.: F-3: TBPLS No.: 10	INT DR., STE. 840), TX 78229 8 33 194506
	CIVI		EC ING CONSULTANTS DON DURDEN, INC.	11550 H SAN ANTON TEL: (210) 641 1 TBPE REGIS TBPLS REGIS	10 WEST, SU IIO, TEXAS 7 9999 FAX: (2 STRATION N TRATION NC	JITE 395 8230-1037 210) 641-6440 O.: F-2214).: 100410-00
			WATS	ON ROA	٨D	
			DRA			
					ILE	
10				OVOTEM	"^"	
			STURM	SISIEM	А	
		STA	A 113+00.00	TO STA 1	17+00.0	00
i i			SHE	<u>ET 3 OF 4</u>		
				9		
		© 2017	7	Texas of Trai	Depart nsporta	ment ation
	F	ED RD. DIV NO	FEDERA	L AID PROJECT	NO.	PLAN SHT NO
RT I		6				134
KED I		STATE	DIST.		COUNTY	
A N N N N N N N N N N N N N N N N N N N		TX	SAT		BEXAR	
)		CONT.	SECT.	JOB	HIGHWA	Y / STREET
	(0915	12	562	WATS	SON RD



Ð

PLAN VIEW LEGEND BINLET DI = DROP INLET

CI = CURB INLET CS = CURB SLOT CAP = CONC ARCH

CAP = CONC ARCH	PIPE RCP = REINF CONC PIPE
	PROPOSED STRUCTURE
	PROPOSED CURB
	EXISTING RIGHT OF WAY
	PROPOSED RIGHT OF WAY
	EXISTING EASEMENT
	EXIST FEATURES
—— × -	BARB WIRE FENCE
	UNDERGROUND TELE
— GAS —	GAS LINE
— W - X" —	WATER LINE
— ELEC —	OVERHEAD ELECTRIC
°O	UTILITY POLE
ŴV	WATER VALVE
ĴÇ,	FIRE HYDRANT
Ī	TELEPHONE PEDESTAL
EJB	ELECTRIC JUNCTION BOX
P8x	PULL BOX
PROF	LE VIEW LEGEND
	10 YR EGL
	10 YR HGL
	EXISTING GROUND
	@ CL OF PIPE
	CONCRETE COLLAR SEE
	DETAIL ON SHEET 160

ESTIMATED QUANTITIES						
ITEM	DESCRIPTION	UNIT	QTY			
420 6002	CL A CONC (MISC)	CY	4			
432 6007	RIPRAP (CONC)(CL C)	CY	26			
464 6030	REC PIPE (ARCH) (CL III)(DES 3)	LF	144			
465 6006	JCTBOX (COML) (PJB) (4FTX4FT)	EA	2			
465 6054	INLET (COMPL)(PSL)(SL)(3FTX3F⊺)	ĒA	1			

		-			-
		-			-
	NO DATE				APPROVED
+ +		GRAF (I	PHIC SCALE		
	25 12.5	0	25	50	75
! L		1	" = 50'		
		ver	t: 1° = 10°		
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	CARLOS DATE C		THE SEAL A DOCUMENT \ CARLOS L	PPEARING WAS AUTHO UNA III, P.E	ON THIS DRIZED BY 125042
· +	XRSSION	AL ENGINE		6/24/2020	
	MA	ES	ras	8122 DATAPOI SAN ANTONIO (210) 366-1988 TBPE No.: F-33 TBPLS No.: 103	NT DR., STE. 840 , TX 78229 3 3 94506
		EC	11550 H SAN ANTON TEL: (210) 641 TBPE REGI TBPLS REGIS	10 WEST, SU NO, TEXAS 78 9999 FAX: (2 STRATION NO TRATION NO.	ITE 395 3230-1037 10) 641-6440 D.: F-2214 : 100410-00
		WATS	ON ROA	٨D	
		DR/	AINAGE		
·		PLAN AI	ND PROF	ILE	
		STORM	SYSTEM	"A"	
	STA	A 117+00.00	TO STA 1	21+50.0	0
		SHE	ET 4 OF 4		
			<u></u>		
	© 2017	7	Texas of Tra	Departı nsporta	ment tion
	FED RD. DIV.NO.	FEDERA	L AID PROJECT	ΓNO.	PLAN SHT NO.
	6				135
NAGI NAGI					
a. .		SAL	IOB		STREET
	0915	12	562	WATS	
		14	1 002		



			DI ANU ///			
			PLAN VI	<u>=WLEGE</u>		
	1	CI = CURI	B INLET	DI = DI	ROP INLE	T
		CS = CUR		PJB =		
	L .					
	$\langle \rho \rangle$					-
						v
	a second s					
						VAT
	(b)		EXIS			
\frown	Y		EXIS	STFEATUR	ES	
\asymp			X - BAR	B WIRE FE	NCE	
<u> </u>	×.	—UG TE	ELE UND	DERGROUN	D TELE	
\bigcirc	LINCK	— GAS	s — Gas	LINE		
\overline{a}		— W - 2	X" — WAT	FER LINE		
Ť		ELE	C OVE	RHEAD EL	ECTRIC	
T.		0	5 UTIL	ITY POLE		
<u> </u>		WV				
\mathbf{N}		\bowtie	WAT	FER VALVE		
<u> </u>		0	FIRE		-	
1		ريد 1	тен			
4		E IP	IEL		EDESTAL	
			ELE	CTRIC JUN	CTION BO	XC
$\hat{\boldsymbol{\Omega}}$		PBX	PH			
•••						
		ł	<u>PROFILE \</u>	/IEW LEQ	<u>jEND</u>	
-			- <u> </u>	'R EGL		
			— 10 Y	'R HGL		
			EXIS	STING GRO	UND	
Ŧ			@ C	L OF PIPE		
			PRC		RADE	
\mathbf{O}			0.0			_
			DET	ALL ON SHE	FT 160	=
-	ECTI					
1	ESTI		JANTITIES	`		
2	ITEM D	ESCRIPT	ON		UNIT	QTY
	420 6002 CL A CONC (MI	SC)			CY	6
	432 6007 RIPRAP (CONC				CY	11
					1 5	202
	404 0003 REC FIFE (CL I	<u>II)(24 IIN)</u>				293
	464 6030 RC PIPE (ARCH	H)(CL III)(D	ES 3)		LF	94
	465 6024 INLET (COMPL))(PCO)(5F	T)		EA	4
	465 6054 INLET (COMPL)	(PSL)(SL)	(3FTX3FT))	EA	2
	465 6013 INLET (COMPL	(PCO)(3E	T)		EA	2
		<u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>	• /			
		· · · · · · · · · · · · · · · · · · ·				
			-			-
			-			-
		NO DATE	- F	REVISION		- APPROVED
		- · · · · · · · · · · · · · · · · · · ·	GRAP	HIC SCALE		
40			11)	N FEET)		
		25 12.5	0	25	50	75
			1	" = 50'		
			Vert	: 1" = 10'		
			M11.			
		ATEC	F TEL			
				THE SEAL A	PPEARING	ON THIS
30	·	2×/ 1	X ↓ ¥ ½	DOCUMENT \	WAS AUTH	DRIZED BY
50		CARLOS		CARLOST		105010
			S LUNA III 🌛	0/11/20012	UNA III, P.E	. 125042
		मू. 125	SLUNA III	0,112002	UNA III, P.E	. 125042
		В. 125 Д. 125	042		0NA III, P.E	. 125042
		90, 125 90, 125 55, 125 55, 125	S LUNA III 1042 Stranger INSE CONTRACTOR		0NA III, P.E	. 125042
		3, 125 3,	S LUNA III		0/24/2020	. 125042
		30, 125 70, 125 70, 125 70, 125	NSEP ON		8122 DATAPO	NT DR., STE 840
		125 Solution			UNA III, P.E 6/24/2020 8122 DATAPO SAN ANTONIO (210) 366-198	NT DR., STE. 840 TX 78229
		125 Soloris			0000 0000 0000 0000 0000 0000 0000 0000 0000	. 125042
		125 MA		TAS	8122 DATAPO SAN ANTONIO (210) 366-198 TBPE No.: 10	. 125042
		MA			6/24/2020 6/24/2020 8122 DATAPO SAN ANTONIC (210) 366-198 TBPE No.: 10 TBPLS No.: 10 10 WEST, SU	NT DR., STE. 840 TX 78229 394506 ITE 395 2304-1037
				TAS 11550 IH SAN ANTON TEL: (210) 641-	8122 DATAPO SAN ANTONIC (210) 366-198 TBPE No.: F43 TBPLS No.: 10 10 WEST, SL IO, TEXAS 7 9999 FAX: (2	NT DR., STE. 840 17 78229 18 19 19 19 19 10 10 10 10 10 10 10 10 10 10
20			ELUNA III 1042 / PE 14 EST EC 19500 DUDUETANTÉE	11550 H SAN ANTON TEL: (210) 641 TBPE REGIS	8122 DATAPO S/24/2020 8122 DATAPO SAN ANTONIO (210) 366-198 TBPE No.: F-33 TBPE NO.: F-34 TBPE N	NT DR. STE. 840 TX 78229 33 194506 ITE 395 3230-1037 10) 641-6440 D.: F-2214 -10040.00
				TAS 11550 H SAN ANTON TEL: (210) 641- TBPE REGI TBPLS REGIS	8122 DATAPO 5/24/2020 8122 DATAPO 5AN ANTONIC (210) 36-138 178PL No. 1-33 178PLS No. 1-33 10 WEST, SL 100, TEXAS 7 9999 [FAX: (2 STRATION NO TRATION NO	NT DA., 57E 840 107 5329 3 3 194506 ITE 395 200-1037 100 641-6440 2): F-2214 : 100410-00
				11550 H SAN ANTON TEL: (210) (641 TBPE REGI TBPLS REGIS ON ROA	3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24 1/2/24 1/2/24 1/2/24 1/2/24 1/2/24 1/24	NT DR., STE. 840 NT DR., STE. 840 TR. 78229 394506 ITE 395 3230-1037 10) 641-640 : 100410-00
				TASO IH SAN ANTON TEL: (2/10) 641- TBPLS REGIS ON ROA ANAGE	3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 1/2/24/202 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/20 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24/2 1/2/24 1/2/24 1/2/24 1/24/2 1/24/	NT DR. STE. 840 TV 78229 3 3 94506 IEE 3956 IEE 39566 IEE 39566 IEE 39566 IEE 39566 IEE 39566 I
				TASO IH SAN ANTON TEL: (2/10) 641- TBPLS REGIS ON ROA AINAGE	3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 10 10 WEST, SL 10, TEXAS 7, SL 10	NT DR. STE. 840 TV 78229 194506 ITE 395 2320-1037 10) 641-6440 D. F-2214 : 100410-00
 20 			EUNA III 042 NS EEST EC NB CON BUBULTANTS WATSO DRA PLAN AN	TASS Internet State SAN ANTO TEL: (210) 641- TBPE REGIS TBPLS REGIS ON ROA AINAGE ND PROF	3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 10 USAN ANTONIO 10 WEST, SL 10/0, TEXAS 7, SP 3/2999 IFAX: (3/25 1/25 1/25 1/25 1/25 1/25 1/25	NT DR. STE 840 TX 78229 33 34506 ITE 395 2320-1037 10) 641-6440 .: F-2214 : 100410-00
 20 			EUNA III 042 NS EC NS CONSULTANTS WATS DRA PLAN AN STORM	11550 IH SAN ANTO TEL: (210) 641 TBPLS REGIS ON ROA NNAGE ND PROF SYSTEM	3/24/2020 3/24/2020 3/24/2020 3/24/2020 1/2/10/36-13 1/2/10/36-13 1/2/10/36-13 1/2/10/36-13 1/2/10/36-13 1/2/10/36-13 1/2/10/36-14	NT DP, STE 840 TV 78229 3 94505 TE 395 200-1037 10641-6440 .: F-2214 : 100410-00
 20 10				11550 IH SAN ANTON TEL: (210) 641 TBPE REGIS TBPLS REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1	3/24/2020 3/24/2020 3/24/2020 3/24/2020 2/10/36-18 178/2 No. F-3 178/2 No	NT DK, STE, B40 TX 78229 3 3 3 3 3 3 3 3 3 3 3 3 3
 20 10			EUNA III OA2 NS ECONSULTANTS RECONSULTANTS WATSO DRA PLAN AN STORM	11550 H SAN ANTON TEL: (210) 641 TBPLS REGIS TBPLS REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1	3/24/2020 3/24/2020 3/24/2020 3/24/2020 (210) 36-134 1/210 36-134 1/210 36-134 1/210 36-134 1/210 36-134 1/210 36-134 1/210 36-134 1/210 36-134 1/210 36-134 1/210 1/	NT DR. STE 840 NT DR. STE 840
 20 10			EUNA III 042 NS ECONSULTANTS RECONSULTANTS ECONSULTANTS ECONSULTANTS NS ECONSU	TASSO H SAN ANTON TEL: (2/0) 641- TBPE REGI TBPLS REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9	3/24/2020 3/24/2020 3/24/2020 3/24/2020 (210) 3/6-198 178/2 No.1-83 178/2 No.1-83 178/2 No.1-83 178/2 No.1-83 178/2 No.1-83 100 VEST, SL 100 VEST	NT DR. STE. 840 TV 78229 3 3 3 194506 ITE 395 2320-1037 10) 641-6440 .: F-2214 .: 100410-00 0
 20 10			EUNA III 042 NS ECC NECONDUCTANTS	TALSO H SAN ANTON TEL: (210) 641- TBPE REGIS TBPLS REGIS TBPLS REGIS TBPLS REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9	8/22/04/2020 8/24/2020 8/24/2020 1/210/386-198	NT DR., STE, 840 TV 78229 33 34 35 35 35 35 35 35 35 35 35 35
			ELINA III OA2 VEST EC NECONDUCTANTS WATSO DRA PLAN AN STORM A 121+50.00 SHE	TASS 11550 H SAN ANTO TEL: (210) 641- TBPE REGIS TBPE REGIS TBPE REGIS TBPE REGIS TBPE REGIS TBPE REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9 Texas	ала III, P.E. 3/24/2020 3/24/2020 3/24/2020 3/20 / 10/6-199 TBPE No.: 10 10 WEST, SL UIO, TEXAS 7. 9999 [FAX: (3/25, 10/6-199 10 WEST, SL 0/0, 10/6-199 10 WES	NT DR. STE. 840 TX 78229 33 194506 ITE 395 2320-1037 10) 641-6440 D. :F-2214 : 100410-00 0 ment
				TASS 11550 IH SAN ANTO TEL: (210) 641- TBPLS REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9 Texas of Tray	3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 10 100 110	NT DR. STE 840 TV 78229 33 194506 ITE 395 2320-1037 10) 641-6440 D: F-2214 : 100410-00 0 ment tion
			EUNA III OA2 AL EST EST EST MS CONSULTANTS DRA PLAN AN STORM A 121+50.00 SHE EEERA	11550 IH SAN ANTO TEL: (210) 641 TBPLS REGIS ON ROA NINAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9 Texas of Tra.	3/24/2020 3/24/2020 3/24/2020 3/24/2020 2/20 36-18 178/2	125042 NT DR. STE. 840 TV.78229 3939506 ПТЕ 395 2230-1037 10) 641-6440 .: F-2214 : 100410-00 0 ment tion PLANSHT.
			EUNA III DO42 DO42 NS EST EST NS CONSULTANTS DRA PLAN AN STORM A 121+50.00 SHE FEDERA	11550 IH SAN ANTON TEL: (210) 641 TBPE REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9 Texas of Trai LAID PROJECT	3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 10 WEST, SL 10 WEST, SL 9999 IFAX: (2) STRATION NO ND ILE "B" 26+00.0 Departing nsporta	NT DR. STE. 840 TV.78229 39506 TTE 395 2200-1037 10) 641-6440 .: F-2214 : 100410-00 0 ment tion TEON SHT. NO. 136
			EUNA III OA2 NS EST EST EST NS CONSULTANTS DRA PLAN AN STORM A 121+50.00 SHE FEDERA PLERA	11550 IH SAN ANTON TEL: (210) 641 TBPLS REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9 Texas of Tra L AID PROJECT	B12 DATANO 3/24/2020 3/24/2020 SAN ANTONIO (210) 365-187 TBFE No.: F33 TBFE No.: F33 TBFE No.: F33 TRATION NO AD TILE "B" 26+00.0 Depart. nsporta COUNTY	NT DR. STE 840 VT DR. STE 840 VT 28229 3 3 3 10) 641-6440 :100410-00 0 0 ment tion PLAN SHT NO.
 20 10			EUNA III O42 VEST EST EST WATSO WATSO DRA PLAN AN STORM A 121+50.00 SHE FEDERA DIST. SAT	TALSO H SANANTON TEL: (210) 641- TBPE REGI TBPE REGI TBPE REGI TBPE REGI TBPE REGI TBPE REGI TBPE REGIS TBPE REGIS TBPE REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9 Texas of Tra.	ала III, Р.е. ала ин, Р.е. ала интерести ала ин	NT DR. STE 840 TV 78229 3 3 3 194506 ITE 395 2200-1037 10) 641-6440 .: F-2214 .: 100410-00 0 ment tion PLAN SHT. NO. 136
 20 10 		CIVIL ENGINEERI CIVIL ENGINEER	ELUNA III OA2 SEC EC EC VATSO DRA PLAN AN STORM A 121+50.00 SHE FEDERA DIST. SAT STOT	TALSO IN SAN ANTO TEL: (210) 641- TBPE REGIS TBPLS REGIS ON ROA AINAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9 Texas of Trai L AID PROJECT 	3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 10 WEST, SL 10 WEST, SL WO, TEXAS 7. 9999 [FAX: STRATION NO AD ILLE "B" 26+00.0 Depart. nsporta FNO. COUNTY BEXARY	NT DE, STE, 840 TX 78229 33 194506 TTE 395 2320-1037 10) 641-640 0 0 ment tion PEAN SHT. NO. 136
 20 10 0	Image: state stat	CONT.	ELUNA III OA2 AL EST EST STORM A 121+50.00 SHE FEDERA DIST. SAT SECT. SEC. 12	11550 IH SAN ANTO TEL: (210) 641 TBPE REGIS ON ROA NNAGE ND PROF SYSTEM TO STA 1 ET 1 OF 9 Texas of Trai LAID PROJECT	BI22 DATAPO SATA ATTONIC SATA ANTONIC (210) 36-139 BI22 DATAPO SATA ANTONIC (210) 36-139 TIBE PACE TO WEST, SL (0, TEXAS 7: 9999 FAX; (0) STRATION NO TRATION NO ND BILE "B" 26+00.0 Depart. nsporta NO. COUNTY BEXAR HIGHWARD	NT DK. STE 840 TV 78229 3 3 3 3 3 3 3 3 3 3 3 3 3



				PI AN VI		i+NI)	
			CI = CUR	B INLET	DI = [DROP INLE	T
1			CS = CUF		PJB =	JUNCTIC	N BOX
			UAP = UU	PRC	DPOSED S		RE
				PRC	POSED C	URB	
			— -	- — EXI	STING RIG	HT OF WA	٩Y
			PROPOSED RIGHT OF \				
				- EXI	STING EAS	SEMENT	
Ŷ							
E			GA	s — GAS	S LINE		
NOR			— W-	X" — WA	TER LINE		
			— ELE	C — OVE	ERHEAD E	LECTRIC	
			\mathcal{T}	D UTI	ITY POLE		
			wv	WA.		F	
			~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	, 10A			
			\$ <del>\</del>	FIRI	= HYDRAN	IT	
			U F IB	IEL	EPHONE I	PEDESTAL	-
			8	ELE	CTRIC JU	NCTION B	ОХ
			PBX	PUL	L BOX		
				PROFILE \	/IFW I F	GEND	
				- <u> </u>	'R EGL		
				— 10 Y	'R HGL		
				EXI	STING GR	OUND	
				@(			
				PRC	L OF PIPE	RADE	
				ČŎ	<b>VCRETE</b> C	OLLAR SE	E
				DET	AIL ON SH	HEET 160	
		ESTIM	ATED QU	JANTITIES			
	ITEM	DE	SCRIPTI	ON		UNIT	QTY
	402 6001	TRENCH EXCA	VATION F	ROTECTIO	DN	LF	262
	420 6002	CL A CONC (MIS	SC)			CY	3
	432 6007	RIPRAP (CONC)	(CLC)			CY	6
	402 6002	REC PIPE (CL III	)(24 IN)			LF	132
	464 6007	REC PIPE (CL III	)(30 IN)			LF	209
	464 6008	REC PIPE (CL III	)(36 IN)			LF	53
	465 6024	INLET (COMPL)	(PCO)(5F	T)		EA	4
	465 6054			., (3FTX3FT)		FA	1
						_/ \	
1	1			-			
	1	1		-			-
	l I		· ·	-			
		 	NO DATE	- - -			APPROVED
    _ ·	   	     +	NO DATE	- - - - - - - - - - - - - - - - - - -	REVISION PHIC SCALE N FEET )		APPROVED
  -  -  -	   	     +	NO DATE	- - - - - - - - - - - - - - - - - - -	REVISION PHIC SCALE N FEET ) 25	50	APPROVED
	       	         	 NO DATE 25 12.5	- - GRAF (II 0	REVISION PHIC SCALE N FEET ) 25	50	APPROVED
			25 12.5	- - - - - - - - - - - - - - - - - - -	REVISION PHIC SCALE N FEET ) 25 ===================================	50	APPROVED
			 NO DATE	GRAF (II 0 1 Ver	REVISION PHIC SCALE N FEET ) 25 	50	APPROVED
			25 12.5	- - - - - - - - - - - - - - - - - - -	REVISION PHIC SCALE N FEET ) 25 	50	APPROVED
			25 12.5	GRAF GRAF (II 0 DF TR TR TR	REVISION PHIC SCALE N FEET ) 25 = = = = = = = 50' t: 1" = 10' THE SEAL		APPROVED 75
			NO DATE	GRAF GRAF (II 0 DF 76 to	REVISION PHIC SCALE N FEET ) 25 " = 50' t: 1" = 10' THE SEAL DOCUMENT	50 APPEARING	APPROVED 75 3 ON THIS IORIZED BY
			NO DATE	GRAF GRAF (II 0 DF 7645 5 LUNA III	REVISION PHIC SCALE N FEET ) 25 ===================================	50 APPEARING WAS AUTH LUNA III, P.6	APPROVED 75 3 ON THIS IORIZED BY E. 125042
			NO DATE	GRAF GRAF (1) 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	REVISION HIC SCALE N FEET ) 25 " = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS	50 APPEARING WAS AUTH LUNA III, P.1	APPROVED 75 3 ON THIS IORIZED BY 5. 125042
			25 12.5 CARLOS		REVISION HIC SCALE N FEET ) 25 " = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS	50 APPEARING WAS AUTH LUNA III, P.1 6/24/2020	APPROVED 75 3 ON THIS IORIZED BY 5. 125042
			25 12.5 CARLOS CARLOS		REVISION PHIC SCALE N FEET ) 25 " = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS	50 APPEARING WAS AUTH LUNA III, P.I 6/24/2020	3 ON THIS IORIZED BY 5. 125042
			25 12.5 CARLOS	GRAF GRAF (1) 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	REVISION PHIC SCALE N FEET ) 25 = = = = = = = = = = = = = = = = = = =	50 APPEARING WAS AUTH LUNA III, P.I 6/24/2020	APPROVED 75 3 ON THIS IORIZED BY 5. 125042
			25 12.5 CARLOS		REVISION PHIC SCALE N FEET ) 25 = = = = = = = = = = = = =	50 APPEARINO WAS AUTH LUNA III, P.I 6/24/2020 8132 A01496	APPROVED 75 3 ON THIS IORIZED BY 5. 125042
			25 12.5 CARLOS		REVISION PHIC SCALE N FEET ) 25 = = = = = = = = = = = = = = = = = = =	50 50 50 50 50 50 50 50 50 50	3 ON THIS IORIZED BY 2. 125042
			25 12.5 CARLOS 125 125 125 125 125 125 125 125		REVISION PHIC SCALE N FEET ) 25 = = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS	50 APPEARINN WAS AUTH LUNA III, P.1 6/24/2020 100 AUTH 100 A	3 ON THIS IORIZED BY E. 125042
					REVISION PHIC SCALE N FEET ) 25 == 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS	50 50 50 50 50 50 50 50 50 50 50 50 50 5	3 ON THIS ORIZED BY 5. 125042
					REVISION PHIC SCALE N FEET ) 25 1 = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS 11550 SAN ANT TEL: (210)64 TAPE FE	50 50 50 50 50 50 50 50 50 50 50 50 50 5	APPROVED APPROVED 75 3 ON THIS ONIZED BY 5. 125042 2017 08, 57E 540 0, 17 78229 83 31 3134506 UITE 395 8220-1037 210) 641 5440 (0, F-2714
					REVISION PHIC SCALE N FEET ) 25 = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS 11550 SAN ANT TEL: (210) 64 TEPER FRE TBPLS REG	50 50 50 50 50 50 50 50 50 50 50 6/24/2020 6/24/2020 6/24/2020 6/24/2020 6/24/2020 6/24/2020 50 78 50 50 50 6/24/2020 6/24/2020 6/24/2020 6/24/2020 50 50 50 50 50 50 50 50 50 50 50 50 50	3 ON THIS ORIZED BY 5. 125042 2017 78229 88 90194506 2017 78229 88 90194506 2017 78229 88 90194506 2017 78229 88 90194506 2017 78229 88 90194506 2017 7829 88 90194506 2017 782 2019 782 2019 785 2019 785 2019 785 785 785 785 785 785 785 7
					REVISION HIC SCALE N FEET ) 25 1 = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS 11550 SAN ANT TEL: (210) 64 TEPE RES TBPLS RES ON RO	50 50 50 50 50 50 50 50 50 50 50 50 50 5	3 ON THIS ORIZED BY 5. 125042 2017 782 2017 7822 2017 782 2017 782
					REVISION HIC SCALE N FEET ) 25 1 = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS 11550 SAN ANT TEL: (210) 64 TBPLS REG ON RO ANNAGE	50 50 WAS AUTH LUNA III, P. 1 6/24/2020 H 10 WEST, S DNO, TEXAS SERTATION N ISTRATION NI AD	3 ON THIS IORIZED BY 5. 125042 DINT DR, STE 840 D, TX 78229 88 93194506 UITE 395 88230-1037 210) 641,6440 D, 1: F0241 D, 1:04410-00
					REVISION HIC SCALE N FEET ) 25 1 = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS 11550 SAN ANT TEL: (210) 64 TEL: (210) 74 TEL: (210) 74 TEL: (210) 74 TEL: (210)	50 50 50 50 50 50 50 50 50 50	APPROVED APPROVED 75 75 75 75 75 75 75 75 75 75
					REVISION HIC SCALE N FEET ) 25 1 = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS 11550 SAN ANT TEL: (20)64 TBPL REG ON RO AINAGE ND PRO SYSTE'	50 50 50 50 50 50 50 50 50 50	APPROVED APPROVED 75 75 75 75 75 75 75 75 75 75
				SLUNA III SLUNA III SLUNA III SUUNA	REVISION HIC SCALE N FEET ) 25 1 = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS 11550 SANANT TEL: (210) 64 TBPLS REG ON RO AINAGE ND PRO SYSTEM	50 50 50 50 50 50 50 50 50 50	APPROVED APPROVED 75 75 75 75 75 75 75 75 75 75
				Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consultants Consu	REVISION HIC SCALE N FEET ) 25 1 = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS 11550 SANANT TEL: (210) BA TBPLS REG SANANT TEL: (210) BA TBPLS REG ON RO AINAGE ND PRO SYSTEM TO STA	50 50 50 50 50 50 50 50 50 50	APPROVED APPROVED 75 3 ON THIS IORIZED BY 5. 125042 DITE 395 833 3195506 UITE 395 833 195506 UITE 395 837 210) 641 6440 (0. F-2214 2. 100410-00 D0
			CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CA	GRAF (III) GRAF (III) Ver S LUNA III 0042 S LUNA III 0042 S LUNA III 0042 S LUNA III 0042 S LUNA III 0042 S LUNA III 0042 S LUNA III S LUNA III	THE SEAL SALEN THE SEAL THE SEAL CARLOS THE SEAL DOCUMENT CARLOS 11550 SANANT TEL: (210) 64 TBPLS REG ON RO AINAGE ND PRO SYSTEM TO STA FT 2 0 F 9	50 50 50 50 50 50 50 50 50 50	APPROVED APPROVED 75 3 ON THIS ORIZED BY 5. 125042 2007 2100 641-6440 10.: F-2214 2100 641-6440 10.: F-2214 2100 641-6440 210 641-
			LIST	GRAF (III) GRAF (III) O S LUNA III S LUNA II S LUNA III S LUNA III S LUNA III S LUNA III	THE SEAL SALE N FEET ) 25 1 = 50' t: 1" = 10' THE SEAL DOCUMENT CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS 11550 CARLOS CARLOS 11550 CARLOS CARLOS 11550 CARLOS CARLOS 11550 CARLOS CARLOS CARLOS 11550 CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS CARLOS C	50 4 PPEARINN WAS AUTH- IUNA III, P.I 6/24/2020 8 322 DATARA 6/24/2020 8 322 DATARA 19999   FAX: 1 30999   FAX: 3 GSTRATION N STRATION N FILE M "B" 1 30+00.0	APPROVED APPROVED 75 3 ON THIS ORIZED BY 5. 125042 115506 UITE 395 78230-1037 7210 641-6440 10. F-2214 2.100410-00 D0
					THE SEAL SAN ANT THE SEAL OCCUMENT THE SEAL OCCUMENT CARLOS 11550 SAN ANT TEL: (210) 64 TBPLS REG ON RO AINAGE ND PRO SYSTEM TO STA ET 2 OF 9 Texas	50 50 50 50 50 50 50 50 50 50	APPROVED APPROVED 75 3 ON THIS ORIZED BY 5 125042 115506 UTT 395 78230-1037 78230-1037 78230-1037 78230-1037 78230-1037 10641-6440 10: F-2214 3: 10641-6440 10: F-2214 3: 10641-6440 10: F-2214 3: 10641-6400 0: F-2214 3: 10641-6400 0: F-2214 1: 10641-6400 0: 10640-6400 0: 10640-6400
				Construction of the second sec	THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL DOCUMENT CARLOS THE SEAL DOCUMENT CARLOS THE SEAL THE SEAL TEPE REG TEPE REG	50 50 50 50 50 50 50 50 50 50	APPROVED APPROVED 75 3 ON THIS ORIZED BY 5 125042 115706 115706 125042 115706 125042 115706 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042 125042
				GRAF GRAF (II Ver CF TE SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA SILUNA	THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL CARLOS THE SEAL TO SAN ANT TEL: (210) BA TEL: (210)	50 50 50 50 50 50 50 50 50 50	APPROVED           APPROVED           75           SON THIS           ORIZED BY           E. 125042           WH DR. STE. 640           Strate           Strate           B139506           UITE 395           76230-1037           12320-1037           12320-1037           12320-1037           D10 641-6440           D20           D0           D0           D0
				GRAF GRAF (II Ver DF 72-30 SILUNA III SOLUNA II SOLUNA II SO	THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL TO SAN ANT TEL: (210) BAN TEL: (210) BAN TE	50 APPEARING WAS AUTH LUNA III, P.I 6/24/2020 BIJ2 DATAM G/24/2020 BIJ2 DATAM FILE M "B" 130+00.0 CT NO.	APPROVED           APPROVED           75           SON THIS           ORIZED BY           E. 125042           MIT DR. STE. 640           SB           S1239           S1239           S1239           S1239           S1230-1037           ID 0641-6440           ID: F2214           D: 100410-00           D0           Construction           D10           APPROVED           D10           APPROVED           D10
		₩	25 12.5 25 12.5 CARLOS CARLOS CARLOS CIVIL ENGINEER CIVIL ENGINEER CIVIL ENGINEER CIVIL ENGINEER CIVIL ENGINEER	GRAF GRAF (II Ver DE 72 SILUNA III SILUNA II SILUNA II SI	THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL TO STA TEL: (210 MENT TEL: (210 MENT	50 50 50 50 50 50 50 50 50 50	APPROVED           APPROVED           75           SON THIS           IORIZED BY           E. 125042           WT PR. STE. 640           SS 301           SS 3134506           UITE 395           SS 1230-1037           7210) 641-5440           D.: 100410-00           D0           Constraint           APPROVED           THAN STE. 100410-00           D0           Constraint           APPROVED
		PROP		GRAF GRAF (1) Ver St LUNA III SO42 St LUNA III ST	THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL THE SEAL TO STA TEL: (210) EA TBPLS REG ON RO AINAGE ND PRO SYSTEM TO STA ET 2 OF 9 Texas of Tra L AID PROJE	50 50 50 50 50 50 50 50 50 50	Image: Constraint of the second sec
		PROP       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       - <t< th=""><th></th><th>INSTORMA ICCONSULTANTS INSTORMA ICCONSULTANTS INSTORMA ICCONSULTANTS INSTORMA ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTAN</th><th>REVISION HIC SCALE N FEET ) 25 15 15 15 15 15 15 15 15 15 1</th><th>50 30 30 30 30 30 30 30 30 30 3</th><th>APPROVED           APPROVED           75           SON THIS           IORIZED BY           SONZZED BY           1333           1354505           UITE 395           78230-1037           210.641.6440           D.110410-00           DO           Construction           DO           Construction           137           Y STREET</th></t<>		INSTORMA ICCONSULTANTS INSTORMA ICCONSULTANTS INSTORMA ICCONSULTANTS INSTORMA ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTANTS ICCONSULTAN	REVISION HIC SCALE N FEET ) 25 15 15 15 15 15 15 15 15 15 1	50 30 30 30 30 30 30 30 30 30 3	APPROVED           APPROVED           75           SON THIS           IORIZED BY           SONZZED BY           1333           1354505           UITE 395           78230-1037           210.641.6440           D.110410-00           DO           Construction           DO           Construction           137           Y STREET



PLAN	VIEW LEGEND
CI = CURB INLET	DI = DROP INLET
CS = CURB SLOT	PJB = JUNCTION BOX
	PROPOSED STRUCTURE
	PROPOSED CURB
	EXISTING RIGHT OF WAY
	PROPOSED RIGHT OF WAY
	EXISTING EASEMENT
	EXIST FEATURES
X -	
GAG WX"	WATER LINE
- ELEC -	OVERHEAD ELECTRIC
	UTILITY POLE
WV	
$\bowtie$	WATER VALVE
ŞÇ.	FIRE HYDRANT
Ī	TELEPHONE PEDESTAL
EJB	ELECTRIC JUNCTION BOX
PBx	
PROFI	
	10 YR EGL
	10 YR HGL
	EXISTING GROUND
	@ CL OF PIPE
	CONCRETE COLLAR SEE
	DETAIL ON SHEET 160
ESTIMATED QUANTIT	IES

ESTIMATED QUANTITIES						
ITEM	DESCRIPTION	UNIT	QTY			
402 6001	TRENCH EXCAVATION PROTECTION	LF	443			
420 6002	CL A CONC (MISC)	CY	4			
464 6005	REC PIPE (CL III)(24 IN)	LF	65			
464 6008	REC PIPE (CL III)(36 IN)	LF	378			
465 6024	INLET (COMPL)(PCO)(5FT)	EA	4			
465 6013	INLET (COMPL)(PCO)(3FT)	EA	2			

	-	-	-			-
	-	-	-			-
	NO	DATE	-	REVISION		- APPROVED
		•	GRAF	PHIC SCALE		
			(1	N FEET )		
	2	5 12.5	0	25	50	75
	۱ I I			" = 50'		
- $        -$			Ver	= 50 t· 1" = 10'		
		ATE	OF TEL			
		Sile -		THE SEAL A	PPEARING	ON THIS
	13	*/ /	1	DOCUMENT V	WAS AUTHO	0RIZED BY 125042
	1	CARLOS				
	- 14	12	0042			
		SSI ON	AL ENGI	6	6/24/2020	
			11110			
					0122 047400	NT DD 575 040
		MA	EST	<b>Z A</b>	SAN ANTONIO, (210) 366-1988	TX 78229
	•				TBPE No.: F-33 TBPLS No.: 101	3 94506
				11550 H	10 WEST SU	TE 305
			FC	SAN ANTON	IO, TEXAS 78	230-1037
	CIV	IL ENGINEER	ING CONSULTANTS	TEL (210) 641 TBPE REG	9999   FAX: (2 STRATION NO	10) 641 6440 ) . F-2214
' L			DON DURDEN, INC.	TBPLS REGIS	TRATION NO.	: 100410-00
			WATS	ON ROA	٨D	
			DR/	AINAGE		
			PLAN AI	ND PROF	ILE	
			STORM	SYSTEM	"B"	
		QT/	130±00 00		34+00 0	0
		317	- 130+00.00	IUSIAI	34+00.0	0
	· -		SHE	ET 3 OF 9		
				0	_	
		C 2017	7	Texas	Departi	nent
				orira	nsporta	LION IPLAN SHT
	$\vdash$	DIV NO.	FEDERA	L AID PROJECT	FNO.	NO.
<b>4</b> 5	$\vdash$	D	DIST		COUNTY	138
N N N						
<b>₽</b> →		CONT.	SECT.	JOB		/ STREET
		0915	12	562	WATS	
		0010	14	1 JUZ		



pltcfg

					PLAN VI	EW LEGE	ND	
TUYFT AND WIFE, VERSTUYFT .PG. 1475, O.P.R.					PLAN VI INLET B SLOT VC ARCH PIPE PRC PRC PRC BAF ELE UNI S - EXI BAF ELE UNI S - GAS X" WA' C - OVE S - OVE S - FIR FIR FIR PRC PL PRC PRC PL PRC PRC PL PRC PRC PL PRC PRC PL PRC PRC PL PRC PRC PRC PRC PRC PRC PRC PRC	EW LEGE DI = DF JB = JU E RCP = F DPOSED STI DPOSED CU STING RIGH DPOSED CU STING RIGH DPOSED RIG STING RIGH DERGROUN S LINE TER LINE ER HAD ELF LITY POLE TER VALVE E HYDRANT EPHONE PE CTRIC JUNG L BOX VIEW LEC (R EGL (R HGL STING GROI)	ND OP INLET INCTION E REINF CON RUCTURE RB T OF WAY SHT OF	r BOX IC PIPE
ED QUANTITIES					@ (			
RIPTION	U	INIT C	ΩTY		PRO @ 0	CL OF PIPE	ADE	
TION PROTECTION	N	LF 4	488			NCRETE CO	LLAR SEE	
		CY	6		DEI	I AIL ON SHE	ET 160	
_ C)		CY	6					
4 IN)		LF 2	283					
5 IN)		LF 2	205					
PJB) (5FTX5FT)		EA	1					
O)(5FT)		EA	2					
L)(SL)(3FTX3FT)			1					
;O)(3FT)		EA	8					
	640 —	   +   		  NO DATE	- - - - - - - - - - - - - - - - - - -	REVISION PHIC SCALE N FEET ) 25 	50	APPROVED
	630 — 			CARLOS BON 125 FON	Ver	t: 1" = 10' THE SEAL A DOCUMENT V CARLOS LU	PPEARING VAS AUTHO JNA III, P.E.	ON THIS RIZED BY 125042
	620	         				11550 IH SAN ANTON TEL: (210) 641-5 TBPLS REGIS	8122 DATAPOIN SAN ANTONIO, (210) 366-1988 TBPE No.: F-333 TBPLS No.: 1015 10 WEST, SUI IO, TEXAS 78: (999   FAX: (21 STRATION NO. (21 STRATION NO.)	IT DR., STE. 840 TX 78229 54506 TE 395 230-1037 0) 641-6440 .: F-2214 100410-00
		1			WATS	<u>ON RO</u> A	.D	
		1			DR	AINGAE		
'   	610	   		ST/	PLAN AI STORM A 134+00.00	ND PROF SYSTEM ) TO STA 1	ILE "B" 39+00.00	)
 '		+			SHE	<u>ET 4 OF 9</u>		
		 		© 2017 FED.RD. DIV NO	FEDERA	Texas of Trai	Departn Isportai ^{NO.}	nent tion PLAN SHT.
I		RI		6				139
I		N N N E N		STATE	DIST.			
					SAT	100		
				0915	3EU1. 12	562		
					14			



PLOTTED BY: ivette PLOTTED SCALE: 1:50 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_ PLOTTED ON: 6/24/2020 @ 11:37; PLOTTED ON: 6/24/2020 @ 11:37;

pltcfq

CEC.



PLOTTED BY: ivette PLOTTED SCALE: 1:50 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:37:43 AM

PLAN	I VIEW LEGEND
CI = CURB INLET CS = CURB SLOT	DI = DROP INLET PJB = JUNCTION BOX
CAP = CONC ARCH	PIPE RCP = REINF CONC PIPE
	PROPOSED STRUCTURE
	PROPOSED CURB
	EXISTING RIGHT OF WAY
	PROPOSED RIGHT OF WAY
~	
-UG IELE	
GAS —	
wv	UNEITY FOLE
$\bowtie$	WATER VALVE
Ş	FIRE HYDRANT
	TELEPHONE PEDESTAL
EJB	ELECTRIC JUNCTION BOX
	PULL BOX
PROFI	LE VIEW LEGEND
	10 YR EGL
	10 YR HGL
	EXISTING GROUND
	PROPOSED GRADE
	@ CL OF PIPE
	CONCRETE COLLAR SEE
	DETAIL ON SHEET 160

ESTIMATED QUANTITIES						
ITEM	DESCRIPTION	UNIT	QTY			
160 6003	FURNISHING AND PLACING TOPSOIL(4")	SY	323			
162 6002	BLOCK SODDING	SY	323			
402 6001	TRENCH EXCAVATION PROTECTION	LF	394			
420 6002	CL A CONC (MISC)	CY	2			
462 6004	CONC BOX CULV (4 FT X 3 FT)	LF	394			
465 6009	JCTBOX (COML) (PJB) (6FTX6FT)	EA	1			

Ð

		-			
		-			-
		-			-
	NO DATE		REVISION		APPROVED
·   +		GRAF	PHIC SCALE		
		(1	N FEET )		
I I I	25 12.5	0	25	50	75
		1	" = 50'		
·! L		Ver	t: 1" = 10'		
	TEC	DF TEL			
	Sin	A	THE SEAL A		
	E\$ 7	$\mathbf{x}$	DOCUMENT	NAS AUTHO	DRIZED BY
	CARLOS	S LUNA III	CARLOS L	UNA III, P.E	125042
	12 12	5042			
	10	-0.14			
	SSI CE	ENGI		6/24/2020	
·		AL			
				8122 DATAPOI	NT DR., STE. 840
	MA	ES1	LV Z	SAN ANTONIO (210) 366-1988	TX 78229
·				18PE No.: F-33 TBPLS No.: 101	3 .94506
			11550 H	10 WEST, SU	TE 395
	- C1		5AN ANTO TEL: (210) 641	99991 FAX 72	10) 641-6440
	CIVIL ENGINEER	ING CONSULTANTS	TBPE REG	STRATION NO	D.F 2214
		DON DURDEN, INC.	TBPLS REGIS	TRATION NO.	.: 100410-00
		WATS	ON ROA	٨D	
		DR	AINAGE		
		ΡΙ ΑΝ Δ		EII F	
	OTOD				
	STOR	IVI 5151EN	/I B AF	:RANO	
	VERAN	O STA 203+	00.00 TO	STA 207	+00.00
·		0.17			
		SHE	<u>========</u>		
				Danat	
	C 2017		iexas	ueparti	nent
			of Ira	nsporta	tion
	FED RD DIV NO	FEDERA	L AID PROJECT	ΓNO.	PLAN SHT NO
	6				141
ନ୍ତ୍	STATE	DIST.		COUNTY	
N.N.	ТΥ			REXAR	
ш <b>н</b>			100		( OTDEET
	CONT.	SECI.	JOR	HIGHWAY	/ SIREET
	0915	I 12	I 562	I WATS	ON RD



PLOTTED BY: ivette PLOTTED SCALE: 1:50 PEN TABLE: M058_pentbl.tb PLOT DRIVER: WATSON_B' PLOTTED ON: 6/24/2020 @

pltcfg

					DI = DI IR - II		T
			CAP = CO	NC ARCH PIPE	RCP =	REINF CO RUCTUR	NC PIPE E
				EXI	DPOSED CL	IRB IT OF WA	Y
				PRO	OPOSED RIG STING EASE	GHT OF V EMENT	VAY
				EXI: BAF	ST FEATUR RB WIRE FE	ES NCE	
			UG T	ELE UNE		D TELE	
			— W-	X" — WA			
					ITY POLE	ECTRIC	
			WV	WA	FER VALVE		
			Ç.				
			EJB X	ELE	CTRIC JUN	CTION B	ХX
			PBX	PUL			
	SY	23		10 Y	/IEW LE( 'R EGL	JEND	
	LF	40	]— -	10 Y			
")	SY SY	350		— - @C	L OF PIPE		
	SY	35	1	PRC	L OF PIPE	ADE	
	LF	393			ACRETE CC	EET 160	E
_	CY	5	-				
_	LF	393	-				
	EA	2					
	EA	1					
_		1	-				
	LF	40	-				
	SY	23					
				-			-
	1		NO DATE	- F	REVISION		APPROVED
_	+			GRAF ( II	PHIC SCALE N FEET )		
			25 12.5	0	25	50	75
_	1						
	⊥			1	" = 50' + 1" - 10'		
	⊥ !			1 Ver	" = 50' t: 1" = 10'		
	⊥   		STATE	1 Ver	" = 50' <u>t: 1" = 10'</u>		
_	⊥     			1 DF TELS	" = 50' <u> :: 1" = 10'</u> THE SEAL A DOCUMENT \ CARLOS L	PPEARING WAS AUTHO	ON THIS ORIZED BY 125042
_	⊥           		CARLOS B 125	DF TE+35 S LUNA III 5042	" = 50' <u>:: 1" = 10'</u> THE SEAL A DOCUMENT \ CARLOS LI	NPPEARING WAS AUTHO UNA III, P.E	ON THIS DRIZED BY . 125042
			CARLOS 125 00	1 Ver DF 75 + 35 S LUNA III 5042	" = 50' :: 1" = 10' THE SEAL A DOCUMENT \ CARLOS L'	PPEARING WAS AUTHO UNA III, P.E 6/24/2020	ON THIS DRIZED BY . 125042
	⊥		CARLOS CARLOS 12t SSION	1 Ver DF 75-45 S LUNA III 5042	" = 50' :: 1" = 10' THE SEAL # DOCUMENT \ CARLOS L'	DPEARING WAS AUTHO UNA III, P.E 6/24/2020	ON THIS DRIZED BY . 125042
	⊥		CARLOS 122 MA		" = 50' :: 1" = 10' THE SEAL A DOCUMENT 1 CARLOS L' 	PPEARING WAS AUTH UNA III, P.E 6/24/2020	NT DR, STE, 840
_			CARLOS CARLOS IZE		" = 50' :: 1" = 10' THE SEAL A document ' CARLOS L'	APPEARING WAS AUTH UNA III, P.E 5/24/2020 8112 DATAMO SAN ANTONIO SAN ANTONIO 21201 356-1389 TBPE No.: F-33 TBPLS No.: 10	CON THIS ORIZED BY .125042
_					" = 50' 1: 1" = 10' THE SEAL A DOCUMENT V CARLOS L' CARLOS L' 11550 HH SAN ANITON TEL: (110.641	APPEARING WAS AUTH( UNA III, P.E 5/24/2020 8122 DATAPO 5/24/2020 10 2013 56:19 10 VEST. 50 10 WEST. 50	CON THIS ORIZED BY . 125042
					" = 50' t: 1" = 10' THE SEAL A DOCUMENT 1 CARLOS L' CARLOS L' TALSO H SAN ANTON TEL: (210) 641- TBPE REGIS TEPL: REGIS	APPEARING WAS AUTH UNA III, P.E 5/24/2020 8122 DATAPO 5/24/2020 10 WEST, SL IO, TEXAS 7: 999 [FAX: STRATION N STRATION N	CON THIS DRIZED BY . 125042
					THE SEAL A DOCUMENT V CARLOS LI CARLOS LI TABLE SAN ANTON TEL: (210) 641- TBPLS REGIS ON ROA	PPEARING WAS AUTHO UNA III, P.E 3/24/2020 3/24/2020 3/24/2020 10 WEST, SL IIO, TEXS, 7 39999 [FAX: (2 39999 [FAX: (2 37RATION NO NDRATION NO	ON THIS ORIZED BY .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125
					THE SEAL A DOCUMENT 1 CARLOS L CARLOS L CARLOS L TI550 IH SAN ANTO TEL: (210) 641 TBPLS REGIS ON ROA CAINAGE	APPEARING WAS AUTH UNA III, P.E 5/24/2020 3/24/2020 3/24/2020 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0156-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/0100-05 10/01000-05 10/0100-0000000000000000000000000000	ON THIS DRIZED BY . 125042
					THE SEAL A DOCUMENT V CARLOS LI CARLOS LI TABLE SAN ANTON TEL: (2/10) 641- TBPLS REGIS ON ROA CAINAGE ND PRO	PPEARING WAS AUTHO UNA III, P.E 3/24/2020 312 DATAPO 312 DATAPO 15 PR SN.21 319 PR SN.21 319 PR SN.21 319 PR SN.21 319 PK	ON THIS DRIZED BY . 125042 . 1
				TEST SI LUNA III SI LUNA III S	THE SEAL A DOCUMENT V CARLOS L CARLOS L CARLOS L TASSO H SAN ANTON TEL: (210) 641 TBPE REGI TBPLS REGIS ON ROA CAINAGE ND PRO M "B" - VE	APPEARING WAS AUTHO UNA III, P.E 3/24/2020 3/24/2020 3/24/2020 10 WEST, SU IIO, TEXAS 7. 9999 IFAX: (2 STRATION NO TRATION NO ND FILE FILE ERANO STA 21(	CON THIS DRIZED BY . 125042 . 125042
				SLUNA III SLUNA III SUMA III SUMA SUMA SUMA SUMA SUMA SUMA SUMA SUMA	THE SEAL A DOCUMENT I CARLOS LI CARLOS LI TASO HI SAN ANTON TEL: (210) 641 TBPE REGIS TBPE REGIS TB	APPEARING WAS AUTH UNA III, P.E 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 10 WEST, SL 10	CON THIS DRIZED BY .125042 .125042 .125042 .125042 .175042 .17504 .10641-6440 .1752214 .100410-00 .1552214 .100410-00
				The second secon	THE SEAL A DOCUMENT V CARLOS LI CARLOS LI TABLE SAN ANTON TEL: (210) 641 TBPLS REGIS ON ROA CAINAGE ND PRO M "B" - VE COULD TO EET 7 OF 9	APPEARING WAS AUTHO UNA III, P.E 3/24/2020 3/24/2020 3/24/2020 10 WEST, SU IIO, TEXAS 7 9999   FAX: (2 9999   FAX: (2 9999   FAX: (2 9999   FAX: (2 9999   FAX: (2 9999   FAX: (2 9999   FAX: (2 970   2 971   2 971	CON THIS DRIZED BY . 125042
				SLUNA III SLUNA III SLUNA III SUM SUSSEE MALEST EC ING CONSULTANTSC DR PLAN A M SYSTEI IO STA 207- SHI	THE SEAL A DOCUMENT I CARLOS L CARLOS L CARLOS L TABOR TALSO H SAN ANTO TEL: (210) 641 TBPLS REGIS ON ROA CAINAGE ND PRO M "B" - VI COU.00 TO EET 7 OF 9 Texas of Tray	APPEARING WAS AUTH UNA III, P.E 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2020 3/24/2000 3/24/2000 3/24/2000 3/24/2000 3/24/2000 3/20	CON THIS DRIZED BY .125042 .125042 .125042 .125042 .125042 .125042 .10641640 .2:F2214 .:100410-00 
				S LUNA III S LUNA III S LUNA III S LUNA III S LUNA III S LUNA III S CONDUCTANTS ECONDUCTANTS DR PLAN A M SYSTEI IO STA 207- SHI FEDERA	THE SEAL A DOCUMENT I CARLOS LI CARLOS LI SANANTON TEL: (210) 641- TBPE REGI TBPLS REGIS ON ROA CAINAGE ND PRO M "B" - VIE COU.OU TO EET 7 OF 9 Texas of Tra. L AID PROJECT	APPEARING WAS AUTH UNA III, P.E. 5/24/2020 SIZE DATAPO SIZE DATAPO SIZE AND AND SIZE DATAPO SIZE AND SIZE DATAPO SIZE DATAPO S	CON THIS DRIZED BY .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .125042 .12
				TEDERA TEDERA TEDERA TEDERA TEDERA TEDERA TEDERA TEDERA TEDERA	THE SEAL A CONCLIMENT I CARLOS LI CARLOS LI TABLE SEAL A DOCUMENT I CARLOS LI CARLOS LI TABLE SEAL A CALONG TEL: (210) 641 TBPLS REGIS TON ROA CAINAGE ND PRO CON ROA CAINAGE ND PRO M "B" - VI COO.00 TO EET 7 OF 9 Texas of Trai LAID PROJECT	APPEARING WAS AUTHO UNA III, P.E. 3/24/2020 3/24/2020 3/24/2020 10 WEST, SL IIO, TEXAS 7. 9999 IFAX: (2 STRATION NO AD FILE ERANO STA 21( Departin nsporta rNO.	CON THIS DRIZED BY .125042
	PROF INVERT		CARLOS CARLOS IZE CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSION CONTREMENSIO	S LUNA III S LUNA III	THE SEAL A DOCUMENT Y CARLOS L CARLOS L CARLOS L TI550 IH SAN ANTO TEL: (210) 641 TBPLS REGIS ON ROA CAINAGE ND PRO M "B" - VE COU.00 TO EET 7 OF 9 Texas of Trai	APPEARING WAS AUTH UNA III, P.E 3/24/2020 3/24/2020 3/24/2020 3/24/2020 10 WEST, SL 10 WES	CON THIS DRIZED BY . 125042

0915 12 562 WATSON RD

SCRIPTION	UNIT	QTY
IC (RIPRAP)	SY	16
IC (SIDEWALKS)	SY	23
IC (CURB)	LF	40
D PLACING TOPSOIL(4")	SY	350
G	SY	350
E ASPH PAVING	SY	35
ATION PROTECTION	LF	393
SC)	CY	5
(CL C)	CY	6
V (4 FT X 3 FT)	LF	393
.) (PJB) (6FTX6FT)	EA	2
CURB)(TY C1)	EA	1
_ET)	EA	1
PE)	LF	135
(  )	LF	40
KS (4")	SY	23



pltcfg

		PLAN VIEW LEGEND
I		CI = CURB INLET DI = DROP INLET CS = CURB SLOT PJB = JUNCTION BOX CAP = CONC ARCH PIPE RCP = REINF CONC PIPE PROPOSED STRUCTURE
ON EXISTING ROW	0.00	
	)3+0	EXIST FEATURES     EARB WIRE FENCE     UNDERGROUND TELE     CASE UNE
CP (6' 0.00	A 20	W - X" WATER LINE ELEC OVERHEAD ELECTRIC UTILITY POLE
<u> </u>	ST	
	Щ	
	TCF	
EXISTING ROW	MA	C L OF PIPE     PROPOSED GRADE     @ CL OF PIPE     @ CL OF PIPE     CONCRETE COLLAR SEE     DETAIL ON SHEET 160

··						
	ESTIMATED QUANTITIES					
	ITEM	DESCRIPTION	UNIT	QTY		
	402 6001	TRENCH EXCAVATION PROTECTION	LF	140		
	420 6002	CL A CONC (MISC)	CY	2		
	464 6005	REC PIPE (CL III)(24 IN)	LF	140		
	465 6024	INLET (COMPL)(PCO)(5FT)	EA	2		
	465 6013	INLET (COMPL)(PCO)(3FT)	EA	2		

		_					
		<u> </u>	-	-			-
		ŀ	-	-			-
1	1	-		-			
l		110	DATE	CRA			ATTROVED
	+	-		(I	N FFFT )		
	I.	2	5 12.5	0	25	50	75
		11		_		_	
1				1	" = 50'		
		-		Ver	t: 1" = 10'		
	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	"Ininin"	CARLOS 125 CARLOS			APPEARING WAS AUTH UNA III, P.E 6/24/2020 8122 DATAPO SAN ANTONIO (210) 366-198	ON THIS DRIZED BY . 125042
     	+				11550 IH SAN ANTOI TEL: (210) 641 TBPLS REGIS	10 WEST, SU 10 WEST, SU 9999   FAX: (2 STRATION NO STRATION NO	ITE 395 3230-1037 10) 641-6440 D: F-2214 : 100410-00
i i				WAIS	ON ROP	AD	
				DR/	AINAGE		
!		_		PLAN AI	ND PROF	ILE	
			STORM	SYSTEM	"B" - VFF		RIGHT
I.							
			VERAN	J STA 200+	00.00 10 3	51A 203	+00.00
	E00 - +	-		SHF	FT 8 OF 9		
	000				0		
			© 2017	7	Texas of Tra	Depart nsporta	ment tion
· · · ·			FED RD. DIV NO.	FEDERA	L AID PROJEC	T NO.	PLAN SHT NO
I	R I		6				143
	l l l l l l l l l l l l l l l l l l l		STATE	DIST.		COUNTY	
	R N		ΤX	SAT		BEXAR	
) 20:	3+00		CONT	SECT.	JOB	HIGHWAY	//STREET
			0915	12	562	WATS	ON RD


PLOTTED BY: ivette PLOTTED SCALE: 1:50 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pitcfg PLOT DRIVER: WATSON_BW_PDF_CEC.pitcfg PLOTTED ON: 6/24/2020 @ 11:37:51 AM DESIGN FILENAME: Z:Projects\Watson Road\Drai

	PLAN	I VIEW LEGEND
	CI = CURB INLET CS = CURB SLOT CAP = CONC ARCH	DI = DROP INLET PJB = JUNCTION BOX PIPE RCP = REINF CONC PIPE
		PROPOSED STRUCTURE
		PROPOSED CURB
		PROPOSED RIGHT OF WAY
		EXISTING EASEMENT
		EXIST FEATURES
P.R.	— X -	
	— UG TELE—	GAS LINE
IL.	— W - X" —	WATER LINE
	— ELEC —	OVERHEAD ELECTRIC
	C)	UTILITY POLE
	₩V  >>>	WATER VALVE
	ŞÇ	FIRE HYDRANT
	T	TELEPHONE PEDESTAL
0	EJB	ELECTRIC JUNCTION BOX
	PBX	PULL BOX
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		
3		

EXISTING ROW

SEE THIS SHEET FOR RIP RAP DETAIL

- 2'

Г							
F		ESTI	MATED Q		s		
F	ITEM	D	ESCRIPT	ION		UNIT	QTY
	432 6007	RIPRAP (CONC	C)(CLC)			CY	10
F	465 6338	INLET (COMP)	LOT)	EA	2		
-		, , , , , , , , , , , , , , , , , , ,			· · · ·		
				-			-
			- ·	-			-
			NO DATE	- F	REVISION		APPROVER
				GRAF	HIC SCALE		
			25 12 5	0 (1	N FEET) 25	50	75
				, in the second	20		
				1	" = 50'		
PROP RIF IST . DITC	PRAP H CL				CARLOS I CARLOS I SAN ANTO TEL: (210) 641 TBPE REG TBPLS REGI	UNA III, Р.Е 6/24/2020 8122 ДАТАРС 5 8122 ДАТАРС 2019 366-193 ТВРС № 10 10 WEST, SL NIO, ТЕХАБ 7 -9999 [FAX: () STRATION NC	INT DR., STE. 840 NT DR., STE. 840 NTX 78229 134506 JITE 395 8230-1037 210) 641-6440 0. F-2214 1. 100410-00
	D			WATS	ON RO	٩D	
STA	<u> 0/S</u>	ELEV.		DR	AINAGE		
40.04.0				PLAN A	ND PRO	FILE	
40+01.0	21.00	KI 021.45		STORM	SYSTM	E "B"	
40+49.4	4 27.31	LI 022.24	STA	139+00.00 1	FO END C	F PROJ	ECT
				QUE			
					<u>. Lisois</u> 9		
			© 2013	7	Texas of Tra	Depart nsporta	ment ation
			FED.RD. DIV.NO.	FEDERA	L AID PROJEC	T NO.	PLAN SHT NO.
			6				144
			STATE TV	DIST.			
			CONT.	SAI SECT.	JOB		Y/STREET
			0915	12	562	WATS	



PROP ROW

PLOTTED BY: ivette PLOTTED SCALE: 1:20 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:37:54 AM



PLOTTED BY: ivette PLOTTED SCALE: 1:20 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:37:55 AM



PLOTTED BY: ivette PLOTTED SCALE: 1:20 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:37:56 AM

Culvert Station and/or Creek name followed by applicable end (Lt, Rt or Both)	Description of Box Culvert	Max Fill Height	Applicable Box Culvert Standard	Applicable Wingwall or End Treatment Standard	Skew Angle (0°,15°, 30° or	Side Slope or Channel Slope Ratio	T Culvert Top Slab Thickness	U Culvert Wall Thickness	C Estimated Curb Height	Hw () Height of Wingwall	A Curb to End of Wingwall
	Span X Height	(F+)	(4)		45°)	(SL:1)	(In)	(In)	(F†)	(F†)	(F+)
Sta 110+64.09 (LT)(UPSTREAM)	2~3'× 2'	3.70'	SCP-3	PW-1	0°	3:1	7"	4"	1.12′	3.71′	N/A
Sta 110+64.09 (RT)(UPSTREAM)	2~3'× 2'	3.70'	SCP-3	FW-O	0°	3:1	7"	4"	1.12′	3.46′	9.38′
Sta 110+64.09 (BOTH) (DOWNSTREAM)	3~3'× 2'	3.50′	SCP-3	SW-0	0°	3:1	7"	4"	0.92′	3.25′	N/A

NOTES:

- Skew Angle = 0° for SW-0, FW-0, SETB-CD, SETB-SW-0, and SETB-FW-0 standards. 30° Maximum for Safety End Treatment
- SL:1 = Horizontal:1 Vertical
 - Side Slope at culvert for Flared or Straight Wingwalls. Channel Slope for Parallel Wingwalls. Slope shall be 3:1 or flatter for Safety End Treatments.
- T = Box Culvert Top Slab Thickness. Dimension can be found on the applicable Box Culvert Standard.
- U = Box Culvert Wall Thickness. Dimension can be found on the applicable Box Culvert Standard.
- C = Curb Height.
- See applicable wing or end treatment standards for calculations of Hw, A, B, Lw, Ltw, Atw, and Total Wingwall Area. Hw = Height of Wingwall. A = Distance from Face of Curb to End of Wingwall (Not applicable to Parallel or Straight Wingwalls). B = Offset of End of Wingwall (Not applicable to Parallel or Straight Wingwalls).

- Lw = Length of Longest Wingwall. Ltw = Length of Culvert Toewall (Not applicable when using Riprap Apron). Atw = Length of Anchor Toewall (Applicable to Safety End Treatment only). Total Wingwall Area = Wingwall area in S.F. for two wingwalls (one structure end) if Lt or Rt. Area for four wingwalls (two structure ends) if Both.

- (1) The wall heights shown will be rounded to the nearest Foot for bidding purposes.
- 2 Concrete volume shown is for box culvert curb only. For curbs using the RAC standard, quantities shown must be increased by a factor of 2. If Class "S" concrete is required for the top slab of the culvert, the curb concrete shall also be Class "S". Curb concrete is considered part of the Box Culvert for payment.
- 3 Concrete volume shown is total of wing, footing, culvert toewall (if any), anchor toewall (if any) and wingwall toewall. Riprap apron, culvert and curb quantities are not included.
- (4) Regardless of the type of culvert shown on this sheet, the Contractor shall have the option of furnishing cast-in-place or precast culverts unless otherwise shown elsewhere on the plans. If the Contractor elects to provide culverts of a different type than those shown on this sheet, it shall be the Contractor's responsibility to make the necessary adjustments to the dimensions and quantities shown.



6/24/2020

Lw Length of Uorgest Ltw Current Toewall Atw Anchor Toewall Riprop Apron Class "C" Corc (Curb) Total "C" (wingwall) (f+) (F+) (f+) (C+) (C,Y_1) (C,Y_1) (C,Y_1) 11.13' 7.83' N/A 0 0.3 6.5 83 10.82' N/A N/A 1.9 0 3.0 41 11.13' 7.83' N/A 0 0.3 6.5 83 10.82' N/A N/A 1.9 0 3.0 41 8.75' N/A N/A 3.0 0.8 4.8 54								
(F+) (F+) (F+) (C, Y,) (C, Y,) (C, Y,) (S, F,) 11, 13' 7, 83' N/A 0 0, 3 6, 5 83 10, 82' N/A N/A 1, 9 0, 3 3, 0 41 8, 75' N/A N/A 3, 0 0, 8 4, 8 54 - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -	Lw Length of Longest Wingwall	Ltw Culvert Toewall Length	Atw Anchor Toewall Length	Riprap Apron	Class "C" Conc (Curb)	Class "C" Conc (Wingwall)	Total Wingwall Area	
11.13' 7.83' N/A 0 0.3 6.5 83 10.82' N/A N/A 1.9 0.3 3.0 41 8.75' N/A N/A 3.0 0.8 4.8 54	(F+)	(F†)	(F+)	(C.Y.)	(C.Y.)	(C.Y.)	(S.F.)	
10.82' N/A N/A 1.9 0.3 3.0 41 8.75' N/A N/A 3.0 0.8 4.8 54	11.13′	7.83′	N/A	0	0.3	6.5	83	
8.75' N/A N/A 3.0 0.8 4.8 54	10.82′	N/A	N/A	1.9	0.3	3.0	41	
	8.75′	N/A	N/A	3.0	0.8	4.8	54	
Image: section of the section of th								
Image: section of the section of th								
Image: set of the								
Image: state in the state in								
Image: set of the								
Image: state s								
Image: set of the								
Image: set of the								
Image: state s								
Image: state s								
Image: state in the state								
Image: state in the state								
Image: state stat								

End of

SPECIAL NOTE:

This sheet is a supplement to the Box Culvert standards. It is to be filled out by the culvert specifier and provides dimensions for the construction of the Box Culvert Wingwalls and Safety End Treatments.

An Excel 97 spreadsheet to assist in completing this table can be downloaded from the Bridge Standards (English) web page on the TxDOT web site. The completed sheet shall be signed, sealed, and dated by a licensed Professional Engineer.



		BCS								
FILE: bcss	tde1.dgn	DN: TXL	DOT	ск:	T x D 0 T	DW:	TxD0T	Ck	- G	AF
©TxDOT F	ebruary 2010	CONT	SECT		JOB			HIGHM	/AY	
	REVISIONS									
		DIST			COUNTY			SH	EET)	VO.
								1	48	3



PLOTTED BY: ivette PLOTTED SCALE: 1:20 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltc PLOT DENVER: WATSON_0 11:38:15 AM

pltcfg

ID PR11 RAI	LING	3						PLAN	1 VIE	W LE	EGENI	D		
A 110+44.50							PJB = JUN	ICTION	вох					-
5 62.10 LI	— F	PROP	5" C(ONC		/							=	
	Ē	RIPRAF	Ś	0110.									-	
			-		\sim				FYIS				v	
	2		_		N.				PROF	POSEL	RIGHT	OFV	/AY	
62	.2—			à			$- \cdot xx$	х— -	PROF	P 1' CC		₹	.,	
621	_		-	Je	•		XX	X — –	EXIS	T 1' CC	ONTOUR	2		
· · · · · · · ·			- 1						EXIS	T FEA	TURES			
1-2-1			NOR.	e			-UG TE	ELE	UNDE	ERGR	DUND T	ELE		
- PROP W	ATE						— GA	s —	GAS	LINE				
	1	((W// G)	•				— W -	X" —	WATE	ER LIN	IE			
- /							— ELE	с —	OVEF	RHEAD	D ELECT	RIC		
_/							0	5	UTILI	TY PO	DLE			
- v ²⁹							WV		\A/A TI					
_	_		_						WAI	ER VA	LVE			
	-7	- 65	_				ļ,		FIRE	HYDR	ANT			
-2-	_						Ī		TELE	PHON	IE PEDE	STAL		
0							EJB		FLEC	TRIC	JUNCT)X	
- 974 110-4	24.00						PBX							
O/S 61 83	1 T	,							PULL	BOX				
END CON	C.R	PRAP					r							
TIE TO EX	ISTI	NG DII	СН					-KUFI			LEGE	ND		_ [
									10 YF	KEGL				
ALL (PW-0)									10 YF	K HGL		~		
									EXIS @ CI	OF P	JKUUNI IPE	J		
									PROF	POSE	D GRAD	E		
IG									@ ČL	OF P	IPE	-		
									CON	CRETE		AR SE	E	
									UEIA		SHEEL	100	_	
					ESTIN	IATE	D QUAN	TITIE	S					
		ITEM			DE	ESCF	RIPTION				UNIT	QT	Y	
	40	2 600)1	TRENC	CHEXCA	VATIO	ON PRC	TECT	ION		LF	19	8	
	42	0 600)2		CONC (MIS	SC)					CY	1		
	12		57				(2110)					18		
	42	22 60	7				$\frac{1}{2}$					43	_	
	43	2 000	57				0)					40	<u>'</u>	
	45	0610)3	RAIL (IY PR11)							86		
	46	2 600)1	CONC	BOX CUL	_V (3	FIX2F	-1)			LF	19	8	
	49	7 600)7	REMO	V STR (PI	PE)					LF	22	5	
					1		-	-						
					1			-						
						- - NO		- - -	RE				APPR	OVED
		00				- - - NC	- D DATE	- - -	RE	VISION	.LE		APPR	OVED
 -		-50.00)' LT	64	0	 +	 NC	- - D DATE	-	RE GRAPH (IN	VISION IIC SCA FEET)	LE		APPR	OVED
 		10+50.00 5.00' LT	64	0	 +	- - - NC -		- - -	RE GRAPH (IN	VISION IIC SCA FEET) 10	ILE 2	10	APPR	OVED
 	N	A 110+50.00 S 95.00' LT	64	0	 + 	- - NC - 1	D DATE	- - - 0	RE GRAPH (IN	IC SCA FEET) 10	ILE 2	0	APPR	OVED 30
 	TIE IN	STA 110+50 00 O/S 95.00' LT	64	0 — - F —	 + 	 1		- - -	RE GRAPH (IN 1"	VISION IIC SCA FEET) 10 = 20' 1" = 1/	LE 2	20	APPR	OVED
 	TIE IN	STA 110+50.00 O/S 95.00' LT	64 63	0	 				RE GRAPH (IN 1" Vert:	VISION IIC SCA FEET) 10 = 20' 1" = 10	LE 2	0	APPR	30
	TIE IN	STA 110+50.00 O/S 95.00' LT	64	0 ⁻ 5 ⁻		 NC 1		- - -	RE GRAPH (IN 1" Vert:	UISION IIC SCA FEET) 10 = 20' 1" = 1(LE 2	0	APPR	30
	TIE IN	STA 110+50.00 O/S 95.00' LT	64	0 ⁻ 5 ⁻		 NC 1			RE GRAPH (IN 1" Vert:	VISION IIC SCA FEET) 10 = 20' 1" = 11	LE 2 0'		APPR	
	TIE IN	STA 110+50.00 O/S 95.00' LT	64	<u>0</u> — -				- - - -	RE GRAPH (IN 1" Vert:	VISION IIC SCA FEET) 10 = 20' 1" = 11 THE SE OCUME	LE 2 0' EAL APPE		APPR ON T DRIZE	
	TEIN	STA 110+50.00 O/S 95.00' LT	64(63)	0 ⁻			D DATE	- - - - - - - - - - - - - - - - - - -	RE GRAPH (IN 1" Vert:	THE SE CARL	ULE 2 0' EAL APPE ENT WAS OS LUNA	aring Auth III, P.E	APPR ON T DRIZE 1250	30 30 HIS D BY 42
	TIEIN	STA 110+50.00 O/S 95.00' LT	64(63)	0 ⁻			D DATE	- - - - - - - - - - - - - - - - - - -	RE GRAPH (IN 1" Vert:	THE SE CARL	ULE 2 0' EAL APPE ENT WAS OS LUNA	aring Auth III, P.E	ON T PRIZE 1250	30 HIS D BY 42
	TEIN	STA 110+50.00 O/S 95.00' LT	64(63)	0 ⁻ 5 ⁻			0 5 CARLOS 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	- - - - - - - - - - - - - - - - - - -	RE GRAPH (IN 1" Vert:	THE SE CARL	LLE 2 0' EAL APPE ENT WAS OS LUNA 6/24/	20 AUTHO III, P.E 2020	APPR ON T DRIZE 1250	30 HIS D BY 42
	TIE IN	STA 110+50.00 0/S 95.00' LT	64(63)	0 ⁻ 5 ⁻ 0 ⁻			D DATE	0 5 LUNA I 042	RE GRAPH (IN 1" Vert:	IC SCA FEET) 10 = 20' 1" = 11 THE SE CARL	LE 2 0' EAL APPE ENT WAS OS LUNA 6/24/	20 ARING AUTH II, P.E 2020	APPR ON T DRIZE 1250	30 30 HIS D BY 42
	TTEIN	STA 110+50.00 O/S 95.00' LT	63 63	0 ⁻ 5 ⁻ 0 ⁻			D DATE	0 0 0 0 0 0 0 0 0 0 0 0 0 0	RE GRAPH (IN 1" Vert:	UISION IIC SCA FEET) 10 = 20' 1" = 11 THE SE CARL	LLE 2 0' EAL APPE ENT WAS OS LUNA 6/24/	0 AUTH(III, P.E	APPR ON T DRIZE 1250	30 BY BY 42
	TIEIN	STA 110+50.00 O/S 95.00' LT	64(63)	0 ⁻ 5 ⁻ 5 ⁻			D DATE	0 5 LUNA 1 042	RE GRAPH (IN Vert: Uert:	EVISION IIC SCA FEET) 10 = 20' 1" = 11 THE SE CARL	O' EAL APPEENT WAS OS LUNA 6/24/		ON T DRIZE 1250	30 30 HIS D BY 42
		STA 110+50.00 O/S 95.00' LT	64(63)	0 5 0 5					REF GRAPH (IN 1" Vert:	THE SEA	O' EAL APPE ENT WAS OS LUNA 6/24/	0 AUTH III, P.E 2020	ON T ON T DRIZE 1250	30 30 10 BY 42 5TE: 540
	TE N	STA 110+50.00 O/S 95.00' LT	64(63) 62(0 5 5 5					GRAPH (IN 1" Vert:	THE SEA	ALE 2 0' EAL APPEE ENT WAS SOS LUNA 6/24/ 6/24/ 6/24/	0 AUTHI III, P.E 2020 2 ANTONIO 3) 366-138 55 No: 10	ON T DRIZE 1250	30 30 10 BY 42 5TE: 840
		STA 110+50.00 O/S 95.00' LT	64(63) 62(0 5 5 5					GRAPH (IN 1" Vert:	EVISION IIC SCA FEET) 10 = 20' 1" = 11 THE SE CARLI	0' EAL APPEE ENT WAS OS LUNA 6/24/ 6/24/ 50 H 10 W	20 CARING AUTH III, P.E 2020 2 attaon 2	ON T DRIZE 1250 NT DR. 1250 ITE 39506	30 HIS D BY 42 55 55 55 55 55 55 55 55 55 5
		STA 110+50.00 0/S 95.00' LT	64(63) 62(0 ⁻ 5 ⁻ 5 ⁻ 0 ⁻					RE GRAPP (IN Vert:	EVISION IIC SCA FEET) 10 = 20' 1" = 11 THE SE CARLI 1151 SANA SANA	0' EAL APPPE ENT WAS OS LUNA 6/24/ 50 H 10 W NTONIO, T, 10 641.9990	20 CARING AUTH 11, P.E 2020 2020 2020 2020 2020 EST, SU 15 No.: 10 EST, SU 2020	ON T DRIZE 1250	30 30 HIS D BY 42 515 517 517 517 517 517 517 517
	TEIN	TA 110+50.00	64(63) 62(0 ⁻ 5 ⁻ 5 ⁻					RE GRAPH (IN 1" Vert:	IIC SCA IIC SCA IIC SCA IIC SCA III III IIII IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	0' EAL APPE ENT WAS OS LUNA 6/24/ 50 H 10 W NTONIO, T 0) 641-9995 1041-9995 50 H 10 W	20 CARING AUTHH III, P.E 2020 22 DATAPO 22 DATAPO 20 DATAPO 22 DATAPO	ON T ON T DRIZE 1250 1250 ITE 39: 33-94506 ITE 39: 2230-10 10164'	HIS D BY 42 537 16440
	TEIN	STA 110+50.00 O/S 95.00' LT	64(63) 62) 62) 621	0 ⁻ 5 ⁻ 5 ⁻ 0 ⁻					RE GRAPH (IN 1" Vert:	THE SEE THE SEE THE SEE THE SEE CARLI THE SEE SAN A TISI SAN A TISI TBPE TBPLS F	0' EAL APPE EAL APPE EAL APPE EAL APPE SO LUNA 6/24/ 6/24/ 50 H 10 W NTONIO, T 189 19999 50 H 10 W NTONIO, T 19999 50 H 10 W NTONIO, T 19999 50 H 10 W	20 AUTHI AUTHI 11, P.E 2020 2020 EST, SL 2020 EST, SL 202	ON T PRIZE 1250 NT DR. 25 3 3 94506 ITE 39(2230-10) 64' 2:10) 64' 2:10) 64'	OVED 30 D BY 42 5155. 840 5137 16440 114 10-00
		STA 110+50.00 O/S 95.00' LT	64(63) 62) 62(61)	0 ⁻ 5 ⁻ 5 ⁻ 5 ⁻					RE GRAPH (IN 1" Vert:	THE SEE 10 10 10 11 11 11 11 11 11 11	0' EAL APPEE EAL APPEE ENT WAS OS LUNA 6/24/ 50 H 10 W NTONIO, T 19999 50 H 10 W NTONIO, T 19999 EGISTRAT COAD	20 AUTHI 11, P.E 2020 2017 00 2020 2020 2020 2020 2020 2020 2020	ON T PRIZE 1250 ITE 39: 1230-61 2: 1004	30 30 D BY 42 5155. 840 5137 144 144 10-00
		STA 110+50.00 0/S 95.00' LT	64(63) 62(62) 61)	0 ⁻ 5 ⁻ 5 ⁻ 5 ⁻						THE SEE THE SEE THE SEE THE SEE CARLING THE SEE THE	0' EAL APPE EAL APPE ENT WAS OS LUNA 6/24/ 50 H1 10 W NTONIO, T 10 641-93792 REGISTRAT COAD OAD	20 AUTHI 111, P.E 20200 2010/00 20200 20000 2000 200000 2000000	ON T PRIZE 1250 IT 250 IT 250	HIS D BY 42 537 1-6440 10-00
		STA 110+50.00 O/S 95.00' LT	64(63) 62) 62) 61)	0 ⁻						THE SEE THE SEE THE SEE THE SEE THE SEE CARLING THE SEE THE	0' EAL APPE ENT WAS OS LUNA 6/24/ 50 H 10 W NTONIO, T) 641-93992 REGISTRAT COAD OAD 2 PRO	2 DATAPOO AUTHI III, P.E 20200 EST, SL EST, SL EST, SL FILL F	ОN Т ОN Т PRIZE 1250	30 30 D BY 42 537 1-6440 10-00
		STA 110+50.00 O/S 95.00' LT	64(63) 62) 62(61)	0 ⁻ 5 ⁻ 5 ⁻ 5 ⁻ 5 ⁻					Time States of the second seco	THE SEA	Coad Coad Coad Coad Coad Coad Coad Coad	20 AUTHI 20200 2020 2020 2020 2020 2020 2020 2	ОN T PRIZE 1250 NT DR. 25 1250 1250 1250 1250 10 64 10 64 10 64	OVED 30 D BY 42
		STA 110+50.00 O/S 95.00' LT	64(63) 62(61) 61)	0 5 5 5 5 5					RE GRAPP (IN Vert: Vert: ST ST TANTSC	THE SECOND	Coad Coad Coad Coad Coad Coad Coad Coad	2020 2020 2020 2020 2020 2020 2020 202	ON T DRIZE 1250 1250 1250 110164	HIS D BY 42
		STA 110+50.00	64(63) 62(61) 61)	0 5 5 5 5 5						THE SECONDARY CONTRACTOR OF CONTRACTOR CONTR	0' EAL APPPE EAL APPPE ENT WASS OS LUNA 6/24/ 6/24/ 6/24/ 50 HH 10 WASS 00 LUNA 6/24/ 50 HH 10 WASS 1200 1000	2020 2020 2020 2020 2020 2020 2020 202	ON T DRIZE 1250 NT DR.2 1250 1250 10164 2394506	HIS D BY 42 537
		STA 110+50.00	64(63) 62(61) 61(0					RE GRAPP- (IN Vert: Vert: STA TSC ATSC ATSC ATSC ATSC	1151 1152 1152 1154		20 AUTHA AUTHA 2020 20 AUTHA 2020 EST, SL EXAS 7, SL EX	ON T DRIZE 1250 NT DR. : 1250 1250 1250 10164 : 1004	30 HIS D BY 42 537 16440 14 10-00
PROP. 16" WATER MAI		STA 110+50.00 O/S 95.00' LT	64(63) 62) 62) 61) 61)	0 5 5 5 5 0 5					RE GRAPP- (IN Vert: Vert: Vert: STSC ATSC ATSC ATSC ATSC ATSC ATSC	1151 1152		2020 2021 20220 2020000 20000 2000000	ON T DRIZE 1250 NT DR. 2 9:94506 TTE 39: 2230-10 10-164 .: F-222 : 1004	30 HIS D BY 42 5155. 840 5137 10-6440 14 10-00
		STA 110+50.00 O/S 95.00' LT	64(63) 62(61) 61(60)	0^{-}						THE SEA THE	0' EAL APPPE ENT WAS OS LUNA 6/24/ 50 H 10 W NTONIO, T. 1967 90 REGISTRA 20 AD 0 AD 20 AD	2020 2017APO 2020 2020 2020 2020 2020 2020 2020 20	ON T APPR ON T DRIZE 1250 NT DR.; 1250 S230-10-64 10-6	30 HIS D BY 42 5 5 137 165440 14 10-00 14 10-00 14
		STA 110+50.00 O/S 95.00' LT	64(63) 62(61) 61(60)	0^{-}					Tants Caracteria Tants Tants TAC TAC TAC TAC TAC TAC TAC TAC	THE SEA THE	0' EAL APPE ENT WAS OS LUNA 6/24/ 50 H 10 W MTONIO, T 10641-9999 REGISTRA COAD OAD COAD COAD COAD COAD COAD COAD	20 AARING AUTH III, P.E 2020 201400 2015 2020 2014 2020 2014 2020 2014 2020 EXS 7 100 NO FILE part.	ON T DRIZE 1250 1250-11 1250-1	HIS D BY 42 537 1-6440 114000
		STA 110+50.00	64(63) 62) 61) 61) 60)	0^{-}						THE SEA THE		2 DATADO AUTHI III, P.E 2020 201400 2015 No. 10 2020 2014 2020 2014 2020 2020 2014 2020 2020	ON T PRIZE 1250 1250-11 1250 1230-11 1250-11 1	ні s 30 30 1 1 30 30 30 30 30 30 30 30 30 30
		TA 110+50.00	64(63) 62) 61) 61) 60)	0^{-}						THE SEA THE	Content of the second sec	2020 AUTHA AUTHA III, P.E 2020 2020 EST, SL EXAS 7. [FNC: IO Sec. 198 EST, SL EXAS 7. [FAIC: IO ION NO FILE FILE	ON T PRIZE 1250 1250 TX 7822 33 3230-11 10.64 2230-12 10.75 2230-12 10.75 2230-12 10.75 2230-12 10.75 2230-12 10.75 22 20.75 22 20.75 22 20.75 22 20.75 22 20.75 22 20.75 22 20.75	ніs 30 30 ВУ 142 144 16440 144 144 10000 157 144 144 10000 100 110 144 10000
PROP. 16"		48 STA 110+50.00	64(63) 62) 61) 61) 60)	0 ⁻ 5 ⁻ 5 ⁻ 5 ⁻ 5 ⁻						THE SEE THE		20 AUTHIN AUTHIN 111, P.E 2020 2020 2020 2020 2020 2020 2020 20	ON T PRIZE 1250 1250 1250 10164 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 1000	оved 30 30 1 1 1 1 1 1 1 1 1 1 1 1 1
PROP. 16" WATER MAI		220.48 STA 110+50.00 O/S 95.00 LT	64(63) 62) 61) 61) 60)	0						THE SECONDARY OF THE SE	COLOR CO	Contraction of the second seco	ON T DRIZE 1250 TT 394506 TT 39506 TT	00VED 30 D BY 42 00000 14 10000 14 10000 14 10000 14 10000 14 10000 14 10000 14 10000 14 100000 10000 10000 100000 10000 10
PROP. 16" WATER MAI		620.48 STA 110+50.00 O/S 95.00' LT	64(63) 62(61) 61)	0						THE SESTING AND A CONTRACT AND A CON		2 DATAPOO AUTHI III, P.E 2020 2 DATAPOO EXAST. 2020 2020 2 DATAPOO EXAST. 2020 2020 2 DATAPOO EXAST. 2020 2 DATAPOO EXAST. 2 DATAST. 2 DATAPOO EXAST. 2 DATAS	ON T DR.2 1250 NT DR.2 1064 NT DR.2 106	оved 30 30 В В У 42 Ст. 840 537 16440 14 10-00 10-00 14 10-00 14 10-00 14 10-00 10



1:10

Б



ISTREA	M ELEVATION	٧S							
ATION	O/S	ELEVATION							
+59.50	45.51 RT	622.40							
+75.90	45.51 RT	622.40							
+60.20	46.51 RT	618.90							
+75.20	46.51 RT	618.90							
+60.20	56.02 RT	618.85							
+75.20	56.02 RT	618.85							
+52.73	66.00 RT	621.00							
+44.80	76.60 RT	622.00							
+42.24	81.00 RT	623.00							
+74.97	101.97 RT	621.00							
+66.88	117.25 RT	620.00							
+59.53	136.60 RT	619.00							
+63.64	152.38 RT	619.00							
+55.00	156.50 RT	620.00							
+60.86	174.15 RT	618.50							





SCALE: 1" = 10

REVISION DATE GRAPHIC SCALE (IN FEET) 15 30 1" = 10' TE OF TA CARLOS LUNA III 125042 Å, 6/24/2020 SIONAL EN MAESTAS BIZ2 DATAPOINT OR. 51 SAN ANTONIO, TX 7822 (210) 366-1988 TBFF No: 1:019506 11550 IH 10 WEST, SUITE 395 SAN ANTONIO, TEXAS 78230-1037 TEL: (210) 641-5949 JFAX: (210) 641-544 TBPL REGISTRATION NO.: F-2214 TBPLS REGISTRATION NO.: 100410-00 CEC WATSON ROAD WATSON ROAD **UPSTREAM RIPRAP** CULVERT DETAILS STA 110+64.09 SHEET 2 OF 2 Texas Department C 2017 of Transportation EED F FEDERAL AID PROJECT NO. PLAN S DIV.NO NO. 151 6 STATE DIST. COUNTY TX SAT BEXAR JOB HIGHWAY / STREET CONT. SECT. 0915 12 562 WATSON RD









STA O/S LT FS FL BS 7400.00 51.5 5.9:1 623.25 10.8:1 7400.00 51.5 5.9:1 623.25 10.8:1 7400.00 51.5 5.9:1 623.25 10.8:1
--









I.tbl BW_PDF_ @ 11:38:3 PLOTTED BY: ivette PLOTTED SCALE: 1:50 PEN TABLE: M058_pentbl.tb PLOT DRIVER: WATSON_B PLOTTED ON: 6/24/2020 @

pltcfg



tbl.tbl N_BW_PDF_ 20 @ 11:38:3 PLOTTED BY: ivette PLOTTED SCALE: 1:50 PEN TABLE: M058_pentbl.tb PLOT DRIVER: WATSON_B PLOTTED ON: 6/24/2020 @ ivette 1:50

bltcfg

PLOTTED SCALE: 1:5 PEN TABLE: M058_pentbl.tbl PLOT DRIVER: WATSON_BW_PDF_CEC.pltcfg PLOTTED ON: 6/24/2020 @ 11:38:35 AM ivette I E: 1:5 BY: TTED Б





4-WAY INLET TABLE

SA

%

0.7

0.64

1.12

0.61

0.70



WIDTH

2. REFER TO TXDOT CONCRETE RIPRAP STANDARD (CRR) FOR ADDITIONAL NOTES AND REINFORCEMENT DETAILS.

C-C

SB

%

25.36

21.91

31.95

58.85

49.47

1. PROPOSED CONCRETE RIPRAP IN DITCH AND AT 4-WAY INLETS SHALL HAVE CONCRETE TOE DOWNS AS SHOWN IN SECTION DETAIL C-C.

NOTES:

INLET ELEV.

AT FLOWLINE



SLC	PE		POINT ELEVATION									
в	sc	SD	1	2	3	4	5	6				
, 0	%	%	FT.	FT.	FT.	FT.	FT.	FT.				
36	0.81	39.98	623.97	623.37	624.45	623.96	623.37	624.52				
91	0.70	28.15	624.54	624.03	625.00	624.56	624.04	624.95				
95	0.71	18.6	624.57	623.83	624.44	624.57	623.81	624.45				
85	0.61	28.38	624.14	622.70	623.68	624.14	622.70	623.63				
47	0.70	20.83	623.08	621.52	622.79	622.76	621.52	622.79				







PLOTTED BY: PLOTTED SCALE: PEN TABLE: PLOT DRIVER: WATSON_BW_PDF_CEC.pttcfg PLOTTED ON: 11:38:45 AM





- Provide Class "H" concrete in accordance with Item 421 and having a minimum compressive strength of 5,000 psi. Provide Grade 60 reinforcing steel or equivalent area of WWR. Provide typical clear cover of $1\frac{1}{2}$ " to reinforcing steel at interior or exterior walls.
- Walls or slabs with a thickness of 8" or greater require shrinkage and temperature reinforcing steel. Provide 4. steel area = 0.11 in²/ft each way. No substitution is allowed for vertical and horizontal #4 bars in corners.
- Manufacture base and risers to nearest 3" increment.
- Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is ¾".
- Provide lifting devices in conformance with Manufacturer's recommendations. See sheet PDD for sizes, dimensions, and reinforcing steel not shown.
- 10. Provide hole in below grade slab only when PJB is installed with inlet type POD.

INSTALLATION NOTES:

- 1. Inverts (benching) to be provided by Contractor. Concrete or mortar used for invert is subsidiary to junction box.
- Seal tongue and groove joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or ½ the joint depth, whichever is greater.

- Do not grout rubber gasket joints without Manufacturer's recommendation.
 For rigid pipe, cut hole in thin wall panel (K0) 4" Max, 2" Min larger than pipe OD.
 For flexible pipe, consult boot/seal Manufacturer's specification for placement tolerance and hole size. Center pipe in hole and install boot/seal per Manufacturer's specification.

GENERAL NOTES:

- Precast Junction Box consists of base slab, base unit, risers (as required), and below grade slab. 1. Precision for sizes.
 Designed according to ASTM C913.
 Payment for junction box is per Item 465 "Junction Boxes, Manholes, and Inlets" by type and size.

Angle of entry Angle of entry is less than is greater than 7° or equal to 7°

PIPE CONNECTION DETAIL

Connect pipes within 7° of normal to PJB wall. If necessary, use pipe elbow or curved approach alignment to stay within this limit.

SHRINKAGE/TEMPERATURE WHEN REQUIRED. SEE FABRICATION NOTE 4.

(2) ADDITIONAL REBAR #4 @ 2" O.C. EACH WALL 1" TO JOINT

BSHORT / BLONG

ADDITIONAL REBAR #4 EACH WALL 1" TO JOINT

(2) ADDITIONAL REBAR #4 @ 2" O.C. EACH WALL 1" TO JOINT

BSHORT / BLONG

1½" TYP

5

SHRINKAGE/TEMPERATURE WHEN REQUIRED. SEE FABRICATION NOTE 4.

Cover dimensions are clear dimensions, unless noted otherwise.





					MAX D	EPTH = 15 ft.	to top of BA	SE SLAB							MAX D	EPTH = 25 ft.	to top of BA	SE SLAB						
			Base Slab			Base Unit or Riser Walls			Below Grade Reducing S	Slab (w/PJB) Slab (w/PB)			Base Slab			Base Unit or Riser Walls			Below Grade Reducing :	Slab (w/PJB) Slab (w/PB)		(e 3)	IA te 2)	te 2)
	Size	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Reduced Riser Size	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Reduced Riser Size	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Min Height (See Gen Noi	Max HOLE D (See Fab No	Max KO DIA (See Fab No
	ХхҮ	Ashort	Along	BS	Bshort	Blong	W	RWSxRWL or ID	Dshort	Dlong	TS	Ashort	Along	BS	Bshort	Blong	W	RWSxRWL or ID	Dshort	Dlong	TS	BH MIN	HOLE DIA	KO DIA
	ft.	in²/ft	in²/ft	in.	in²/ft	in²/ft	in.	ft. **	in²/ft	in²/ft	in.	in²/ft	in²/ft	in.	in²/ft	in²/ft	in.	ft. **	in²/ft	in²/ft	in.	ft.	in.	in.
(B)	3x3	0.23	0.23	6	0.19	0.19	6	N/A	0.37	0.37	9	0.29	0.29	6	0.24	0.24	6	N/A	0.37	0.37	9	3.5	36	36
(d)	4x4	0.29	0.29	6	0.24	0.24	6	N/A	0.41	0.41	9	0.47	0.47	6	0.38	0.38	6	N/A	0.41	0.41	9	4.5	48	48
Box	3x5	0.29	0.18	6	0.19	0.35	6	N/A	0.48	0.48	9	0.39	0.18	6	0.23	0.59	6	N/A	0.48	0.48	9	3.5	36/60	36/60
tion	4x5	0.36	0.18	6	0.22	0.34	6	N/A	0.42	0.42	9	0.53	0.26	6	0.39	0.59	6	N/A	0.42	0.42	9	4.5	48/60	48/60
lunc	5x5	0.36	0.36	6	0.34	0.34	6	N/A	0.43	0.43	9	0.62	0.62	6	0.59	0.59	6	N/A	0.43	0.43	9	5.5	60	60
ist J	5x6	0.27	0.27	9	0.34	0.45	6	N/A	0.48	0.48	9	0.47	0.45	9	0.38	0.54	8	N/A	0.48	0.48	9	5.5	60/72	60/72
rece	6x6	0.27	0.27	9	0.45	0.45	6	N/A	0.56	0.56	9	0.52	0.52	9	0.54	0.54	8	N/A	0.56	0.56	9	6.5	72	72
ď	8×8	0.46	0.46	9	0.51	0.51	8	N/A	0.45	0.45	12	0.87	0.87	9	0.59	0.59	10	N/A	0.45	0.45	12	8.5	96	72
	3x3	0.23	0.23	6	0.19	0.19	6	N/A	N/A	N/A	N/A	0.29	0.29	6	0.24	0.24	6	N/A	N/A	N/A	N/A	3.5	36	36
	4x4	0.29	0.29	6	0.24	0.24	6	N/A	N/A	N/A	N/A	0.47	0.47	6	0.38	0.38	6	N/A	N/A	N/A	N/A	4.5	48	48
	3x5	0.29	0.18	6	0.19	0.35	6	3x3	0.30	0.34	9	0.39	0.18	6	0.23	0.59	6	3x3	0.40	0.40	9	3.5	36/60	36/60
	4x5	0.36	0.18	6	0.22	0.34	6	3x3	0.30	0.30	9	0.53	0.26	6	0.39	0.59	6	3x3	0.46	0.37	9	4.5	48/60	48/60
	4x5	0.36	0.18	6	0.22	0.34	6	4x4	0.30	0.30	9	0.53	0.26	6	0.39	0.59	6	4x4	0.39	0.39	9	4.5	48/60	48/60
	4x5	0.36	0.18	6	0.22	0.34	6	48"	0.39	0.39	9	0.53	0.26	6	0.39	0.59	6	48"	0.47	0.47	9	4.5	48/60	48/60
	4x5	0.36	0.18	6	0.22	0.34	6	3x5	0.33	0.40	9	0.53	0.26	6	0.39	0.59	6	3x5	0.48	0.48	9	4.5	48/60	48/60
	5x5	0.36	0.36	6	0.34	0.34	6	3x3	0.34	0.34	9	0.62	0.62	6	0.59	0.59	6	3x3	0.53	0.53	9	5.5	60	60
-	5x5	0.36	0.36	6	0.34	0.34	6	4x4	0.36	0.36	9	0.62	0.62	6	0.59	0.59	6	4x4	0.64	0.64	9	5.5	60	60
(PB,	5x5	0.38	0.38	6	0.34	0.34	6	48"	0.36	0.36	9	0.62	0.62	6	0.59	0.59	6	48"	0.64	0.64	9	5.5	60	60
ase	5x5	0.36	0.36	6	0.34	0.34	6	3x5	0.34	0.40	9	0.62	0.62	6	0.59	0.59	6	3x5	0.53	0.53	9	5.5	60	60
st B.	5x6	0.31	0.31	9	0.34	0.45	6	3x3	0.34	0.34	9	0.47	0.45	9	0.38	0.54	8	3x3	0.61	0.50	9	5.5	60/72	60/72
ecas	5x6	0.27	0.27	9	0.34	0.45	6	4x4	0.36	0.45	9	0.47	0.45	9	0.38	0.54	8	4x4	0.74	0.57	9	5.5	60/72	60/72
Pr	5x6	0.29	0.29	9	0.34	0.45	6	48"	0.36	0.45	9	0.47	0.45	9	0.38	0.54	8	48"	0.74	0.57	9	5.5	60/72	60/72
	5x6	0.29	0.29	9	0.34	0.45	6	3x5	0.45	0.45	9	0.47	0.45	9	0.38	0.54	8	3x5	0.61	0.61	9	5.5	60/72	60/72
	6x6	0.29	0.29	9	0.45	0.45	6	3x3	0.41	0.41	9	0.52	0.52	9	0.54	0.54	8	3x3	0.74	0.74	9	6.5	72	72
	6x6	0.27	0.27	9	0.45	0.45	6	4x4	0.45	0.45	9	0.52	0.52	9	0.54	0.54	8	4x4	0.87	0.87	9	6.5	72	72
	6x6	0.29	0.29	9	0.45	0.45	6	48"	0.45	0.45	9	0.52	0.52	9	0.54	0.54	8	48"	0.87	0.87	9	6.5	72	72
	6x6	0.29	0.29	9	0.45	0.45	6	3x5	0.45	0.45	9	0.52	0.52	9	0.54	0.54	8	3x5	0.87	0.87	9	6.5	72	72
	8x8	0.52	0.52	9	0.51	0.51	8	3x3	0.61	0.61	12	0.91	0.91	9	0.70	0.70	10	3x3	0.85	0.85	12	8.5	96	72
	8x8	0.52	0.52	9	0.51	0.51	8	4x4	0.70	0.70	12	0.87	0.87	9	0.70	0.70	10	4x4	1.01	1.01	12	8.5	96	72
	8x8	0.52	0.52	9	0.51	0.51	8	48"	0.70	0.70	12	0.87	0.87	9	0.70	0.70	10	48"	1.01	1.01	12	8.5	96	72
	8×8	0.52	0.52	9	0.51	0.51	8	3x5	0.70	0.85	12	0.87	0.87	9	0.70	0.70	10	3x5	1.01	1.01	12	8.5	96	72

** Unless otherwise indicated.

FABRICATION NOTES:

PABRICATION NOTES:
1. Maximum spacing of reinforcement is 8".
2. At manufacturer's option, provide cast or cored holes or thin wall panels (KO) to the maximum diameter shown for each. When no penetration is required, it is acceptable to provide a wall with no sectional reduction.

GENERAL NOTES:

- Precast Junction Box consists of base slab, base unit, risers (as required), and below grade slab. See sheet PJB for details.
 Precast Base consists of base slab, base unit, risers (as required), reducing slab (as
- Precast base consists of base stab, base diff, fisers (as required), reducing stab (a required), and reduced risers (as required). See sheet PB for details.
 Min Height shown is for stock base units. Use stock base units whenever practical. Smaller height base units can be used in special installation circumstances, when noted elsewhere in the plans. Absolute minimum height of base units is 2'-6".





HS20 LOADING			SHEE	Т	1 OF	2
Texas Department	of Tra	ansp	ortation	,	Bri Div Sta	dge vision andard
PRECAST	- C	Uŀ	RB I	N	LET	Г
OUTSID	PE I	RC	ADV	V,	4 <i>Y</i>	
				\sim		
			PC	\mathbf{O}		
FILE: prestd03.dgn	DN: TX	DOT	ск: ТхD0Т	DW:	TxD0T	ск: ТхD0Т
CTxDOT January 2015	CONT	SECT	JOB		ŀ	HIGHWAY
REVISIONS						
	DIST		COUNTY			SHEET NO.
						164



LID PLAN VIEW

(SHOWING LEFT AND RIGHT EXTENSIONS)

THROAT PLAN VIEW (SHOWING LEFT AND RIGHT EXTENSIONS)

FABRICATION NOTES:

- Provide Class "H" concrete in accordance with Item 421 and having a minimum compressive strength of 5,000 psi.
 Provide Grade 60 reinforcing steel or equivalent area of WWR.
 Extensions may be right, left, both or none. Provide extensions as specified elsewhere in the plans.

- 4. Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is $\frac{3}{4}$ ".
- Lid may employ a butt joint with dowels at the Contractor's option. 5. Provide lifting devices in conformance with Manufacturer's recommendations. 6. Provide cast iron solid cover, unless noted otherwise elsewhere in the plans.
- 7. Chamfer vertical edges of inlet lid $\mathscr{Y}_4^{"}$ as shown in Front View, sheet 1.

INSTALLATION NOTES:

- Inlet throat and lid are not intended for direct traffic. Do not place in roadway.
 Seal tongue and groove joints and butt joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or ¹/₂ the joint depth, whichever is greater.
- 3. Do not grout rubber gasket joints without Manufacturer's recommendation.

GENERAL NOTES:

- 1.
- Designed according to ASTM C913. Open area of main throat = 360 sq in. Open area of one extension throat = 324 sq in. Payment for inlet is per Item 465, "Junction Boxes, Manholes, and Inlets" by type, size, and extension placement. 3. Extensions are subsidiary to inlet.

Cover dimensions are clear dimensions, unless noted otherwise.

SIZE(Y)	Ν	MH DIA*	Ra
3'	9"	18"	(4) #5 Additional
4'	16"	32"	(4) #5 Additional
5'	16"	32"	(4) #5 Additional
6'	16"	32"	(4) #5 Additional

* Nominal ring and cover size.

HS20 LOADING			SHEE	2 OF 2										
Texas Department	,	Bridge Division Standard												
PRECAST	PRECAST CURB INLET													
OUTSIDE ROADWAY														
				\sim										
			PC	\mathcal{O}										
FILE: prestd03.dgn	DN: TXE	D0T	ск: ТхD0Т	DW:	T x D0T	ск: ТхДОТ								
©TxDOT January 2015	CONT	SECT	JOB		н	IGHWAY								
REVISIONS														
	DIST COUNT													
						165								



CONSTRUCTION NOTES: Align top face of curb with PCO Inlet as shown.

MATERIAL NOTES: Provide ½" Preformed Bituminous Fiber Material.

GENERAL NOTES:

See Precast Curb Inlet Outside Roadway (PCO) standard for details and notes not shown. See Concrete Curb and Curb and Gutter (CCCG-12) standard for details and notes not shown. Curb and Gutter Transitions is paid for and in accordance with Item 529, "Concrete Curb, Gutter, and Combined Curb and Gutter. Preformed Bituminous Fiber Material is subsidiary to PCO Inlet.

Texas Department	Texas Department of Transportation												
CURB AND GUTTER													
TRANSITION DETAILS													
FOR PCO INLET													
	C	\sim		h									
	C	GI	-PCC)									
FILE: prestd13.dgn	DN: TX	D0T	CK: AES D	v: JTR	CK: AES								
CTxDOT January 2015	CONT	SECT	JOB		HIGHWAY								
REVISIONS													
	DIST		COUNTY		SHEET NO.								
					166								



SAT

BEXAR

167



2"

THROAT PLAN VIEW (Shown without extensions)



LID SECTION A-A





(Showing reinforcing bar extended from pecast base or precast riser or precast slab lid style "S1".)

No warranty of any bility for the conversion ng Practice Act" mes no responsi DISCLAIMER: The use of this standard is governed by the "Texas Engi kind is made by TXDDT for any purpose whatsoever. TXDDT of this standard to other formats or for incorrect

DATE: 6/24/2020 11:38:59 AM FILE: Z:NProjects\Watson Road\S







- 3 Matches inside face of wall of precast base or precast riser or precast slab lid style "51" below inlet.
- $\overset{\textcircled{4}}{=}$ Cut reinforcing bars as needed to provide 1 $\frac{1}{2}$ " clear to manhole.
- 5 Extend reinforcing bars from precast base or precast riser or precast slab lid style "51" 7".
- Extend reinforcing bars from precast base or precast riser or precast slab lid style "S1" 1'-7 ½".

HL93 LOADING			SHEE	Т2	OF 4								
Texas Department	of Tra	nsp	ortation	Bridge Division Standard									
CAST-IN-PLACE CURB													
INLET OUTSIDE ROADWAY													
			ССС)									
FILE: ccostds1-20.dgn	DN: TXE	D0T	CK: TXDOT DI	v: TxD01	ск: ТхДОТ								
CTxDOT February 2010	CONT	SECT	JOB		HIGHWAY								
REVISIONS	0915	12	562	WA	TSON RD								
	DIST		COUNTY		SHEET NO.								
	SAT		BEXAR		168								



No warranty of any lity for the conversion ractice no resp . TxDOT by the vhatsoe governed purpose v DISCLAIMER: The use of this standard is kind is made by TxDOT for any of this forded to about form

6/24/2020 11:39:00 AM Z:\Proiects\Watson Rogo



No warranty of any lity for the conversion by hat rnec Se for DISCLAIMER: The use of this standar Kind is made by TXDOT for of this created

6/24/2020 11:39:01 AM Z:\Projects\Watson Road





CUDR INFET EVTENSION											
<u>COND INLET EXTENSION</u>											
TYPE C-E											
© 1999 🛹 Texas Department of Transportation											
SHEET 2 OF 2											
FED. RD. DIV. NO. PROJECT NO. SHEE NO.											
6											
STATE DISTRICT COUNTY											
TEXAS SAT											
8/01											

UPSTREAM END OF THE INLET. FOR CURB INLET EXTENSION REINFORCING STEEL, NOTES & VARIOUS OTHER APPLICABLE DETAILS NOT FOUND ON THIS SHEET, REFER TO SHEET 1.

WHEN INLET EXTENSIONS ARE REQUIRED FOR ON GRADE INLETS THE EXTENSION (S) SHALL BE PLACED ON THE

★ FOR CONTRACTOR'S INFORMATION ONLY. NO DEDUCTION MADE FOR PIPES. QUANTITIES SHOWN ARE FOR "H" = 4'-10". "H" MAY VARY

	REINFORCING STEEL												
E	STIMATE	D QUANT	ITIES - (EXTENSIO	N)								
BAR	NO.	SIZE	SPAC	LENGTH	WEIGHT								
Α	29	#4	5"	9′-8"	187								
В	5	#5	3"	11'-5"	60								
С	20	#5	6"	2'-11"	61								
F	12	#4	11"	14'-1"	113								
G	4	#4	11"	1'-11"	5								
н	6	#4	11"	2'-2"	9								
Р	4	#5	-	2′-2"	9								
м	3	#4	10"	11'-5"	23								
D	2	#5	-	5′-0"	11								
TOTAL	- REIN	F. STEE	L - LBS.		478 X								
TOTAL	- CLAS	s "C" C	ONC C	۲.	3.55 X								
TOTAL	TOTAL - CLASS "C" CONC CY. DEPRESSION SLAB												



1 Matches inside face of wall of precast base or riser below inlet.

FABRICATION NOTES:

- 1. Provide Class "H" concrete in accordance with Item 421 and having a minimum compressive strength of 5,000 psi.
- Provide Grade 60 reinforcing steel or equivalent area of WWR. Provide clear cover of ¾" to reinforcing from bottom of slab for structural reinforcement. Place short span reinforcing closest to surface.
- No substitution is allowed for diagonal #4 bars around openings.
 Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is ³/₄".
- 6. Provide lifting devices in conformance with Manufacturer's recommendations.

INSTALLATION NOTES:

- 1. PAZD is for use in ditches and medians outside of the horizontal clearance (clear zone). Precast Area Zone Drain is not intended for direct traffic and may not be placed in roadway.
- Seal tongue and groove joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or ½ the joint depth, whichever is greater.
- 3. Do not grout rubber gasket joints without Manufacturer's recommendation.

GENERAL NOTES:

- Designed according to ASTM C913. Payment for inlet is per Item 465, "Junction Boxes, Manholes, and Inlets" by type, style, size, and opening size (when applicable).

Construct cast-in-place reinforced concrete apron when shown elsewhere in plans. Use Class "A" concrete. Apron is subsidiary to PAZD. Apron is 1'-6" Min width around precast zone drain.



DETAIL "A"

(Reinforcing not shown for clarity) When an apron is to be cast around PAZD, use detail above to create an apron ledge on all 4 sides.

warranty of any for the conversior

No

by hat se

DISCLAIMER: The use of this standard is kind is made by TxDOT for any



FILE: prestd08.dgn	DN: TX	D0T	CK: TXDOT DV		TxD0T	ск: TxD0T	
CTxDOT January 2015	CONT	SECT	JOB		HIGHWAY		
REVISIONS							
	DIST		COUNTY			SHEET NO.	
						17.3	



DE SIGN TRUCTURE

E	ESTIMATED QUANTITIES FOR REINFORCING STEEL											
BAR	NO.	SIZE	SPAC.	LENGTH	WEIGHT							
G	7	•4	/3'- 9"	64								
н	5	4′- 6"	15									
J	J 6 •4 8* 5'-0'											
TOTAL W	TOTAL WEIGHT * LBS. 99											
CONCRET	TE FOR F	OUNDATION	· *	с.ү.	0.47							
CONCRET	re FOR G	UTTER DE	PRESSION	* C.Y.	0.78							
STRUC	TURAL S	STEEL F	OR ARM	OR CURE	B SLOT							
STUD A	NCHORS (1/	2"DIA.)		LBS.	3.5							
STEEL F	PLATE			LBS.	45/							
TOTAL W	EIGHT *			LBS.	454.5							

NOR CURB SLOT ©"	998	of	Tran	sportat	ion
	FED.RD.	PRO	JECT NO.		SHEET
H CONCRETE FOUNDATION	6				174
ANNA DISTRIAT STANDARDS	STATE	STATE DISTRICT	TE COU		
UNIU DISTRICT STANDARDS	TEXAS	SAT			
10/95	CONT.	SECT.	JOB	H1GHWAY	NO.
REV.07/0/					



DATE: FILE:

Style	Sizo (X × X)	w (2)	A v B (nominal)	Short Span Reinf Steel	Long Span Reinf Steel
June	5120 (/ / /)		A X D (nominal)	Area	Area
SL	3' x 3'	6"	n/a	0.37 in²/ft	0.37 in²/ft
RH,RC,RG,SH,S1,FG	3' x 3'	6"	3'x3' or 32" Dia	0.37 in²/ft	0.37 in²/ft
SFG	3' x 3'	6"	3' x 3'	0.32 in²/ft	0.32 in²/ft
SL	4' x 4'	6"	n/a	0.34 in²/ft	0.34 in²/ft
RH,RC,RG,SH,S1,FG	4' x 4'	6"	3'x3' or 32" Dia	0.41 in²/ft	0.41 in²/ft
SH,S1,FG	4' x 4'	6"	4' x 4'	0.41 in²/ft	0.41 in²/ft
SFG	4' x 4'	6"	4' x 4'	0.32 in²/ft	0.32 in²/ft
SL	3' x 5'	6"	n/a	0.39 in²/ft	0.39 in²/ft
RH,RC,RG,SH,S1,FG	3' x 5'	6"	3'x3' or 32" Dia	0.48 in²/ft	0.48 in²/ft
SH,S1,FG	3' x 5'	6"	3' x 5'	0.48 in²/ft	0.48 in²/ft
SFG	3' x 5'	6"	3' x 5'	0.32 in²/ft	0.32 in²/ft
SL	4' x 5'	6"	n/a	0.42 in²/ft	0.42 in²/ft
RH,RC,RG,SH,S1,FG	4' x 5'	6"	3'x3' or 32" Dia	0.42 in²/ft	0.42 in²/ft
SH,S1,FG	4' x 5'	6"	4' x 4'	0.63 in²/ft	0.63 in²/ft
SH,S1,FG	4' x 5'	6"	3' x 5'	0.66 in²/ft	0.66 in²/ft
SL	5' x 5'	6"	n/a	0.36 in²/ft	0.36 in²/ft
RH,RC,RG,SH,S1,FG	5' x 5'	6"	3'x3' or 32" Dia	0.43 in²/ft	0.43 in²/ft
SH,S1,FG	5' x 5'	6"	4' x 4'	0.63 in²/ft	0.63 in²/ft
SH,S1,FG	5' x 5'	6"	3' x 5'	0.63 in²/ft	0.63 in²/ft
SL	5' x 6'	6"/8"	n/a	0.48 in²/ft	0.48 in²/ft
RH,RC,RG,SH,S1,FG	5' x6'	6"/8"	3'x3' or 32" Dia	0.48 in²/ft	0.48 in²/ft
SH,S1,FG	5' x6'	6"/8"	4' x 4'	0.60 in²/ft	0.60 in²/ft
SH,S1,FG	5' x6'	6"/8"	3' x 5'	0.60 in²/ft	0.60 in²/ft
SL	6' x 6'	6"/8"	n/a	0.43 in²/ft	0.43 in²/ft
RH,RC,RG,SH,S1,FG	6' x 6'	6"/8"	3'x3' or 32" Dia	0.56 in²/ft	0.56 in²/ft
SH,S1,FG	6' x 6'	6"/8"	4' x 4'	0.56 in²/ft	0.56 in²/ft
SH,S1,FG	6' x 6'	6"/8"	3' x 5'	0.59 in²/ft	0.59 in²/ft
SL	8' x 8'	8"/10"	n/a	0.45 in²/ft	0.45 in²/ft
RH,RC,RG,SH,S1,FG	8' x 8'	8"/10"	3'x3' or 32" Dia	0.45 in²/ft	0.45 in²/ft
SH,S1,FG	8' x 8'	8"/10"	4' x 4'	0.45 in²/ft	0.45 in²/ft
SH,S1,FG	8' x 8'	8"/10"	3' x 5'	0.45 in²/ft	0.45 in²/ft

(2) See sheet PDD for corresponding wall thickness (W) of base unit or riser.

Construct cast-in-place reinforced concrete apron, when shown elsewhere in plans. Use Class "A" concrete. Apron is subsidiary to PSL. Apron is 1'-6" Min width around precast zone drain.



DETAIL "A"

(Reinforcing not shown for clarity) When an apron is to be cast around PSL, use detail above to create an apron ledge on all 4 sides.

FABRICATION NOTES:

1. Locate penetration (Style 'RH'), ring and cover (Style 'RC'), ring and grate (Style 'RG'), and frame and grate (Style 'FG') in a corner. Only one penetration is allowed per slab lid.

Statistical Statis Statistical Statistical Statistical Statistical Statistica

structural reinforcement, and 2" from top of slab for shrinkage and temperature reinforcement. Place short span reinforcing closest to surface. Slabs with a thickness of 8" or greater require shrinkage and temperature

reinforcing. Provide steel area = 0.11 in²/ft each way.

No substitution is allowed for diagonal #4 bars around openings. Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is $\frac{3}{4}$ ".

8. Provide lifting devices in conformance with Manufacturer's recommendations.

INSTALLATION NOTES:

5.

6. 7.

1. Precast slab lids are intended for direct traffic and may be placed in roadway. Seal tongue and groove joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or ½ the joint depth, whichever is greater.

 Do not grout rubber gasket joints without Manufacturer's recommendation.
 Initial installation of grade adjustment rings for Styles 'RH' and 'SH' is limited to 1'-O" Max as shown.

5. Grade adjustment rings for Styles 'RH' and 'SH' may be increased to 2'-0" Max when future construction affects final grade of structure. Make adjustments greater than 2'-0" with additional risers. Adjustments can be made up to Max depth shown on sheet PDD. Structure must be evaluated if Max depth will be

exceeded.6. Orient long dimension of grate slots perpendicular to traffic, unless noted otherwise on plans

GENERAL NOTES:

 Designed according to ASTM C913.
 Payment for lid is per Item 465, "Junction Boxes, Manholes, and Inlets" by type, style, size, and opening size (when applicable).

Cover dimensions are clear dimensions, unless noted otherwise.

HL93 LOADING			SHEET	20	DF 2							
Texas Department of Transportation												
PRECAST SLAB LID												
			PS	L								
FILE: prestd05.dgn	DN: TXE	D0T	ςκ: ΤxD0Τ ι	ow: TxDO	т ск: ТхДОТ							
CTxDOT January 2015	CONT	SECT	JOB		HIGHWAY							
REVISIONS			23-01627	r								
	DIST		COUNTY		SHEET NO.							
					176							

							E	BOX	DATA	A						
	SEC	TION	DIME	NSIC	NS	Fill	м			REI	NFORC	ING (i	1 ² ∕f†)	2		1 ift
	S	H			T _S	Height	(Min)	A _{S1}	A _{S2}	A _{S3}	A _{S4}	A _{S5}	A _{S6}	A _{S7}	A ₅₈	Weight (Tons)
	3	2	7	6	4	(11)	-	0.17	0.25	0.16	0.10	0.17	0.17	0.17	0.14	3.3
ĺ	3	2	4	4	4	2<3	31	0.13	0.19	0.18	0.10	-	-	-	-	2.4
	3	2	4	4	4	3-5	31	0.10	0.11	0.12	0.10	-	-	-	-	2.4
	3	2	4	4	4	10	31	0.10	0.10	0.10	0.10	-	-	-	-	2.4
	3	2	4	4	4	15	31	0.10	0.13	0.13	0.10	-	-	-	-	2.4
	3	2	4	4	4	20	31	0.14	0.77	0.21	0.10	-	_	-	_	2.4
	3	2	4	4	4	30	31	0.17	0.25	0.25	0.10	-	-	-	-	2.4
ľ	3	2	4	4	4	35	31	0.20	0.29	0.30	0.10	-	-	-	-	2.4
Ī	3	3	7	6	4	<2	-	0.17	0.27	0.17	0.10	0.17	0.17	0.17	0.14	3.7
	3	3	4	4	4	2<3	31	0.10	0.22	0.21	0.10	-	-	-	-	2.8
	3	3	4	4	4	3-5	31	0.10	0.14	0.14	0.10	-	-	-	-	2.8
	3	3	4	4	4	10	31	0.10	0.11	0.11	0.10	-	-	-	-	2.8
	<u>२</u>	<u> </u>	4 4	4 4	4 4	20	<u>।</u> रा	0.10	0.14	0.15	0.10	-	-	-	-	2.8
	3	3	4	4	4	25	31	0.10	0.23	0.23	0.10	-	-	-	-	2.8
	3	3	4	4	4	30	31	0.12	0.27	0.28	0.10	-	-	-	-	2.8
	3	3	4	4	4	35	31	0.14	0.32	0.32	0.10	-	-	-	-	2.8
ľ																
																<u> </u>
[
		1	1	1	1	1			1	1	1		1	1	1	



FILL HEIGHT 2 FT AND GREATER



JOINT REINFORCEMENT)

No warranty of any lity for the conversion ractice Act" no respons exas Engi TxDOT by t /hat: governed purpose v DISCLAIMER: The use of this standard is wind is made by TxDD for any of this standard to other form

(1) For Box Length = 8'-0"

(2) As1 thru As4, As7 and As8 are minimum required areas of reinforcement per linear foot of box length. AS6 and AS5 are minimum required areas of reinforcement per linear foot of box width.



							E	зох	DATA	A						
	SEC	TION	DIME	NSIC	NS	FILL	м			REIM	NFORC	ING (i	ר ² /f†)	2		
	S (f+)	H (f+)	T _T	T _B	T _s	Height	(Min)	A _{S1}	A _{S2}	A _{S3}	A _{S4}	A _{S5}	A _{S6}	A _{S7}	A _{S8}	Weight (Tons)
ł	4	2	7.5	6	5	<2	-	0.18	0.27	0.15	0.12	0.18	0.18	0.18	0.14	4.5
	4	2	5	5	5	2<3	38	0.18	0.19	0.17	0.12	-	-	-	-	3.6
	4	2	5	5	5	3-5	38	0.13	0.13	0.13	0.12	-	-	-	-	3.6
╞	4	2	5	5	5	10	38	0.12	0.12	0.12	0.12	-	-	-	-	3.6
┟	4	2	5	5	5	20	38 38	0.14	0.16	0.16	0.12	-	-	-	-	3.6
ł	4	2	5	5	5	25	38	0.23	0.20	0.25	0.12	-	-	-	-	3.6
ł	4	2	5	5	5	30	38	0.28	0.30	0.30	0.12	-	-	-	-	3.6
Ī																
	4	3	7.5	6	5	<2	-	0.18	0.31	0.18	0.12	0.18	0.18	0.18	0.14	5.0
╞	4	3	5	5	5	2<3	38	0.15	0.23	0.20	0.12	-	-	-	-	4.1
╞	4	3	5	5	5	3-5	38	0.12	0.16	0.16	0.12	-	-	-	-	4.1
┟	4	<u> </u>	5	5	5	15	58 79	0.12	0.14	0.14	0.12	-	-	-	-	4.1
┟	4	3	5	5	5	20	38	0.14	0.23	0.24	0.12	-	-	-	-	4.1
┟	4	3	5	5	5	25	38	0.17	0.29	0.29	0.12	-	-	-	-	4.1
Ī	4	3	5	5	5	30	38	0.21	0.35	0.35	0.12	-	-	-	-	4.1
Ī																
	4	4	7.5	6	5	<2	-	0.18	0.33	0.20	0.12	0.18	0.18	0.18	0.14	5.5
	4	4	5	5	5	2<3	38	0.12	0.26	0.23	0.12	-	-	-	-	4.6
╞	4	4	5	5	5	3-5	38	0.12	0.18	0.18	0.12	-	-	-	-	4.6
╞	4	4	5	5	5	10	38	0.12	0.15	0.15	0.12	-	-	-	-	4.6
ŀ	4	4	5	5	5	20	38	0.12	0.79	0.20	0.12	-	-	_	_	4.6
ł	4	4	5	5	5	25	38	0.14	0.31	0.31	0.12	-	-	-	-	4.6
ł	4	4	5	5	5	30	38	0.17	0.37	0.37	0.12	-	-	-	-	4.6
╞																
╞																
ŀ																
ł																
ł																
╞																
╞																
┟																
┟																
ŀ																
ľ																
ļ																
╞																
╞																
┟																
┟																
f																
Ī																
ſ																
╞																
╞																<u> </u>
- 1		1	1	1	1	1	1	1	1	1	1		1	1	1	I



FILL HEIGHT 2 FT AND GREATER



JOINT REINFORCEMENT)

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

(1) For Box Length = 8'-0"

(2) As1 thru As4, As7 and As8 are minimum required areas of reinforcement per linear foot of box length. As6 and As5 are minimum required areas of reinforcement per linear foot of box width.





(1) 0" min to 5'-0" max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail, bicycle rail or curbs taller than 1'-0", refer to ECD standard. For structures with T6 traffic rail, refer to T6-CM standard. For structures with traffic rail, other than T6, refer to RAC standard.

(2) For curbs less than 1'-0" high, tilt Bars K or reduce bar height as necessary to maintain cover. For curbs less than 3" high, Bars K may be omitted.

Curb, Wingwall or Safety End Treatment reinforcing shall extend into concrete closure. Any reinforcing that does not fit into the closure shall be bent or trimmed as necessary.

(4) Cast-in-place concrete closure shall be 3'-0" min. Boxes shall be cast short or broken back in the field. All reinforcing in Boxes shall the closure shall be the same size and spacing as in the precast box section. Except where shown otherwise, the cast-in-place closure shall be flush with the inside and outside faces of the precast box section.

(5) For multiple unit placements the length of the closure for the interior walls may be adjusted as necessary. The length of the top slab, bottom slab, and exterior wall closure shall not be less than 3'-0". See Section B-B detail when interior walls are cast full length.

6 Precast box reinforcing shall extend a minimum of 1'-0" into concrete closure (Typ).

7 Bands of reinforcing matching the inside and outside face reinforcing shall be placed in the gaps of the top and bottom slabs. A band matching the outside face reinforcing of the wall shall be placed in the gaps of the walls (placed in the outside face only). The bands shall be tack welded to the exposed reinforcing at each point of contact.

8 For vehicle safety, the following requirements must be met: - For structures without bridge rail, curbs shall project no more than 3" above finished grade.

For structures with bridge rail, curbs shall be flush with finished grade.

Curb heights shall be reduced, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.

Cement Stabilized Backfill between boxes is considered part of the Box Culvert for payment.

All curb concrete and reinforcing is considered part of the Box Culvert for payment.

Any additional concrete and reinforcing required for the closures shall be considered as subsidiary to the Concrete Box Culvert.

1'-0" typical. 2'-0" when RAC standard is referred to elsewhere in the plans.

(13) For multiple unit placement with overlay, with 1 to 2 course surface treatment, or with the top slab as the final riding surface, provide wall closure as shown in DETAIL "A".

(14) This dimension may be increased with approval of the Engineer to allow the precast boxes to be tunneled or jacked in accordance with Item 476, "Jacking, Boring, or Tunneling Pipe or Box". No payment will be made for any additional material in the gap between adjacent boxes.

GENERAL NOTES:

Designed according to AASHTO LRFD Specifications.

All closure concrete shall be Class "C" with a minimum compressive strength of 3600 psi and shall be placed according to the Item, "Concrete Substructures". Any additional concrete required for the closures shall be

considered as subsidiary to the Concrete Box Culvert. Refer to the Single Box Culverts Precast standard for details

The bottom edge of the top slab closure shall be chamfered 3 inches at the entrance.

HL93 LOADING

Texas Department of Transportation				Bridge Division Standard	
BOX CULVERTS					
PRECAST					
MISCELLANEOUS DETAILS					
SCP-MD					
FILE: scpmdsts.dgn	DN: GAF		ск: LMW	DW: B	NH/TxDOT CK: GAF
CTxDOT February 2010	CONT	SECT	JOB		HIGHWAY
REVISIONS					
	DIST	COUNTY SHEET NO.			


- (1) Extend Bars P 3'-0" minimum into bottom slab of Box Culvert.
- Adjust to fit as necessary to maintain 1 $^{\prime}\!\!/_4$ " clear cover and 4" minimum between bars. 2
- Quantities shown are based on an average wing height (3) for two wings (one structure end). To determine total quantities for two wings multiply the tabulated values by Lw.
- (4)Recommended values of Slope are: 2:1, 3:1, 4:1, & 6:1.
- 5 When shown elsewhere on the plans, a 5" deep concrete riprap shall be constructed. Payment for riprap shall be as required by Item 432, "Riprap". Unless otherwise shown on the plans or directed by the Engineer, the riprap shall have a 6" wide by 1'-6" deep reinforced concrete toewall along all edges adjacent to natural ground; the toewall shall be reinforced by extending typical riprap reinforcing into the toewall; construction joints or grooved joints, oriented in the direction of flow, shall extend across the full distance of the riprop, at intervals of approximately 20'. When such riprop is provided, the culvert toewall shown in SECTION B-B will not be required.
- At Contractor's option, Culvert Toewall may be ended flush with Wingwall Toewall. Adjust reinforcing (6) from that shown as necessary.
- (7) 0" min to 5'-0" max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail, bicycle rail or curbs taller than 1'-0", refer to ECD standard. For structures with T6 bridge rail, refer to T6-CM standard. For structures with traffic rail, other than T6, refer to RAC standard.
- (8) For vehicle safety, curb heights and wall heights shall be reduced, if necessary, to provide a maximum 3" projection above finished grade. No changes will be made in quantities and no additional compensation will be allowed for this work.

GENERAL NOTES:

Designed according to AASHTO LRFD Specifications. All reinforcing steel shall be Grade 60. Synthetic fibers listed on the "Fibers for Concrete" Matérial Producer List (MPL) may be used in lieu of steel reinforcing in riprap concrete unless noted otherwise.

All concrete shall be Class "C" and shall have a minimum compressive strength of 3600 psi. All reinforcing bars shall be adjusted to provide a minimum of $1\frac{1}{4}$ " clear cover.

When structure is founded on solid rock, depth of toewalls for culverts and wingwalls may be reduced or eliminated as directed by the Engineer. See BCS sheet for additional dimensions and information. The quantities for concrete and reinforcing steel

resulting from the formulas given on this sheet are for Contractor's information only.

Texas Department	Bridge Division Standard							
CONCRETE WINGWALLS								
WITH FLARED WINGS FOR								
0° SKEW I	во)	((CULV	Έŀ	RTS			
			FW	'-C)			
FILE: fw-Ostde.dgn	DN: GA	-	ск: САТ	DW:	TxD0T	ск: GAF		
CTxDOT February 2010	CONT	SECT	JOB		HIGHWAY			
REVISIONS								
11–10: Add note for synthetic fibers.	DIST	COUNTY		Y		SHEET NO.		
, , , , , , , , , , , , , , , , , , ,						180		



1 Skew Angle = 0° $^{\scriptsize (2)}$ At discharge end, chamfer may be $\rlap{0.4ex}{4}$ ". (3) For 15° Skew ~ 1" For 30° Skew ~ 2" For 45° Skew ~ 3"

- (4) Quantities shown are for two Type PW-1 wings. Adjust concrete volume for Type PW-2 wings. To determine estimated quantities for two wings, Quantities shown do not include weight of Bars D.
- (5) Provide weepholes for Hw = 5'-0" and greater. Fill around weepholes with coarse gravel.
- $^{(6)}$ Extend Bars E2 1′-6" minimum into the wingwall footing.
- $^{(7)}$ Lap Bars Mı 1'-6" minimum with Bars M2.
- 8 Bars G equally spaced at 8" maximum, place as shown. Provide at least two pair Bars G per wing.
- 9 0" min to 5'-0" max. Estimated_curb heights are shown elsewhere in the plans. For structures with pedestrian rail, bicycle rail or curbs taller than 1'-0", refer to ECD standard. For structures with T6 bridge rail, refer to T6-CM standard. For structures with traffic rail, other than T6, refer to RAC standard.
- (10) For vehicle safety, the following requirements must be met: - For structures without bridge rail, curbs
 - cannot project more than 3" above finished grade. - For structures with bridge rail, build curbs
- Flush with finished grade. Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.
- (11)1'-0" typical. 2'-0" typical when RAC standard is referenced elsewhere in the plans.
- (12) 3' 0'' for Hw < 4'.
- (13) 6" for Hw < 4'.

GENERAL NOTES:

Designed in accordance with AASHTO LRFD Bridge Design Specifications. Provide Class_"C" Concrete (f'c = 3,600 psi Min)

and Grade 60 reinforcing steel. Provide 1 1/4" Min clear cover to reinforcing steel. Depth of toewalls for wingwalls and culverts may be reduced or eliminated when founded on solid rock, when directed by the Engineer.

See BCS sheet for wingwall type and additional dimensions and information.

The quantities for concrete and reinforcing steel resulting from the formulas given on this sheet are for the Contractor's information only.

DESIGNER NOTES:

Type PW-1 can be used for all applications and must be used if railing is to be mounted to the wingwall. Type PW-2 can only be used for applications without a railing mounted to the wingwall.

Image: Second standardBridgeImage: Second standardDivisionStandardStandard								
CONCRETE WINGWALLS								
WITH PARALLEL WINGS FOR								
BOX	JUL	VE	RIS					
TYPES PW	'-1 A	٩N	DРИ	1-2	2			
			Ρ	W	,			
FILE: pwstde01.dgn	DN: GAR	-	ск: САТ	DW:	T x D0T	ск: GAF		
©TxDOT February 2010	CONT	SECT	JOB			HIGHWAY		
REVISIONS								
11–10: Reinforcing Quantities. 01–12: PW–1 & PW–2.	DIST		COUNTY	·		SHEET NO.		
						181		



this stan TxDOT 1 he he

- (1) Extend Bars P 3'-0" minimum into bottom slab of Box Culvert.
- 2 Adjust to fit as necessary to maintain 1 1/4" clear cover and 4" minimum between bars.
- 3 Quantities shown are based on an average wing height for two wings (one structure end). To determine total quantities for two wings multiply the tabulated values by Lw.
- (4) Recommended values of Slope are: 2:1, 3:1, 4:1, & 6:1.
- (5) When shown elsewhere on the plans, a 5" deep concrete riprop shall be constructed. Payment for riprop shall be as required by Item 432, "Riprop". Unless otherwise shown on the plans or directed by the Engineer, the riprop shall have a 6" wide by 1'-6" deep reinforced concrete toewall along all edges adjacent to natural ground; the toewall shall be reinforced by extending typical riprap reinforcing into the toewall; construction joints or grooved joints, oriented in the direction of flow, shall extend across the full distance of the riprap, at intervals of approximately 20'. When such riprap is provided, the culvert toewall shown in SECTION B-B will not be required.
- 6 At Contractor's option, Culvert Toewall may be ended flush with Wingwall Toewall. Adjust reinforcing from that shown as necessary,
- (7) 0" min to 5'-0" max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail, bicycle rail or curbs taller than 1'-0", refer to ECD standard. For structures with T6 bridge rail, refer to T6-CM standard. For structures with traffic rail, other than T6, refer to RAC standard.
- 8 For vehicle safety, curb heights and wall heights shall be reduced, if necessary, to provide a maximum 3" projection above finished grade. No changes will be made in quantities and no additional compensation will be allowed for this work.

GENERAL NOTES:

Designed according to AASHTO LRFD Specifications. All reinforcing steel shall be Grade 60. Synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing in riprop concrete unless noted otherwise.

All concrete shall be Class "C" and shall have a minimum compressive strength of 3600 psi.

All reinforcing bars shall be adjusted to provide a minimum of 1 $\frac{1}{4}$ " clear cover. When structure is founded on solid rock, depth of toewalls for culverts and wingwalls may be reduced or eliminated as directed by the Engineer. See BCS sheet for additional dimensions and

information. The quantities for concrete and reinforcing steel resulting from the formulas given on this sheet are for Contractor's information only.





this star TYDOT he he



	ΤΥ	ΡE	PR	11			
LE: rlstd028-18.dgn	DN: TA	R	ск: ТВЕ	DW:	JTR		ск: TAR
TxDOT March 2018	CONT	SECT	JOB			HIG	HWAY
REVISIONS							
	DIST	COUNTY				SHEET NO.	
							184



No warranty of any lity for the conversion act 10 / Engi ×D0T by t /hat: 'nec Se for gover purpo DISCLAIMER: The use of this standard is kind is made by TxDOT for any

CONSTRUCTION NOTES:

Panel lengths of railing must be attached to a minimum of three posts except at abutment wingwalls.

At the Contractor's option anchor bolts may be an adhesive anchorage system. See "Material Notes".

Test adhesive anchors in accordance with Item 450.3.3, "Tests". Test 3 anchors per 100 anchors installed. Perform corrective measures to provide adequate capacity if any of the tests do not meet the required test load. Repair d'amagé from testing as directed.

Face of rail and posts must be vertical transversely unless otherwise approved. Posts must be perpendicular to adjacent roadway grade. Use Type VIII epoxy mortar under post base plates if gaps larger than ¼₁₆" exist.

For curved railing applications, fabricate the HSS rail to the radius when the radius is 600' or less. Submit shop drawings for approval when tubes are required to be fabricated to a radius. Shop drawings must be submitted to the Engineer for approval.

Round or chamfer all exposed edges of steel components V_{16} " by grinding prior to galvanizing.

MATERIAL NOTES: Provide ASTM A500 Gr B, A1085 or A53 Gr B for all HSS. Galvanize all metal components of steel rail system. Apply additional coatings when shown elsewhere on the plans. When plans require paint over galvanizing, follow the requirements for painting galvanized steel in Item 445, "Galvanizing" and when field painting, Item 446, "Field Cleaning and Painting Steel". Sleeve members and anchor bolts must receive galvanization prior to installation and only field paint after installation unless directed otherwise by Engineer.

Anchor bolts must be 🚀 Dia ASTM A307 Gr A with one hardened steel washer (ASTM F436) placed under each hex nut or ASTM A307 Gr A threaded rods with one tack welded hex nut each and with one hex nut with one hardened steel washer (ASTM F436) each. Nuts must conform to ASTM A563 requirements.

. Optional adhesive anchorage system must be %" Dia ASTM A307 Gr A fully threaded rods with one hex nut and one hardened steel washer (ASTM F436) Nuts must conform to ASTM A563 requirements. Embed fully threaded rods into slab, wingwalls, or culvert curbs using a Type III, Class C, D, E, or F anchor adhesive. Anchor adhesive chosen must be able to achieve a nominal bond strength in tension, Na, of a single anchor of 10 kips (edge distance must be accounted for). Submit signed and sealed calculations or the manufacturer's published literature showing the proposed anchor adhesive's ability to develop this load to the Engineer for approval prior to use. Anchor installation, including hole size, drilling, and clean out, must be in accordance with Item 450, "Railing".

GENERAL NOTES:

Designed according to AASHTO LRFD Specifications. Do not use this railing on bridges with expansion joints providing more than 5" movement.

Rail anchorage details shown on this standard may require modification for select structure types. See appropriate details elsewhere in plans for these modifications.

For all rails, submit erection drawings showing section lengths, splice locations, rail post spacing and anchor bolt setting for approval. Average weight of railing is 30 plf.

SHE	EET 2	20	F 2						
Texas Department	of Tra	nsp	ortation		Bridge Division Standard				
PEDES	PEDESTRIAN RAIL								
FILE: rlstd028-18.dgn	DN: TA	AR	ск: TBE I	ow: JTR	CK: TAR				
©TxDOT March 2018	CONT	SECT	JOB		HIGHWAY				
REVISIONS									
	DIST		COUNTY		SHEET NO.				
					185				



PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 12:53:34 PM

			SHEET SUMMARY OF ESTIMATED QUANTITIE	ES	
		ITEM#	DESCRIPTION	UNIT	QTY
	A	0666	RE PM W/RET REQ TY I (W) 4" (BRK) (100MIL)	LF	578
W1-6R	В	0666	RE PM W/RET REQ TY I (W) 4" (SLD) (100MIL)	LF	1243
40 V 04	С	0666	REFL PAV MRK TY I (W) 8" (SLD) (100MIL)	LF	375
48 X 24	D	0666	REFL PAV MRK TY I (W) 8" (DOT) (100MIL)	LF	
	E	0666	REFL PAV MRK TY I (W) 24" (SLD) (100MIL)	LF	40
	F	0666	REF PAV MRK TY I (W) 18" (YLD TRI) (100MIL)	EA	
	G	0666	REFL PAV MRK TY I (W) (ARROW) (100MIL)	EA	4
	H	0666	REFL PAV MRK TY I (W) (WORD) (100MIL)	EA	4
-		0666	RE PM W/RET REQ TY I (Y) 4" (SLD) (100MIL)	LF	880
	J	0666	REFL PAV MRK TY I (Y) (MED NOSE) (100MIL)	EA	1
	K	0666	REFL PAV MRKR TY II-C-R	EA	19
•	L	0666	REFL PAV MRKR TY II-A-A	EA	44

SIGNING AND PAV MRK LEGEND

- → LANE DIRECTION
- EXISTING SIGN
- PROPOSED SIGN
- PROPOSED SIGN MOUNTED BACK TO BACK
- # PROPOSED SMALL SIGN
- EXISTING SMALL SIGN TO REMAIN
- # EXISTING SMALL SIGN TO BE RELOCATED
- EXISTING SMALL SIGN TO BE REMOVED



MATCHLINE STA 113+00.00





PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOTTED ON: 6/25/2020 @ 12:53:37 PM PLOTTED ON: 6/25/2020 @ 12:53:37 PM PLOTTED ON: 6/25/2020 @ 12:53:37 PM

		SHEET SUMMARY OF ESTIMATED QUANTITI	ES	
	ITEM#	DESCRIPTION	UNIT	QTY
Α	0666	RE PM W/RET REQ TY I (W) 4" (BRK) (100MIL)	LF	1809
В	0666	RE PM W/RET REQ TY I (W) 4" (SLD) (100MIL)	LF	1800
С	0666	REFL PAV MRK TY I (W) 8" (SLD) (100MIL)	LF	90
D	0666	REFL PAV MRK TY I (W) 8" (DOT) (100MIL)	LF	
E	0666	REFL PAV MRK TY I (W) 24" (SLD) (100MIL)	LF	
F	0666	REF PAV MRK TY I (W) 18" (YLD TRI) (100MIL)	EA	
G	0666	REFL PAV MRK TY I (W) (ARROW) (100MIL)	EA	1
Η	0666	REFL PAV MRK TY I (W) (WORD) (100MIL)	EA	1
	0666	RE PM W/RET REQ TY I (Y) 4" (SLD) (100MIL)	LF	1803
J	0666	REFL PAV MRK TY I (Y) (MED NOSE) (100MIL)	EA	
K	0666	REFL PAV MRKR TY II-C-R	EA	91
L	0666	REFL PAV MRKR TY II-A-A	EA	91

SIGNING AND PAV MRK LEGEND

- → LANE DIRECTION
- ____ EXISTING SIGN
- PROPOSED SIGN
- PROPOSED SIGN MOUNTED BACK TO BACK
- (#) PROPOSED SMALL SIGN
- EXISTING SMALL SIGN TO REMAIN
- # EXISTING SMALL SIGN TO BE RELOCATED
- EXISTING SMALL SIGN TO BE REMOVED





PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOTTED ON: 6/25/2020 @ 12:53:39 PM DESIGN FILENAME: X:\data\Infra\Proi_2016\E0543800_Bx_Co_Watson\CADD\PLAN_SHTS\SPM\WATSON_SPM_03

		S		
	ITEM#	DESCRIPTION	UNIT	QTY
A	0666	RE PM W/RET REQ TY I (W) 4" (BRK) (100MIL)	LF	1305
В	0666	RE PM W/RET REQ TY I (W) 4" (SLD) (100MIL)	LF	1600
С	0666	REFL PAV MRK TY I (W) 8" (SLD) (100MIL)	LF	466
D	0666	REFL PAV MRK TY I (W) 8" (DOT) (100MIL)	LF	
E	0666	REFL PAV MRK TY I (W) 24" (SLD) (100MIL)	LF	
F	0666	REF PAV MRK TY I (W) 18" (YLD TRI) (100MIL)	EA	
G	0666	REFL PAV MRK TY I (W) (ARROW) (100MIL)	EA	2
Η	0666	REFL PAV MRK TY I (W) (WORD) (100MIL)	EA	1
	0666	RE PM W/RET REQ TY I (Y) 4" (SLD) (100MIL)	LF	1600
J	0666	REFL PAV MRK TY I (Y) (MED NOSE) (100MIL)	EA	
K	0666	REFL PAV MRKR TY II-C-R	EA	66
L	0666	REFL PAV MRKR TY II-A-A	EA	80



SIGNING AND PAV MRK LEGEND

- → LANE DIRECTION
- ____ EXISTING SIGN
- PROPOSED SIGN
- PROPOSED SIGN MOUNTED BACK TO BACK
- (#) PROPOSED SMALL SIGN
- EXISTING SMALL SIGN TO REMAIN
- # EXISTING SMALL SIGN TO BE RELOCATED
- EXISTING SMALL SIGN TO BE REMOVED









PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 12:53:43 PM PLOTTED ON: 6/25/2020 @ 12:53:43 PM DESIGN FILENAME: X:\data\Infra\Proj_2016\E0543800_Bx_Co_Watson\CADD\PL

			SHEET SUMMARY OF ESTIMATED QUANTITIES					
		ITEM#	ITEM# DESCRIPTION					
	A	0666	RE PM W/RET REQ TY I (W) 4" (BRK) (100MIL)	LF				
	В	0666	RE PM W/RET REQ TY I (W) 4" (SLD) (100MIL)	LF	801			
-	С	0666	REFL PAV MRK TY I (W) 8" (SLD) (100MIL)	LF	39			
STD_	D	0666	REFL PAV MRK TY I (W) 8" (DOT) (100MIL)	LF				
	E	0666	REFL PAV MRK TY I (W) 24" (SLD) (100MIL)	LF				
	F	0666	REF PAV MRK TY I (W) 18" (YLD TRI) (100MIL)	EA	8			
	G	0666	REFL PAV MRK TY I (W) (ARROW) (100MIL)	EA				
	Η	0666	REFL PAV MRK TY I (W) (WORD) (100MIL)	EA				
		0666	RE PM W/RET REQ TY I (Y) 4" (SLD) (100MIL)	LF	967			
	J	0666	REFL PAV MRK TY I (Y) (MED NOSE) (100MIL)	EA				
	K	0666	REFL PAV MRKR TY II-C-R	EA				
	L	0666	REFL PAV MRKR TY II-A-A	EA	49			

END PROJECT STA 143+00.00

SIGNING AND PAV MRK LEGEND

- → LANE DIRECTION
- ____ EXISTING SIGN
- PROPOSED SIGN
- PROPOSED SIGN MOUNTED BACK TO BACK
- # PROPOSED SMALL SIGN
- EXISTING SMALL SIGN TO REMAIN
- # EXISTING SMALL SIGN TO BE RELOCATED
- EXISTING SMALL SIGN TO BE REMOVED





20B



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



20G





DATE: FILE:



DATE: FILF:



DATE: FILE:

GENERAL NOTES: FRP sign supports for a single type sign support may be used for signs up to and including 16 square feet. Dual post installation may be used for signs up to and including 32 square feet. 2. All nuts, bolts and washers shall be galvanized per Item 445, "Galvanizing." 3. See the Traffic Operations Division website for detailed drawings of sign clamps. The website address is: http://www.txdot.gov/publications/traffic.htm FRP POST REQUIREMENTS 1. Materials shall conform to the requirements of Departmental Material Specification DMS-4410 and will be furnished in a yellow or gray color as specified elsewhere in the plans. 2. Thickness of FRP sign support is 0.125" + 0.031", - 0.0". 3. FRP sign supports are prequalified by the Traffic Operations Division. Prequalification procedures are obtained by writing: Texas Department of Transportation Traffic Operations Division 125 East 11th Street Austin, Texas 78701-2483 UNIVERSAL ANCHOR SYSTEM INSTALLATION PROCEDURES 1. Dig foundation hole. Where solid rock is encountered at ground level, the foundation shall be a minimum depth of 18". When solid rock is encountered below ground level, the foundation shall extend in the solid rock a minimum depth of 18" or provide a minimum foundation depth of 30". If solid rock is encountered, the socket/stub may be reduced in length as required to a minimum length of 18". Any material removed from the socket/stub shall be from the bottom and the clearance requirements given on SMD(GEN) must be followed. The inner surfaces of the socket/stub must remain free of concrete or other debris. 2. The Engineer may permit batches of concrete less than 2 cubic yards to be mixed with a portable, motor driven concrete mixer. For small placements less than 0.5 cubic yards, hand mixing in a suitable container may be allowed by Engineer. Concrete shall be Class A. 3. Insert base post in foundation hole to depths shown and fillhole with concrete. Cut base post from bottom and ensure a minimum of 18" embedment if installed in solid rock. 4. Level and plumb the base post with coupler using a torpedo level and let concrete set a minimum of 4 days, unless otherwise directed by Engineer. Bottom of base post slots shall be above the concrete footing. 5. Attach sign to FRP post. 6. Insert sign post into base post. Lower until the post comes to rest on the steel rod. 7. Use hammer to ensure the coupler is firmly seated. Top of coupler should be level with top of base post in most instances. 8. Check sign to ensure there is no twist. If loose, increase the tightening of coupler BOLT DOWN SIGN SUPPORT 1. Position base plate with coupler on existing concrete. 2. Drill holes into concrete and insert the 5/8" diameter bolts with wedge anchors, and tighten nuts. 3. Attach sign to FRP post. 4. Insert bottom of sign post into pipe stub. 5. Use hammer to ensure the coupler is firmly seated. Top of coupler should be level with top of base post in most instances. 6. Check sign to ensure there is no twist. If loose, increase the tightening of coupler Texas Department of Transportation Traffic Operations Division SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS UNIVERSAL ANCHOR SYSTEM WITH FRP POST SMD (FRP)-08 © TxDOT July 2002 DN: TXDOT CK: TXDOT DW: TXDOT CK: TXDOT REVISION CONT SECT JOB HIGHWAY 9-08 0915 12 WATSON RD 562

COUNT

BEXAR

SAT

SHEET NO

197

TRIANGULAR SLIPBASE INSTALLATION GENERAL REQUIREMENTS



NOTE

There are various devices approved for the Triangular Slipbase System. Please reference the Material Producer List for approved slip base systems. http://www.txdot.gov/business/producer list.htm The devices shall be installed per manufacturers' recommendations. Installation procedures shall be provided to the Engineer by Contractor.

GENERAL NOTES:

1. Slip base shall be permanently marked to indicate manufacturer. Method, design, and location of marking are subject to approval of the TxDOT Traffic Standards Engineer. 2. Material used as post with this system shall conform to the following specifications 10 BWG Tubing (2.875" outside diameter) 0.134" nominal wall thickness Seamless or electric-resistance welded steel tubing or pipe Steel shall be HSLAS Gr 55 per ASTM A1011 or ASTM A1008 Other steels may be used if they meet the following: 55,000 PSI minimum yield strength 70,000 PSI minimum tensile strength 20% minimum elongation in 2" Wall thickness (uncoated) shall be within the range of 0.122" to 0.138" Outside diameter (uncoated) shall be within the range of 2.867" to 2.883" Galvanization per ASTM A123 or ASTM A653 G210. For precoated steel tubing (ASTM A653), recoat tube outside diameter weld seam by metallizing with zinc wire per ASTM B833. Schedule 80 Pipe (2.875" outside diameter) 0.276" nominal wall thickness Steel tubing per ASTM A500 Gr C Other seamless or electric-resistance welded steel tubing or pipe with equivalent outside diameter and wall thickness may be used if they meet the following: 46,000 PSI minimum yield strength 62,000 PSI minimum tensile strength 21% minimum elongation in 2" Wall thickness (uncoated) shall be within the range of 0.248" to 0.304" Outside diameter (uncoated) shall be within the range of 2.855" to 2.895" Galvanization per ASTM A123 3. See the Traffic Operations Division website for detailed drawings of sign clamps and Texas Universal Triangular Slipbase System components. The website address is: http://www.txdot.gov/publications/traffic.htm 4. Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced. ASSEMBLY PROCEDURE

Foundation

- direction.

Support

- straiaht.
- clearances based on sign types

CONCRETE ANCHOR



Concrete anchor consists of 5/8" diameter stud bolt with UNC series bolt threads on the upper end. Heavy hex nut per ASTM A563, and hardened washer per ASTM F436. The stud bolt shall have a minimum yield and ultimate tensile strength of 50 and 75 KSI, respectively. Nuts, bolts and washers shall be galvanized per Item 445, "Galvanizing." Adhesive type anchors shall have stud bolts installed with Type Illepoxy per DMS-6100, "Epoxies and Adhesives." Adhesive anchors may be loaded after adequate epoxy cure time per the manufacturer's recommendations. Top of bolt shall extend at least flush with top of the nut when installed. The anchor, when installed in 4000 psinormalweight concrete with a 5 1/2" minimum embedment, shall have a minimum allowable tension and shear of 3900 and 3100 psi, respectively.

DATE: FILE:

1. Prepare 12-inch diameter by 42-inch deep hole. If solid rock is encountered, the depth of the foundation may be reduced such that it is embedded a minimum of 18 inches into the solid rock. 2. The Engineer may permit batches of concrete less than 2 cubic yards to be mixed with a portable. motor-driven concrete mixer. For small placements less than 0.5 cubic yards, hand mixing in a suitable container may be allowed by Engineer. Concrete shall be Class Á. 3. Push the pipe end of the slip base stub into the center of the concrete. Rotate the stub back and forth while pushing it down into the concrete to assure good contact between the concrete and stub. Continue to work the stub into the concrete until it is between 2 to 4 inches above the ground. 4. Plumb the stub. Allow a minimum of 4 days to set, unless otherwise directed by the Engineer. 5. The triangular slipbase system is multidirectional and is designed to release when struck from any

1. Cut support so that the bottom of the sign will be 7 to 7.5 feet above the edge of the travelway (i.e., edge of the closest lane) when slip plate is below the edge of pavement or 7 to 7.5 feet above slip plate when the slip plate is above the edge of the travelway. The cut shall be plumb and

2. Attach sign to support using connections shown. When multiple signs are installed on the same support, ensure the minimum clearance between each sign is maintained. See SMD(SLIP-2) for

Texas Department of Transportation Traffic Operations Division									
SIGN MOUN SMALL ROA TRIANGULAR S SMD	SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM								
© TxDOT July 2002	DN: TXD	от	CK: TXDOT	DW:	TXDOT	CK: TXDOT			
9-08 REVISIONS	CONT	SECT	JOB	-	ню	GHWAY			
	0915	12	562		WAT	SON RD			
	DIST COUNTY SHEET NO.								
	SAT		BEXAR			198			
26B									



DATE: FILE:

B633 Class FE/ZN 8.

GENERAL NOTES:

1.

SIGN SUPPORT	• OF POSTS	MAX. SIGN AREA
10 BWG	1	16 SF
10 BWG	2	32 SF
Sch 80	1	32 SF
Sch 80	2	64 SF

- 2. The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fillslope.
- 3. Sign supports shall not be spliced except where shown.
- Sign support posts shall not be spliced.
 Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
- 5. Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
- 6. For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of areater height.
- 7. When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
- 8. Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
- 9. Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
- 10. Additional route markers may be added vertically, provided the totalsign area does not exceed the maximum allowable amount per Note 1.
- 11. Additional sign clamp required on the "T-bracket" post for 24 inch height signs. Place the clamp 3 inches above bottom of sign when possible.
- 12. Post open ends shall be fitted with Friction Caps. 13.Sign blanks shall be the sizes and shapes shown on the plans.

	REQUIRED SUPPORT								
	SIGN DESCRIPTION	SUPPORT							
	48-inch STOP sign (R1-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)							
	60-inch YIELD sign (R1-2)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)							
atory	48x16-inch ONE-WAY sign (R6-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)							
Regul	36x48, 48x36, and 48x48-inch signs	TY 10BWG(1)XX(T)							
	48x60-inch signs	TY \$80(1)XX(T)							
	48x48-inch signs (diamond or square)	TY 10BWG(1)XX(T)							
	48x60-inch signs	TY \$80(1)XX(T)							
ırning	48-inch Advance School X-ing sign (S1-1)	TY 10BWG(1)XX(T)							
WC	48-inch School X-ing sign (S2-1)	TY 10BWG(1)XX(T)							
	Large Arrow sign (W1-6 & W1-7)	TY 10BWG(1)XX(T)							

Texas Department of Transportation Traffic Operations Division SIGN MOUNTING DETAILS

SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM

SMD (SLIP-2)-08									
©.	TxDOT July 2002	DN: TXC	от	CK: TXDOT	DW:	TXDOT	CK: TXDOT		
9-08	REVISIONS	CONT	SECT	JOB		HIGHWAY			
	0915	12	562		WAT	WATSON RD			
		DIST		COUNTY			SHEET NO.		
		SAT		BEXAR			199		
26C									



GENERAL NOTES:

1

<		
she	er	
er	ASTM	

,	•			

OF POSTS	MAX. SIGN AREA
1	16 SF
2	32 SF
1	32 SF
2	64 SF
	OF POSTS 1 2 1 2

- 2. The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fillslope.
- 3. Sign supports shall not be spliced except where shown.
- Sign support posts shall not be spliced.
 Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
- 5. Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
- 6. For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height. 7. When two triangular slipbase supports are used to
- support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
- Wing channelshall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
 Excess pipe, wing channel, or windbeam shallbe cut
- off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
- 10. Sign blanks shall be the sizes and shapes shown on the plans. 11. Additional sign clamp required on the "T-bracket" post
- for 24 inch high signs. Place the clamp 3 inches above bottom of sign when possible.
- 12. Post open ends shall be fitted with Friction Caps.

	REQUIRED SUPPORT						
		SUPPORT					
	48-inch STOP sign (R1-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)					
	60-inch YIELD sign (R1-2)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)					
atory	48x16-inch ONE-WAY sign (R6-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)					
Regul	36x48, 48x36, and 48x48-inch signs	TY 10BWG(1)XX(T)					
	48x60-inch signs	TY \$80(1)XX(T)					
	48x48-inch signs (diamond or square)	TY 10BWG(1)XX(T)					
	48x60-inch signs	TY \$80(1)XX(T)					
Irning	48-inch Advance School X-ing sign (S1-1)	TY 10BWG(1)XX(T)					
WC	48-inch School X-ing sign (S2-1)	TY 10BWG(1)XX(T)					
	Large Arrow sign (W1–6 & W1–7)	TY 10BWG(1)XX(T)					

Texas Department of Transportation Traffic Operations Division							
SIGN MOUN SMALL ROA TRIANGULAR SI SMD (S	TIN ADS _IP SLIP	G SIDI BA ?-3:	DET# E SI(SE S	AIL GN SY	_S IS 'ST	E١	M
© TxDOT July 2002	DN: TXD	от	CK: TXDOT	DW:	TXDOT	Cł	K: TXDOT
9-08 REVISIONS	CONT	SECT	JOB		H	HIGHW.	AY
	0915 12 562 WATSON RD						
	DIST COUNTY SHEET NO.				EET NO.		
	SAT		BEXAR			2	200
26D							



ie use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXOOT for any purpose whatsoever. IXDOT assumes no responsibility for the consiston of this standard to other formats or for incorrect results or damages resulting from its use.

AIMER:

1. The Wedge Anchor System and the Universal Anchor System with thin wall tubing post may be used to support up to 10 square feet of sign area. 2. The tubular socket, wedge and prefabricated T-bracket shall be permanently marked to indicate manufacturer. Method, design, and location of marking are subject to the approval of the TxDOT Traffic Standards Engineer. 3. Except for posts (13 BWG Tubing), clamps, nuts and bolts, all components shall be prequalified. A list of prequalified vendors may be obtained from the Material Producer List web page. The website address is: http://www.txdot.gov/business/producer list.htm 4. Material used as post with this system shall conform to the following specifications: 13 BWG Tubing (2.375" outside diameter) (TWT) 0.095" nominal wall thickness Seamless or electric-resistance welded steel tubing Steel shall be HSLAS Gr 55 per ASTM A1011 or ASTM A1008 Other steels may be used if they meet the following: 55,000 PSI minimum yield strength 70.000 PSI minimum tensile strength 18% minimum elongation in 2" Wall thickness (uncoated) shall be within the range of .083" to .099" Outside diameter (uncoated) shall be within the range of 2.369" to 2.381" Galvanization per ASTM 123 or ASTM A653 G210. For precoated steel tubing (ASTM A653), recoat tube outside diameter weld seam by metallizing with zinc wire per ASTM B833. Sign blanks shall be the sizes and shapes shown on the plans.
 Additional sign clamp required on the "T-bracket" post for 24" high signs. Place clamp at least 3" above bottom of sign when possible. 7. Sian supports shall not be spliced except where shown. Sian support posts shall not be spliced. 8. See the Traffic Operations Division website for detailed drawings of sign clamps and Wedge Anchor System components. The website address is: http://www.txdot.gov/publications/traffic.htm WEDGE ANCHOR SYSTEM INSTALLATION PROCEDURE 1. Dig foundation hole. Where solid rock is encountered at around level, the foundation shall be a minimum depth of 18". When solid rock is encountered below ground level, the foundation shall extend in the solid rock a minimum depth of 18" or provide a minimum foundation depth of 30". If solid rock is encountered, the socket/stub may be reduced in length as required to a minimum length of 18". Any material removed from the socket/stub shall be from the bottom and the clearance requirements given on SMD(GEN) must be followed. The nner surfaces of the socket/stub must remain free of concrete or other debris. 2. The Engineer may permit batches of concrete less than 2 cubic yards to be mixed with a portable, motor driven concrete mixer. For small placements less than 0.5 cubic yards, hand mixing in a suitable container may be allowed by Engineer Place concrete into hole until it is approximately flush with the ground. Concrete shall be Class A. 3. Insert tubular socket into concrete until top of socket is approximaely 1/4 ' above the concrete footing. 4. Plumb the socket. Allow a minimum 4 days for concrete to set, unless otherwise directed by Engineer. 5. Attach the sign to the sign post. 6. Insert the sign post into socket and align sign face with roadway. 7. Drive the wedge into the socket to secure post. This will leave approximately 3 inches of the wedge exposed. UNIVERSAL ANCHOR SYSTEM INSTALLATION PROCEDURE 1. Dig foundation hole. Where solid rock is encountered at ground level, the foundation shall be a minimum depth of 18". When solid rock is encountered below around level, the foundation shall extend in the solid rock a minimum depth of 18" or provide a minimum foundation depth of 30". If solid rock is encountered, the socket/stub may be reduced in length as required to a minimum length of 18". Any material removed from the socket/stub shall be from the bottom and the clearance requirements given on SMD(GEN) must be followed. The inner surfaces of the socket/stub must remain free of concrete or other debris. 2. Insert base post in hole to depths shown and backfill hole with concrete. 3. Level and plumb the base post using a torpedo level and allow concrete adequate time to set. The bottom of the slots provided in the stub pipe shall remain above the top of the concrete foundation 4. Attach the sign to the sign post 5. Install plastic insert around bottom of post. 6. Insert sign post into base post. Lower until the post comes to rest on steelrod. 7. Seat compression ring using a hammer. Typically, the top of compression ring will be approximately level with top of stub post when optimally installed. 8. Check sign post by hand to ensure it is unable to turn. If loose, increase the tightening of the compression ring. Texas Department of Transportation Traffic Operations Division SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS WEDGE & UNIVERSAL ANCHOR WITH THIN WALL TUBING POST SMD (TWT)-08 DN: TXDOT CK: TXDOT DW: TXDOT CK: TXDOT © TxDOT July 2002 REVISIONS CONT SECT JOB HIGHWAY 9-08 0915 12 562 WATSON RD COUNT SHEET NO SAT 201 BEXAR

26E







75C



LAIMER: The use of this stondord is governed by the "Texos Engineering Proctice Act". No warranty of any is mode by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion statistic dayother formats or for incorrect results or damages resulting from its use. 6/25/2020 12:53:55 PM X:\data\Infra\Proi_201

1. Transverse or in-lane rumble strips should only be used at high incident and special geometric locations. These special geometric locations may include approaches to rural, high speed signalized or Stop -controlled intersections with sight restrictions and/or high crash rates, approaches to unexpected urban intersections, approaches to newly installed Stop or signalized controlled intersections, approaches to tollplazas, approaches to hazardous horizontal curves, and approaches to railroad grade crossings.

2. When used, the rumble strips shall be placed 200 feet prior to and after the placement of the warning device.

3. The use of rumble strips should not be widespread or used

4. Preformed black raised rumble strips should be used. They should be installed in accordance with the manufacturer's recommendations.

5. A list of approved, preformed raised rumble strips can be obtained from the Traffic Operations Division.

6. Consideration should be given to noise levels when in -lane or transverse rumble strips are installed near residential areas, schools, churches, etc.

7. The use of the "Rumble Strips Ahead" sign may be used in advance of in -lane or transverse rumble strips, based on engineering judgement. This sign is typically not necessary for rumble strip installations built to the guidelines on this standard sheet. When used, this sign should be spaced in advance of the rumble strips based on the guidelines for advance placement of warning sign included in the "Texas Manual on Uniform Traffic Control Devices".



8. Consideration should be given to bicyclists. A 12 inch gap from the edge line may be used to accommodate bicyclists when a usable shoulder is not available. Additional gaps in the in -lane or transverse rumble strips are not recommended since they could cause motorists to swerve to avoid the rumble strips.

9. Other signs can be used as conditions warrant.

Texas Department of Transportation						Traffic perations Division tandard	
TRANSVERSE OR IN-LANE RUMBLE STRIPS RS(5)-13							
FILE:	rs(5)-13.dgn	DN: Tx	DOT	ск: TxDOT Dw:	TxDO	т ск: ТхDOT	
© TxD0T	April 2006	CONT	SECT	JOB		HIGHWAY	
0.40	REVISIONS	0915	12	562	WA	TSON RD	
2-10		DIST		COUNTY		SHEET NO.	
10-13		SAT		BEXAR		203	
94							







CABLE AND CONDUIT RUN							
	0618 2018	0620 2011	0620 2012	RUN LENGTH			
RUN	CONDT (PVC)(SCHD 40)(2")	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 8) INSULATED	FEET			
1A	87	87	174	87			
TOTAL LF	87	87	174				

NOTE: ALL WIRE LENGTHS HAVE 2 FEET ADDITIONAL LENGTH FOR EACH END CALCULATED.





۲

РМ 2 55 04 0 2020 TTED ON: Ь



CABLE AND CONDUIT RUN								
	0618 2018	0620 2011	0620 2012	RUN LENGTH				
RUN	RUN (PVC)(SCHD 40)(2")		ELEC CONDR (NO. 8) INSULATED	FEET				
8B	177	177	354	177				
TOTAL LF	177	177	354					

NOTE: ALL WIRE LENGTHS HAVE 2 FEET ADDITIONAL LENGTH FOR EACH END CALCULATED.

PLOTTED ON: 7/6/2020 @ 2:55:07 PM DESIGN FILENAME: \\Ssa-main\pmwork\Jobs\15024-Watson-Rd\Techprod\Illumination\WATSON_ILLUM_05.dgn





FILES

GENERAL NOTES FOR ALL ELECTRICAL WORK

- 1. The location of all conduits, junction boxes, ground boxes, and electrical services is diagrammatic and may be shifted to accommodate field conditions.
- 2. Provide new and unused materials. Ensure that all materials and installations comply with the applicable articles of the National Electrical Code (NEC), TxDOT standards and specifications, National Electrical Manufacturers Association (NEMA), and are listed by Underwriters Laboratories (UL) or a Nationally Recognized Testing Lab (NRTL), NRTLs such as Canadian Standard Association (CSA), Intertek Testing Services NA Inc., or FM Approvals LLC can be considered equivalent to UL. Where reference is made to NEMA listed devices, International Electrotechnical Commission (IEC) listed devices will not be considered an acceptable equal to a NEMA listed device. Acceptable devices may have both a NEMA and IEC listing. Faulty fabrication or poor workmanship in any material, equipment, or installation is justification for rejection. Replace or reinstall rejected material or equipment at no additional cost to the Department.
- 3. Miscellaneous nuts, bolts and hardware, except for high strength bolts, may be stainless steel when plans specify galvanized, provided the bolt size is $\frac{1}{2}$ in. or less in diameter.
- 4. Provide the following test equipment as required by the Engineer to confirm compliance with the contract and the NEC: voltmeter, ammeter, megohm meter (1000 volt DC), ground resistance tester, torque wrenches, and torque screwdrivers. Ensure all equipment has been properly calibrated within the last year. Provide calibration certification to the Engineer upon request. Operate test equipment during inspection as requested by the Engineer.
- 5. Install grounding as shown on the plans and in accordance with the NEC. Ensure all metallic conduits; metal poles; luminaires; and metal enclosures are bonded to the equipment grounding conductor. Provide stranded bare copper or green insulated grounding conductors. Ground rods, connectors, and bonding jumpers are subsidiary to the various bid items.
- 6. When required by the Engineer, notify the Department in writing of materials from the Material Producers List (MPL) intended for use on each project. Prequalified materials are listed on the MPL on TxDOT's website under "Roadway Illumination and Electrical Supplies." No substitutions will be allowed for materials on this list.

CONDUIT

A. MATERIALS

- 1. Provide conduit, junction boxes, fittings, and hardware as per TxDOT Departmental Material Specification (DMS) 11030 "Conduit" and Item 618 "Conduit" of TxDOT's "Standard Specifications For Construction And Maintenance Of Highways, Streets, And Bridges," latest edition. Provide conduits listed under Item 618 on the MPL under "Roadway Illumination and Electrical Supplies." Provide conduit types according to the descriptive code or as shown on the plans. Do not substitute other types of conduits for those shown. Provide liquidtight flexible metal conduit (LFMC) when flexible conduit is called for on galvanized steel rigid metallic conduit (RMC) systems, Provide liquidtight flexible nonmetallic conduit (LFNC) when flexible conduit is called for on polyvinyl chloride (PVC) systems.
- 2. Provide galvanized steel RMC for all exposed conduits, unless otherwise shown on the plans. Properly bond all metal conduits.
- Unless otherwise shown on the plans, provide junction boxes with a minimum size as shown in 3. the following table, which applies to the greatest number of conductors entering the box through one conduit with no more than four conduits per box. When a mixture of conductor sizes is present, count the conductors as if all are of the larger size. For situations not applicable to the table, size junction boxes in accordance with NEC.

AWG	3 CONDUCTORS	5 CONDUCTORS	7 CONDUCTORS
#1	10" x 10" x 4"	12" x 12" x 4"	16" × 16" × 4"
#2	8" × 8" × 4"	10" x 10" x 4"	12" x 12" x 4"
#4	8" × 8" × 4"	10" x 10" x 4"	10" x 10" x 4"
#6	8" × 8" × 4"	8" × 8" × 4"	10" x 10" x 4"
#8	8" × 8" × 4"	8" × 8" × 4"	8" × 8" × 4"

- 4. Junction boxes with an internal volume of less than 100 cu. in. and supported by entering raceways must have threaded entries or hubs identified for the intended purpose and supported by connection of two or more rigid metal conduits. Secure conduit within 3 ft. of the enclosure or within 18 in. of the enclosure if all conduit entries are on the same side. Mechanically secure all junction boxes with an internal volume greater than 100 cu. inches.
- 5. Provide hot dipped galvanized cast iron or sand cast aluminum outlet boxes for junction boxes containing only 10 AWG or 12 AWG conductors. Do not use die cast aluminum boxes. Size outlet boxes according to the NEC.
- 6. Do not use intermediate metal conduit (IMC) or electrical metallic tubing (EMT) unless specifically required by the plan sheets. When EMT is called for, provide junction boxes made from galvanized steel sheeting, listed and approved for outdoor use, unless otherwise noted on the plans. Size all galvanized steel junction boxes in accordance with the NEC. Provide junction boxes for IMC conduit systems that meet the same requirements for junction boxes used with RMC systems.
- 7. Provide PVC junction boxes intended for outdoor use on PVC conduit systems, unless otherwise noted on the plans.

- 8. Provide PVC elbows in PVC conduit systems, unless otherwise shown on the p a flat, high tensile strength polyester fiber pull tape for pulling conduct the PVC conduit system. When galvanized steel RMC elbows are specifically c the plans and any portion of the RMC elbow is buried less than 18 in., grou elbow by means of a grounding bushing on a rigid metal extension. Grounding metal elbow is not required if the entire RMC elbow is encased in a minimum concrete. PVC extensions are allowed on these concrete encased rigid metal PVC elbows are subsidiary to various bid items.
- 9. When required, provide High-Density Polyethylene (HDPE) conduit with factor conductors according to Item 622 "Duct Cable." At the Contractor's request the Engineer, substitute HDPE conduit with no conductors for bored schedule conduit bid under Item 618. Ensure bored HDPE substituted for PVC is schedu size PVC called for in the plans. Ensure the substituted HDPE meets the red except that the conduit is supplied without factory-installed conductors. the HDPE conduit to PVC (or RMC elbow when required) at the bore pit. Prov and schedule as shown on the plans. Do not extend substituted conduit into foundations. Provide PVC or galvanized steel RMC elbows as called for at al foundations.
- 10. Use two-hole straps when supporting 2 in. and larger conduits. On electrico properly sized stainless steel or hot dipped galvanized one-hole standoff s the service riser conduit.

B. CONSTRUCTION METHODS

- Provide and install expansion joint conduit fittings on all structure-moun the structure's expansion joints to allow for movement of the conduit. In and install expansion joint fittings on all continuous runs of galvanized externally exposed on structures such as bridges at maximum intervals of 1 requested by the project Engineer, supply manufacturer's specification shee joint conduit fittings. Repair or replace expansion joint fittings that do movement at no additional cost to the Department. Provide the method of de amount of expansion to the Engineer upon request. Do not use LFMC or LFNC for the required expansion conduit fittings.
- 2. Space all conduit supports at maximum intervals of 5 ft. Install conduit sp attaching metal conduit to surface of concrete structures. See "Conduit Mou on ED(2). Install conduit support within 3 ft. of all enclosures and condu
- 3. Do not attach conduit supports directly to pre-stressed concrete beams exce specifically in the plans or as approved by the Engineer.
- 4. Unless otherwise shown on the plans, jack or bore conduit placed beneath ex driveways, sidewalks, or after the base or surfacing operation has begun. compact the bore pits below the conduit per Item 476 "Jacking, Boring, or or Box" prior to installing conduit or duct cable to prevent bending of the
- 5. When placing conduit in the sub-grade of new roadways, backfill all trenche material unless otherwise noted on the plans. When placing conduit in the new roadways, backfill all trenches with cement-stabilized base as per requ Items 110 "Excavation", 400 "Excavation and Backfill for Structures", 401 Backfill", 402 "Trench Excavation Protection", and 403 "Temporary Special
- 6. Provide and place warning tape approximately 10 in. above all trenched cond
- 7. During construction, temporarily cap or plug open ends of all conduit and after installation to prevent entry of dirt, debris and animals. Temporary durable duct tape are allowed. Tightly fix the tape to the conduit opening conduit and prove it clear in accordance with Item 618 prior to installing
- 8. Ensure conduit entry into the top of any enclosure is waterproof by instal hubs or using boxes with threaded bosses. This includes surface mounted sat cans, service enclosures, auxiliary enclosures and junction boxes. Groundir tight sealing hubs are not required.
- 9. Fit the ends of all PVC conduit terminations with bushings or bell end fitt install a grounding type bushing on all metal conduit terminations.
- 10. Install a bonding jumper from each grounding bushing to the nearest ground or equipment grounding conductor. Ensure all bonding jumpers are the same s arounding conductor. Bonding of conduit used as a casing under roadways for required, if the duct extends the full length through the casing.
- 11. At all electrical services, install a 6 AWG solid copper grounding electroc
- 12. Place conduits entering ground boxes so that the conduit openings are betwee from the bottom of the box. See the ground box detail on sheet ED(4).
- 13. Seal ends of all conduits with duct seal, expandable foam, or by other meth the Engineer. Seal conduit immediately after completion of conductor instal tests. Do not use duct tape as a permanent conduit sealant. Do not use sil conduit sealant.
- 14. File smooth the cut ends of all mounting strut and conduit. Before install cut ends of all mounting strut and RMC (threaded or non-threaded) with zinc more zinc content) to alleviate overspray. Use zinc rich paint to touch up as allowed under Item 445 "Galvanizing." Do not paint non-galvanized materi paint as an alternative for materials required to be galvanized.

lans. Use only tors through called for in und the RMC g of the rigid n of 2 in. of elbows. RMC or		
ry installed internal and with approval by e 40 or schedule 80 PV ule 40 and of the same quirements of Item 622 Make the transition of ide conduit of the size ground boxes or II ground boxes and	C , e	
al service poles, straps are allowed on		
ted conduits at addition, provide steel RMC conduit 50 ft. When et for expansion not allow for termining the as a substitute		
pacers when unting Options" it terminations.		
ept as shown		
xisting roadways, Backfill and Tunneling Pipe e connections.		
es with excavated sub-base of uirements of "Flowable Shoring."		
duit as per Item 618.		
raceways immediately caps constructed of . Clean out the any conductors.		
ling conduit sealing fety switches, meter ng bushings on water		
tings. Provide and		
rod, grounding lug, size as the equipment r duct cable is not		
de conductor.	Taxas Department of Transportation	Operations Division
een 3 in. and 6 in.		Standard
nods approved by llation and pull icone caulk as a	ELECTRICAL DETA	ILS FS
ing, paint the field c rich paint (94% or galvanized material ial with a zinc rich	ED(1)-14	
	CK: DW: CTXDOT October 2014 CONT SECT JOB	CK: HIGHWAY
	MEVISIONS 0915 12 562 DIST COUNTY	WATSON RD SHEET NO.
	71A BEXAR	207

ELECTRICAL CONDUCTORS

A. MATERIAL INFORMATION

of any version

warranty the conv

Sp.

Practice Act". responsibility

Texas Engineering TxDOT assumes no

whatsoever

goverr urpose

° D D

ĔΒċ

this standa TxDOT for

²Q

- 1. Provide Type XHHW insulated conductors in accordance with Departmental Material Specification (DMS)11040 "Conductors" and Item 620 "Electrical Conductors." Provide conductors as listed on the Material Producers List (MPL) on the Department web site under "Roadway Illumination and Electrical Supplies" Item 620. Color code insulated conductors in conformance with the NEC. Identify grounded (neutral) conductors with white insulation. Identify grounding conductors (ground wires) with green insulation or bare conductors. Identify ungrounded (hot) conductors with any color insulation except green, white, or gray. Keep color scheme consistent throughout the wiring system. Identify conductors 6 American Wire Gauge (AWG) and smaller by continuous color jacket. Identify electrical conductors 4 ÅWG and larger by continuous color jacket or by colored tape. When identifying conductors with colored tape, mark at least 6 in. of the conductor's insulation with half laps of tape.
- Provide a solid copper 6 AWG grounding electrode conductor to bond the electrical service equipment to the concrete encased grounding electrode or the ground rod at 2. the service location. Connect the grounding electrode conductor to the ground rod with a UL listed connector in accordance with DMS 11040. Connect the grounding electrode conductor to the concrete encased grounding electrode as shown in the plans.
- 3. Where two or more circuits are present in one conduit or enclosure, permanently identify the conductors of each branch circuit by attaching a non-metallic tag around both circuit conductors at each accessible location. Provide tags with two straps, large enough to indicate circuit number, letter, or other identification as shown in the plans. Print circuit identification on the tag with a permanent marker.
- Use listed compression or screw type pressure connectors, terminal blocks, or split bolt connectors for splicing as specified in DMS 11040. Use hot melt adhesive tape to fill the gap and seal the ends of heat shrink tubing. Provide UL listed gel-filled insulating splice covers. Splicing materials, insulating materials, breakaway disconnects, splice covers, and fuse holders are subsidiary to various bid items.

B. CONSTRUCTION METHODS

- 1. Use only a flat, high tensile strength polyester fiber pull tape for pulling conductors through the conduit system. After installing conductors in conduit, perform conductor pull test. If a conductor cannot be freely pulled, make any needed alterations or repairs at no additional cost to the department. Perform insulation resistance tests in accordance with Item 620. Coordinate with the Engineer to witness the tests.
- 2. Leave 2 ft. minimum, 3 ft. maximum length for each conductor up to the splice in ground boxes. Leave 3 ft. minimum, 4 ft. maximum length of conductor in ground boxes when pulled through with no splice. Leave 1 ft. minimum, 1.5 ft. maximum length of conductor at enclosures, weatherheads and pole bases.
- Make splices only in junction boxes, ground boxes, pole bases, or electrical enclosures and use only listed compression or screw type pressure connectors, terminal blocks, or split bolt connectors. Insulate splices with heavy wall heat shrink tubing or gel-filled insulating splice covers to provide a watertight splice. Overlap conductor insulation with heat shrink tubing a minimum of 2 in. past both sides of the splice. Where heat shrink tubing may not shrink sufficiently to provide a watertight seal around the individual conductors, prior to heating the tubing, increase the diameter of the conductor insulation using hot melt adhesive tape to provide a watertight seal between the individual conductors and the heat shrink tubing. Ensure the tape extends past the heat shrink tubing. Use hot melt adhesive tape to fill the gap and seal the ends of heat shrink tubing. Heat shrink tubing that appears to have been burned, or overheated, is considered defective and must be replaced.
- Size and install gel-filled insulating splice covers according to manufacturer's specifications when used in place of heat shrink tubing.
- Wire nuts with factory applied waterproof sealant may be used for 8 AWG or smaller conductors in above ground junction boxes, but not in pole bases or ground boxes. Install wire nuts in an upright position to prevent the accumulation of water.
- 6. Support conductors in illumination poles with a J-hook at the top of the pole.
- 7. When terminating conductors, remove the insulation and jacketing material without nicking the individual strands of the conductor. Conductors with nicked individual conductor strands or removed strands will be considered damaged.
- 8. Replace conductors and cables that are damaged beyond repair or that fail an insulation resistance test at no additional cost to the department.
- 9. Do not repair damaged conductors with duct tape, electrical tape, or wire nuts. Use only approved splicing methods.
- 10. Do not terminate more than one conductor under a sinale connector. unless the connector is rated for multiple conductors. Do not exceed the pressure connector's listing for maximum number and size of conductors allowed.
- 11. Install breakaway connectors on conductors bid under Item 620 whenever those conductors pass through a breakaway support device. Follow manufacturer's instructions when terminating conductors to breakaway connectors. Properly torque threaded connections. Proper terminations are critical to the safe operation of breakaway devices. Trim waterproofing boots on breakaway connectors to fit snugly around the conductor to ensure waterproof connection. Only one conductor may enter a single opening in a boot. Provide waterproof boots with the correct number of openings. Leave unused openings factory sealed. Use prequalified breakaway connectors as shown on the MPL.

- 12. Provide and install a separate stranded equipment grounding conductor (EGC) in all conduits that contain circuit wiring of 50 volts or more. Unless shown elsewhere, size the EGC to be the same size as the largest current carrying conductor contained in the conduit. Ensure all EGCs are bonded together at every accessible location. For traffic signal installations, provide a minimum size 8 AWG EGC. The EGC is paid for under Item 620.
- C. TEMPORARY WIRING
- Install temporary conductors and electrical equipment in accordance with the NEC article "Temporary Installations" and Department standard sheets.
- 2. Provide a ground fault circuit interrupter (GFCI) for power outlets for portable electrical equipment, power tools, ice machines, ice storage bins and refrigerators located outdoors at grade. GFCI may be any one of following: molded cord and plug set, receptacle, or circuit breaker type.
- 3. Use listed wire nuts with factory applied sealant for temporary wiring where approved.
- 4. Enclose conductor splices within a listed enclosure or ground box, or ensure the splices are more than 10 ft. above grade vertically and more than 5 ft. horizontally from any metal structure. Where installing temporary conductors in areas subject to vehicle traffic or mobile construction equipment, ensure the vertical clearance to ground is at least 18 ft. when measured at the lowest point. Ground messenger wires that support power conductors in conformance with the NEC.
- 5. Protect and when necessary repair any existing electrical conduits uncovered during the construction process in a timely manner and in conformance with the NFC.

GROUND RODS & GROUNDING ELECTRODES

A. MATERIAL INFORMATION

1. Provide and install a grounding electrode at electrical services. Provide around rods according to DMS 11040 and the plans, Larger diameter or longer length rods may be called for in some specific locations, see the individual plans sheets. Concrete encased grounding electrodes may be called for in specific locations including electrical service, see individual plan sheets.

B. CONSTRUCTION METHODS

- Furnish auxiliary ground rods for lightning protection and install in soil, concrete, or both, as called for in the plans. For ground rods installed in concrete, ensure the connection of the conductor to the ground rod is readily accessible for inspection or repairs. For ground rods installed in soil, ensure that the upper end is between 2 to 4 in. below finished grade.
- 2. Do not place ground rods in the same drilled hole as a timber pole.
- 3. Install ground rods so the imprinted part number is at the upper end of the rod.
- 4. Remove all non-conductive coatings such as concrete splatter from the rod at the clamp location.
- 5. Route all conductors as short and straight as possible for connection to lightning protection ground rods. When a bend is required, ensure a minimum radius bend of four inches for these conductors.
- 6. Unless otherwise called for in the plans, protect grounding electrode conductors with non-metallic conduit. When protecting grounding electrode conductors with metal conduit, provide and install a grounding type bushing and properly sized bonding jumper on each end of the metal conduit.
- 7. Written authorization is required before installing a ground rod in a horizontal trench for rocky soil or a solid rock bottom.





71C



- (2) Maintain sufficient space between conduits to allow for proper installation of bushing.
- (3) Place aggregate under the box, not in the box. Aggregate should not encroach on the interior volume of the box.
- (4) Install a grounding bushing on the upper end of all RMC terminating in a ground box. Ground RMC elbows when any part of the elbow is less than 18 in. below the bottom of the ground box. Install a PVC bushing or bell end fitting on the upper end of all PVC conduits terminating in a ground box.

GROU	ND BOX DIMENSIONS
TYPE	OUTSIDE DIMENSIONS (INCHES) (Width x Length X Depth)
Α	12 X 23 X 11
В	12 X 23 X 22
С	16 X 29 X 11
D	16 X 29 X 22
E	12 X 23 X 17

GROUND BOX COVER DIMENSIONS								
DIMENSIONS (INCHES)								
TIPE	Н	Ι	J	К	L	м	N	Р
A, B & E	23 1⁄4	23	13 3⁄4	13 1/2	9 7/8	5 1⁄8	1 3/8	2
C & D	30 ½	30 1⁄4	17 1/2	17 1/4	13 1/4	6 3/4	1 3/8	2



GROUND BOXES

A. MATERIALS

- Item 624 "Ground Boxes."
- and Electrical Supplies," Item 624.

- B. CONSTRUCTION METHODS
- aaareaate.
- boxes.

- Do not use silicone caulk as a sealant.
- together and to the ground rod with listed connectors.
- below arade.
- fully describing the work required.



1. Provide polymer concrete ground boxes measuring 16x30x24 in. (WxLxD) or smaller in accordance with Departmental Material Specification (DMS) 11070 "Ground Boxes" and

2. Provide Type A, B, C, D, and E ground boxes as shown in the plans, and as listed on the Material Producers List (MPL) on the Department web site under "Roadway Illumination

3. Ensure ground box cover is correctly labeled in accordance with DMS 11070.

4. Provide larger ground boxes in accordance with Item 624 and as shown in the plans.

Remove all gravel and dirt from conduit. Cap all conduits prior to placing aggregate and setting ground box. Provide Grade 3 or 4 coarse aggregate as shown on Table 2 of Item 302 "Aggregates for Surface Treatments." Ensure aggregate bed is in place and at least 9 inches deep, prior to setting the ground box. Install ground box on top of

2. Cast ground box aprons in place. Reinforcing steel may be field bent. Ensure the depth of concrete for the apron extends from finished grade to the top of the aggregate bed under the box. Ground box aprons, including concrete and reinforcing steel, are subsidiary to ground boxes when called for by descriptive code.

3. Keep bolt holes in the box clear of dirt. Bolt covers down when not working in ground

4. Install all conduits and ells in a neat and workmanlike manner. Uniformly space conduits so grounding bushings and bell end fittings can easily be installed.

5. Temporarily seal all conduits in the ground box until conductors are installed.

6. Permanently seal conduits immediately after the completion of conductor installation and pull tests. Permanently seal the ends of all conduits with duct seal, expandable foam, or other method as approved. Do not use duct tape as a permanent conduit sealant.

7. When a ground rod is present in a ground box, bond all equipment grounding conductors

8. When a type B or D ground box is stacked to meet volume requirements, it is allowable to cut an appropriately sized hole for conduit entry in the side wall at least 18 inches

9. If an existing ground box in the contract has a metal cover, bond the cover to the equipment grounding conductor with a 3 ft. long stranded bonding jumper the same size as the grounding conductor. The bonding jumper is subsidiary to various bid items. Verify existing ground boxes with metal covers are shown on the plans, with notes

10. If other ground boxes with metal covers are within the project limits but are not part of the contract, the Engineer may direct the Contractor to bond the metal covers, identifying the specific boxes in writing. This work will be paid for separately.

11. Bond metal ground box covers to the grounding conductor with a tank ground type lug.

	Texas Departme	ent of Trans	portation	Traffic Operations Division Standard								
DE	ELECTR	ELECTRICAL DETAILS GROUND BOXES										
	FILE: ed4-14.dgn	DN: TxDOT	CK: TxDOT DW:	TxDOT CK: TxDOT 6								
	© TxDOT October 2014	CONT SECT	JOB	HIGHWAY L								
	REVISIONS	0915 12	562	WATSON RD								
		DIST	COUNTY	SHEET NO. 69								
			BEXAR	209								
				1 2 1 2 1								

ELECTRICAL SERVICES NOTES

1. Provide new materials. Ensure installation and materials comply with the applicable provisions of the National Electrical Code (NEC) and National Electrical Manufacturers Association (NEMA) standards. Ensure material is Underwriters Laboratories (UL) listed. Provide and install electrical service conduits, conductors, disconnects, contactors, circuit breaker panels, and branch circuit breakers as shown on the Electrical Service Data chart in the plans. Faulty fabrication or poor workmanship in material, equipment, or installation is justification for rejection. Where manufacturers provide warranties and guarantees as a customary trade practice, furnish these to the State.

2. Provide electrical services in accordance with Electrical Details standard sheets, Electrical Services in accordance with Electrical Details standard sheets Departmental Material Specification (DMS) 11080 "Electrical Services, "DMS 11081 "Electrical Services-Type A," DMS 11082 "Electrical Services-Type C," DMS 11083 "Electrical Services-Type D," DMS 11084 "Electrical Services-Type T," DMS 11085 "Electrical Services-Pedestal (PS)", and Item 628 "Electrical Services" of the Standard Specifications. Provide electrical service types A, C, and D, as listed on the Material Producers List (MPL) on the Department web site under "Roadway Illumination and Electrical Supplies," Item 628. Provide other service types as detailed on the plans.

3. Provide all work, materials, services, and any incidentals needed to install a complete electrical service as specified in the plans.

- 4.Coordinate with the Engineer and the utility provider for metering and compliance with utility requirements. Primary line extensions, connection charges, meter charges, and other charges by the utility company to provide power to the location are paid for in accordance with Item 628. Get approval for the costs associated with these charges prior to engaging the utility company to do the work. Consult with the utility provider to determine costs and requirements, and coordinate the work as approved. work as approved.
- 5. The enclosure manufacturer will provide Master Lock Type 2 with brass tumblers keyed #2195 for all custom electrical enclosures. Installing Contractor is to provide Master Lock #2195 Type 2 with brass tumblers for "off the shelf" enclosures. Master Lock #2195 keys and locks become property of the State. Unless otherwise approved, do not energize electrical service equipment until locks are installed.
- 6. Enclosures with external disconnects that de-energize all equipment inside the enclosure do not need a dead front trim. Protect incoming line terminations from incidental contact as required by the NEC.
- 7.When galvanized is specified for nuts, screws, bolts or miscellaneous hardware, stainless steel may be used.

8. Provide wiring and electrical components rated for 75°C. Provide red. black. and white colored XHHW service entrance conductors of minimum size 6 American Wire Gauge (AWG). Identify size 6 AWG conductors by continuous color jacket. Identify electrical conductors sized 4 AWG and larger by continuous color jacket or by colored tape. Mark at least 6 inches of the conductor's insulation with half laps of colored tape, when identifying conductors. Ensure each service entrance conductor exits through a separately bushed non-metallic opening in the weatherhead. The lengths of the conductors outside the weatherhead are to be 12 inches minimum, 18 inches maximum, or as required by utility.

9. All electrical service conduit and conductors attached to the electrical service including the riser or the elbow below ground are subsidiary to the electrical service. For an underground utility feed, all service conduit and conductors after the elbow, including service conduit and conductors for the utility pole riser when furnished by the Contractor, will be paid for separately

0.Provide rigid metal conduit (RMC) for all conduits on service, except for the $\frac{1}{2}$ in. PVC conduit containing the electrical service grounding electrode conductor. Size the service entrance conduit as shown in the plans. Ensure conduit for branch circuit entry to enclosure is the same size as that shown on the layout sheets for branch circuit conduit. Extend all rigid metal conduits minimum of 6 inches underground and then couple to the type and schedule of the conduit shown on the layout for that particular branch circuit. Install a grounding bushing on the RMC where it terminates in the service enclosure.

.Use of liquidtight flexible metal conduit (LFMC) is allowed between the meter and service enclosure when they are mounted 90 to 180 degrees to each other. Size the LFMC the same size as service entrance conduit. LFMC must not exceed 3 feet in length. Strap LFMC within 1 foot of each end. LFMC less than 12 inches in length need not be strapped. Each end of LFMC must have a grounding bushing or be terminated with a grounding fitting. The LFMC must contain a grounded (neutral) conductor. Ensure any bend in LFMC never exceeds 180 degrees. A pull test is required on all installed conductors, with at least six inches of free conductor movement demonstrated to the satisfaction of the Engineer.

2. Ensure all mounting hardware and installation details of services conform to utility company specifications.

3.For all electrical service enclosures listed under Item 628 on the MPL, the UL 508 enclosure manufacturers will prepare and submit a schematic drawing unique to each service. Before shipment to the job site, place the applicable laminated schematic drawings and the laminated plan sheet showing the electrical service data chart used to build the enclosure in the enclosure's data pocket. The installing contractor will copy and laminate the actual project plan sheets detailing all equipment and branch circuits supplied by that service. The laminated plan sheets are to be placed in the service enclosure's document pocket. Reduce 11 in. x 17 in. plan sheets to 8.46 is x 11 in before lamination. If the installation differs from the place shows the installing contractor is to redline plan sheets before laminating.

4.When providing an "Off The Shelf" Type D or Type T service, provide laminated plan sheets detailing equipment and branch circuits supplied by that service. Reduce 11 in. x 17 in. plan sheets to 8 $\frac{1}{2}$ in. x 11 in before laminating. Deliver these drawings before completion of the work to the Engineer, instead of placing in enclosure that has no door pocket.

5. Do not install conduit in the back wall of a service enclosure where it would penetrate the equipment mounting panel inside the enclosure. Provide grounding bushings on all metal conduits, and terminate bonding jumpers to grounding bus. Grounding bushings are not required when the end of the metal conduit is fitted with a conduit sealing hub or threaded boss, such as a meter base hub.

SERVICE ASSEMBLY ENCLOSURE

1. Provide threaded hub for all conduit entries into the top of enclosure.

- 2. Type galvanized steel (GS) enclosures may be used for Type C panelboards and for Type D and T services that do not use an enclosure mounted photocell or lighting contactor. Provide GS enclosures in accordance with DMS 11080, 11082, 11083, and 11084.
- 3. Provide aluminum (AL) and stainless steel (SS) enclosures for Types A, C, and D in accordance with DMS 11080, 11081, 11082, 11083, and 11084. Do not paint stainless steel.
- 4. Provide pedestal service (PS) enclosures in accordance with ED(9) and DMS 11080 and 11085. Do not provide GS pedestal services. If GS is shown in the PS descriptive code, provide an AL enclosure.

			* ELE	CTRICAL	SERV	ICE DATA	4					
Elec. Service ID	Plan Sheet Number	Electrical Service Description	Service Conduit **Size	Service Conductors No./Size	Safety Switch Amps	Main Ckt. Bkr. Pole/Amps	Two-Pole Contractor Amps	Panelbd/ Loadcenter Amp Rating	Branch Circuit ID	Branch Ckt. Bkr. Pole/Amps	Branch Circuit Amps	KVA Load
SB 183	289	ELC SRV TY A 240/480 100(SS)AL(E)SF(U)	2"	3/#2	100	2P/100	100	N/A	Lighting NB	2P/40	26	28.1
									Lighting SB	2P/40	25	
									Underpass	1P/20	15	
NB Access	30	ELC SRV TY D 120/240 060(NS)SS(E)TS(0)	1 1⁄4"	3/#6	N/A	2P/60		100	Sig. Controller	1P/30	23	5.3
							30		Luminaires	2P/20	9	
									CCTV	1P/20	3	
2nd & Main	58	ELC SRV TY T 120/240 000 (NS) GS (N) SP (0)	1 1⁄4"	3/#6	N/A	N/A	N/A	70	Flashing Beacon 1	1P/20	4	1.0
									Flashing Beacon 2	1P/20	4	

* Example only, not for construction. All new electrical services must have electrical service data chart specific to that service as shown in the plans.

** Verify service conduit size with utility. Size may change due to utility meter requirements. Ensure conduit size meets the National ELectrical Code.

EXPLANATION OF ELECTRICAL SERVICE DESCRIPTIVE CODE

ELEC SERV TY <u>x xxx/xxx</u> <u>xxx</u> (<u>xx</u>) <u>xx</u> (<u>x</u>) <u>xx</u> (<u>x</u>)	<u>x)</u>
Schematic Type	
Service Voltage V / V	
Disconnect Amp Rating 000 indicates main lug only/ Typically Type T	
(SS)= Safety Switch Ahead of Meter-Check with Utility (NS)= No safety Switch Ahead of Meter-Check with Utility	
Enclosure Type GS= Galvanized steel("off the shelf") SS= Stainless steel(Custom Enclosure)See MPL AL= Aluminum (Custom Enclosure)See MPL	
Photocell Mounting Location (E) = Inside Service/Enclosure Mounted (T) = Top of pole (L) = Luminaire mounted (N) = None/No Photocell or Lighting Contactor Required	
Service Support Type GC= Granite concrete OC= Other concrete TP= Timber pole SP= Steel pole SF= Steel frame OT= Pole by others or paid for separately EX= Existing pole TS= Service on traffic signal pole PS= Pedestal Service	
O= Overhead Service Feed from Utility U= Underground Service Feed from Utility	

2. When the utility company provides a transformer larger than 50 KVA. verify that the available fault current is less than the circuit breaker's ampere interrupting capacity (AIC) rating and provide documentation from the electric utility provider to the Engineer.

1. Provide photocell as listed on the MPL. Move, adjust, or shield the photocell from stray or ambient night time light to ensure proper operation. Mount photocell facing north when practical. Mount top of pole photocells as shown on Top Mounted Photocell Detail.

MAIN DISCONNECT & BRANCH CIRCUIT BREAKERS

Field drill flange-mounted remote operator handle if needed, to ensure handle is lockable in both the "On" and "Off" positions.

PHOTOELECTRIC CONTROL



			•					
FILE:	ed5-14.dgn	DN: TXDOT CK		CK: TxDOT DW:		TxDOT	ск: TxDOT	θ
CTxDOT October 2014		CONT SECT		JOB		HIGHWAY		ш
REVISIONS		0915	12	562 WA		WATS	TSON RD	
		DIST	COUNTY			SHEET NO.		φ
				BEXAR	2		210	

71E





SCHEMATIC TYPE D - CUSTOM 120/240 VOLTS - THREE WIRE

	SCHEMATIC LEGEND
1	Safety Switch (when required)
2	Meter (when required-verify with electric utility provider)
3	Service Assembly Enclosure
4	Main Disconnect Breaker (See Electrica) Service Data)
5	Circuit Breaker, 15 Amp (Control Circuit)
6	Auxiliary Enclosure
7	Control Station ("H-O-A" Switch)
8	Photo Electric Control (enclosure- mounted shown)
9	Lighting Contactor
10	Power Distribution Terminal Blocks
11	Neutral Bus
12	Branch Circuit Breaker (See Electrical Service Data)
13	Separate Circuit Breaker Panelboard
14	Load Center
15	Ground Bus

6



71F

DIST

COUNT

BEXAR

Ē

SHEET NO.

211



TIMBER POLE (TP) SERVICE SUPPORT NOTES

- 1. Ensure electrical service support is a class 5 treated timber pole as per Item 627 "Treated Timber Poles." Embed timber pole to depth required in Item 627.
- 2. Conduit and electrical conductors attached to the electrical service pole and underground within 12 in. of service pole are not paid for directly but are subsidiary to the electrial service.
- Install pole-top mounted photocell (T) on north side of pole, or in service enclosure (E) as required. See Electrical Service Data chart in plan set.
- 4. Gain pole as required to provide flat surface for each channel. Gain timber pole to % in. max. depth and 1 % in. max. height. Gain pole in a neat and workmanlike manner.
- 5. Mount meter and service equipment on stainless steel or golvanized channel (Unistrut, Kindorf, or equal). Provide channel sized 1 in. to 3 $\frac{3}{4}$ in. maximum depth, and $\frac{1}{2}$ in. to $\frac{1}{2}$ in. maximum width. File smooth the cut ends of galvanized channel and paint with zinc rich paint before installing on pole. Secure each channel section to timber pole with two galvanized or SS lag bolts, $\frac{1}{4}$ in. minimum diameter by $\frac{1}{2}$ in. minimum length. Use a galvanized or SS flat washer on each lag bolt. Do not stack channel.
- 6. When excess length must be trimmed from poles, trim from the top end only.
- (1) Class 5 pole, height as required
- Service drop from utility company (attached below weatherhead)
- (3) Service conduit (RMC) and service entrance conductors - One Red, One Black, One White (See Electrical Service Data)
- (4) Safety switch (when required)
- (5) Meter (when required)
- (6) Service enclosure
- 6 AWG bare grounding electrode conductor in 1/2 in. PVC to ground rod - extend 1/2 in. PVC
 6 in. underground.
- (8) % in. x 8 ft. Copper clad ground rod - drive ground rod to a depth of 2 in. to 4 in. below grade.
- (9) RMC same size as branch circuit conduit.
- (1) See pole-top mounted photocell detail on ED(5).
- When required by the serving utility provide bare 6 AWG copper conductor. Run wire from pole top to butt wrap or copper butt plate. Protect conductor with non-conductive material to a height of 8 ft. above finished grade.
- (12) When required by utility, cut top of pole at an angle to enhance rain run off.

rel. 8. s, Point of attachment to be below weather head Pole brand must be 5' or less above grade

-(5)

Couple to

Circuit

Conduit

Upper end of ground rod to be 2" to 4"

below finished grade

SERVICE SUPPORT TYPE TP (0)

5-30

6

(7)

 (\mathfrak{P})

6" to 10

typical

Bushing

Fitting

or Bell

End

typ.

GRANITE CONCRETE (GC) & OTHER CONCRETE (OC) NOTES

Ensure electrical service support structures bid as type Granite Concrete (GC) or Other Concrete (OC) meet the following requirements.

- 1. Provide GC and OC poles that meet the requirements of DMS 11080 "Electrical Services."
- 2. Provide prestressed concrete poles suitable for direct embedment into the ground without special foundations.
- 3. Verify poles are marked as required on DMS 11080. Location of marking should be approximately 4' above final grade. Use the two-point pickup locations when handling pole in horizontal position, and one-point pickup location for use in raising the pole to a vertical position. These marks are small but conspicuous.
- 4. Embed poles 42 in. or 10% of the length plus 2 ft., whichever is greater.
- 5. Ensure all installation details of services are in accordance with utility company specifications.
- 6. Install a one point rack or eye bolt bracket 6 inches to 12 inches below the weatherhead as an overhead service drop anchoring point for the electric utility.
- 7. Furnish and install galvanized or stainless steel channel strut $1\frac{1}{2}$ in. or $1\frac{5}{6}$ in. wide by 1 in. up to $3\frac{3}{4}$ in. deep (Unistrut, Kindorf, B-line or equal). Attach channel strut with stainless steel concrete anchors (max. $1^{"}$ depth), square U-bolts or back to back channel strut with long bolts, or other secure mounting as approved by the Engineer. Ensure bolts are galvanized in accordance with ASTM A153. Do not stack channel struts.
- 8. Backfill the holes thoroughly by tamping in 6 in. lifts. After tamping to grade, place additional backfill material in a 6 inch high cone around the pole to allow for settling. Use material equal in composition and density to the surrounding area. Backfilling will not be paid for directly but is subsidiary to various bid items.



CONCRETE SERVICE SUPPORT Overhead (0)



71K

DIST

COUNTY

BEXAR

\$F IL

SHEET NO.

DUCT CABLE & HDPE CONDUIT NOTES

- 1. Provide duct cable in accordance with Departmental Material Specification (DMS) 11060 "Duct Cable" and Item 622 "Duct Cable." Provide duct cable as listed on the Material Producer List (MPL) on the Department web site under "Roadway Illumination and Electrical Supplies" Item 622.
- Provide High-Density Polyethylene (HDPE) conduit in accordance with DMS 11060 and Item 618, "Conduit." Provide HDPE as listed on the MPL on the Department web site under "Roadway Illumination and Electrical Supplies," Item 618.
- 3. Supply duct cable with a minimum 2 in. diameter, unless otherwise shown in the plans. Provide duct cable and HDPE conduit as shown by descriptive code or on the plans. Bend duct cable and HDPE conduit as recommended by the manufacturer, with a minimum bending radius of 26 in. for 2 in. duct. Follow manufacturers' recommendations when handling duct cable and HDPE conduit reels and during installation of duct cable and HDPE conduit.
- 4. Do not splice conductors within duct cable or HDPE conduit. Couple duct cable and HDPE entering a ground box or foundation to a PVC elbow. When galvanized steel RMC elbows are called for in the plans and any portion of the RMC elbow is buried less than 18" from possible contact, ground the RMC elbow.
- 5. Furnish and install duct cable with factory installed conductors, sized as shown in the plans and as required by the National Electrical Code (NEC). The NEC contains specific requirements for duct cable in Article, "Nonmetallic Underground Conduit with Conductors: Type NUCC.
- 6. When conduit casing is called for in the plans, extend duct cable or HDPE conduit through the conduit casing in one continuous length without connection to the casing.
- 7. Seal the ends of duct cable or HDPE conduit with duct seal, expandable foam, or other approved method after completing the pull tests required by Item 622.
- 8. Provide minimum cover of 24 in. under roadways, 18 in. in other locations, or as shown on the plans.
- 9. Furnish and install listed fittings to couple duct cable or HDPE conduit to other types of conduit. Duct cable and HDPE conduit may be field-threaded and spliced with PVC or RMC threaded couplings; connected with listed tie-wrap fittings; connected using listed coupling made of HDPE with stainless steel external banding clamps and locking rings; connected with approved electrofusion conduit couplings; or connected using an approved chemical fusion method using an epoxy or adhesive specifically designed for HDPE couplings and connectors all installed in accordance with their manufacturer's instructions. Do not use PVC glue on HDPE. Do not use water pipe fittings, or connect conduit with heat shrink tubing.



DUCT CABLE/HDPE TO PVC















-Ground box

Aggregate bed is to be a minimum, of 9 inches deep, placed under and not in the ground box. Ensure the aggregate does not encroach into the interior of the box.

When the upper end of an RMC Ell does not enter the ground box, it may be extended with a SCH-40 PVC conduit nipple and bell end, provided there is a minimum of 18" of cover over all parts of the elbow. If not, a rigid extension and ground bushing is required.

1"-3" exposed

2" min., from top of drill shaft to RMC

RMC elbow

Ground rods are not shown on this standard sheet, but may be required elsewhere in plans.

Drill shaft foundation Class A Concrete



BATTERY BOX GROUND BOXES NOTES

A. MATERIALS

- Provide polymer concrete or fiberglass reinforced plastic (FRP) battery box ground box and cover in accordance with Departmental Material Specification (DMS) 11071 "Battery Box Ground Boxes." Battery box will accommodate up to 4 batteries, each measuring 8 in. x 13.5 in. x 10 in. (W x L x D). Label battery box ground box cover in accordance with DMS 11071.
- 2. Supply a marine grade batteries with covers. Secure the marine grade batteries with covers to the stainless steel rack in the bottom of the ground box with tie down straps.

B. CONSTRUCTION METHODS

- 1. Ensure conduit entry will not interfere with placement of the batteries in the battery box ground box.
- 2. Remove all gravel and dirt from conduit. Cap all conduits prior to placing aggregate and setting bottery box ground box. Provide Grade 3 or 4 coarse aggregate as shown on Table 2 of Item 302 "Aggregates for Surface Treatments." Ensure the aggregate bed is in place and is a minimum of 9 in. deep prior to setting the box. Install battery box ground box on top of aggregate.
- 3. Cast battery box aprons in place. Reinforcing steel may be field bent. Ensure the depth of concrete for the apron extends from finished grade to the top of the aggregate bed under the box. Battery box ground box aprons, including concrete and reinforcing steel, are subsidiary to battery box ground boxes when called for by descriptive code.
- 4. Bolt covers down when not working in battery box ground boxes. Keep bolt holes in the box clear of dirt.







- () Place aggregate under the box and not in the box. Aggregate should not encroach on the interior volume of the box.
- (2) Install bushing or bell end fitting on the upper end of all ells.
- (3) Install all conduits in a neat and workmanlike manner.



BATTERY BOX TOP VIEW



SECTION X-X







Texas Department	of Tra	nsp	ortation	,	Ti Ope Di Sta	raffic rations vision undard
ELECTRI BAT GROU	CAI TER IND	L Y E	DE T BOX BOXE	A X S	IL	S
ED ED	(12)	-14			
FILE: ed12-14.dgn	DN: TX	DOT	ск: TxDOT	DW:	TxDOT	ск: TxDOT
CTxDOT October 2014	CONT	SECT JOB HIGHWAY				GHWAY
REVISIONS	0915)915 12 562 WATS		SON RD		
	DIST		COUNTY			SHEET NO.
			BEXAR	!		215
ROADWAY ILLUMINATION ASSEMBLY NOTES

- 1. Details apply to roadway lighting installations bid or referenced under Item 610, "Roadway Illumination Assemblies." Provide, furnish, and install all other materials not shown on the plans which may be necessary for complete and proper construction. Where manufacturers provide warranties or guarantees as a customary trade practice, furnish to the State such warranties or quarantees.
- 2. The locations of poles and fixtures may be shifted by the Engineer to accommodate local conditions. Install or remove poles and luminaires located near overhead electrical lines using established industry and utility safety practices and in accordance with laws governing such work. Consult with the appropriate utility company prior to beginning such work.
- 3. Provide new and unused materials. Ensure that all materials and installations comply with the applicable articles of the National Electrical Code (NEC), TxDOT standards and specifications, National Electrical Manufacturers Association (NEMA), and are listed by Underwriters Laboratories (UL) or a Nationally Recognized Testing Lab (NRTL). NRTLs such as Canadian Standard Association, Intertek Testing Services NA Inc., or FM Approvals LLC can be considered equivalent to UL. Faulty fabrication or poor workmanship in any material, equipment, or installation is justification for rejection.
- 4. Provide Roadway Illumination Light Fixtures as per TxDOT Departmental Material Specification (DMS) 11010, Item 610, and as shown on the Material Producers List (MPL) for Roadway Illumination and Electrical Supplies.
- 5. Fabricate steel roadway illumination poles in accordance with Roadway Illumination Poles (RIP) standards and Item 610. Poles fabricated according to RIP standards do not require shop drawing submittals.
 - a. Alternate designs to RIP standards or the use of aluminum to fabricate poles will require the submission of shop drawings electronically. For instructions on submitting shop drawings electronically see "Guide to Electronic Shop Drawing Submittal" on the TxDOT web site.
 - b. Limitations on use of the RIP standard: The RIP standard details were developed for installations in locations where the 3-second gust basic maximum wind speed is 110 mph, and where the elevation of the base of the pole is less than (i.e. not more than) 25' above the elevation of the surrounding terrain, in accordance with the "AASHTO Standard Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals," 4th Edition (2001) (AASHTO Design Specifications). For poles to be installed in regions where the maximum basic wind speed exceeds 110 mph or to be mounted more than 25' above the surrounding terrain, provide poles meeting the following requirements:
 - i. Submittals. Following the electronic shop drawing submittal process (see Guide to Electronic Shop Drawing Submittal on the TxDOT web site), submit to the Engineer for approval fabrication drawings and calculations for the poles, sealed by a Texas licensed professional engineer (P.E.).
 - ii. Luminaire Structural Support Requirements. Provide light poles, arms, and anchor bolt assemblies with a 25 year design life to safely resist dead loads, ice loads and the required basic wind speeds at the location of installation in accordance with the 6th edition (2013) of the AASHTO Design Specifications. For transformer base poles, include transformer base and connecting hardware in calculations and shop drawing submittals. Structurally test all transformer bases to resist the theoretical plastic moment capacity of the pole. Submit certification of the plastic moment load test and FHWA breakaway requirement test of the model of base being furnished with the shop drawings. Show breakaway base model number, manufacturer's name, and logo on shop drawings. Include on manufacturer's shop drawings the ASTM designations for all materials to be used.
- 6. For both transformer and shoe-base type illumination poles, provide and install double-pole breakaway fuse holders as specified by DMS-11040. Breakaway fuse holders are listed on the MPL for Roadway Illumination and Electrical Supplies under Items 610 & 620. Provide 10 amp time delay fuses for breakaway connectors in light poles, or inside the light fixture for underpass luminaires. In each pole, connect luminaires to the breakaway connector with continuous stranded 12 AWG copper conductors as listed on the MPL. Bond all equipment grounding conductors together and to the ground lug in the transformer base or hand hole.
- 7. Tighten anchor bolts for shoe base, concrete traffic barrier base, and bridge mount roadway illumination poles, in accordance with Item 449.
- 8. Install T-Base with following procedure:
 - a. Anchor Bolt Tightening.
 - i. Coat the threads of the anchor bolts with electrically conductive lubricant.
 - ii. Place the T-base over the anchor bolts. Foundation must be level and flat. The maximum permissible gap under any one corner of the t-base is 1/8" before nuts are tightened.
 - iii.Coat the bearing surfaces of the nuts and washers with electrically conductive lubricant. Install (1) 1/2" hold down washer, (1) lock washer, and (1) nut on each anchor bolt. Turn the nuts onto the bolts so that each is hand-tight against the washer.
 - iv. Using a torque wrench, tighten each nut to 150 ft-Ib. Uniform contact is required between the foundation and the T-base in the corner regions of the T-base, and all corner gaps must be closed after applying torque. If a gap still exists after torquing to 150 ft-lbs, continue torquing each bolt incrementally until gap is closed or maximum allowable torque of 250 ft. pound is reached, whichever comes first. If 250 ft-lbs is not enough to close the gap the foundation must be leveled. Gaps along the straight sides of the T-bases and the foundation are permissible. Ensure that no high point of contact occurs between the straight sides of the T-base and the foundation.
 - v. Check top of T-base for level. If not level then foundation must be leveled.
 - b. Top Bolt Procedure
 - i. Erect pole over T-base with crane. Coat bolts, nuts, washers, and lock washers with electrically conductive lubricant.

- "Structural Bolting."
- iii.Tighten each nut to 150 ft-1b. using a torque wrench.
- c. Level and Plumb
 - dearees.
- standard sheet RID(2).
- RID(3), Typical luminaire size for underpass luminaires is 150W HPS or 150W EQ LED.
- 11. Mount luminaires on arms level as shown by the luminaire level indicator.



TYPICAL WIRING DIAGRAM

LUMINAIRES SERVED AT 480V ON 240/480 VOLT SERVICE OR LUMINAIRES SERVED AT 240V FOR 120/240 VOLT SERVICE.

ii. Install bolts and 1/2" connecting washers from the inside of the T-base, thread up through the pole base. Install flat washers, lock washers and nuts snug tight according to Item 447,

i. Ensure pole is plumb and mast arm is perpendicular to the roadway according to plans to within 5

9. Construct luminaire pole foundations in accordance with Item 416, "Drilled Shaft Foundations," and TxDOT

10. Provide and install underpass luminaires in accordance with Item 610, DMS-11010, and TxDOT standard sheet

12. Orient luminaires perpendicular to the roadway intended to be lit unless otherwise shown on the plans.

NOTES:

Use 1/2 in.-13 UNC threaded, copper or tin-plated copper. pole bonding connector, sized appropriately for conductors, bonded to T-base, or use ground lug in handhole as available.

Use pre-qualified two-pole breakaway connectors for all luminaire pole installations. For luminaires fed by a circuit with a neutral conductor, use double pole breakaway connectors with the neutral side unfused and marked white.

Split Bolt or other connector.

Traffic Operations Division Standard								
R(ILLU)AD MII	W/ NA	AY TIC)N				
DE	TA	I	_S					
RIC)(1)	-17					
FILE: rid1-17.dgn	DN:		СК:	DW:		CK:	e	
©TxDOT January 2007	CONT	SECT	JOB		Ŧ	IGHWAY	L L	
REVISIONS	0915	12	562		WAT	SON	RD	
7-17	DIST		COUNT	Y		SHEET	NO. 6	
			BEXAF	۲		216	5	
72A								



No warranty of any for the conversion Practice Act". responsibility is governed by the "Texas Engineering purpose whatsoever. IxDOI assumes no mots or for incorrect results or domag ٩¢ MER: Use made DISCLAIM The kind is

this standard i y TxDOT for any rd to other form

1. "Recommended Foundation Lengths" table is for information purposes only. Foundation lengths shall be as shown on the plans, or as directed by the Engineer. Foundations will be paid for under Item 416, "Drilled Shaft Foundations." unless otherwise shown on the plans.

2. Erect roadway illumination assembly poles plumb and true. Form and level the top 6" of the foundation so the pole will be plumb. Use leveling nuts to plumb shoe base poles. Do not use shims or leveling nuts under transformer bases. Do not grout between baseplate and the foundation.

3. Ensure Class 2A and 2B fit for anchor bolts and nuts. Tap and chase nuts after galvanizing. Anchor bolt body with rolled threads need not be full

4. Use appropriate class of concrete as specified in Items 416 and 432. Concrete for riprap may be upgraded to Class C at no extra cost to the

5. Place riprop around the foundation when called for elsewhere in the plans. Riprop will be paid for under Item 432.

6. Locate breakaway roadway illumination assemblies as shown in the placement table, unless otherwise dimensioned on the plans. Protect non-breakaway illumination assemblies from vehicular impact (i.e. 2.5 ft. behind guard rail or mounted on traffic barrier), or located outside the clear zone, except that 2.5 ft. from curb face is minimum desired for light poles on city streets, 45 mph or less. See Roadway Design Manual for further

7. Use 4 hold down and 4 connecting washers on transformer base poles as recommended by the manufacturer and supplied with base.

8. Install a minimum of 2 conduits in each foundation. See lighting layout sheets for locations of foundations with more than 2 conduits. Cap unused conduits in foundations on both ends.

9. Conduit location in foundations is critical for breakaway devices. Place conduits 2 in. apart on centerline as shown.

Bond anchor bolt to rebar cage with #6 bare stranded copper conductor. Use listed mechanical connectors rated for embedment in concrete. The bonded steel in the foundation creates a concrete encased grounding electrode which replaces the ground rod.

11. Use riprap on T-base foundations that are located on sloped grades.

TABLE 4					
BREAKAWAY POLE PLACEMENT (See note 6)					
ROADWAY FUNCTIONAL CLASSIFICATION	** POLE OFFSET (DISTANCE TO FACE OF TRANSFORMER BASE)				
Freeway Mainlanes (roadway with full control of access)	15 ft. (minimum and typical) from lane edge				
All curbed, 45 mph or less design speed	2.5 ft. minimum (15 ft. desirable) from curb face				
All others	10 ft. minimum*(15 ft. desirable) from lane edge				

* or as close to ROW line as is practical

** provide 2/5 of the luminaire mounting height behind the pole for "falling area" to prevent encroachment on the other travel lanes. See design guidelines.

Traffic Operations Division Standard								
RC ILLU DE (RDWY ILLUM RID)AD 	WA NA II OL	AY TIO S INDA ⁻	N T I (ONS	5)		
FILE: rid2-17.dgn	DN:		СК:	DW:		CK:	φ	
© TxDOT January 2007	CONT	SECT	JOB		н	GHWAY	ES	
REVISIONS	0915	12	562		WATS	SON RE	기년	
7-17	DIST		COUNTY			SHEET NO	. ⊮	
			BEXAR	2		217		
72B								

<u>ک</u> ر	м	No oun	min tin (ft	a g)
s or			20	
ver	<u> </u>		30	
e. Con	<u> </u>		50	
he us				
0 4 5 + + 0	<u> </u>		40	
ĭ, ž			-0	
, 1 Dia 1 Dia 1 Dia 1 Dia 1 Dia				
ons suls				
esp				
n Pr Des	<u> </u>		50	
in si				
sumer Sumer				
ngin as: ts a				
sul sul				
exe T T exe				
the "I ever. orrect	GE	NE	R	41
erned by 1 se whatsoe sr for inco	1.	AII shc equ guc	wo 111 1ipn 1rar	b b ne
ard is gov any purpo formats o	2.	The cor anc cor	e Ic Idii Iui Ipar	
s stand DOT for o other	3.	Sto her sto	indo eir indo	or N, Or
of thi by Tx idard t	4.	0pt per	ior mil	na +
The use 1 is made his star		а.	Sho sec The	op J I S

				1					
SHIPPI	NG I	PARTS	LIST	-	POLES	AND	LUMINAIRE	ARMS	

Nominal	Shoe Base		T-Base			CSB/SSCB Mounted			
Mounting Ht.	Designation		Quantity	Designation			D	esignation	0.000+1+1
(f†)	Pole A1 A2 Lumi	inaire	addining	Pole A1 A2	Luminaire	Quantity	Pole	A1 A2 Luminaire	Quantity
20	(Type SA 20 S - 4) (150	OW EQ) LED		(Type SA 20 T - 4)	(150W EQ) LED				
	(Type SA 20 S - 4 - 4) (150	OW EQ) LED		(Type SA 20 T - 4 - 4)	(150W EQ) LED				
30	(Type SA 30 S - 4) (250	OW EQ) LED		(Type SA 30 T - 4)	(250W EQ) LED		(Type SP 28 S	- 4) (250W EQ) LE	D
	(Type SA 30 S - 4 - 4) (250	OW EQ) LED		(Type SA 30 T - 4 - 4)	(250W EQ) LED		(Type SP 28 S	- 4 - 4) (250W EQ) LE	D
	(Type SA 30 S - 8) (250	OW EQ) LED		(Type SA 30 T - 8)	(250W EQ) LED		(Type SP 28 S	- 8) (250W EQ) LE	D
	(Type SA 30 S - 8 - 8) (250	OW EQ) LED		(Type SA 30 T - 8 - 8)	(250W EQ) LED		(Type SP 28 S	- 8 - 8) (250W EQ) LE	D
40	(Type SA 40 S - 4) (250	OW EQ) LED		(Type SA 40 T - 4)	(250W EQ) LED		(Type SP 38 S	- 4) (250W EQ) LE	D
	(Type SA 40 S - 4 - 4) (250	OW EQ) LED		(Type SA 40 T - 4 - 4)	(250W EQ) LED		(Type SP 38 S	- 4 - 4) (250W EQ) LE	D
	(Type SA 40 S - 8) (250	OW EQ) LED		(Type SA 40 T - 8)	(250W EQ) LED	5	(Type SP 38 S	- 8) (250W EQ) LE	D
	(Type SA 40 S - 8 - 8) (250	OW EQ) LED		(Type SA 40 T - 8 - 8)	(250W EQ) LED	4	(Type SP 38 S	- 8 - 8) (250W EQ) LE	D
	(Type SA 40 S - 10) (250	OW EQ) LED		(Type SA 40 T - 10)	(250W EQ) LED		(Type SP 38 S	- 10) (250W EQ) LE	D
	(Type SA 40 S - 10 - 10) (250	OW EQ) LED		(Type SA 40 T - 10 - 10)	(250W EQ) LED		(Type SP 38 S	- 10 - 10) (250W EQ) LE	D
	(Type SA 40 S - 12) (250	OW EQ) LED		(Type SA 40 T - 12)	(250W EQ) LED		(Type SP 38 S	- 12) (250W EQ) LE	D
	(Type SA 40 S - 12 - 12) (250	OW EQ) LED		(Type SA 40 T - 12 - 12)	(250W EQ) LED		(Type SP 38 S	- 12 - 12) (250W EQ) LE	D
50	(Type SA 50 S - 4) (400	OW EQ) LED		(Type SA 50 T - 4)	(400W EQ) LED		(Type SP 48 S	- 4) (400W EQ) LE	D
	(Type SA 50 S - 4 - 4) (400	OW EQ) LED		(Type SA 50 T - 4 - 4)	(400W EQ) LED		(Type SP 48 S	- 4 - 4) (400W EQ) LE	D
	(Type SA 50 S - 8) (400	OW EQ) LED		(Type SA 50 T - 8)	(400W EQ) LED		(Type SP 48 S	- 8) (400W EQ) LE	D
	(Type SA 50 S - 8 - 8) (400	OW EQ) LED		(Type SA 50 T - 8 - 8)	(400W EQ) LED		(Type SP 48 S	- 8 - 8) (400W EQ) LE	D
	(Type SA 50 S - 10) (400	OW EQ) LED		(Type SA 50 T - 10)	(400W EQ) LED		(Type SP 48 S	- 10) (400W EQ) LE	D
	(Type SA 50 S - 10 - 10) (400	OW EQ) LED		(Type SA 50 T - 10 - 10)	(400W EQ) LED		(Type SP 48 S	- 10 - 10) (400W EQ) LE	D
	(Type SA 50 S - 12) (400	OW EQ) LED		(Type SA 50 T - 12)	(400W EQ) LED		(Type SP 48 S	- 12) (400W EQ) LE	D
	(Type SA 50 S - 12 - 12) (400	OW EQ) LED		(Type SA 50 T - 12 - 12)	(400W EQ) LED		(Type SP 48 S	- 12 - 12) (400W EQ) LE	D

L NUIES:

rk, materials and services not shown on the plans which may be necessary for complete and proper construction be performed, furnished and installed by the Contractor. Faulty fabrication or poor workmanship in any material, ent or installation will be considered justification for rejection. Where manufacturers provide warranties or ees as a customary trade practice, furnish to the Department such warranties or guarantees.

cation of poles and fixtures are diagrammatic only and may be shifted by the Engineer to accommodate local ions. Install or remove poles and luminaires located near overhead electrical lines using established industry ility safety practices and in accordance with laws governing such work. Consult with the appropriate utility prior to beginning such work.

- d Steel Pole Designs. Steel poles fabricated in accordance with the details and dimensions shown shall be considered standard designs. Submission of shop drawings and design calculations for rd designs is not required.
- al Steel Pole Designs. Multi-sided steel poles may be allowed as optional designs, if steel poles are ted or required, pending approval by the Department as outlined below.
- p Drawings. Optional designs require submission of shop drawings and design calculations bearing the I of an engineer licensed in the State of Texas, in accordance with Item 441, "Steel Structures." Department may elect to pre-approve some shop drawings for optionally designed poles. Submission of p drawings and design calculations is not required for structures fabricated in accordance with the details of shop drawings on the pre-approved list maintained by the TxDOT Traffic Operations Division. Any deviation from the pre-approved shop drawings will require submission of shop drawings of the complete
- deviation from the pre-approved shop drawings will require submission of shop drawings of the complete assembly and design calculations as described above.
 b. Structural Support Design for Luminaires. Lighting support structures shall be designed for a 25 year design life in accordance with the AASHTO Standard Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals, 6th Edition (2013) and Interim Revisions thereto. All poles shall be designed for 110 mph 3-second gust wind speeds. The Gust Factor, G, and Wind Importance Factor, Ir, shall be applied as per the AASHTO Specifications assuming a 25-year design life. The design wind pressure for hurricane wind velocities greater than 100 mph shall not be less than the design wind pressure using 100 mph with the non-hurricane Wind Importance Factor, Ir, value. For transformer base poles, fabricator shall include transformer base and connecting hardware in design calculations and shop drawing submittals. All transformer base shall have been structurally tested to resist the theoretical plastic moment capacity of the pole. Certification of the plastic moment load test and FHWA breakaway requirement test of the model of base being furnished shall be submitted with the shop and FHWA breakaway requirement test of the model of base being furnished shall be submitted with the shop drawings. Shop drawings shall show breakaway base model number, and manufacturer's name and logo. Manufacturer's shop drawings shall include the ASIM designations for all materials to be used. c. Mast Arm Attachments. All poles and attachments shall be structurally designed to support two 12-foot mast arms and luminaires. Poles shall be supplied with mast arm combinations as shown in the plans. All
- mast arms shall be designed for a 60-pound luminaire having an effective projected area of 1.6 square feet. d. Anchor Bolt Assembly. Anchor bolt assemblies for optionally designed poles shall be the same as those shown herein.

5. Aluminum Pole Designs. Aluminum pole designs may be allowed, if aluminum poles are permitted or required, pending approval by the Department as outlined below.

- a. Meet all of the requirements stated above for optional steel pole designs and the following: 1. Aluminum poles shall be fabricated in accordance with "Structural Welding Code-Aluminum" AWS D1.2. Aluminum poles shall be fabricated in accordance with "Structural Welding Code-Aluminum" AWS D1.2.
 Aluminum pole designs shall use the same anchor bolt assembly and be subject to the same geometric restraints and other requirements for steel poles specified herein.
 Aluminum poles shall be equipped with vibration mitigation devices, as approved by the engineer.
 Pole components shall be constructed using the following material: Shaft: ASTM B221 or B241 Alloy 6063-T6, ASTM B209 Alloy 5086-H34, ASTM B221 Alloy 6005-T5. Base Flange: ASTM B26 Alloy 356.0-T6 or ASTM B108 Alloy 356.0-T6 (Yield strength test required). Mast Arms: ASTM B261 NID 6061-T6 or ASTM B108 Alloy 356.0-T6.
 Pole Cap: ASTM B241 Alloy 6061-T6 or ASTM B108 or B26 Alloy 356.0-T6. Pole Cap: ASTM B209 Alloy 5086-H32 or ASTM B108 or B26 Alloy 356.0-T6. Bolts: Stainless Steel Alloy 5086-H32 or ASTM B108 or B26 Alloy 356.0-T6.

 - anti-seize compound, Never-Seez Compound, Permatex 133K or equal.

6. Special Designs. Poles with architectural treatments shall meet the requirements shown elsewhere in the plans.

7. Luminaire Mounting Height. Actual luminaire mounting height shall be the nominal mounting height given on RIP(2) for all pole-arm combinations except for poles with 4 ft. luminaire arms, which shall be 3'-0" lower than the nominal height, unless otherwise shown or directed.

- SA: Pole and mast arm may be steel aluminum.
- ST: Pole and mast arm must be steel
 - AL: Pole and mast arm must be alumi SP: Special (ovalized) steel or alur
 - for installing on CSB or SSCB. sheet CSB (4), or SSCB (4).

Two numerical digits denote nominal-mounting height in feet.

Next letter denotes type of base, (S T-Transformer Base, or B-Bridge/Ret.

First number denotes length of mast in feet.

Use of second mast arm is indicated dashed number which denotes length i

Luminaire ratina in watts (i.e. 400) wattage LED fixtures will include EQ

Last letters indicate light source (S Sodium; LED - LED luminaire)

	отн	ER	
Desid	anatio	n	
A1	A2	Luminaire	Quantity
	-		
	Desi(A1	OTH Designatio	OTHER Designation A1 A2 Luminaire

EXPLANATION OF ROADWAY ILLUMINATION ASSEMBLY DESIGNATIONS

TYPE SA 50	т-х	-	X)	(400W	EQ)	LED
or] num. minum pole See standard						
-Shoe Base, ——— Wall Mount) arm ————————————————————————————————————						
by second ——— n feet.						
/). Equivalent) (i.e. 400W EQ)						
- High Pressure						

SHEET 1 OF 4							
Traffic Safety Division Standard							
R(ILLU F RI	DAD MII POL	W/ NA E?	AY TIO S) - 19	N)			
FILE: rip-19.dgn	DN:		СК:	DW:	CK:		
© TxDOT January 2007	CONT	SECT	JOB		HIGHWAY		
REVISIONS	0915	12	562		WATSON RD		
1-11	DIST		COUNTY		SHEET NO.		
12 13			BEXAR	2	218		
73A							



GENERAL NOTES:

- 1. Designs conform to AASHTO Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, 6th Edition (2013) and Interim Revisions thereto. Design 3-Second Gust Wind Speed equals 110 mph with a 1.14 gust factor. A wind importance factor of 0.80 is applied to adjust the wind speed to a 25 year recurrence interval. Design moments listed in tables assume base of pole is 25' above natural ground level.
- 2. Structures are designed to support two 12' luminaire most arms and luminaires. Mast arms are designed to support a 60-pound luminaire having an effective projected area of 1.6 square feet.
- 3. Fabrication shall be in accordance with the Specifications and with the details, dimensions, and weld procedures shown herein. Do not submit shop drawings for roadway illumination pole assemblies fabricated in accordance with the details, dimensions, and weld procedures shown herein. Weld references call for preapproved weld procedures which the Fabricator must obtain prior to shipping practices shall meet the requirements of these sheets and the Specifications. In the absence of specified fabrication tolerances, dimensions shall be within the tolerances generally obtainable in normal fabrication practice.

- 4. For mounting heights between values shown in the tables, use base diameter and thickness values for the larger height.
- 5. Unless otherwise noted, all steel parts shall be galvanized in accordance with Item 445, "Galvanizing.
- 6. Steel poles shall be fabricated in accordance with Item 441, "Steel Structures." Longitudinal seam welds for pole sections shall have 60% minimum penetration. All welding shall be in accordance with AWS D1.1, Structural Welding Code-Steel.
- 7. Two-section poles joined by circumferential welds will not be permitted, unless otherwise shown on the plans. Poles may be fabricated in two sections and fieldassembled by the lap-joint method. The two sections shall telescope together with a lap length of not less than 1-1/2 times the shaft diameter at the lap joint.
- 8. Alternate material equal to or better than material specified may be substituted with the approval of the Engineer
- 9. Lubricate and tighten anchor bolts, when erecting shoe base poles and concrete traffic barrier base poles, in accordance with Item 449, "Anchor Bolts.

- 10. All poles, except Transformer Base Poles, shall have hand holes with reinforcing frames and covers. For ground mounted shoe base poles, hand holes shall be placed 90 degrees to mast arm unless otherwise noted on the plans. For poles mounted on a concrete traffic barrier with one luminaire arm hand holes shall be located 180 degrees from luminaire arm. For poles mounted on a concrete traffic barrier with two luminaire arms, all hand holes shall be on the same side of the barrier. For poles mounted on a bridge lighting bracket or a retaining wall lighting bracket, hand hole shall be on traffic side of the pole, at a height that will clear the barrier.
- 11. The finished pole shall have a smooth, uniform finish free of pits, blisters, or other defects. Scratched, chipped, and other damaged galvanized areas on poles and mast arms shall be repaired in accordance with Item 445, "Galvanizina,
- 12. Pole length is based on a 5'-6" luminaire arm rise. 4 ft. luminaire arms have a 2'-6" rise. A pole with 4 ft. luminair arms will have an actual mounting height 3'-0" less than the nominal mounting height. Increasing the pole length to meet the nominal mounting height is allowed, but unnecessary unle otherwise directed by the engineer.

13. Erect transformer base poles in accordance with sheet RID(1)

of any version

• •	_		MATERIAL	DATA	
Rise			COMPONENT	ASTM DESIGNATION	MIN. YIELD (ksi)
¥		Po	le Shaft (0.14"/ft. Taper)	A572 Gr 50, A595 Gr A, A1011 HSLAS Gr 50 Cl 2 (3), or A1008 HSLAS Gr 50 Cl 2	50
		Ba	se Plate and Handhole Frame	A572 Gr.50, or A36	36
nomino		T - I	Base Connecting Bolts	F3125 Gr A325	92
eight (An	chor Bolts	F1554 Gr 55, A193-B7 or A321	55 105
ang He	`	And	chor Bolt Templates	A36	36
Mount	, ,	Heo	ovy Hex (H.H.) Nuts	A194 Gr 2H,or A563 Gr DH	
inaire		FI	at Washers	F436	
ן ב ן ב			NOTES:		
			①2'-6" rise for 4 ft. lum	ninaire arms.	-
Š	<u></u>		(2) Before ovalized as shown Traffic Barrier Base Bas Sheet 4 of 4.	n on Concrete seplate details,	
e Traff Ancho y Deta	ic r iil,		③A1011 SS Gr 50 may be us HSLAS, provided the mote the elongation requirement	ed instead of erial meets ents for HSLAS.	
ł			POLE ASSEMBLY F TOLERANCES	ABRICATION TABLE	
			DIMENSION	TOLERANCE	
			Shaft length	+1"	
SSCBI			of slip fitting pieces	+1/8", -1/16"	·
gn Mome	ent		O.D. of inside piece of slip fitting pieces	+1/32", -1/8"	·
(K-f+) • G Pe	erp.		Shaft diameter: other	+3/16"	
iii to	Rail		Out of "round"	1/4"	
3 13	5.2		Straightness of shaft	±1/4" in 10 f	t
6 20	J. 8		Twist in multi-sided shaft	4° in 50 ft	
1 30	J. 5		Perpendicular to baseplate	1/8" in 24"	
		•	Pole centered on baseplate	±1/4"	
		-	Location of Attachments	±1/4"	

	SHEET 2	OF 4	Traffic
	Texas Department of Tra	nsportation	Safety Division Standard
	ROAD		
	POL	ES	N
	POL RIP (2	NATIO ES 2)-19)
e	FILE: rip-19. dgn	ES 2) - 19	М ом: ск:
S	FILE: rip-19. dgn DN: () TXDDT January 2007 CONT	NA ΓΙΟ ES 2) - 19 <u>cκ</u> : sect job	О Dov: СК: Н1GHWAY
5	FILE rip-19. dgn DNI © TXDDT January 2007 CONT REVISIONS 0915	NATIO ES 2)-19	DW: CK: HIGHWAY WATSON RD
5	FILE rip-19. dgn DNI © TXD0T January 2007 CONT REVISIONS 0915 7-17 12-19 DIST	NATIO ES 2) - 19 ск: sect JOB 12 562 солиту	DW1 CK1 HIGHWAY WATSON RD SHEET NO.

Bolt hole spacing

±1/16



Pole or Arm Simplex	ASTM A27 Gr 65-35 or Gr 70-36, A148 Gr 80-50, A576 Gr 1021 (5), or A36 (Arm only)
Arm Pipes	ASTM A53 Gr A or B,A500 Gr B, A501, A 1008 HSLAS-F Gr 50 6, or A1011 HSLAS-F Gr 50 6
Arm Struts and Gusset Plates ④	ASTM A36,A572 Gr 50 6, or A588
Misc.	ASTM designations as noted



Texas Engineering Practice Act". TXDOT assumes no responsibility + results or domones resulting for this standard y TxDOT for any ٩ و The

113+00.00 STA <u>144.60'</u> S 45° 25' 12.73" E MATCHLINE PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOT DRIVER: WATSON_@ 12:53:59 PM DESIGN FILENAME: X:\data\Infra\Proj_2016\ - UG-TELE



!	
-	00.00
0	113+0
-	Ì
113	ST/
	Щ
G ↓ -	MATCHLIN

UTILITY LEGEND

— OP —	CPS ELECTRIC O/H
— EG —	ENTERPRISE GAS LINE
— cc —	CPS GAS
— UT —	SBC U/G TELEPHONE LINE
— то —	SBC O/H TELEPHONE LINE
— ww —	SANITARY SEWER LINE
— X Water —	SAWS
	EXISTING R.O.W.
۲	UTILITY POLE
\rightarrow	GUY WIRE
0	ROAD SIGN
\odot	FIRE HYDRANT
\bigotimes	WATER VALVE
•	GAS VALVE
Ø	GAS METER
Ø	WATER METER
ØO	MANHOLES
(30)	STORM DRAIN
õ	CENTER POINT OF TREE
T	TELEPHONE PEDESTAL
TV	TV CABLE CONTROL BOX







PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6(25/2020 @ 12:54:00 PM

-	121+50.00
	STA
	HLINE
	MATC

UTILITY LEGEND

— OP —	CPS ELECTRIC O/H
— EG —	ENTERPRISE GAS LINE
— cc —	CPS GAS
— UT —	SBC U/G TELEPHONE LINE
— от —	SBC O/H TELEPHONE LINE
— ww —	SANITARY SEWER LINE
— X Water —	SAWS
	EXISTING R.O.W.
۲	UTILITY POLE
\rightarrow	GUY WIRE
	ROAD SIGN
\odot	FIRE HYDRANT
\bigotimes	WATER VALVE
•	GAS VALVE
Ø	GAS METER
Ø	WATER METER
ØO	MANHOLES
(30)	STORM DRAIN
õ	CENTER POINT OF TREE
T	TELEPHONE PEDESTAL
TV	TV CABLE CONTROL BOX



MATCHLINE STA 126+00.00

PLOTTED BY: evaldez PLOTTED SCALE: 1:50 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 12:54:03 PM PLOTTED ON: 6/25/2020 @ 12:54:03 PM DESIGN FILENAME: X:\data\Infra\Proj_2016\0543800_Bx_Co_Watson\CADD\PLAN_SHTS\UTL\







UTILITY LEGEND

OP	CPS ELECTRIC O/H
— EG —	ENTERPRISE GAS LINE
— cc —	CPS GAS
— UT —	SBC U/G TELEPHONE LINE
— то —	SBC O/H TELEPHONE LINE
— ww —	SANITARY SEWER LINE
— X Water —	SAWS
	EXISTING R.O.W.
۲	UTILITY POLE
\rightarrow	GUY WIRE
	ROAD SIGN
\odot	FIRE HYDRANT
\bigotimes	WATER VALVE
•	GAS VALVE
Ø	GAS METER
Ŵ	WATER METER
$\bigcirc \bigcirc$	MANHOLES
(30)	STORM DRAIN
õ	CENTER POINT OF TREE
T	TELEPHONE PEDESTAL
	TV CABLE CONTROL BOX







UTILITY LEGEND

OP	CPS ELECTRIC O/H
— EG —	ENTERPRISE GAS LINE
— cc —	CPS GAS
— UT —	SBC U/G TELEPHONE LINE
— то —	SBC O/H TELEPHONE LINE
— ww —	SANITARY SEWER LINE
— X Water —	SAWS
	EXISTING R.O.W.
	UTILITY POLE
\rightarrow	GUY WIRE
	ROAD SIGN
\odot	FIRE HYDRANT
\bigotimes	WATER VALVE
•	GAS VALVE
Ø	GAS METER
Ø	WATER METER
\odot	MANHOLES
(()	STORM DRAIN
Õ	CENTER POINT OF TREE
T	TELEPHONE PEDESTAL
ΓV	TV CABLE CONTROL BOX







UTILITY LEGEND

OP	CPS ELECTRIC O/H
— EG —	ENTERPRISE GAS LINE
— cg —	CPS GAS
— UT —	SBC U/G TELEPHONE LINE
— то —	SBC O/H TELEPHONE LINE
— ww —	SANITARY SEWER LINE
— X Water —	SAWS
	EXISTING R.O.W.
۲	UTILITY POLE
\rightarrow	GUY WIRE
_@	ROAD SIGN
\odot	FIRE HYDRANT
\bigotimes	WATER VALVE
•	GAS VALVE
Ø	GAS METER
Ø	WATER METER
ØO	MANHOLES
(50)	STORM DRAIN
õ	CENTER POINT OF TREE
T	TELEPHONE PEDESTAL
TV	TV CABLE CONTROL BOX





								ı			
	50			\vdash							
+	Ħ		+	Ħ	-	Ħ	+				
			-	\square							
				\square							
							-				
	$\left \right $	+	+	\vdash	-	$\left \right $					
		\square	-	\square			_				
		\square	+		_						
				Ħ							
			-	\square							
		\square	+	Ħ	-	\square					
							+				
				⊢		⊢					
	F	F	Ŧ	Ħ	Ŧ	A	Ŧ				
	Ħ	Ħ	+	Ħ	-	Ħ	-				
	Ħ		+				+				
				⊢		⊢					
	\square	\square	-	H		H	-				
			-			\square					
			-	\square	-		-				
	\square		-	\square	_		-	· ·	-		-
+ -	. +	-	+		+				-		40000//50
				H				NO DATE	GRAP	PHIC SCALE	APPROVED
			-	\square			_	25 12 5	11)	N FEET)	50 75
		\square	-	\square		\square			0	25	
							-		1	" = 50'	
									<u></u>		
			-	\square	_		_	STATE O	TELAS	THEOLOGIA	
			-	\square				<u>;</u> */			AS AUTHORIZED BY
	\square				-		-	JULIO F	RAMOS	00210101	100,11.2.107072
								POTRES LICE	NSED	6	/25/2020
				╞		⊢		11 STONA	IL ENTE		
++		+	+	H		$\left \right $					
	\square	H	-	Ħ		H	-				
	Ħ	Ħ	+	Ħ	-	Ħ	+				
				╞╡		╞		C	EC	11550 H SAN ANTON	10 WEST, SUITE 395 IO, TEXAS 78230-1037
				⊢		⊢		CIVIL ENGINEER	NG CONSULTANTS	TBPE REGIS	STRATION NO. F-2214
++	\square	+	+	H		H			~ -		TTATION NO. 100410-00
		H	-	Ħ		F			BE Public W	VORKS D	UNIY Epartment
	Ħ	Ħ	+	Ħ	-	Ħ	+			. UKKO D	-
				╞╡		╞			WATS	<u>ON ROA</u>	D
				⊢		⊢			WAT	SON RD	NI
$+ \square$	\mathbb{H}	+	+	H	+	H	+		CROSS	SECHC	/IN
	Ħ	Ħ	+	Ħ	-	Ħ	+				
		Ħ		Ħ		Ħ			SHEE	T 1 OF 27	
									0	Ð	
		+	+	H		$\left \right $		© 2019	7	Texas	Department
	H	H	+	Ħ	-	H	-	FED.RD.	FEDERA	L AID PROJECT	NO. PLAN SHT
	Ħ		+	Ħ	-	Ħ	+	6			227
	50			4		<u>i l</u>		 STATE	DIST. SAT		
	50							 CONT.	SECT.	JOB	
								0915	12	562	WATSON RD



	5	0			-				1			
\square												
		H			-							
\mp	+	Ħ	+	Ħ		-	Ħ					
	\pm				\pm							
+	+	H		+	+							
	\pm	⊢			\pm							
+	-	$ \overline{ }$		+	F							
\mp	+	Ħ		Ħ		-						
+	+	H		+	+							
\mp	+	Ħ	+	Ħ	+	-	Ħ					
++		H	-									
	-		-		_							
	+	Ħ	+	Ħ								
	+	\vdash										
\square		F		\square	\square							
	+	Ħ		$\downarrow \downarrow$								
+	+	\vdash		+	+							
+	+	Ħ		\square								
	+	Ħ										
+	+	$\left \right $		+	+							
	-	\square	-	\square								
	+											
++	+	H	+	+	+		\square					
	+	Ħ	+	\square								
										-		-
	-		_		_					-		<u> </u>
$\downarrow \downarrow$	+	Ħ	+	Ħ					NO DATE	F	REVISION	APPROVE
	-	\vdash	-							GRAF (II	HIC SCALE	
+	-	Ħ	-	\square	\square				25 12.5	0	25	50 75
	+	Ħ								1	" = 50'	
	+	\vdash		+								
\square	-	H		Ħ						F TALL		
									Stand Stand	- tas	THE SEAL A	PPEARING ON THIS
	+	\vdash	+	+					<u> </u>		DOCUMENT V	AS AUTHORIZED BY
\square	-	H		Ħ					JULIO F	KAMOS 672		,
\mp	+	Ħ							OR LICE	NSEPREN	6	/25/2020
	+	\vdash		+					NON/	IL ENT	-	
+ -		┝╺┝		11		-						
	+	Ħ										
++	+	\vdash	+	+	+		$\left \right $					
+	-	Ħ	-	\square	\square						11550 H	10 WEST, SUITE 395
	+	Ħ									TEL: (210) 641	9999 FAX: (210) 641-644
	+	\vdash							GIVIL ENGINEER	DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: 100410-00
\square	-	H		Ħ						BE	XAR CO	UNTY
	+	Ħ								PUBLIC W	VORKS E	EPARTMENT
	+	\vdash										
\square	-	H		Ħ						<u></u>		
\mp	+	Ħ								WAT	SUN RD	N
	+	\vdash								08035	-320110	/IN
+	-	H		\square								
	+	Ħ								SHEF	T 2 OF 27	
++	+	$\left \right $		+	+		$\left \cdot \right $				0	
\mp	+	Ħ	+		+	-			 		Texas	Department
		Ħ									of Tra	nsportation
+	+	$\left \right $		+	+					FEDERA	L AID PROJECT	NO. NO. NO. 279
	-								STATE	DIST.		COUNTY
	5	0							TEXAS	SAT		BEXAR
										SECT.	JOB 560	
									0160	14	002	



							ı			
	<u> 50</u>									
			+							
			+							
	\vdash	\vdash	+	++	++	+				
	\square		+		\square					
\mp	\square		+	\square	\mp					
+ -	$ \top$	H	Ŧ	+ -	$+\top$					
			-							
			-							
							· ·	-		-
								-		-
		_	-	-			NO DATE	GRAP	REVISION PHIC SCALE	APPROVED
			-		+			(1)	N FEET)	
			+				25 12.5	0	25	50 75
								1	" = 50'	
	\vdash	$\left \right $	+	++	++	+				
							TATEO	FTELY		
	Ħ		+				<u>=</u> */ 7		THE SEAL A	PPEARING ON THIS /AS AUTHORIZED BY
							JULIO F	RAMOS	JULIO RAI	MOS, P.E. 107672
							NO CE	NSEP	6	/25/2020
	$+ \top$	F	Ŧ	$+ \top$	$+\top$		S/ON/	IL EN	U	
	Ħ	Ħ	+	\square	\parallel					
		\square								
+ -	H	H	f	$+ \Gamma$	$+ \Gamma$				11550 H SAN ANTON	10 WEST, SUITE 395 IO, TEXAS 78230-1037
	\square	Ħ	-	\square	\square			NG CONSULTANTS	TEL: (210) 641 TBPE REGI	9999 FAX. (210) 641-6440 STRATION NO.: F-2214
								DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: 100410-00
								BE	XAR CO	UNTY
			+	++	++			PUBLIC W	VORKS E	DEPARTMENT
+	H	F	-	Ħ	\square			WATS	ON ROA	ND
\mp	Ħ	Ħ	-		\square			WAT	SON RD	
		\square						CROSS	S-SECTIC	N
+ -	H	H	-	+	$+ \Gamma$					
	\square	Ħ	-	\square	\square			SHEE	::ເວບ⊨2/ ຄ	
		Ħ	+	Ħ	\parallel		@ 2010	_	Texas	Department
									of Tra	nsportation
		$\left \right $					DIV.NO.	FEDERA	L AID PROJECT	NO. NO. 229
				4			STATE	DIST.		COUNTY
	5U							SAT	JOB	
							0915	12	562	WATSON RD



-						ı			
 50			_						
\parallel	Ħ	$\downarrow \downarrow$							
++	\square				_				
	\square	+							
++	\square				_				
\square	\square	\square							
 \square	$\left \right $	++	++	+					
Ħ	\square								
 ++	\vdash	++	++	+	_				
Ħ	\square								
 ++	\vdash	++	++	+	_				
Ħ	\square								
+ -	$ \top$	\square	$+ \mp$	+					
Ħ	Ħ	\ddagger	$\downarrow \downarrow$						
	H	\square	+	\square					
Ħ	Ħ	$\downarrow \downarrow$							
\square	F	\square	\square	\square					
++	\vdash	+	++	+					
	\square								
	Ħ								
++	\square	+				· ·	-		
	\square						-		
						NO DAIL	GRAP	HIC SCALE	ALLINGUED
 \square	\square	++	++-			25 12 5	11)	N FEET)	50 75
	\square						0	25	
							1	" = 50'	
\square	\square				-				
						TATEO	FTEL		
	Ħ					ل ة مُرْجَة		THE SEAL AN DOCUMENT W	PPEARING ON THIS AS AUTHORIZED BY
\square	\square				-	JULIOF	RAMOS	JULIO RAI	MOS, P.E. 107672
	\square					107 8	672 <u>6</u> 72		
						KSSION/	NSE ENGI	6	/25/2020
\square	\square				-				
\square	H	\square	\square	\square	-				
	Ħ								
+		+	++	+	-			11550 ILI	10 WEST SUITE 305
\square	Ħ	$\downarrow \downarrow$	+		-		EC	SAN ANTON TEL (210) 641 0	IO, TEXAS 78230-1037
	Ħ					CIVIL ENGINEER	NG CONSULTANTS	TBPE REGIS	STRATION NO.: F-2214
	$\left \right $	+					~ -	TELEVILLOID	
\square	H	\square	\square	\square	-		BE BUBLIC W	VORKS D	UNIY FPARTMENT
	Ħ							OKKS D	-LIANIMENI
	$\left \right $	+					WATS	ON ROA	/D
\square	H	\square	\square	\square	-		WAT	SON RD	
	Ħ						CROSS	S-SECTIC	N
+	$\left \right $	+	++	+	+				
\square	H	Ħ	\square	Ħ	-				
	Ħ					ļ	SHEE	T 4 OF 27	
		+					_	D Texas	Department
\square	H	\square	++		-	© 2019		of Trai	nsportation
	Ħ	\ddagger				FED.RD. DIV.NO.	FEDERA	L AID PROJECT	NO. PLAN SHT. NO.
		+				6 STATE	DIST		230
50						TEXAS	SAT		BEXAR
 						 CONT	SECT.	JOB	HIGHWAY / STREET
						0915	12	562	WATSON RD



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF,pltcfg PLOT DRIVER: WATSON_BW_PDF,pltcfg PLOTTED ON: 6/25/2020 @ 1:56:41 PM DESIGN FILENAME: X:\dataNnfra\Proj_2016\E0543800_

	50)						ן				
					\vdash							
	Ħ	+		+	\square	-						
	H	+		+	\square	-						
	H	-		+	\square	-						
	H	+		+		-						
	H	-		+	\square	-						
	H	-		+	\square	-						
	H	+		+	\square	-						
	\square	+		+	\square	-						
	\square	+		+	\square	-						
	\square	+		+	\square	-						
	\square	+		+	\square	-						
	H	+		+	\square	-						
	H	+		+	\vdash	-						
	H	+		+	\vdash	-						
	Ħ	-	Ħ	+	Ħ							
	<u>†</u> -		Ħ	+	Ħ	+						
+	Ħ	-	Ħ	+	Ħ							
	Ħ	-	Ħ	+	Ħ	+						
	Ħ	+		+	\vdash	-						
	Ħ	+		+	$\left \right $	-						
	H	+		+	\square	-						
	H	+		+		-			-			-
	H	+		+		-			-			-
	H	+		+		-		NO DATE	GRAP	REVISION PHIC SCALE	AF	PROVED
	H	+		+				05 10 5	11)	N FEET)	50	75
	\square	+		+	\square	-				20	50	
	\square	-		-	\square	-			1	" = 50'		
		-						TEO	ETEL			
		-		-								
								JULIO F	RAMOS	JULIO RAI	MOS, P.E. 107	672
								1070 1070	672	6	/25/2020	
	H		Η		\square			SIONA	IL EN	U		
	\square		\square		\square							
										11550 H	10 WEST, SUITE	395
										SAN ANTON TEL: (210) 641	0, TEXAS 7823	0-1037 641-6440
				+					DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: 1	00410-00
									BE	XAR CO	UNTY	(ENT
	Ħ		H						FUBLIC W	VUKKS L	- CPAKIN	α Ε Ν Γ
+				+	Ħ				WATS		D	
	Ħ		Ħ	+	Ħ				WAT CROSS	SON RD S-SECTIC	N	
	Ħ		Ħ		Ħ				51,000			
+	Ħ		H	+	Ħ	+						
									SHEE	0 0		
								© 2019	7	Texas of Trai	Departm nsportati	ent on
								DIV NO.	FEDERA	L AID PROJECT	NO. P	NO.
	50				μT			STATE	DIST.			_• '
	JU	,						CONT.	SAI SECT.	JOB		STREET
								0915	12	562	WATSO	N RD



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 1:56:44 PM PLOTTED ON: 6/25/2020 @ 1:56:44 PM

								ı			
	50)									
+	\square	-	H	+			+				
	Ħ										
	+			_							
	\square	-				\square					
	Ħ			+			-				
	+	+	$\left \right $	+		\square					
	\square			-		\square	_				
	Ħ	+	-	+		\square					
	\ddagger			+							
	+	_		+		\square					
	\square	-	\square	-		\square	-				
			Ħ								
			\square								
++	\mathbb{H}	-	H	+	$\mathbb{H}^{\mathbb{H}}$	H	+				
+	Ħ	-	F	-		Ħ	+				
						Ħ					
	\ddagger			+			\pm				
	+		\square								
	\square			-		\square					
	Ħ	-		-		\square	-				
	\square										
	+	+	$\left \right $	+		$\left \right $	+		-		
	\square	_		-		\square	_	NO DATE	-	REVISION	APPROVED
							-		GRAP	HIC SCALE	111110112
								25 12.5	11) 0	N FEET) 25	50 75
	\square								I	- 50	
	\square	-		-			-	2220			
								Si Andrew	- tro	THE SEAL A	PPEARING ON THIS
										DOCUMENT W JULIO RAI	AS AUTHORIZED BY MOS, P.E. 107672
	+	+		+		\square	-	到 107	672		
	\square							RSSICE	NSED	6	/25/2020
\mp	Ħ	-		-		Ħ	-	1111	11111		
	#			+			+				
	\square		\exists								
+	H		H	+	$\left \right ^{-}$					11550 4	10 WEST, SUITE 395
	Ħ	-	F	-		Ħ	-		EC	SAN ANTON TEL. (210) 641	O, TEXAS 78230-1037 9999 FAX: (210) 641-6440
	Ħ	-	Ħ	+		Ħ	+	CIVIL ENGINEER	NG CONSULTANTS DON DURDEN, INC.	TBPE REGIS	STRATION NO.: F-2214 TRATION NO.: 100410-00
	\ddagger			+			+		RF	XARCO	UNTY
									PUBLIC W	VORKS D	EPARTMENT
	+		$\left \right $			$\left \right $					
	Ħ	-	F			F			<u>vvais</u> +		
+	Ħ	-		-		Ħ			CROSS	SON KD	N
	#	+		+			+				
	\square										
	+								SHEE	T 6 OF 27	
+	Ħ		F			H				• • • • • • • • • • • • • • • • • • • •	Department
	Ħ	-		+		Ħ	+	© 2019		of Trai	nsportation
	\ddagger		Ħ					FED.RD. DIV.NO.	FEDERA	L AID PROJECT	NO. PLAN SHT
	+							 6 STATE	DIST		COUNTY 232
	50)	_					TEXAS	SAT		BEXAR
								CONT.	SECT.	JOB	
								0915	12	562	I WAISON RD



	5	0]			
	Ť					\square						
	+	_	\vdash		++	+						
	\square	_			++		_					
	+	-	\vdash		++	+	-					
	\square											
	+	_	\vdash	_	++	+	+					
\square	Π	-			\square	П						
+	H	-			+ +	F						
	\square				#							
+	+	+	-	\vdash	++	+						
	Ħ	-			$\downarrow \downarrow$	Ħ						
+	П	-			+ +	F						
					#							
+	+	-	-	\vdash	++	+						
	\square											
	+	_	\vdash		++	+	_					
									· ·	-		-
	+	-	\vdash		++	+	-			-		
					\square				NO DATE	F		APPROVE
		-	-		++					GRAP (II	N FEET)	
	+	-	\vdash		++	+	+		25 12.5	0	25	50 75
										1	" = 50'	
	$\left \right $	-	\vdash		++	+	_		TE O	FTALL		
									Sala and	- tys	THE SEAL A	PPEARING ON THIS
	\square	-	\vdash		++	+	+		<u>;</u> ;/		DOCUMENT W	AS AUTHORIZED BY
					\square		_		JULIO F	RAMOS		,
									OT CE	NSED	6	/25/2020
+	+	-	-	\vdash	$\left \right $	+	+		S/ON/	IL EN	·	
	Ħ	-			\square	П						
+	+	+	-		++	+						
	Ħ	-	F		$\downarrow \downarrow$		1				11550 H	10 WEST, SUITE 395
									<u> </u>		SAN ANTON TEL: (210) 641 4	IIU, TEXAS /8230-1037 9999 FAX: (210) 641-644
$+\top$	H	F	-	H	++	F			CIVIL ENGINEER	NG CONSULTANTS DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: F-2214
	Ħ				$\downarrow \downarrow$	Ħ				BE	XAR CO	UNTY
++		+	-							PUBLIC W	VORKS D	EPARTMENT
	П		F			F					<u> </u>	
			F		#					WATS	<u>UN ROA</u>	ND
	+	-				+				WAT	SON RD	
\square	Π	-			\square	П				CROSS	S-SECTIC	N
$+\top$	+	-	-		+	+	-			0		
	Ħ		F		#		1			SHEE	: 1 / UF 27	
											Texas	Department
+	H	-	-		$+ \overline{+}$	F	-		C 2019		of Trai	nsportation
	Ħ				Ħ		+		FED RD DIV NO	FEDERA	L AID PROJECT	NO. PLAN SHI
									6 STATE	піет		233
	5	0							TEXAS	SAT		BEXAR
	-							1	CONT.	SECT.	JOB	HIGHWAY / STREET
									0915	12	562	WATSON RD



							ı			
	5			$\left \right $						
+	+	-	F	Ħ		+				
	+	_	\vdash	\vdash	+	+				
						_				
	-	_	-	\vdash	$\left \right $	_				
		_	\square	\square	$\left \right $	_				
	-									
		-	\vdash	\vdash	\square	-				
			Ħ	Ħ		+				
				┢						
+	F		F	\square	F					
			Ħ	Ħ						
	\pm			╞		+				
+	+		\mathbb{H}	$\left \right ^{-}$	+	+				
+	\square	-	F	F	H	+				
				\vdash						
				\square		_				
	+	_	\vdash	\vdash	+	+		-		
	-	-		\square		-		-		
							NO DATE	GRAP	HIC SCALE	TAFFROVED
	+	-	\vdash	\vdash	+	-	25 12 5	11)	N FEET)	50 75
									20	
				Ħ				1	" = 50'	
	+	_	\vdash	\vdash	+	_	CTATE O	FTELA		
				\square		-	<u>;</u> ;;/ 7	T *;)	THE SEAL AI	PPEARING ON THIS
							JULIO F	RAMOS	JULIO RAI	WOS, P.E. 107672
							CEI	NSED	6	/25/2020
$+\top$	F	-	F	+	H	+	S/ON/	IL EN	0	
\mp	H	-	F	Ħ	Ħ	-				
				Ħ						
				┢						
+	F		F	$\left \right $	F	-			11550 H	10 WEST, SUITE 395
$\downarrow \downarrow$		-	Ħ	Ħ		+		NG CONSULTANTS	TEL. (210) 641 (TBPE REG!	9999 FAX. (210) 641 6440 STRATION NO. F 2214
				Ħ		\pm		DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: 100410-00
								BE	XAR CO	UNTY
-					\square			PUBLIC W	VORKS D	EPARTMENT
+		-	F	Ħ		+		WATS	<u>ON ROA</u>	\D
			Ħ	Ħ				WAT	SON RD	
						+		CROSS	S-SECTIC	N
			$\left \right $	⊢						
$+\top$	F	-	F	\mathbb{H}	Н	-				
+		-	F	H	H	-		SHEE		
							© 2019	7	Texas of Trai	Department nsportation
+		-	Ħ	Ħ		+	FED.RD. DIV.NO.	FEDERA	L AID PROJECT	NO. PLAN SHT. NO.
				Þ			0 STATE	DIST.		COUNTY
	5	0					TEXAS	SAT		BEXAR
							СОNТ. 0915	sест. 12	_{ЈОВ}	
								16	004	



	-						1			
	50									
			-							
	$\left \cdot \right $	+	+	$\left \right $	$\left \right $					
		\square	_							
		\square	-							
			_							
		\square	-							
++	F	F	T							
	Ħ									
		\square								
			_							
		\square	-					-		-
								-		
							NO DATE	GRAP	REVISION PHIC SCALE	APPROVED
	\square	\square	_				05 40 5	11)	N FEET)	50 75
			-				25 12.5	0	25	50 75
		\square						1	" = 50'	
	\square	+	-	\square			STATE O	TETAS		
	\square	\square	_				<u>;</u> */	₹		AS AUTHORIZED BY
		\square	-				JULIO F	RAMOS	30210 1141	NO3, 1. L. 10/0/2
							DO REAL CEI	NSED	6	/25/2020
							110NA	IL ENTE		
++		+								
	\square	\square	-	\square						
	Ħ									
								FC	11550 H SAN ANTON	10 WEST, SUITE 395 IO, TEXAS 78230-1037
							CIVIL ENGINEERI	NG CONSULTANTS	TBPE REGIS	9999 [FAX: (210) 641 6440 STRATION NO : F-2214
			_						IBPLS REGIS	TRATION NO.: 100410-00
			-					BE BUBLIC W	XAR CO	UNTY EDADTMENT
								I OBLIC W	OKK5 D	ELAKIMENI
								WATS	ON ROA	D
								WAT	SON RD	
	F	F	Ŧ					CROSS	SECTIC	N
\mp			+	\square						
								SHEE	T 9 OF 27	
								0	Ð	
							© 2019	7	Texas	Department
	\square	H	+	\square			FED.RD.	FEDERA	L AID PROJECT	NO. PLAN SHT.
\mp	Ħ		-	\square			6			235
	50						STATE			
						 I	CONT.	SECT.	JOB	HIGHWAY / STREET
							0915	12	562	WATSON RD

50 45	40 35 3	30 25 3	<u>20 15</u>	10	5 0 5	10 15	20 2	<u>5 30</u>	35 40) 45	50		
													+
					WAT SON								
632				>			3						
		<u>x</u> .		0									
					89 89 89 89	Q.A.							
628		8.71 24.48 225-	37.7 24:0		62540 6254 524	32.0	25 12 12 12 12 12						
626		132162	50:/	DOOD ET JET			7:L						
624											+	、	
622													
620					0	0 (
618						Щ. Н.							
						ED 4	54						
						2,0W							
						AXX AXX	- SS						<u> </u>
		<u>0</u>					55						
		<u> </u>											+1
					WATSON								
					121+50.00								<u>–</u>
				¥									+
632		≥		ф. 2									<u>+</u>
630		275 247	120 52	ts	- 0 <u>7</u> - <u>50</u> - <u>0</u>	00							
628		75 47 625 625	3252		62 <u>8</u> 625 625	24.5							
626			501				2/ **©						NO DATE REVISION
624				<u>0.020 FIJFI.</u>									GRAPHIC SCALE (IN FEET)
622													
620						<u></u>							1" = 50'
618						V #							
							<u>а</u>						PTE OF TELY
						MEC WA							
		0			×	16" SSU							JULIO RAMOS JULIO RA
						шё g	ASS ASS						
													- SI ONAL E
		A A A A A A A A A A A A A A A A A A A											
					WATSON 121+00.00								
6.32		⇒.											
630		<u> 35 79</u> 70	<u>417</u>	ts	<u> 26: 000 26</u>	06	ist. R						CIVIL ENGINEERING CONSULTANTS TOPPEREC
628		<u>878</u> 471 525	37 621 621	<u> </u>	<u>8.0</u> 8.0 8.0	32.0	2420 EX						
626			504										BEXAR CC
624				0.020 FI_/FI.		20 F1./FT. ~	<u> </u>		• = = = = =				
622													WATSON RO/
620													WATSON RD
						Щ ф	<u> </u>						
													SHEET 10 OF 27
						1919							
					- XX	<u> </u>	Ä			+ $+$ $+$ $+$ $+$ $+$ $+$ $+$ $+$ $+$	$+++\mp$		C 2019
		0.											
													FED.RD. FED.RD. FED.RD. FED.RD.
		WATER PROP 16"											FED.RD. FED.RD. FED.RAL AID PROJEC 6

PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 1:56:56 PM DESIGN FIL ENAME: Y:Vatablinfes/broid 2014.BFC



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pttcfg PLOT DRIVER: WATSON_BW_PDF.pttcfg PLOTTED ON: 6/25/2020 @ 1:57:00 PM DESIGN FILENAME: X:\data\Infra\Proj_2016\E054380

		_						ı			
	5	0	1		+						
		Ħ	t		\ddagger						
	+	\vdash	+		++	+					
	-	\vdash	+			+	_				
						\square					
	+	\vdash	+		++	$\left \right $					
	-	\vdash	+		++	+	_				
	-	\vdash	+		++	+	_				
-		-	F		+ -	\square					
	Ē	Ħ	t		$\downarrow \downarrow$	Ħ					
		\square									
	-	\square	F		\square	П					
		Ħ	t		$\downarrow \downarrow$	Ħ					
		\vdash	+								
	-	\square	F		\square	П					
	-		-								
					\square						
									-		
	-		-					NO DATE	-	REVISION	APPROVED
									GRAP	HIC SCALE	1011101110
	+	\vdash	+		++	+		25 12 5	11)	N FEET) 25	50 75
	-	\vdash	+-		++	$\left \right $	_			20	
					\square				1	" = 50'	
			+		++	$\left \right $	_	CTATE O	FTELY		
								<u>=</u> */ 7	T *:	THE SEAL AI	PPEARING ON THIS
								JULIO F	RAMOS	JULIO RAI	MOS, P.E. 107672
	-	-	+		++	+	_		612		105/0000
								SS/ON/	IL ENG	6	12512020
		Ħ	t								
		\vdash	+			$\left \right $					
+		\square	-		\square	Ħ	-				
		Ħ	t							11550 H	10 WEST, SUITE 395
		\vdash	+			$\left \right $			<u> </u>	SAN ANTON TEL: (210) 641	O, TEXAS 78230-1037 9999 FAX: (210) 641-6440
	F		F		\square	F		CIVIL ENGINEER	NG CONSULTANTS DON DURDEN, INC.	IBPE REGIS	TRATION NO .: F-2214
		Ħ	t		\ddagger				RE	XARCO	UNTY
		\vdash	-						PUBLIC W	VORKS D	EPARTMENT
+	F	H	F		F	П	-		14/4	<u> </u>	
		Ħ	t		$ \uparrow \rangle$		-		WAIS		U.
		\square	t						WAT	SON RD	NI I
$+\top$	F	H	F		+ -	H	-		CROSS	SECTIC	NN
		Ħ	1				+				
			t						SHEE	T 11 OF 27	
+		\vdash	F		+ -	+	-		.0	<u>.</u>	
\mp		Ħ	F		\mp		-	 		Texas	Department
		Ħ								of Trai	nsportation
	+	\vdash	+		++	+	-	DIV NO.	FEDERA	L AID PROJECT	NO. NO. NO. 237
								STATE	DIST.		
	5	0						TEXAS	SAT		BEXAR
								солт. 0015	SECT. 12	_{ЈОВ}	
									14	002	



	Б	<u> </u>			_			1			
	50)			\vdash						
	\square	-			\square						
	$\downarrow \downarrow$	-			Ħ						
	\square	+				_					
	+	-		_	\vdash						
		-		_							
	++	+		_	\vdash	-					
	\square	-									
					Ħ						
$+ \mp$	+	-	H		H						
	\square	-			Ħ						
					Ħ						
	+										
						_					
	++	+			\vdash	-					
	\square	+		_	\square	_		· ·	-		
	\square	-				_			-		
								NOT DATE	GRAP	HIC SCALE	APPROVED
								25 12 5	11)	N FEET) 25	50 75
		-				_				20	
	\square	-				-			1	" = 50'	
								22,23	<u>"</u> "		
								ATE O	Et AS		
++-	+	+		_	\vdash	-		<u>;</u> */		JULIO RAL	AS AUTHORIZED BY
	\square	-		_		_		JULIO F	RAMOS	00210100	
	$\downarrow \downarrow$				Ħ			OR CEI	NSED	6	/25/2020
								S/ONA	AL FILE		
					\vdash						
	\square										
	$\downarrow \downarrow$	+		-						44550 P.	A WEAT OUTE OAS
					Ħ				EC	SAN ANTON	IU WEST, SUITE 395 IO, TEXAS 78230-1037
	\pm				Ħ			CIVIL ENGINEERI	NG CONSULTANTS DON DURDEN, INC.	TBPE REGIS	STRATION NO : F-2214
			\square		\mathbb{H}					IN A D. C.C.	TINTES7
	H	-	7	-	\square	-			BE BUBLIC W	AAR CO VORKS D	UNIY EPARTMENT
\mp		-			Ħ						
	\parallel		╞		Ħ				WATS	ON ROA	D
									WAT	SON RD	NI
++	+	+	+		H	+			CROSS	-SECHC	IN
	\square	+		-	Ħ						
	$\downarrow \downarrow$	+			Ħ				SHEE	T 12 OF 27	
					Ħ				0	0	
	+	+	\square		$\left \right $			© 2019	7	Texas	Department
	\square	-			\square			FED.RD.	FEDERA	L AID PROJECT	NO. PLAN SHT
		+			Ħ			6			238
	50)						STATE	DIST.		
	<u> </u>						 L	CONT.	SECT.	JOB	HIGHWAY / STREET
								0915	12	562	WATSON RD

632 630 628 626 624 622 618		WATSON /25-50.00	EX 15: WATER EX 15: WATER (ASSUMED 4) (ASSUMED 4) (AS		
632 630 628 626 624 622 620 618	PROP 16"		EX 16" WATER EX 16" WATER (ASSUMED 4') (ASSUMED 4') (A		
630 628 626 624 622 620 618 618 618		ET	EX 16" WATER EX 16" WATER (ASSUMED 4) CASSUMED 4) CASS		
626 624 622 620 618 618			EX 12: WATER C 250		
622 620 618			EX 16" WATER (ASSUMED 4') UG TELEPHONE (ASSUMED 4') (ASSUMED 4)		
			EX 16: WATER EX 16: WATER (ASSUMED 4) (ASSUMED 4) (ASSUMED 4)		
		WATSON			
		WATSON			
		WATSON			
632 630					
628 626	5849 1 624.0 624.0 624.0 624.0 624.0 624.0 624.0 623.72 624.0 623.72 623.72 623.72 623.72 623.72 623.72 623.72 624.00	8200 62420 62420 62420 62420	22000 5549 E249		· · ·
624	- 68/95+ - 50/ - 0020 FT/	/FT> P			NO DATE REVISION GRAPHIC SCALE (IN FEET)
50 620 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		0	0.8		25 12.5 0 25
	22 24 24 24	WATER WATER 4)	MWATER MED 4)		TE OF TELL
		E Lectronic Contraction Contra	EX 16" (ASSUG:		JULIO RAMOS
Xsec/M/					10/6/2 (CENSE) 6
		WATSON 124-50.00			
630	est R 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	m ok n			
	623353 62447 62447 533 62350 62447 77 62447 62447 62447 62447 62447 62447 62447 62447 62447 62447 62447 62447 62447 62447 6247 62	8800 62400 62400 62400 62400			CIVIL ENGINEERING CONSULTANTS DON DURDEN INC. TBPE REGIS
8624 622	$1 = \frac{1}{200} + $	7FT: - F 0.020 FT./			PUBLIC WORKS D
620 618		0 			WATSON ROA WATSON RD CROSS-SECTIC
			0.000000000000000000000000000000000000		
X:Vdat:					SHEET 13 OF 27
ENAME					FED.RD. DIV.NO. 6
년 중 <u>50</u> 45 40	35 30 25 20 15 10	5 Ø 5 10	15 20 25 30 35	40 45 50	

	40 35 30 25 20 15 10	5 0 5 10		40 45 50	
		WATSON			
632					
630 628	EXIST 25 23.25 25.25	10000000000000000000000000000000000000			
626					
622					
620		ш .			
		WATSON			
632					
628	232200 223320 223300 22330 223000 223000 223000 223000 223000 22300000000	24.27 24.27			-1 - 1-
626		6 FT_/FT	- +		NO DATE REVISION
622					GRAPHIC SCALE (IN FEET) 25 12.5 0 25
618		0 			1" = 50'
	R 24				A DE OF TELESEN AL
		EX IE			JULIO RAMOS JULIO RAMOS
					SONAL STATE
		WATSON 1/26+00.00			
632	A A A A A A A A A A A A A A A A A A A				
628	EXEL_F EXEL_F 23.00 24.38 24.38 24.38 24.38 24.38 24.38 24.38 24.38 27.42	24.45 59.00 57.46 6.25.19 58.01 57.45 57.45 57.19 57.10 57.1			CIVIL ENGINEERING CONSULTANTS DON DURDEN, INC. TBPLS REGIST
626		6 FFL/ET			BEXAR CO PUBLIC WORKS D
622					WATSON ROA
618					WATSON RD CROSS-SECTIO
	PR 24				
		EX .			Texas l
					FED.RD. FEDERAL AID PROJECT
50 45	40 35 30 25 20 15 10	5 Ø 5 10	15 20 25 30 35	40 45 50	STATE DIST. TEXAS SAT E
	· · · · · · · · · · · · · · · · ·	· · · · · ·			сонт. <u>sect.</u> јов 0915 12 562



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOT DRIVER: WATSON_@ 1:57:12 PM DESIGN FILENAME: X:\data\Infra\Proj_2016)

	FIC						1			
	50									
	\square		-							
	++	+	+	+						
	\square									
	$\left \right $		-							
	++		+							
			-							
	++	+	+	$\left \right $						
	\square		-							
	\parallel									
	+	+		$\left \right $						
	\square			\square						
	\ddagger		+							
	\square	H								
	Ħ		+							
	++	+	+							
			+							
	++	+	+	++						
	\square		-				· ·	-		
								-		
							NO DATE	GRAP	REVISION PHIC SCALE	APPROVED
	\square		-				05 40 5	(1)	N FEET)	50 75
	\square						25 12.5	0	25	50 75
								1	" = 50'	
	++	+	+	$\left \right $						
	\square		-				TATEO	FTEL		
							<u>;</u> ;*/ ¥		THE SEAL AN DOCUMENT W	PPEARING ON THIS
							JULIO F	RAMOS	JULIO RAI	MOS, P.E. 107672
	++		+	\square				612		105/0000
	\square		+				SS/ONA	IL ENO	6	123/2020
	$\downarrow \downarrow$									
$+\top$	$+\top$	\square	F	+ -	\square					
\mp	Ħ		+	\parallel					11550 H	10 WEST, SUITE 395
	\ddagger								SAN ANTON TEL: (210) 641 (10, 1EARS / 8230-1037 9999 FAX: (210) 641-6440 STRATION NO. E 2214
++	+	+	+	++	$\left \right $		UIVIL ENGINEERI	NG CONSULTANTS DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: F-2214 TRATION NO.: 100410-00
+	H	Ħ	-	F				BE	XAR CO	UNTY
								PUBLIC W	VORKS D	EPARTMENT
								\ <u>\</u> \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
	+	\square	Ŧ	+ -	+			10/10/10		
+	\square		+					VVAI CROSS	SON RD	N
	\ddagger							01000		· · ·
	Ħ	Ħ	-					SHEE	T 15 OF 27	
	\ddagger		+						•	
							© 2019		lexas of Trai	uepartment
							FED.RD. DV.NO.	FEDERA	L AID PROJECT	NO. PLAN SHT
	\square	H	-				6			241
	50)					TEXAS	SAT		BEXAR
				1		 	CONT	SECT.	JOB	HIGHWAY / STREET
							0915	12	562	WATSON RD



	FIC						ı			
	50									
+	\square		-							
	$\downarrow \downarrow$									
	++	+	-	$\left \right $						
			_							
	\square		_							
	\square									
	++	+	-	\square						
+	\square		-							
	+									
+	H	Ħ		F						
	$\downarrow \downarrow$		-							
	\ddagger									
	+									
	\square									
	+	+	-	\square						
	\square							_		
								-		
							NO DATE	- F	REVISION	APPROVED
	+	+	-	\vdash				GRAP	HIC SCALE	
	\square						25 12.5	0	25	50 75
	$\downarrow \downarrow$		-					1	" = 50'	
							TEO	FTEL		
	$\left \right $		_					788	THE SEAL A	PPEARING ON THIS
			-				JULIO F	RAMOS	JULIO RAI	MOS, P.E. 107672
							B 107	672		
							CE SS/ON	NSE KON	6	/25/2020
++	+	+	-	+	+					
	\square		-							
	\ddagger									
	+								11550 H	10 WEST, SUITE 395
									SAN ANTON TEL: (210) 641	O, TEXAS 78230-1037 9999 FAX: (210) 641-6440
+	Ħ	Ħ	Ŧ	F			CIVIL ENGINEER	NG CONSULTANTS DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: F-2214
+	Ħ			\square	\square			BE	XAR CO	UNTY
	\ddagger							PUBLIC W	VORKS D	EPARTMENT
	+									D.
	+							\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
	\square							CROSS	S-SECTIC	N
	\square		-							
	$\downarrow \downarrow$		-							
	\ddagger							SHEE	16 OF 27	
							© 2019		Texas	Department
		H					FED.RD. DIV NO	FEDERA	L AID PROJECT	NO. PLAN SHT.
	\square	Ħ	-	\square			6			242
	50)					TEXAS	SAT		BEXAR
						•	CONT.	SECT.	JOB	HIGHWAY / STREET
							I U915	12	562	I WATSON RD



							ı			
	<u>с</u>			$\left \right $						
+	H			H						
\mp		+	Ħ	Ħ						
		+								
		-			-					
		+		\square	-					
				\vdash						
		+			-					
		-		\square						
	+	+	\vdash	\vdash	+					
+	Ħ	-	F	Ħ	-					
		+		Ħ						
++	+	-	H	\mathbb{H}						
+	H	-	H	Ħ	-					
				Ħ						
		+		Ħ						
				$\left \right $						
		-		\square	_					
	+	+			+					
		-					<u> </u>	-		<u> </u>
		+		\square	-			-		
		+					NO DAIL	GRAP	HIC SCALE	ATTROVED
							25 12 5	11) 0	N FEET) 25	50 75
	+	+		 \vdash	-					
		-		\square	-			1	" = 50"	
								<u></u>		
		+					ATE STATE	- tro	THE SEAL A	PPEARING ON THIS
							<u>;</u> ; / /		JULIO RAN	AS AUTHORIZED BY MOS, P.E. 107672
		-			_		JULIO F 및 107	672 £		
		-		\square	-		OR CE	NSED	6	/25/2020
\mp		+		Ħ				ALL LIVE		
				\square						
++	+		+	\mathbb{H}						
+	H	-		\square					44550 P.	10 WEST SUITE 105
		+	Ħ	Ħ				EC	SAN ANTON TEL (210) 641 (IO WEST, SUITE 395 IO, TEXAS 78230-1037 1999 FAX: (210) 641 6440
	\parallel	+		Ħ			CIVIL ENGINEER	NG CONSULTANTS DON DURDEN, INC.	TBPE REGIS	STRATION NO.: F-2214 TRATION NO.: 100410-00
				\square				חת	YAP CO	UNTV
++	+	-	\parallel	\mathbb{H}				ве PUBLIC W	VORKS D	EPARTMENT
+	Ħ	+	Ħ	Ħ	-			14/4-6	011553	
		+		Ħ				WATS		۳. ا
								WAT	SON RD	N
				⊢				08035	-320110	'IN
	П	Ŧ	\square	H						
+	\parallel	+	H	Ħ				SHEE	T 17 OF 27	
				Ħ						
				\square			© 2019	7	Texas of Trai	Department Isportation
				$\left \right $			FED.RD DIV.NO	FEDERA	L AID PROJECT	NO. PLAN SHT
\square	Ħ	-	F	F	-		6			243
	5	0					TEXAS	SAT		BEXAR
						 	CONT.	SECT.	JOB	HIGHWAY / STREET
							0915	12	562	WATSON RD



	Ē	0						ן			
		ĥ									
		⊢									
	-	A			H						
	+	Ħ	1		#		+				
	+	\vdash	+		++						
		\square			\square						
		\square			+						
					\square						
	+	\vdash	+		$\left \right $		_				
					\square						
	+	\vdash	+		++		-				
		\square			\square						
		\square									
\square	-	H			H	\square					
		Ħ			\ddagger						
++	+	H	+	-	\mathbb{H}	+					
		Ħ			$ \uparrow $						
++	+	\vdash	+	$\left \cdot \right $	++	+					
	+	Ħ	+		Ħ						
+	+	\vdash	+	$\left \cdot \right $	$\left \right $	+					
		\square			\square						
		⊢									
+	-	H	-		H						
	+	\square	+		++		_				
++	+	\vdash	+		++		+				
		\square			\square						
		\square							-		-
	_	\square			\square				-		
	+	Ħ	+	Ħ	#			NOT DATE	GRAP	HIC SCALE	
++	+	H	+		\mathbb{H}	+	+	05 40 5	(Î)	N FEET)	F0
	+	Ħ	+		Ħ			20 12.5	U	20	ου 75
	╞	\vdash		╞┼╴	+				1	" = 50'	
\square	F	H	-		H	\square					
	\pm	Ħ	+		Ħ			ATEO	FTE		
+	+	\mathbb{H}	-		+	+	-		- ***	THE SEAL A	PEARING ON THIS
\mp	1	Ħ			Ħ		1	JULIOF	RAMOS	JULIO RAI	MOS, P.E. 107672
	+	\vdash		┢				J 107	672		
+	-	H		\square	\square		-	CE CE	NSED	6	/25/2020
		⊢							AL FILS		
$+\top$	+	H	+	-	+	+	+				
	+	Ħ			Ħ						
++	+	\vdash	+	$\left \cdot \right $	$\left \right $	+	+				
\mp	+	Ħ	+		\square		+			11550 H	10 WEST, SUITE 395
		⊢						<u> </u>		5AN ANTON TEL: (210) 641 4	ю, техаб /8230-1037 9999 [FAX: (210) 641-64
\square	F	A	Ŧ		H	\square		CIVIL ENGINEER	NG CONSULTANTS DON DURDEN, INC.	TBPL REGIS	TRATION NO.: F-2214
	+	Ħ	+		\ddagger				DE	XARCO	UNTV
++	+	\vdash	-	$\left \cdot \right $	+	+	_		PUBLIC W	VORKS D	EPARTMEN
\mp	+	Ħ	1	Ħ	Ħ		+				
	+	\vdash		┢					WATS	ON ROA	D
\square	-	F	-		H	\square			WAT	SON RD	
	+	⊢			\square				CROSS	S-SECTIC	N
++	+	H	+		\mathbb{H}	+	+				
++	+	\mathbb{H}	+	$\left \cdot \right $	+	+	+		SHEE	T 18 OF 27	
	+	Ħ	+		$\downarrow \downarrow$						
	+	\vdash		┢				© 2019		Texas	Department
\square	-	H			\square		-	FED.RD	EEDEPA		NO. PLAN SF
		Ħ			\ddagger		\pm	6 DIV.NO.	, LDLIVA		244
		닏			┝└			STATE	DIST.		COUNTY
	5	ν						TEXAS	SAT	105	BEXAR
								0915	seor. 12	562	
									16	004	



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOTTED ON: 6/25/2020 @ 1:57:24 PM PLOTTED ON: 6/25/2020 @ 1:57:24 PM

	=							ı			
	50					-					
						+					
						-					
	\square	\vdash		++	\vdash	+					
						F					
						-					
	\square	\vdash	++-	++	\vdash	+					
						\vdash					
	\square	\vdash		++		+					
						F					
++-	\vdash	\vdash	++	++	\vdash	+					
	F	F		\square	F	F					
				+	+	-					
		Ħ	\mp	\parallel	\square	-	1				
	\square		+	+ -	$\left \right ^{-}$						
		Ħ				1					
						-					
						t					
		\square		++		+					
									-		-
	\square	\vdash	+	++	\vdash	+			-		<u> </u>
						-		NO DATE	F		APPROVED
									GRAP (II)	HIC SCALE N FEET)	
	\square	\vdash	+	++	\vdash	+		25 12.5	0	25	50 75
		\square				1			1	" = 50'	
	\square			++		+		TEO	E TELL		
										THE SEAL A	PPEARING ON THIS
								;*/		JULIO RAI	AS AUTHORIZED BY MOS, P.E. 107672
	\square			++		+		五 107	672		
						-		OR CE	NSED	6	/25/2020
		Ħ				1		" " " NA	111111		
		\vdash			\square	-					
				\square	\square						
					Ħ						
		╞			\vdash	-				11550 H SAN ANTON	10 WEST, SUITE 395 O, TEXAS 78230-1037
				\square	\square			CIVIL ENGINEER	NG CONSULTANTS	TEL: (210) 641 (TBPE REGIS	9999 FAX: (210) 641-6440 STRATION NO : F-2214
		Ħ			Ħ	1			DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: 100410-00
		┢							BE	XAR CO	UNTY
									PUBLIC W	ORKS D	EPARTMENT
		Ħ			Ħ	1		⊢ ──	WATS		D
		┢							 \//ΔT		
	\square								CROSS	SECTIC	N
		Ħ	\parallel	\parallel	Ħ	1					
++	+		++	++	+	+			SHEE	T 19 OF 27	
	\square	Ħ	\square	\square	Ħ	-				• <u> </u>	
						t		© 2019		iexas of Trai	Department Insportation
++	+		++	++	+	+		FED.RD. DIV NO	FEDERA	L AID PROJECT	NO. PLAN SHT.
		Ħ	\mp	$\downarrow \downarrow$	Ħ	-		6			245
	50			+		l		STATE	DIST.		
	90							CONT.	SECT.	JOB	HIGHWAY / STREET
								0915	12	562	WATSON RD



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOT DRIVER: WATSON_@ 1:57:28 PM DESIGN FILENAME: X:\data\Infra\Proj_2016)

	F	<u></u>			1			ı			
	5	<u>)</u>			$\left \right $						
	\square	-		_			-				
	+	+	\vdash	-	\vdash	+	+				
				_			_				
	\square	-		_	$\left \right $	$\left \right $	_				
	$\left \right $	+		_	\square	$\left \right $	_				
		+									
	$\left \right $	+	\square	_	\vdash	$\left \right $					
	\square	-				\square					
	Ħ	+	日		Ħ		+				
	+		\parallel		$\left \cdot \right $	+					
		+			\square	H					
	Ħ	Ē	E	T	╞		+				
			\vdash								
	H	-	H	-	++	\square	-				
	Ħ	+	Ħ	-	#		+				
			⊢								
	+	+	\square		\vdash	+	+				
		+					-				
	+	+	\square	-	\vdash	+	+				
	\square	-		_			_		-		
									-		-
								NO DATE	GRAP	REVISION PHIC SCALE	APPROVED
	\square	-		_			_	05 40 5	(1)	N FEET)	50 75
		+		-				25 12.5	0	25	50 75
									1	" = 50'	
	$\left \right $	+	\square	-	\vdash	$\left \right $	-				
	\square	-						TATEO	FTEL		
								لآ / * تَذَ		THE SEAL AN DOCUMENT W	PPEARING ON THIS
								JULIO F	RAMOS	JULIO RAI	MOS, P.E. 107672
	+	+	\square	_	\vdash	+	_		612		105/0000
	Ħ	+	Ħ	-	Ħ	Ħ	+	SS/ON/	IL ENO	6	123/2020
	Ħ	+	Ħ		#		+				
			\square								
	F	Ŧ	F	Ŧ	-	+	-				
+	Ħ	+	Ħ	-	\square	Ħ	-			11550 H	10 WEST, SUITE 395
		+	╘		Ħ					TEL: (210) 641 4	10, 16230-1037 9999 FAX: (210) 641-6440 STRATION NO - E 2214
			\square		\blacksquare			GIVIL ENGINEER	DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: 100410-00
	H	-	F	Ŧ	$+ \overline{+}$	\square	+		BE	XAR CO	UNTY
	Ħ	+	Ħ	-	Ħ		+		PUBLIC W	VORKS D	EPARTMENT
		+	\square						WATS		<u>л</u>
	\parallel		Н		╞				\\\\\T		
	Ħ	-	П	-	\square	F	-		CROSS	SECTIC	N
	Ħ	+	Ħ		Ħ		-		5		
		\pm	\square				\pm				
	+		H		$\left \right $	+			SHEE	T 20 OF 27	
	H	-	F		\square		-			• •	Dopartment
	Ħ	+	Ħ		Ħ		+	© 2019		of Trai	nsportation
	\square	+			Ħ		+	FED RD DIV NO	FEDERA	L AID PROJECT	NO. PLAN SHT
			\vdash		\square			6 STATE	DIST		246
	5)						TEXAS	SAT		BEXAR
					-			CONT.	SECT.	JOB	HIGHWAY / STREET
								0915	12	562	I WATSON RD



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 1:57:31 PM



50					
	1				
0.0					
ASSL ASSL					
		-			-
		-			
	NO DATE	GRAF			AFFROVED
	25 12.5	0	25	50	75
		1	" = 50'		
		<u></u>			
	AT	Etys .	THE SEAL A	PPEARING	ON THIS
	JULIO F	RAMOS	DOCUMENT V JULIO RA	VAS AUTHC MOS, P.E. 1	07672
	107 107	672		25/2020	
	12STON/	AL ENG	e	<i>,, 2012</i> 020	
			11550 H	10 WEST, SU	TE 395
			TEL: (210) 641 TBPE REG	9999 FAX: (2	200-1037 10) 641-6440 D . F-2214
		DON DONDEN, INC.	TBPLS REGIS	STRATION NO.	.: 100410-00
		BE PUBLIC V	VORKS I	DUNIY DEPART	MENT
		WATS		AD	
		WAT	SON RD		
		CROSS	S-SECTIO	ON	
		SHEE	T 22 OF 27		
		_	Texas	Departı	ment
	FED.RD.	FEDERA		nsporta	tion PLAN SHT
	6	FEDERA		. 110.	NO. 248
50	TEXAS	DIST.		COUNTY	
<u></u>	СОNТ. 0915	SECT.	JOB 562		



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOT DRIVER: WATSON_@ 1:57:37 PM DESIGN FILENAME: X:\data\Infra\Proj_2016)

		0			-			1	ı			
	о —											
$\pm \mp$												
	_					\square						
	-				\square	\square	-					
	-		-		\square		-					
							+					
	-											
	-		-		\vdash	$\left \right $	+					
	_					\square						
	-		-		\square		-					
							-					
			\vdash									
$+\top$	F		-		\square	H						
+	-	\square			\square	H	-					
+	-	Ħ			$\left \right $	H	+					
	-						+					
	_						-			-		
	-				\square	\square	-			-		
	-				\square		-		NO DATE	F		APPROVED
										GRAP (II	N FEET)	
									25 12.5	0	25	50 75
										1	" = 50'	
	-								STATE O	TELAS		
									<u>;</u> */	X	DOCUMENT W	AS AUTHORIZED BY
	_						_		JULIO F 3 107	672		
	_				\square	\square	-		CEI CEI	NSED	6	/25/2020
+	+	Ħ	-	\square			+		""((V)	trive		
\mp	+	\mid	-				+					
\mp	+				#		+					
		\parallel					+				11550 H	10 WEST, SUITE 395
		\parallel									SAN ANTON TEL: (210) 641 -	IU, TEXAS 78230-1037 9999 FAX: (210) 641-6440 STRATION NO: E 2214
									CIVIL ENGINEERI	DON DURDEN, INC.	TBPLS REGIS	TRATION NO.: 100410-00
										BE	XAR CO	UNTY
										PUBLIC W	VORKS D	EPARTMENT
	-						-			WATS	ON ROA	۱D
	_		-		\square	\square	-			WAT	SON RD	
\mp	+	Ħ	-	\square		Ħ	-			CROSS	S-SECTIC	N
\mp	+	Ħ	-	Ħ			+					
++	+	Ħ					+			SHEE	T 23 OF 27	
		\mid					+					_
	+	\models					+		© 2019	7	Texas of Trai	Department
									FED.RD. DIV.NO.	FEDERA	L AID PROJECT	NO. PLAN SHT. NO.
+									6 STATE			249
	5	0							TEXAS	SAT		BEXAR
									CONT.	SECT.	JOB	
									0010	14	JUZ	



	- Fla	<u> </u>						ı			
	50)									
		-		-			-				
		-									
	++	+				$\left \right $					
		_		_			_				
	\square	-									
				_			_				
		-									
	\parallel				Ħ						
			\square		⊢						
+	H	-	7	-	\square	П	-				
		-		-		Ħ	-				
					Ħ						
				_			_				
				+			+				
		-		-			-				
		-		-			-		-		-
									-		42220//52
								NO DATE	GRAP	PHIC SCALE	APPROVED
								0F 10 F	11)	N FEET)	F0 75
									0	25	
	\square	-		-			-		1	" = 50'	
									<u></u>		
								SATE .	Et as		
	+	-		-		$\left \right $	-	<u>;</u> */		DOCUMENT W	AS AUTHORIZED BY
	\square	-		-			-	JULIO F	RAMOS	00210100	
								OR CE	NSED	6	/25/2020
								"INNA	AL FILL		
					⊢						
	\square		-			\square					
	$\downarrow \downarrow$	-		+			+			44550 P.	
					Ħ				EC	SAN ANTON	IU WEST, SUITE 395 IO, TEXAS 78230-1037
								CIVIL ENGINEER	NG CONSULTANTS	TBPE REGIS	STRATION NO 100410440 TRATION NO 100410-00
	++	+		+		$\left \right $	+		DE		
				_			_		BE BUBLIC W	VORKS D	UNIY Epartment
		-		-		Ħ	-				
									WATS	<u>ON ROA</u>	۸D
									WAT	SON RD	NI.
++	+	+	H	-	H	+	-		CROSS	SECHC	IN
	\square	-		-	\square	H	-				
	$\downarrow \downarrow$	+		+			+		SHEE	T 24 OF 27	
									0	Ð	
			\parallel		⊢			© 2019	7	Texas	Department
	+		H	-			-	FED.RD. DIV NO	FEDERA	L AID PROJECT	NO. PLAN SHT.
	\square	-		-	\square		-	6			250
	50)	[STATE			
								CONT.	SECT.	JOB	HIGHWAY / STREET
								0915	12	562	WATSON RD



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOT DRIVER: WATSON_BW_PDF.pltcfg PLOTTED ON: 6/25/2020 @ 1:57:43 PM PLOTTED ON: 6/25/2020 @ 1:57:43 PM PLOTTED ON: 6/25/2020 @ 1:57:43 PM

								1				
	50			-				-				
\mp		$ \downarrow \rangle$	Ħ	+	Ħ							
				_								
			$\left \right $	-								
			\square									
+		\vdash	\vdash	+-	\vdash	$\left \right $						
			\square									
+			++	-								
-			-	+	_	+ -						
				-								
				_								
+		\square	\vdash	-		\square						
		Ħ	Ħ	\downarrow								
+			$\left \right $	+								
		Ħ	Ħ	1	Ħ		1					
+		++	$\left \right $	+	\vdash	$\left \cdot \right $						
			Ħ	1								
+		+	+	+	\vdash							
			Ħ	\downarrow								
+		++	++	+		++						
				-								
+		\vdash	$\left \right $	+		$\left \right $			-			
-		-	E	+		+			-			-
			$\left \right $	+				NO DATE	- R	EVISION		- APPROVED
								NO DATE	GRAP	HIC SCALE		THINGTEE
+		\square	++	-		++		05 40 5	(1)	N FEET)	50	75
			\square					25 12.5	0	25	50	/5
+			++	+					1'	" = 50'		
								TEO	FTEL			
+		\vdash	\vdash	+		\square		in shared	- 40*	THE SEAL A	PPEARING	ON THIS
								5 */		JULIO RA	VAS AUTHC MOS, P.E. 1	DRIZED BY 107672
+			$\left \right $	+				300101	672 E			
		\square		1				CEI	VSED		j/25/2020	
+		+	+	+	\vdash			NONA	IL ENTE			
		\square	Ħ									
\square		Ш.	Ħ	\top								
										11550 H	10 WEST SU	JTE 395
\square			H	F					<u></u> ⊂C	SAN ANTO TEL. (210) 641	10, TEXAS 70	8230-1037 210) 641-6440
		EXIS	Ħ	\downarrow	Ħ			CIVIL ENGINEER	NG CONSULTANTS DON DURDEN, INC.	TBPE REG	STRATION NO	0 F 2214
+		╢╀	$\left \right $	+	\vdash	++						
		-	F1	+	 -	+ -			BE	XAR CC	UNTY	
		+	$\left \right $	+	\vdash	++			ANRLIC M	ORKS I	PEPART	IMENT
			Ħ	1					WATS	ON ROA	۸D	
	ш								\ <u>\</u> \ΔT			
$' \square$	ш		H	-					CROSS	SECTIC)N	
4	NO (01000		* • •	
	ΗĒ	++	H	\square	\square	++						
5	Ш.Б		Ħ	\downarrow					SHEE	T 25 OF 27		
ASS	19 SS		H	F								
3	-5₹								*	Texas	Departi	ment
+		++		+	\vdash			C 2019		of Tra	nsporta	ntion
		Ħ	Ħ		Ħ			FED.RD. DIV.NO	FEDERAL	AID PROJEC	ΓNO.	PLAN SHT NO.
+		++	$\left \right $	+	\vdash	$\left \right $		6			001	251
	50										COUNTY	
	50							CONT.	SECT.	JOB		Y / STREET
								0915	12	562	WATS	ON RD


PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOTTED ON: 6/25/2020 @ 1:57:46 PM DESIGN FILENAME: X:\data\Infra\Proj_2016\E0543800_Bx_Co_Watson\CADD\Xsec\WATSO

	50	1						ו						
							1	1						
							_							
	\square		+	$\downarrow \downarrow$	\square		_							
	Ħ		+		\mp									
	++		+	++	+		_							
	++		+	++	+		_							
							_							
							_							
			_											
	++		+	++	+		_							
							_							
	++	+	+	++	+		_							
	Ħ			$\downarrow \downarrow$										
++-	++		+	++	+		_							
\square	H			\square	\square									
							_							
	H	F	-	\square	\square		-							
	+		_	+	\square	+	-							
	Ħ													
++	$\left \right $	+	+	+	+	+	-							
	Ħ													
	$\left \right $	+		+										
	Ħ	П		\square	\square									
							_							
			_				_							
	++		+	+			_	- - -	-		<u> </u>			
	Ħ								-					
	++		+	++	+		_	NO DATE	GRAE	REVISION	APPROVE			
	Ħ				$\downarrow \downarrow$				(II	N FEET)				
							_	25 12.5	0	25	50 75			
					\square		_		1	" = 50'				
++	+	+	+	+	+	+	-	TEO	ETEN					
	Ħ			$\downarrow \downarrow$				ليتشين من المرجع تي الم		THE SEAL A	PPEARING ON THIS			
	+	+	+	+	+		-	3×1. 1		DOCUMENT V	AS AUTHORIZED B			
	Ħ			\square				JULIO F	AMOS		_, 			
								OK /CE	NSED		/25/2020			
++	+	+	-	+	+	+	-	S/ON/	AL EN	0				
	Ħ													
++	+	+	+	+	+	+	-							
	Ħ			$\downarrow \uparrow$										
							_			11550 H	10 WEST, SUITE 395			
\square	F	\square	+	\square	\square		_		EC	SAN ANTON	IO, TEXAS 78230-1037			
								CIVIL ENGINEER	ING CONSULTANTS	TBPE REG	STRATION NO. F 2214			
++	$\left + \right $	+	-	+	+	+	-							
	Ħ								BE	EXAR CO	UNTY			
+	+	+	+	+	+		-		PUBLIC W	VORKS E	PEPARTMEN			
	\square			\square					WATS		\D			
	\square								\W/ΔT	SON RD				
	H	F		+	\square		-							
	Ħ								5,000					
++	++	+	-	+	+	+	-							
	Ħ								SHEF	T 26 OF 27				
++	+	+	+	+	+	+	-			D				
	Ħ							6	_ 	Texas	Department			
	+	+	+	+	+		-	<u> </u>		of Tra	nsportation			
	Ħ			$\downarrow \uparrow$	\mp			FED.RD. DIV.NO.	FEDERA	L AID PROJECT	NO. PLAN SF			
								6 STATE	niet		252			
	50							TEXAS	SAT		BEXAR			
				(1	CONT	SECT.	ЈОВ	HIGHWAY / STREET			
								0915	12	562	WATSON RD			



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pttcfg PLOT DRIVER: WATSON_BW_PDF.pttcfg PLOTTED ON: 6/25/2020 @ 1:57:49 PM DESIGN FILENAME: X:\dataNnfra\Proj_2016)

	-	<u> </u>						1						
		J 			┢┯									
+	\square		F		\square									
		+	Ħ	-	Ħ									
					$\left \right $									
		+			Ħ									
					$\left \right $									
		-	\square	_	\square									
		-			\square									
	+	+	\square	_	\vdash									
		-		-	\square									
					Ħ									
			\square											
++	+	+	H	-	H	+								
+		-	H	-	Ħ									
					Ħ	\mp								
					H									
			$\left \right $			+								
					\square									
	+	+	\vdash	-	\vdash									
								<u> </u>	-		<u> </u>			
		+		-	Ħ				-					
								NO DAIL	GRAP	HIC SCALE	ATTROVED			
					\square			25 12 5	11) 0	N FEET) 25	50 75			
	+	+		_	\vdash									
	\square	-	\square		\square				1	" = 50"				
									<u></u>					
								STATE	- tro	THE SEAL A	PPEARING ON THIS			
								<i></i>		JULIO RAN	AS AUTHORIZED BY MOS, P.E. 107672			
		+	\square	_	\vdash			30LIO F	672					
		-		_	H			O KS CEI	NSED	6	/25/2020			
		-	Ħ		Ħ				11.11.1					
					Ħ									
			\mathbb{H}		$\left \right $	+								
\square	Ħ	-	F	-	H	T				11550 11				
+	\square	+		-	Ħ				EC	SAN ANTON TEL: (210) 641.0	O, TEXAS 78230-1037			
		+		+	Ħ			CIVIL ENGINEERI	NG CONSULTANTS DON DURDEN, INC.	TBPE REGIS	STRATION NO. F-2214 TRATION NO. 100410-00			
		+							ВГ	XARCO				
			\mathbb{H}						ве PUBLIC W	VORKS D	EPARTMENT			
\square	Ħ	-			F	T			14/4 70					
\mp			Ħ		Ħ						ν υ			
		+			Ħ				WAT	SUN RD	N			
					\square				0000		'I N			
	+		\mathbb{H}		$\left \right $	+								
+		-	F		H			SHEET 27 OF 27						
\mp			Ħ		Ħ					ο 	Danastra (
		+		+	Ħ	\pm		© 2019		i exas of Trai	pepartment sportation			
					\vdash			FED.RD. DIV.NO.	FEDERA	L AID PROJECT	NO. PLAN SHT. NO.			
$+ \top$			H		H	A		6	DIOT		253			
	5)	_					TEXAS	SAT		BEXAR			
								CONT.	SECT.	JOB	HIGHWAY / STREET			
								0915	12	562	WATSON RD			



PLOTTED BY: evaldez PLOTTED SCALE: 1:20 PEN TABLE: WATSON.TBL PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOT DRIVER: WATSON_BW_PDF.pitcfg PLOTTED ON: 6/25/2020 @ 1:57:52 PM PLOTTED ON: 6/25/2020 @ 1:57:52 PM DESIGN FILENAME: X:\data\Infra\Proj_2016\E0543800_Bx_Co_Watson\CADD\Xsec\WA1

50														
	-			\square										
\square	+			Ħ										
\square	-		-	\square	-									
				Ħ										
	-	Ħ	-	Ħ										
Ħ		Ħ	+	Ħ										
	-	Ħ	-	Ħ										
\square	-	F	+	Ħ										
\square	-		_	\square	_									
									-		-			
								NO DATE	- F	REVISION	APPROVED			
									GRAP (∦	HIC SCALE N FEET)				
								25 12.5	0	25	50 75			
Ħ	+			Ħ					1	" = 50'				
H	+		_	Ħ	_			TE O						
\square	+		-	H	-				- tvs	THE SEAL A	PPEARING ON THIS			
\square	+		-	\square	_			JULIO F	RAMOS	JULIO RAI	MOS, P.E. 107672			
								1070 CFI	572 A	6	/25/2020			
		F		F	F			I NONA	IL EN	0				
				\parallel										
										11550 H	10 WEST, SUITE 395			
										TEL: (210) 641- TBPE REG	10, TEXAS /8230-103/ 9999 FAX: (210) 641-6440 STRATION NO.: F-2214			
	+								DON DURDEN, INC.	TBPLS REGIS	TRATION NO .: 100410-00			
\square	+		-	\square	-				BE Public W	XAR CO Vorks e	UNTY Department			
	-		-	\square	_									
											v V			
									CROSS	SECTIC	N			
				╞┼										
				Ħ					SHE	ET 1 OF 2				
				\parallel										
Ħ	-	H		Ħ				© 2019 Texas Department of Transportation						
Ħ	-	Ħ	-	Ħ				FED RD. DIV.NO.	FEDERA	L AID PROJECT	NO. PLAN SHT			
				<u> </u>				STATE DIST. COUNTY						
bC	J							TEXAS CONT.	SAT SECT.	JOB	BEXAR highway/street			
								0915	12	562	WATSON RD			



50	7					
		-				
	NO DATE	- F		APPROVED		
	05 10 5	GRAF (II	N FEET)	E0 7E		
	25 12.5		25	50 75		
		1	" = 50'			
	TEO	FTEX				
		A	THE SEAL A DOCUMENT V	PPEARING ON THIS VAS AUTHORIZED BY		
	JULIO F	RAMOS	JULIO RA	MOS, P.E. 107672		
	No. CE	NSED	6	/25/2020		
	12 STON	AL ENTE				
	C		11550 H SAN ANTON	10 WEST, SUITE 395		
	CIVIL ENGINEER		TEL: (210) 641 TBPE REGI	9999 FAX: (210) 641-6440 STRATION NO.: F-2214		
		DI	IBPLS REGIS	TTATION NO.: 100410-00		
		PUBLIC V	VORKS E	DEPARTMENT		
		WATS		AD.		
		VERA	NO PKW	Y		
		CROSS	S-SECTIC	DN		
	SHEET 2 OF 2					
	© 2019 Texas Department					
	FED.RD. DIV.NO.	FEDERA	L AID PROJECT	NO. PLAN SHT. NO.		
	6 STATE	DIST.		255 COUNTY		
50	TEXAS	SAT	105	BEXAR		
	0915	sест. 12	562	WATSON RD		